

TEST DATA OF MGFS104812

Regulated DC Power Supply
December 28, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL


Model	MGFS104812																																																																																	
Item	Input Current (by Input Voltage)	Temperature 25°C	Testing Circuitry Figure A																																																																															
Object	_____																																																																																	
1.Graph																																																																																		
<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 100% (Solid line with triangles) Load 50% (Dashed line with squares) Load 0% (Dotted line with circles) 																																																																																		
Note: Slanted line shows the range of the rated input voltage.																																																																																		
2.Values																																																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>16.2</td><td>0.004</td><td>0.004</td><td>0.004</td></tr> <tr><td>16.4</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>16.6</td><td>0.018</td><td>0.375</td><td>0.760</td></tr> <tr><td>16.8</td><td>0.018</td><td>0.370</td><td>0.758</td></tr> <tr><td>17.0</td><td>0.018</td><td>0.366</td><td>0.751</td></tr> <tr><td>18.0</td><td>0.017</td><td>0.346</td><td>0.704</td></tr> <tr><td>24.0</td><td>0.014</td><td>0.257</td><td>0.514</td></tr> <tr><td>36.0</td><td>0.011</td><td>0.172</td><td>0.339</td></tr> <tr><td>48.0</td><td>0.008</td><td>0.130</td><td>0.254</td></tr> <tr><td>60.0</td><td>0.008</td><td>0.106</td><td>0.205</td></tr> <tr><td>76.0</td><td>0.004</td><td>0.085</td><td>0.162</td></tr> <tr><td>80.0</td><td>0.004</td><td>0.081</td><td>0.154</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	16.0	0.003	0.003	0.003	16.2	0.004	0.004	0.004	16.4	0.003	0.003	0.003	16.6	0.018	0.375	0.760	16.8	0.018	0.370	0.758	17.0	0.018	0.366	0.751	18.0	0.017	0.346	0.704	24.0	0.014	0.257	0.514	36.0	0.011	0.172	0.339	48.0	0.008	0.130	0.254	60.0	0.008	0.106	0.205	76.0	0.004	0.085	0.162	80.0	0.004	0.081	0.154	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
16.0	0.003	0.003	0.003																																																																															
16.2	0.004	0.004	0.004																																																																															
16.4	0.003	0.003	0.003																																																																															
16.6	0.018	0.375	0.760																																																																															
16.8	0.018	0.370	0.758																																																																															
17.0	0.018	0.366	0.751																																																																															
18.0	0.017	0.346	0.704																																																																															
24.0	0.014	0.257	0.514																																																																															
36.0	0.011	0.172	0.339																																																																															
48.0	0.008	0.130	0.254																																																																															
60.0	0.008	0.106	0.205																																																																															
76.0	0.004	0.085	0.162																																																																															
80.0	0.004	0.081	0.154																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	MGFS104812
-------	------------

Item	Input Current (by Load Current)
------	---------------------------------

Object	_____
--------	-------



Note: Slanted line shows the range of the rated load current.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.00	0.017	0.014	0.011	0.008	0.004
0.18	0.146	0.110	0.076	0.059	0.040
0.36	0.280	0.209	0.140	0.105	0.070
0.54	0.416	0.309	0.206	0.155	0.100
0.72	0.559	0.412	0.272	0.205	0.131
0.81	0.634	0.464	0.306	0.230	0.147
0.90	- *	0.514	0.339	0.254	0.162
0.99	- *	0.571	0.374	0.280	0.178
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS104812	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Power (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.30</td> <td>0.34</td> <td>0.38</td> <td>0.44</td> <td>0.26</td> </tr> <tr> <td>0.18</td> <td>2.63</td> <td>2.65</td> <td>2.75</td> <td>2.82</td> <td>3.02</td> </tr> <tr> <td>0.36</td> <td>5.02</td> <td>5.01</td> <td>5.06</td> <td>5.06</td> <td>5.33</td> </tr> <tr> <td>0.54</td> <td>7.46</td> <td>7.40</td> <td>7.41</td> <td>7.45</td> <td>7.63</td> </tr> <tr> <td>0.72</td> <td>10.00</td> <td>9.88</td> <td>9.81</td> <td>9.85</td> <td>9.97</td> </tr> <tr> <td>0.81</td> <td>11.34</td> <td>11.12</td> <td>11.01</td> <td>11.04</td> <td>11.18</td> </tr> <tr> <td>0.90</td> <td>- ⋆</td> <td>12.35</td> <td>12.22</td> <td>12.22</td> <td>12.39</td> </tr> <tr> <td>0.99</td> <td>- ⋆</td> <td>13.67</td> <td>13.46</td> <td>13.43</td> <td>13.56</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.30	0.34	0.38	0.44	0.26	0.18	2.63	2.65	2.75	2.82	3.02	0.36	5.02	5.01	5.06	5.06	5.33	0.54	7.46	7.40	7.41	7.45	7.63	0.72	10.00	9.88	9.81	9.85	9.97	0.81	11.34	11.12	11.01	11.04	11.18	0.90	- ⋆	12.35	12.22	12.22	12.39	0.99	- ⋆	13.67	13.46	13.43	13.56	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	0.30	0.34	0.38	0.44	0.26																																																																											
0.18	2.63	2.65	2.75	2.82	3.02																																																																											
0.36	5.02	5.01	5.06	5.06	5.33																																																																											
0.54	7.46	7.40	7.41	7.45	7.63																																																																											
0.72	10.00	9.88	9.81	9.85	9.97																																																																											
0.81	11.34	11.12	11.01	11.04	11.18																																																																											
0.90	- ⋆	12.35	12.22	12.22	12.39																																																																											
0.99	- ⋆	13.67	13.46	13.43	13.56																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Note: Slanted line shows the range of the rated load current.		※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																														

COSEL

Model	MGFS104812																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	_____																																	
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>87.3</td> <td>86.4 ※1</td> </tr> <tr> <td>18</td> <td>87.5</td> <td>87.0 ※1</td> </tr> <tr> <td>24</td> <td>87.8</td> <td>88.0</td> </tr> <tr> <td>30</td> <td>87.5</td> <td>88.5</td> </tr> <tr> <td>36</td> <td>87.3</td> <td>89.0</td> </tr> <tr> <td>48</td> <td>86.4</td> <td>89.0</td> </tr> <tr> <td>60</td> <td>85.4</td> <td>88.3</td> </tr> <tr> <td>76</td> <td>84.0</td> <td>87.7</td> </tr> <tr> <td>80</td> <td>83.8</td> <td>87.5</td> </tr> </tbody> </table> <p>※1 : Load 80%</p>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	87.3	86.4 ※1	18	87.5	87.0 ※1	24	87.8	88.0	30	87.5	88.5	36	87.3	89.0	48	86.4	89.0	60	85.4	88.3	76	84.0	87.7	80	83.8	87.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	87.3	86.4 ※1																																
18	87.5	87.0 ※1																																
24	87.8	88.0																																
30	87.5	88.5																																
36	87.3	89.0																																
48	86.4	89.0																																
60	85.4	88.3																																
76	84.0	87.7																																
80	83.8	87.5																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL


Model	MGFS104812																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — △ — Input Volt. 18V - - - □ - - Input Volt. 24V - - * - - Input Volt. 36V - - ○ - - Input Volt. 48V - - ◇ - - Input Volt. 76V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.18</td> <td>82.7</td> <td>82.3</td> <td>79.3</td> <td>77.2</td> <td>72.2</td> </tr> <tr> <td>0.36</td> <td>86.7</td> <td>86.8</td> <td>86.0</td> <td>86.0</td> <td>81.5</td> </tr> <tr> <td>0.54</td> <td>87.5</td> <td>88.2</td> <td>88.1</td> <td>87.5</td> <td>85.4</td> </tr> <tr> <td>0.72</td> <td>87.0</td> <td>88.1</td> <td>88.6</td> <td>88.3</td> <td>87.2</td> </tr> <tr> <td>0.81</td> <td>86.3</td> <td>88.0</td> <td>88.8</td> <td>88.6</td> <td>87.5</td> </tr> <tr> <td>0.90</td> <td>-</td> <td>※ 88.0</td> <td>89.0</td> <td>89.0</td> <td>87.7</td> </tr> <tr> <td>0.99</td> <td>-</td> <td>※ 87.5</td> <td>88.8</td> <td>89.0</td> <td>88.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.18	82.7	82.3	79.3	77.2	72.2	0.36	86.7	86.8	86.0	86.0	81.5	0.54	87.5	88.2	88.1	87.5	85.4	0.72	87.0	88.1	88.6	88.3	87.2	0.81	86.3	88.0	88.8	88.6	87.5	0.90	-	※ 88.0	89.0	89.0	87.7	0.99	-	※ 87.5	88.8	89.0	88.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.18	82.7	82.3	79.3	77.2	72.2																																																																													
0.36	86.7	86.8	86.0	86.0	81.5																																																																													
0.54	87.5	88.2	88.1	87.5	85.4																																																																													
0.72	87.0	88.1	88.6	88.3	87.2																																																																													
0.81	86.3	88.0	88.8	88.6	87.5																																																																													
0.90	-	※ 88.0	89.0	89.0	87.7																																																																													
0.99	-	※ 87.5	88.8	89.0	88.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS104812
Item	Line Regulation
Object	+12V0.9A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	12.041	-
18	12.042	-
24	12.042	12.040
30	12.042	12.044
36	12.042	12.040
48	12.042	12.040
60	12.042	12.043
76	12.043	12.040
80	12.042	12.043

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS104812																																																																																	
Item	Load Regulation																																																																																	
Object	+12V0.9A																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>12.052</td> <td>12.052</td> <td>12.051</td> <td>12.051</td> <td>12.051</td> </tr> <tr> <td>0.18</td> <td>12.050</td> <td>12.050</td> <td>12.049</td> <td>12.048</td> <td>12.048</td> </tr> <tr> <td>0.36</td> <td>12.048</td> <td>12.048</td> <td>12.048</td> <td>12.047</td> <td>12.047</td> </tr> <tr> <td>0.54</td> <td>12.046</td> <td>12.047</td> <td>12.046</td> <td>12.045</td> <td>12.045</td> </tr> <tr> <td>0.72</td> <td>12.044</td> <td>12.045</td> <td>12.045</td> <td>12.044</td> <td>12.044</td> </tr> <tr> <td>0.81</td> <td>12.042</td> <td>12.042</td> <td>12.042</td> <td>12.042</td> <td>12.042</td> </tr> <tr> <td>0.90</td> <td>-</td> <td>12.040</td> <td>12.040</td> <td>12.040</td> <td>12.040</td> </tr> <tr> <td>0.99</td> <td>-</td> <td>12.042</td> <td>12.042</td> <td>12.042</td> <td>12.042</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	12.052	12.052	12.051	12.051	12.051	0.18	12.050	12.050	12.049	12.048	12.048	0.36	12.048	12.048	12.048	12.047	12.047	0.54	12.046	12.047	12.046	12.045	12.045	0.72	12.044	12.045	12.045	12.044	12.044	0.81	12.042	12.042	12.042	12.042	12.042	0.90	-	12.040	12.040	12.040	12.040	0.99	-	12.042	12.042	12.042	12.042	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	12.052	12.052	12.051	12.051	12.051																																																																													
0.18	12.050	12.050	12.049	12.048	12.048																																																																													
0.36	12.048	12.048	12.048	12.047	12.047																																																																													
0.54	12.046	12.047	12.046	12.045	12.045																																																																													
0.72	12.044	12.045	12.045	12.044	12.044																																																																													
0.81	12.042	12.042	12.042	12.042	12.042																																																																													
0.90	-	12.040	12.040	12.040	12.040																																																																													
0.99	-	12.042	12.042	12.042	12.042																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	


COSEL

Model	MGFS104812
Item	Dynamic Load Response
Object	+12V0.9A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 48 V
Cycle 100 msMin.Load (0A)↔
Load 100% (0.9A)

500 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (0.45A)

500 mV/div

2 ms/div




2 ms/div

Load 50% (0.45A)↔
Load 100% (0.9A)

500 mV/div

2 ms/div




2 ms/div

COSEL

Model	MGFS104812
Item	Ripple Voltage (by Load Current)
Object	+12V0.9A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 24 [V]	Input Volt. 76 [V]
0.00	5	25
0.18	5	5
0.36	5	10
0.54	10	10
0.72	15	10
0.81	20	10
0.90	20	10
0.99	30	10
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.
 load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	MGFS104812
Item	Ripple-Noise
Object	+12V0.9A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 24 [V]	Input Volt. 76 [V]
0.00	5	25
0.18	5	10
0.36	10	10
0.54	10	10
0.72	15	10
0.81	20	10
0.90	25	10
0.99	30	10
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS104812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.9A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	10
0	5	10
25	5	10
55	5	10
65	5	10
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS104812
Item	Ambient Temperature Drift
Object	+12V0.9A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	11.949	11.948	11.950	11.951	11.952
-40	11.983	11.982	11.984	11.985	11.986
-20	12.009	12.008	12.009	12.010	12.010
0	12.027	12.027	12.027	12.027	12.028
25	12.040	12.040	12.040	12.040	12.040
55	12.047	12.047	12.048	12.047	12.047
65	12.047	12.047	12.047	12.047	12.047
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of Input Volt. 18V, Load 80%.
Other case Load 100%.



Model	MGFS104812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.9A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 24 - 76V

Load Current : 0 - 0.9A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	76	0	12.056	± 37	± 0.3
Minimum Voltage	-40	24	0.9	11.982		

COSEL

Model	MGFS104812
Item	Time Lapse Drift
Object	+12V0.9A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph


 Input Volt. 48V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	12.035
0.5	12.044
1.0	12.044
2.0	12.044
3.0	12.044
4.0	12.044
5.0	12.044
6.0	12.044
7.0	12.044
8.0	12.044

COSEL

Model	MGFS104812
Item	Rise and Fall Time
Object	+12V0.9A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.4	0.9	2.3	0.2	2.1	
100 %		1.4	1.1	2.5	0.1	1.0	




COSEL

Model	MGFS104812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.9A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	15.0	15.1
-40	14.9	15.0
-20	14.9	15.0
0	14.8	14.9
25	14.8	14.9
55	14.6	14.8
65	14.5	14.6
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGFS104812																																																																																						
Item	Overcurrent Protection																																																																																						
Object	+12V0.9A																																																																																						
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																																						
Temperature Testing Circuitry	25°C Figure A																																																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.981</td><td>1.160</td><td>1.174</td><td>1.152</td><td>1.160</td></tr> <tr><td>10.8</td><td>1.024</td><td>1.204</td><td>1.214</td><td>1.187</td><td>1.187</td></tr> <tr><td>9.6</td><td>1.120</td><td>1.300</td><td>1.300</td><td>1.259</td><td>1.239</td></tr> <tr><td>8.4</td><td>1.233</td><td>1.409</td><td>1.393</td><td>1.334</td><td>1.288</td></tr> <tr><td>7.2</td><td>1.360</td><td>1.535</td><td>1.490</td><td>1.416</td><td>1.353</td></tr> <tr><td>6.0</td><td>1.409</td><td>1.674</td><td>1.590</td><td>1.507</td><td>1.427</td></tr> <tr><td>4.8</td><td>1.523</td><td>1.757</td><td>1.697</td><td>1.594</td><td>1.501</td></tr> <tr><td>3.6</td><td>1.661</td><td>1.855</td><td>1.810</td><td>1.688</td><td>1.576</td></tr> <tr><td>2.4</td><td>1.907</td><td>2.067</td><td>1.988</td><td>1.832</td><td>1.683</td></tr> <tr><td>1.2</td><td>2.044</td><td>2.232</td><td>2.105</td><td>1.931</td><td>1.759</td></tr> <tr><td>0.0</td><td>2.437</td><td>2.461</td><td>2.168</td><td>1.934</td><td>1.702</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	11.4	0.981	1.160	1.174	1.152	1.160	10.8	1.024	1.204	1.214	1.187	1.187	9.6	1.120	1.300	1.300	1.259	1.239	8.4	1.233	1.409	1.393	1.334	1.288	7.2	1.360	1.535	1.490	1.416	1.353	6.0	1.409	1.674	1.590	1.507	1.427	4.8	1.523	1.757	1.697	1.594	1.501	3.6	1.661	1.855	1.810	1.688	1.576	2.4	1.907	2.067	1.988	1.832	1.683	1.2	2.044	2.232	2.105	1.931	1.759	0.0	2.437	2.461	2.168	1.934	1.702	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																						
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																		
11.4	0.981	1.160	1.174	1.152	1.160																																																																																		
10.8	1.024	1.204	1.214	1.187	1.187																																																																																		
9.6	1.120	1.300	1.300	1.259	1.239																																																																																		
8.4	1.233	1.409	1.393	1.334	1.288																																																																																		
7.2	1.360	1.535	1.490	1.416	1.353																																																																																		
6.0	1.409	1.674	1.590	1.507	1.427																																																																																		
4.8	1.523	1.757	1.697	1.594	1.501																																																																																		
3.6	1.661	1.855	1.810	1.688	1.576																																																																																		
2.4	1.907	2.067	1.988	1.832	1.683																																																																																		
1.2	2.044	2.232	2.105	1.931	1.759																																																																																		
0.0	2.437	2.461	2.168	1.934	1.702																																																																																		
--	-	-	-	-	-																																																																																		

COSEL

Model	MGFS104812	Temperature Testing Circuitry	25°C Figure A																																																																											
Item	Switching frequency (by Load Current)																																																																													
Object	+12V0.9A																																																																													
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - -*--- Input Volt. 36V - - -○--- Input Volt. 48V - - -◇--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>18V [kHz]</th> <th>24V [kHz]</th> <th>36V [kHz]</th> <th>48V [kHz]</th> <th>76V [kHz]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>534</td><td>604</td><td>693</td><td>741</td><td>751</td></tr> <tr><td>0.18</td><td>328</td><td>402</td><td>500</td><td>561</td><td>629</td></tr> <tr><td>0.36</td><td>237</td><td>301</td><td>392</td><td>450</td><td>521</td></tr> <tr><td>0.54</td><td>185</td><td>241</td><td>322</td><td>376</td><td>445</td></tr> <tr><td>0.72</td><td>151</td><td>200</td><td>273</td><td>322</td><td>388</td></tr> <tr><td>0.81</td><td>139</td><td>185</td><td>255</td><td>302</td><td>366</td></tr> <tr><td>0.90</td><td>-</td><td>171</td><td>237</td><td>282</td><td>345</td></tr> <tr><td>0.99</td><td>-</td><td>159</td><td>222</td><td>265</td><td>327</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18V [kHz]	24V [kHz]	36V [kHz]	48V [kHz]	76V [kHz]	0.00	534	604	693	741	751	0.18	328	402	500	561	629	0.36	237	301	392	450	521	0.54	185	241	322	376	445	0.72	151	200	273	322	388	0.81	139	185	255	302	366	0.90	-	171	237	282	345	0.99	-	159	222	265	327	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Current [A]	18V [kHz]	24V [kHz]	36V [kHz]	48V [kHz]	76V [kHz]																																																																									
0.00	534	604	693	741	751																																																																									
0.18	328	402	500	561	629																																																																									
0.36	237	301	392	450	521																																																																									
0.54	185	241	322	376	445																																																																									
0.72	151	200	273	322	388																																																																									
0.81	139	185	255	302	366																																																																									
0.90	-	171	237	282	345																																																																									
0.99	-	159	222	265	327																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>534</td><td>604</td><td>693</td><td>741</td><td>751</td></tr> <tr><td>0.18</td><td>328</td><td>402</td><td>500</td><td>561</td><td>629</td></tr> <tr><td>0.36</td><td>237</td><td>301</td><td>392</td><td>450</td><td>521</td></tr> <tr><td>0.54</td><td>185</td><td>241</td><td>322</td><td>376</td><td>445</td></tr> <tr><td>0.72</td><td>151</td><td>200</td><td>273</td><td>322</td><td>388</td></tr> <tr><td>0.81</td><td>139</td><td>185</td><td>255</td><td>302</td><td>366</td></tr> <tr><td>0.90</td><td>-</td><td>171</td><td>237</td><td>282</td><td>345</td></tr> <tr><td>0.99</td><td>-</td><td>159</td><td>222</td><td>265</td><td>327</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	534	604	693	741	751	0.18	328	402	500	561	629	0.36	237	301	392	450	521	0.54	185	241	322	376	445	0.72	151	200	273	322	388	0.81	139	185	255	302	366	0.90	-	171	237	282	345	0.99	-	159	222	265	327	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																													
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																									
0.00	534	604	693	741	751																																																																									
0.18	328	402	500	561	629																																																																									
0.36	237	301	392	450	521																																																																									
0.54	185	241	322	376	445																																																																									
0.72	151	200	273	322	388																																																																									
0.81	139	185	255	302	366																																																																									
0.90	-	171	237	282	345																																																																									
0.99	-	159	222	265	327																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
Note:	<p>Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																																													
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																													




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)