

# TEST DATA OF MGFS302405

Regulated DC Power Supply  
January 6, 2011

Approved by : Kazunari Asano  
Kazunari Asano

Design Manager

Prepared by : Masashi Ueda  
Masashi Ueda

Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1. Input Current (by Input Voltage) . . . . .	1
2. Input Current (by Load Current) . . . . .	2
3. Input Power (by Load Current) . . . . .	3
4. Efficiency (by Input Voltage) . . . . .	4
5. Efficiency (by Load Current) . . . . .	5
6. Line Regulation . . . . .	6
7. Load Regulation . . . . .	7
8. Dynamic Load Response . . . . .	8
9. Ripple Voltage (by Load Current) . . . . .	9
10. Ripple-Noise . . . . .	10
11. Ripple Voltage (by Ambient Temperature) . . . . .	11
12. Ambient Temperature Drift . . . . .	12
13. Output Voltage Accuracy . . . . .	13
14. Time Lapse Drift . . . . .	14
15. Rise and Fall Time . . . . .	15
16. Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17. Overcurrent Protection . . . . .	17
18. Overvoltage Protection . . . . .	18
19. Figure of Testing Circuitry . . . . .	19


(Final Page 19)

Model	MGFS302405																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object																																																																																		
1.Graph	<p style="text-align: center;">—△— Load 100%        - - -□- - Load 50%        - -○--- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.2</td><td>0.109</td><td>2.040</td><td>4.120</td></tr> <tr><td>8.5</td><td>0.100</td><td>1.960</td><td>3.955</td></tr> <tr><td>9.0</td><td>0.093</td><td>1.866</td><td>3.726</td></tr> <tr><td>12.0</td><td>0.079</td><td>1.395</td><td>2.796</td></tr> <tr><td>18.0</td><td>0.068</td><td>0.951</td><td>1.865</td></tr> <tr><td>24.0</td><td>0.062</td><td>0.723</td><td>1.410</td></tr> <tr><td>36.0</td><td>0.058</td><td>0.502</td><td>0.959</td></tr> <tr><td>40.0</td><td>0.058</td><td>0.459</td><td>0.872</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	7.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	8.2	0.109	2.040	4.120	8.5	0.100	1.960	3.955	9.0	0.093	1.866	3.726	12.0	0.079	1.395	2.796	18.0	0.068	0.951	1.865	24.0	0.062	0.723	1.410	36.0	0.058	0.502	0.959	40.0	0.058	0.459	0.872	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-					
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
6.0	0.000	0.000	0.000																																																																															
7.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
8.2	0.109	2.040	4.120																																																																															
8.5	0.100	1.960	3.955																																																																															
9.0	0.093	1.866	3.726																																																																															
12.0	0.079	1.395	2.796																																																																															
18.0	0.068	0.951	1.865																																																																															
24.0	0.062	0.723	1.410																																																																															
36.0	0.058	0.502	0.959																																																																															
40.0	0.058	0.459	0.872																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.2</td><td>0.109</td><td>2.040</td><td>4.120</td></tr> <tr><td>8.5</td><td>0.100</td><td>1.960</td><td>3.955</td></tr> <tr><td>9.0</td><td>0.093</td><td>1.866</td><td>3.726</td></tr> <tr><td>12.0</td><td>0.079</td><td>1.395</td><td>2.796</td></tr> <tr><td>18.0</td><td>0.068</td><td>0.951</td><td>1.865</td></tr> <tr><td>24.0</td><td>0.062</td><td>0.723</td><td>1.410</td></tr> <tr><td>36.0</td><td>0.058</td><td>0.502</td><td>0.959</td></tr> <tr><td>40.0</td><td>0.058</td><td>0.459</td><td>0.872</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	7.0	0.000	0.000	0.000	8.0	0.000	0.000	0.000	8.2	0.109	2.040	4.120	8.5	0.100	1.960	3.955	9.0	0.093	1.866	3.726	12.0	0.079	1.395	2.796	18.0	0.068	0.951	1.865	24.0	0.062	0.723	1.410	36.0	0.058	0.502	0.959	40.0	0.058	0.459	0.872	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
6.0	0.000	0.000	0.000																																																																															
7.0	0.000	0.000	0.000																																																																															
8.0	0.000	0.000	0.000																																																																															
8.2	0.109	2.040	4.120																																																																															
8.5	0.100	1.960	3.955																																																																															
9.0	0.093	1.866	3.726																																																																															
12.0	0.079	1.395	2.796																																																																															
18.0	0.068	0.951	1.865																																																																															
24.0	0.062	0.723	1.410																																																																															
36.0	0.058	0.502	0.959																																																																															
40.0	0.058	0.459	0.872																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

Model	MGFS302405																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.091</td><td>0.077</td><td>0.067</td><td>0.061</td><td>0.058</td></tr> <tr><td>1.2</td><td>0.784</td><td>0.601</td><td>0.418</td><td>0.325</td><td>0.235</td></tr> <tr><td>2.4</td><td>1.498</td><td>1.136</td><td>0.773</td><td>0.593</td><td>0.414</td></tr> <tr><td>3.6</td><td>2.230</td><td>1.677</td><td>1.130</td><td>0.860</td><td>0.594</td></tr> <tr><td>4.8</td><td>2.962</td><td>2.238</td><td>1.504</td><td>1.139</td><td>0.779</td></tr> <tr><td>6.0</td><td>3.748</td><td>2.812</td><td>1.882</td><td>1.420</td><td>0.969</td></tr> <tr><td>6.6</td><td>4.180</td><td>3.120</td><td>2.080</td><td>1.566</td><td>1.063</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.091	0.077	0.067	0.061	0.058	1.2	0.784	0.601	0.418	0.325	0.235	2.4	1.498	1.136	0.773	0.593	0.414	3.6	2.230	1.677	1.130	0.860	0.594	4.8	2.962	2.238	1.504	1.139	0.779	6.0	3.748	2.812	1.882	1.420	0.969	6.6	4.180	3.120	2.080	1.566	1.063	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.0	0.091	0.077	0.067	0.061	0.058																																																																													
1.2	0.784	0.601	0.418	0.325	0.235																																																																													
2.4	1.498	1.136	0.773	0.593	0.414																																																																													
3.6	2.230	1.677	1.130	0.860	0.594																																																																													
4.8	2.962	2.238	1.504	1.139	0.779																																																																													
6.0	3.748	2.812	1.882	1.420	0.969																																																																													
6.6	4.180	3.120	2.080	1.566	1.063																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Note: Slanted line shows the range of the rated load current.

Model	MGFS302405				
Item	Input Power (by Load Current)				
Object	_____				
1.Graph	<p>—△— Input Volt. 9V        - - -□- - Input Volt. 12V        - - * - - Input Volt. 18V        - - ○ - - Input Volt. 24V        - - ◇ - - Input Volt. 36V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0.0 to 6.0). Five curves are shown for different input voltages: 9V (solid line with open triangle markers), 12V (dashed line with open square markers), 18V (dash-dot line with asterisk markers), 24V (dash-dot-dot line with open circle markers), and 36V (long-dash line with open diamond markers). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (0.5, 2) and ending at (6.0, 40), indicating the rated load current range.</p>				
Temperature	25°C				
Testing Circuitry	Figure A				
2.Values					
Load Current	Input Power [W]				
[A]	9[V]	12[V]	18[V]	24[V]	36[V]
0.0	0.82	0.92	1.21	1.47	2.10
1.2	7.07	7.19	7.48	7.78	8.47
2.4	13.48	13.58	13.87	14.17	14.89
3.6	20.01	20.06	20.32	20.59	21.34
4.8	26.73	26.79	26.95	27.22	27.95
6.0	33.67	33.63	33.80	34.00	34.80
6.6	37.22	37.14	37.30	37.46	38.20
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated load current.


Model	MGFS302405																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry      25°C      Figure A																																
Object	—																																	
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (5 to 45). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>90.6</td><td>89.9</td></tr> <tr><td>9.0</td><td>90.6</td><td>89.9</td></tr> <tr><td>12.0</td><td>90.3</td><td>90.0</td></tr> <tr><td>15.0</td><td>89.6</td><td>89.9</td></tr> <tr><td>18.0</td><td>88.9</td><td>89.7</td></tr> <tr><td>24.0</td><td>87.4</td><td>89.0</td></tr> <tr><td>30.0</td><td>85.8</td><td>88.2</td></tr> <tr><td>36.0</td><td>83.9</td><td>87.1</td></tr> <tr><td>40.0</td><td>82.7</td><td>86.5</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	8.5	90.6	89.9	9.0	90.6	89.9	12.0	90.3	90.0	15.0	89.6	89.9	18.0	88.9	89.7	24.0	87.4	89.0	30.0	85.8	88.2	36.0	83.9	87.1	40.0	82.7	86.5			
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
8.5	90.6	89.9																																
9.0	90.6	89.9																																
12.0	90.3	90.0																																
15.0	89.6	89.9																																
18.0	88.9	89.7																																
24.0	87.4	89.0																																
30.0	85.8	88.2																																
36.0	83.9	87.1																																
40.0	82.7	86.5																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>90.6</td><td>89.9</td></tr> <tr><td>9.0</td><td>90.6</td><td>89.9</td></tr> <tr><td>12.0</td><td>90.3</td><td>90.0</td></tr> <tr><td>15.0</td><td>89.6</td><td>89.9</td></tr> <tr><td>18.0</td><td>88.9</td><td>89.7</td></tr> <tr><td>24.0</td><td>87.4</td><td>89.0</td></tr> <tr><td>30.0</td><td>85.8</td><td>88.2</td></tr> <tr><td>36.0</td><td>83.9</td><td>87.1</td></tr> <tr><td>40.0</td><td>82.7</td><td>86.5</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	90.6	89.9	9.0	90.6	89.9	12.0	90.3	90.0	15.0	89.6	89.9	18.0	88.9	89.7	24.0	87.4	89.0	30.0	85.8	88.2	36.0	83.9	87.1	40.0	82.7	86.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	90.6	89.9																																
9.0	90.6	89.9																																
12.0	90.3	90.0																																
15.0	89.6	89.9																																
18.0	88.9	89.7																																
24.0	87.4	89.0																																
30.0	85.8	88.2																																
36.0	83.9	87.1																																
40.0	82.7	86.5																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	MGFS302405																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>86.0</td><td>84.5</td><td>81.3</td><td>78.1</td><td>71.8</td></tr> <tr><td>2.4</td><td>90.2</td><td>89.5</td><td>87.7</td><td>85.8</td><td>81.7</td></tr> <tr><td>3.6</td><td>90.8</td><td>90.6</td><td>89.4</td><td>88.3</td><td>85.2</td></tr> <tr><td>4.8</td><td>90.7</td><td>90.5</td><td>90.0</td><td>89.1</td><td>86.8</td></tr> <tr><td>6.0</td><td>90.0</td><td>90.1</td><td>89.7</td><td>89.2</td><td>87.1</td></tr> <tr><td>6.6</td><td>89.6</td><td>89.8</td><td>89.4</td><td>89.0</td><td>87.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.0	-	-	-	-	-	1.2	86.0	84.5	81.3	78.1	71.8	2.4	90.2	89.5	87.7	85.8	81.7	3.6	90.8	90.6	89.4	88.3	85.2	4.8	90.7	90.5	90.0	89.1	86.8	6.0	90.0	90.1	89.7	89.2	87.1	6.6	89.6	89.8	89.4	89.0	87.3	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-									
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.0	-	-	-	-	-																																																																													
1.2	86.0	84.5	81.3	78.1	71.8																																																																													
2.4	90.2	89.5	87.7	85.8	81.7																																																																													
3.6	90.8	90.6	89.4	88.3	85.2																																																																													
4.8	90.7	90.5	90.0	89.1	86.8																																																																													
6.0	90.0	90.1	89.7	89.2	87.1																																																																													
6.6	89.6	89.8	89.4	89.0	87.3																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values																																																																																		
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>86.0</td><td>84.5</td><td>81.3</td><td>78.1</td><td>71.8</td></tr> <tr><td>2.4</td><td>90.2</td><td>89.5</td><td>87.7</td><td>85.8</td><td>81.7</td></tr> <tr><td>3.6</td><td>90.8</td><td>90.6</td><td>89.4</td><td>88.3</td><td>85.2</td></tr> <tr><td>4.8</td><td>90.7</td><td>90.5</td><td>90.0</td><td>89.1</td><td>86.8</td></tr> <tr><td>6.0</td><td>90.0</td><td>90.1</td><td>89.7</td><td>89.2</td><td>87.1</td></tr> <tr><td>6.6</td><td>89.6</td><td>89.8</td><td>89.4</td><td>89.0</td><td>87.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	-	-	-	-	-	1.2	86.0	84.5	81.3	78.1	71.8	2.4	90.2	89.5	87.7	85.8	81.7	3.6	90.8	90.6	89.4	88.3	85.2	4.8	90.7	90.5	90.0	89.1	86.8	6.0	90.0	90.1	89.7	89.2	87.1	6.6	89.6	89.8	89.4	89.0	87.3	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.0	-	-	-	-	-																																																																													
1.2	86.0	84.5	81.3	78.1	71.8																																																																													
2.4	90.2	89.5	87.7	85.8	81.7																																																																													
3.6	90.8	90.6	89.4	88.3	85.2																																																																													
4.8	90.7	90.5	90.0	89.1	86.8																																																																													
6.0	90.0	90.1	89.7	89.2	87.1																																																																													
6.6	89.6	89.8	89.4	89.0	87.3																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	

Model	MGFS302405
Item	Line Regulation
Object	+5V6A

Temperature 25°C  
Testing Circuitry Figure A


## 1. Graph




## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	5.053	5.053
9.0	5.053	5.054
12.0	5.054	5.054
15.0	5.054	5.054
18.0	5.054	5.054
24.0	5.054	5.054
30.0	5.054	5.055
36.0	5.054	5.055
40.0	5.054	5.055

Note: Slanted line shows the range of the rated input voltage.

Model	MGFS302405	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+5V6A																																																																																			
1.Graph	—△— Input Volt. 9V ---□--- Input Volt. 12V -·-*--- Input Volt. 18V -·○--- Input Volt. 24V -·◇--- Input Volt. 36V	2.Values																																																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.059</td><td>5.059</td><td>5.059</td><td>5.059</td><td>5.059</td></tr> <tr><td>1.2</td><td>5.059</td><td>5.058</td><td>5.058</td><td>5.058</td><td>5.058</td></tr> <tr><td>2.4</td><td>5.058</td><td>5.058</td><td>5.058</td><td>5.058</td><td>5.058</td></tr> <tr><td>3.6</td><td>5.058</td><td>5.057</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>4.8</td><td>5.057</td><td>5.057</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>6.0</td><td>5.056</td><td>5.056</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>6.6</td><td>5.056</td><td>5.056</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.0	5.059	5.059	5.059	5.059	5.059	1.2	5.059	5.058	5.058	5.058	5.058	2.4	5.058	5.058	5.058	5.058	5.058	3.6	5.058	5.057	5.057	5.057	5.057	4.8	5.057	5.057	5.057	5.057	5.057	6.0	5.056	5.056	5.056	5.056	5.056	6.6	5.056	5.056	5.056	5.056	5.056	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
0.0	5.059	5.059	5.059	5.059	5.059																																																																															
1.2	5.059	5.058	5.058	5.058	5.058																																																																															
2.4	5.058	5.058	5.058	5.058	5.058																																																																															
3.6	5.058	5.057	5.057	5.057	5.057																																																																															
4.8	5.057	5.057	5.057	5.057	5.057																																																																															
6.0	5.056	5.056	5.056	5.056	5.056																																																																															
6.6	5.056	5.056	5.056	5.056	5.056																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
																																																																																				
		<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		

**COSEL**

**COSSEL**

Model	MGFS302405																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+5V6A																																							
1.Graph																																								
<p>Input Volt. 9V</p> <p>Input Volt. 36V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>7</td> <td>8</td> </tr> <tr> <td>1.2</td> <td>7</td> <td>8</td> </tr> <tr> <td>2.4</td> <td>7</td> <td>8</td> </tr> <tr> <td>3.6</td> <td>7</td> <td>8</td> </tr> <tr> <td>4.8</td> <td>7</td> <td>8</td> </tr> <tr> <td>6.0</td> <td>7</td> <td>8</td> </tr> <tr> <td>6.6</td> <td>7</td> <td>8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	7	8	1.2	7	8	2.4	7	8	3.6	7	8	4.8	7	8	6.0	7	8	6.6	7	8	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.0	7	8																																						
1.2	7	8																																						
2.4	7	8																																						
3.6	7	8																																						
4.8	7	8																																						
6.0	7	8																																						
6.6	7	8																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								




Model	MGFS302405	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+5V6A	2. Values																																							
1. Graph																																									
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>10</td><td>15</td></tr> <tr><td>2.4</td><td>10</td><td>15</td></tr> <tr><td>3.6</td><td>10</td><td>15</td></tr> <tr><td>4.8</td><td>10</td><td>15</td></tr> <tr><td>6.0</td><td>10</td><td>15</td></tr> <tr><td>6.6</td><td>10</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	10	10	1.2	10	15	2.4	10	15	3.6	10	15	4.8	10	15	6.0	10	15	6.6	10	15	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	10	10																																							
1.2	10	15																																							
2.4	10	15																																							
3.6	10	15																																							
4.8	10	15																																							
6.0	10	15																																							
6.6	10	15																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Noise Wave Form</p>																																									

# COSEL

Model	MGFS302405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V6A

## 1. Graph



Testing Circuitry Figure B


## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	9	9
-40	6	6
-20	6	6
0	6	6
25	6	6
60	5	5
65	5	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFS302405
Item	Ambient Temperature Drift
Object	+5V6A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	5.023	5.024	5.026	5.028	5.030
-40	5.033	5.034	5.034	5.035	5.037
-20	5.040	5.041	5.042	5.042	5.043
0	5.047	5.047	5.047	5.048	5.049
25	5.053	5.053	5.054	5.054	5.054
60	5.057	5.057	5.057	5.058	5.058
65	5.058	5.058	5.058	5.058	5.058
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS302405	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V6A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 36V

Load Current : 0 - 6A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	36	0	5.060	±14	±0.3
Minimum Voltage	-40	9	6	5.033		

**COSEL**

Model	MGFS302405
Item	Time Lapse Drift
Object	+5V6A

Temperature 25°C  
Testing Circuitry Figure A

1. Graph




2. Values

Time since start [H]	Output Voltage [V]
0.0	5.055
0.5	5.056
1.0	5.056
2.0	5.056
3.0	5.056
4.0	5.056
5.0	5.056
6.0	5.056
7.0	5.056
8.0	5.056

**COSEL**


Model	MGFS302405	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+5V6A	

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.2	1.8	3.0	0.9	0.5	
100 %		1.2	3.1	4.3	0.5	0.2	



Model	MGFS302405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V6A

Testing Circuitry Figure A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.9	7.9
-40	7.9	7.9
-20	7.9	7.9
0	7.9	7.9
25	7.9	8.0
60	7.8	7.9
65	7.8	7.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGFS302405	Temperature Testing Circuitry      25°C Figure A																																																																																							
Item	Overcurrent Protection																																																																																								
Object	+5V6A																																																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V</p> <p>Input Volt. 12V</p> <p>Input Volt. 18V</p> <p>Input Volt. 24V</p> <p>Input Volt. 36V</p>	2.Values																																																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>5.00</td> <td>8.014</td> <td>8.063</td> <td>8.046</td> <td>8.006</td> <td>7.653</td> </tr> <tr> <td>4.75</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.50</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.50</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.50</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.50</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.50</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	5.00	8.014	8.063	8.046	8.006	7.653	4.75	-	-	-	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																								
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																				
5.00	8.014	8.063	8.046	8.006	7.653																																																																																				
4.75	-	-	-	-	-																																																																																				
4.50	-	-	-	-	-																																																																																				
4.00	-	-	-	-	-																																																																																				
3.50	-	-	-	-	-																																																																																				
3.00	-	-	-	-	-																																																																																				
2.50	-	-	-	-	-																																																																																				
2.00	-	-	-	-	-																																																																																				
1.50	-	-	-	-	-																																																																																				
1.00	-	-	-	-	-																																																																																				
0.50	-	-	-	-	-																																																																																				
0.00	-	-	-	-	-																																																																																				

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Model	MGFS302405
Item	Oversupply Protection
Object	+5V6A

## 1. Graph



Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-60	6.95	6.96
-40	6.93	6.94
-20	6.92	6.93
0	6.91	6.92
25	6.91	6.92
60	6.91	6.92
65	6.91	6.92
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)