

TEST DATA OF MGFS30243R3

Regulated DC Power Supply
November 19, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Masashi Ueda
Masashi Ueda

Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

Model	MGFS30243R3																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph	<p>—△— Load 100%</p> <p>- -□-- Load 50%</p> <p>- -○-- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>8.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>10.0</td><td>0.000</td><td>0.000</td><td>3.30</td></tr> <tr><td>12.0</td><td>0.000</td><td>0.000</td><td>2.50</td></tr> <tr><td>20.0</td><td>0.000</td><td>0.000</td><td>1.50</td></tr> <tr><td>30.0</td><td>0.000</td><td>0.000</td><td>0.80</td></tr> <tr><td>40.0</td><td>0.000</td><td>0.000</td><td>0.60</td></tr> </tbody> </table>			Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	8.0	0.000	0.000	0.000	10.0	0.000	0.000	3.30	12.0	0.000	0.000	2.50	20.0	0.000	0.000	1.50	30.0	0.000	0.000	0.80	40.0	0.000	0.000	0.60																																																			
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
8.0	0.000	0.000	0.000																																																																															
10.0	0.000	0.000	3.30																																																																															
12.0	0.000	0.000	2.50																																																																															
20.0	0.000	0.000	1.50																																																																															
30.0	0.000	0.000	0.80																																																																															
40.0	0.000	0.000	0.60																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.001</td></tr> <tr><td>4.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.1</td><td>0.103</td><td>1.741</td><td>0.002</td></tr> <tr><td>8.3</td><td>0.101</td><td>1.693</td><td>3.429</td></tr> <tr><td>8.5</td><td>0.099</td><td>1.653</td><td>3.371</td></tr> <tr><td>9.0</td><td>0.095</td><td>1.565</td><td>3.172</td></tr> <tr><td>12.0</td><td>0.082</td><td>1.180</td><td>2.351</td></tr> <tr><td>18.0</td><td>0.067</td><td>0.795</td><td>1.577</td></tr> <tr><td>24.0</td><td>0.059</td><td>0.606</td><td>1.184</td></tr> <tr><td>36.0</td><td>0.053</td><td>0.418</td><td>0.803</td></tr> <tr><td>40.0</td><td>0.052</td><td>0.381</td><td>0.728</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.001	4.0	0.001	0.001	0.001	6.0	0.002	0.002	0.002	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.002	8.1	0.103	1.741	0.002	8.3	0.101	1.693	3.429	8.5	0.099	1.653	3.371	9.0	0.095	1.565	3.172	12.0	0.082	1.180	2.351	18.0	0.067	0.795	1.577	24.0	0.059	0.606	1.184	36.0	0.053	0.418	0.803	40.0	0.052	0.381	0.728	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.001																																																																															
4.0	0.001	0.001	0.001																																																																															
6.0	0.002	0.002	0.002																																																																															
7.0	0.002	0.002	0.002																																																																															
8.0	0.002	0.002	0.002																																																																															
8.1	0.103	1.741	0.002																																																																															
8.3	0.101	1.693	3.429																																																																															
8.5	0.099	1.653	3.371																																																																															
9.0	0.095	1.565	3.172																																																																															
12.0	0.082	1.180	2.351																																																																															
18.0	0.067	0.795	1.577																																																																															
24.0	0.059	0.606	1.184																																																																															
36.0	0.053	0.418	0.803																																																																															
40.0	0.052	0.381	0.728																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
Note:	Slanted line shows the range of the rated input voltage.																																																																																	

Model	MGFS30243R3																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.102</td> <td>0.082</td> <td>0.066</td> <td>0.058</td> <td>0.053</td> </tr> <tr> <td>1.50</td> <td>0.670</td> <td>0.507</td> <td>0.351</td> <td>0.274</td> <td>0.197</td> </tr> <tr> <td>3.00</td> <td>1.259</td> <td>0.945</td> <td>0.644</td> <td>0.491</td> <td>0.344</td> </tr> <tr> <td>4.50</td> <td>1.857</td> <td>1.407</td> <td>0.946</td> <td>0.719</td> <td>0.494</td> </tr> <tr> <td>6.00</td> <td>2.484</td> <td>1.876</td> <td>1.258</td> <td>0.949</td> <td>0.648</td> </tr> <tr> <td>7.50</td> <td>3.159</td> <td>2.340</td> <td>1.575</td> <td>1.190</td> <td>0.807</td> </tr> <tr> <td>8.25</td> <td>3.477</td> <td>2.598</td> <td>1.741</td> <td>1.314</td> <td>0.887</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.102	0.082	0.066	0.058	0.053	1.50	0.670	0.507	0.351	0.274	0.197	3.00	1.259	0.945	0.644	0.491	0.344	4.50	1.857	1.407	0.946	0.719	0.494	6.00	2.484	1.876	1.258	0.949	0.648	7.50	3.159	2.340	1.575	1.190	0.807	8.25	3.477	2.598	1.741	1.314	0.887	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	0.102	0.082	0.066	0.058	0.053																																																																													
1.50	0.670	0.507	0.351	0.274	0.197																																																																													
3.00	1.259	0.945	0.644	0.491	0.344																																																																													
4.50	1.857	1.407	0.946	0.719	0.494																																																																													
6.00	2.484	1.876	1.258	0.949	0.648																																																																													
7.50	3.159	2.340	1.575	1.190	0.807																																																																													
8.25	3.477	2.598	1.741	1.314	0.887																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Note: Slanted line shows the range of the rated load current.

Model	MGFS30243R3																																																																								
Item	Input Power (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.91</td><td>0.98</td><td>1.18</td><td>1.39</td><td>1.89</td></tr> <tr><td>1.50</td><td>6.03</td><td>6.11</td><td>6.32</td><td>6.54</td><td>7.07</td></tr> <tr><td>3.00</td><td>11.31</td><td>11.36</td><td>11.58</td><td>11.80</td><td>12.34</td></tr> <tr><td>4.50</td><td>16.81</td><td>16.81</td><td>17.01</td><td>17.23</td><td>17.76</td></tr> <tr><td>6.00</td><td>22.48</td><td>22.43</td><td>22.60</td><td>22.78</td><td>23.31</td></tr> <tr><td>7.50</td><td>28.34</td><td>28.22</td><td>28.36</td><td>28.54</td><td>29.04</td></tr> <tr><td>8.25</td><td>31.36</td><td>31.18</td><td>31.28</td><td>31.47</td><td>31.94</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.91	0.98	1.18	1.39	1.89	1.50	6.03	6.11	6.32	6.54	7.07	3.00	11.31	11.36	11.58	11.80	12.34	4.50	16.81	16.81	17.01	17.23	17.76	6.00	22.48	22.43	22.60	22.78	23.31	7.50	28.34	28.22	28.36	28.54	29.04	8.25	31.36	31.18	31.28	31.47	31.94	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																				
0.00	0.91	0.98	1.18	1.39	1.89																																																																				
1.50	6.03	6.11	6.32	6.54	7.07																																																																				
3.00	11.31	11.36	11.58	11.80	12.34																																																																				
4.50	16.81	16.81	17.01	17.23	17.76																																																																				
6.00	22.48	22.43	22.60	22.78	23.31																																																																				
7.50	28.34	28.22	28.36	28.54	29.04																																																																				
8.25	31.36	31.18	31.28	31.47	31.94																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note: Slanted line shows the range of the rated load current.																																																																									


Model	MGFS30243R3																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (5 to 45). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>10</td><td>90.0</td><td>89.0</td></tr> <tr><td>15</td><td>89.5</td><td>88.5</td></tr> <tr><td>20</td><td>88.0</td><td>87.0</td></tr> <tr><td>25</td><td>87.0</td><td>86.0</td></tr> <tr><td>30</td><td>85.5</td><td>84.5</td></tr> <tr><td>35</td><td>84.0</td><td>83.0</td></tr> <tr><td>40</td><td>82.5</td><td>81.5</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	10	90.0	89.0	15	89.5	88.5	20	88.0	87.0	25	87.0	86.0	30	85.5	84.5	35	84.0	83.0	40	82.5	81.5								
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
10	90.0	89.0																																
15	89.5	88.5																																
20	88.0	87.0																																
25	87.0	86.0																																
30	85.5	84.5																																
35	84.0	83.0																																
40	82.5	81.5																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8</td><td>89.2</td><td>88.2</td></tr> <tr><td>9</td><td>89.8</td><td>88.8</td></tr> <tr><td>12</td><td>89.2</td><td>89.1</td></tr> <tr><td>15</td><td>88.6</td><td>88.9</td></tr> <tr><td>18</td><td>87.9</td><td>88.4</td></tr> <tr><td>24</td><td>86.5</td><td>88.1</td></tr> <tr><td>30</td><td>85.1</td><td>87.2</td></tr> <tr><td>36</td><td>83.5</td><td>86.7</td></tr> <tr><td>40</td><td>82.4</td><td>86.0</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8	89.2	88.2	9	89.8	88.8	12	89.2	89.1	15	88.6	88.9	18	87.9	88.4	24	86.5	88.1	30	85.1	87.2	36	83.5	86.7	40	82.4	86.0
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8	89.2	88.2																																
9	89.8	88.8																																
12	89.2	89.1																																
15	88.6	88.9																																
18	87.9	88.4																																
24	86.5	88.1																																
30	85.1	87.2																																
36	83.5	86.7																																
40	82.4	86.0																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	MGFS30243R3																																																																								
Item	Efficiency (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>83.8</td><td>82.6</td><td>79.8</td><td>77.1</td><td>71.4</td></tr> <tr><td>3.00</td><td>88.8</td><td>88.4</td><td>86.7</td><td>85.0</td><td>81.3</td></tr> <tr><td>4.50</td><td>89.8</td><td>89.7</td><td>88.7</td><td>87.5</td><td>84.9</td></tr> <tr><td>6.00</td><td>89.5</td><td>89.7</td><td>89.0</td><td>88.3</td><td>86.3</td></tr> <tr><td>7.50</td><td>88.8</td><td>89.2</td><td>88.7</td><td>88.1</td><td>86.6</td></tr> <tr><td>8.25</td><td>88.3</td><td>88.8</td><td>88.5</td><td>87.9</td><td>86.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-	-	-	-	-	1.50	83.8	82.6	79.8	77.1	71.4	3.00	88.8	88.4	86.7	85.0	81.3	4.50	89.8	89.7	88.7	87.5	84.9	6.00	89.5	89.7	89.0	88.3	86.3	7.50	88.8	89.2	88.7	88.1	86.6	8.25	88.3	88.8	88.5	87.9	86.6	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																				
0.00	-	-	-	-	-																																																																				
1.50	83.8	82.6	79.8	77.1	71.4																																																																				
3.00	88.8	88.4	86.7	85.0	81.3																																																																				
4.50	89.8	89.7	88.7	87.5	84.9																																																																				
6.00	89.5	89.7	89.0	88.3	86.3																																																																				
7.50	88.8	89.2	88.7	88.1	86.6																																																																				
8.25	88.3	88.8	88.5	87.9	86.6																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note: Slanted line shows the range of the rated load current.																																																																									

Model	MGFS30243R3
Item	Line Regulation
Object	+3.3V7.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	3.358	3.356
9.0	3.358	3.356
12.0	3.358	3.356
15.0	3.358	3.355
18.0	3.358	3.355
24.0	3.358	3.355
30.0	3.358	3.355
36.0	3.358	3.354
40.0	3.358	3.354

Note: Slanted line shows the range of the rated input voltage.

Model	MGFS30243R3																																																																																	
Item	Load Regulation																																																																																	
Object	+3.3V7.5A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.360</td><td>3.359</td><td>3.359</td><td>3.359</td><td>3.359</td></tr> <tr><td>1.50</td><td>3.359</td><td>3.358</td><td>3.358</td><td>3.358</td><td>3.358</td></tr> <tr><td>3.00</td><td>3.358</td><td>3.358</td><td>3.358</td><td>3.357</td><td>3.357</td></tr> <tr><td>4.50</td><td>3.358</td><td>3.357</td><td>3.357</td><td>3.356</td><td>3.356</td></tr> <tr><td>6.00</td><td>3.357</td><td>3.356</td><td>3.356</td><td>3.355</td><td>3.355</td></tr> <tr><td>7.50</td><td>3.355</td><td>3.355</td><td>3.355</td><td>3.354</td><td>3.354</td></tr> <tr><td>8.25</td><td>3.355</td><td>3.354</td><td>3.354</td><td>3.354</td><td>3.354</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	3.360	3.359	3.359	3.359	3.359	1.50	3.359	3.358	3.358	3.358	3.358	3.00	3.358	3.358	3.358	3.357	3.357	4.50	3.358	3.357	3.357	3.356	3.356	6.00	3.357	3.356	3.356	3.355	3.355	7.50	3.355	3.355	3.355	3.354	3.354	8.25	3.355	3.354	3.354	3.354	3.354	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	3.360	3.359	3.359	3.359	3.359																																																																													
1.50	3.359	3.358	3.358	3.358	3.358																																																																													
3.00	3.358	3.358	3.358	3.357	3.357																																																																													
4.50	3.358	3.357	3.357	3.356	3.356																																																																													
6.00	3.357	3.356	3.356	3.355	3.355																																																																													
7.50	3.355	3.355	3.355	3.354	3.354																																																																													
8.25	3.355	3.354	3.354	3.354	3.354																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Note: Slanted line shows the range of the rated load current.

COSSEL

COSEL

Model	MGFS30243R3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V7.5A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0.0 to 8.0 A. Two data series are plotted: Input Volt. 9V (solid line with open circles) and Input Volt. 36V (dashed line with open circles). Both series show a constant ripple voltage of approximately 5 mV across the load current range. A slanted line indicates the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>5</td><td>6</td></tr> <tr> <td>1.50</td><td>4</td><td>6</td></tr> <tr> <td>3.00</td><td>4</td><td>6</td></tr> <tr> <td>4.50</td><td>4</td><td>6</td></tr> <tr> <td>6.00</td><td>4</td><td>6</td></tr> <tr> <td>7.50</td><td>4</td><td>6</td></tr> <tr> <td>8.25</td><td>4</td><td>6</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	5	6	1.50	4	6	3.00	4	6	4.50	4	6	6.00	4	6	7.50	4	6	8.25	4	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	5	6																																						
1.50	4	6																																						
3.00	4	6																																						
4.50	4	6																																						
6.00	4	6																																						
7.50	4	6																																						
8.25	4	6																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGFS30243R3																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V7.5A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 120 mV, and the X-axis ranges from 0.0 to 8.0 A. Two horizontal lines represent Input Volt. 9V and 36V. A slanted line indicates the rated load current range from 0.0 to 8.25 A.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (9V)</th> <th>Ripple Voltage [mV] (36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>1.50</td><td>10</td><td>10</td></tr> <tr><td>3.00</td><td>10</td><td>10</td></tr> <tr><td>4.50</td><td>10</td><td>10</td></tr> <tr><td>6.00</td><td>10</td><td>10</td></tr> <tr><td>7.50</td><td>10</td><td>10</td></tr> <tr><td>8.25</td><td>10</td><td>10</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (9V)	Ripple Voltage [mV] (36V)	0.00	10	10	1.50	10	10	3.00	10	10	4.50	10	10	6.00	10	10	7.50	10	10	8.25	10	10														
Load Current [A]	Ripple Voltage [mV] (9V)	Ripple Voltage [mV] (36V)																																						
0.00	10	10																																						
1.50	10	10																																						
3.00	10	10																																						
4.50	10	10																																						
6.00	10	10																																						
7.50	10	10																																						
8.25	10	10																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>1.50</td><td>10</td><td>10</td></tr> <tr><td>3.00</td><td>10</td><td>10</td></tr> <tr><td>4.50</td><td>10</td><td>10</td></tr> <tr><td>6.00</td><td>10</td><td>10</td></tr> <tr><td>7.50</td><td>10</td><td>10</td></tr> <tr><td>8.25</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	10	10	1.50	10	10	3.00	10	10	4.50	10	10	6.00	10	10	7.50	10	10	8.25	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	10	10																																						
1.50	10	10																																						
3.00	10	10																																						
4.50	10	10																																						
6.00	10	10																																						
7.50	10	10																																						
8.25	10	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGFS30243R3																																								
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																							
Object	+3.3V7.5A																																								
1.Graph																																									
			2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-60</td><td>6</td><td>6</td></tr> <tr> <td>-40</td><td>5</td><td>5</td></tr> <tr> <td>-20</td><td>4</td><td>4</td></tr> <tr> <td>0</td><td>4</td><td>4</td></tr> <tr> <td>25</td><td>4</td><td>4</td></tr> <tr> <td>60</td><td>3</td><td>3</td></tr> <tr> <td>65</td><td>3</td><td>3</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	6	6	-40	5	5	-20	4	4	0	4	4	25	4	4	60	3	3	65	3	3	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																								
	Load 50%	Load 100%																																							
-60	6	6																																							
-40	5	5																																							
-20	4	4																																							
0	4	4																																							
25	4	4																																							
60	3	3																																							
65	3	3																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

Model	MGFS30243R3																																																																																	
Item	Ambient Temperature Drift																																																																																	
Object	+3.3V7.5A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>3.362</td><td>3.362</td><td>3.362</td><td>3.362</td><td>3.362</td></tr> <tr><td>-40</td><td>3.361</td><td>3.361</td><td>3.360</td><td>3.360</td><td>3.360</td></tr> <tr><td>-20</td><td>3.359</td><td>3.358</td><td>3.358</td><td>3.358</td><td>3.358</td></tr> <tr><td>0</td><td>3.358</td><td>3.358</td><td>3.358</td><td>3.357</td><td>3.357</td></tr> <tr><td>25</td><td>3.357</td><td>3.356</td><td>3.356</td><td>3.356</td><td>3.356</td></tr> <tr><td>60</td><td>3.352</td><td>3.351</td><td>3.351</td><td>3.351</td><td>3.350</td></tr> <tr><td>65</td><td>3.350</td><td>3.350</td><td>3.349</td><td>3.349</td><td>3.348</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	3.362	3.362	3.362	3.362	3.362	-40	3.361	3.361	3.360	3.360	3.360	-20	3.359	3.358	3.358	3.358	3.358	0	3.358	3.358	3.358	3.357	3.357	25	3.357	3.356	3.356	3.356	3.356	60	3.352	3.351	3.351	3.351	3.350	65	3.350	3.350	3.349	3.349	3.348	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
-60	3.362	3.362	3.362	3.362	3.362																																																																													
-40	3.361	3.361	3.360	3.360	3.360																																																																													
-20	3.359	3.358	3.358	3.358	3.358																																																																													
0	3.358	3.358	3.358	3.357	3.357																																																																													
25	3.357	3.356	3.356	3.356	3.356																																																																													
60	3.352	3.351	3.351	3.351	3.350																																																																													
65	3.350	3.350	3.349	3.349	3.348																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model	MGFS30243R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V7.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 36V

Load Current : 0 - 7.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	9	0	3.366	±8	±0.2
Minimum Voltage	60	36	7.5	3.350		

COSEL

Model	MGFS30243R3
Item	Time Lapse Drift
Object	+3.3V7.5A

1. Graph



Temperature 25°C
Testing Circuitry Figure A


2. Values

Time since start [H]	Output Voltage [V]
0.0	3.354
0.5	3.353
1.0	3.353
2.0	3.353
3.0	3.353
4.0	3.353
5.0	3.353
6.0	3.353
7.0	3.353
8.0	3.353

COSEL


Model	MGFS30243R3	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+3.3V7.5A	

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.2	3.2	4.4	0.1	0.3
100 %		1.3	3.5	4.8	0.1	0.1



Model	MGFS30243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V7.5A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.0	8.2
-40	8.0	8.1
-20	8.0	8.0
0	7.9	8.0
25	7.9	7.9
60	7.9	8.0
65	7.9	7.9
--	-	-
--	-	-
--	-	-
--	-	-


Model	MGFS30243R3	Temperature Testing Circuitry 25°C Figure A																																																																																							
Item	Overcurrent Protection																																																																																								
Object	+3.3V7.5A																																																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> △ Input Volt. 9V □ Input Volt. 12V * Input Volt. 18V ○ Input Volt. 24V ◇ Input Volt. 36V 	2.Values																																																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>9.065</td><td>9.057</td><td>9.161</td><td>9.158</td><td>9.048</td></tr> <tr><td>3.14</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.97</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.64</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.31</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.98</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.65</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.32</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.99</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.66</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.33</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	3.30	9.065	9.057	9.161	9.158	9.048	3.14	-	-	-	-	-	2.97	-	-	-	-	-	2.64	-	-	-	-	-	2.31	-	-	-	-	-	1.98	-	-	-	-	-	1.65	-	-	-	-	-	1.32	-	-	-	-	-	0.99	-	-	-	-	-	0.66	-	-	-	-	-	0.33	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																																				
3.30	9.065	9.057	9.161	9.158	9.048																																																																																				
3.14	-	-	-	-	-																																																																																				
2.97	-	-	-	-	-																																																																																				
2.64	-	-	-	-	-																																																																																				
2.31	-	-	-	-	-																																																																																				
1.98	-	-	-	-	-																																																																																				
1.65	-	-	-	-	-																																																																																				
1.32	-	-	-	-	-																																																																																				
0.99	-	-	-	-	-																																																																																				
0.66	-	-	-	-	-																																																																																				
0.33	-	-	-	-	-																																																																																				
0.00	-	-	-	-	-																																																																																				

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Model	MGFS30243R3
Item	Oversupply Protection
Object	+3.3V7.5A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-60	5.03	5.02
-40	4.95	4.95
-20	4.88	4.87
0	4.81	4.81
25	4.73	4.73
60	4.63	4.62
65	4.62	4.61
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)