

TEST DATA OF MGFS304812

Regulated DC Power Supply
December 25, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Masashi Ueda
Masashi Ueda

Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

Model	MGFS304812	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>10.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.0</td><td>0.000</td><td>0.000</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.041</td><td>0.998</td><td>2.014</td></tr> <tr><td>17.0</td><td>0.040</td><td>0.968</td><td>1.955</td></tr> <tr><td>17.5</td><td>0.040</td><td>0.940</td><td>1.898</td></tr> <tr><td>18.0</td><td>0.040</td><td>0.913</td><td>1.846</td></tr> <tr><td>24.0</td><td>0.036</td><td>0.689</td><td>1.383</td></tr> <tr><td>36.0</td><td>0.032</td><td>0.468</td><td>0.931</td></tr> <tr><td>48.0</td><td>0.030</td><td>0.358</td><td>0.705</td></tr> <tr><td>76.0</td><td>0.029</td><td>0.240</td><td>0.462</td></tr> <tr><td>80.0</td><td>0.029</td><td>0.230</td><td>0.442</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.000	0.000	0.000	10.0	0.000	0.000	0.000	15.0	0.000	0.000	0.002	16.0	0.002	0.002	0.002	16.5	0.041	0.998	2.014	17.0	0.040	0.968	1.955	17.5	0.040	0.940	1.898	18.0	0.040	0.913	1.846	24.0	0.036	0.689	1.383	36.0	0.032	0.468	0.931	48.0	0.030	0.358	0.705	76.0	0.029	0.240	0.462	80.0	0.029	0.230	0.442	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
5.0	0.000	0.000	0.000																																																																																
10.0	0.000	0.000	0.000																																																																																
15.0	0.000	0.000	0.002																																																																																
16.0	0.002	0.002	0.002																																																																																
16.5	0.041	0.998	2.014																																																																																
17.0	0.040	0.968	1.955																																																																																
17.5	0.040	0.940	1.898																																																																																
18.0	0.040	0.913	1.846																																																																																
24.0	0.036	0.689	1.383																																																																																
36.0	0.032	0.468	0.931																																																																																
48.0	0.030	0.358	0.705																																																																																
76.0	0.029	0.240	0.462																																																																																
80.0	0.029	0.230	0.442																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	MGFS304812																																																																																
Item	Input Current (by Load Current)																																																																																
Object	_____																																																																																
1.Graph	—△— Input Volt. 18V - - -□- - Input Volt. 24V - - -*--- Input Volt. 36V - - -○--- Input Volt. 48V - - -◇--- Input Volt. 76V																																																																																
Note: Slanted line shows the range of the rated load current.																																																																																	
Temperature	25°C																																																																																
Testing Circuitry	Figure A																																																																																
2.Values																																																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.040</td> <td>0.036</td> <td>0.032</td> <td>0.030</td> <td>0.029</td> </tr> <tr> <td>0.50</td> <td>0.384</td> <td>0.294</td> <td>0.204</td> <td>0.160</td> <td>0.113</td> </tr> <tr> <td>1.00</td> <td>0.736</td> <td>0.559</td> <td>0.380</td> <td>0.292</td> <td>0.198</td> </tr> <tr> <td>1.50</td> <td>1.102</td> <td>0.828</td> <td>0.561</td> <td>0.427</td> <td>0.284</td> </tr> <tr> <td>2.00</td> <td>1.473</td> <td>1.108</td> <td>0.746</td> <td>0.566</td> <td>0.373</td> </tr> <tr> <td>2.50</td> <td>1.858</td> <td>1.393</td> <td>0.938</td> <td>0.710</td> <td>0.466</td> </tr> <tr> <td>2.75</td> <td>2.062</td> <td>1.542</td> <td>1.037</td> <td>0.785</td> <td>0.518</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.040	0.036	0.032	0.030	0.029	0.50	0.384	0.294	0.204	0.160	0.113	1.00	0.736	0.559	0.380	0.292	0.198	1.50	1.102	0.828	0.561	0.427	0.284	2.00	1.473	1.108	0.746	0.566	0.373	2.50	1.858	1.393	0.938	0.710	0.466	2.75	2.062	1.542	1.037	0.785	0.518	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																												
0.00	0.040	0.036	0.032	0.030	0.029																																																																												
0.50	0.384	0.294	0.204	0.160	0.113																																																																												
1.00	0.736	0.559	0.380	0.292	0.198																																																																												
1.50	1.102	0.828	0.561	0.427	0.284																																																																												
2.00	1.473	1.108	0.746	0.566	0.373																																																																												
2.50	1.858	1.393	0.938	0.710	0.466																																																																												
2.75	2.062	1.542	1.037	0.785	0.518																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												

Model	MGFS304812																																																																								
Item	Input Power (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.72</td><td>0.86</td><td>1.16</td><td>1.45</td><td>2.24</td></tr> <tr><td>0.50</td><td>6.89</td><td>7.04</td><td>7.36</td><td>7.67</td><td>8.59</td></tr> <tr><td>1.00</td><td>13.22</td><td>13.36</td><td>13.67</td><td>14.02</td><td>15.03</td></tr> <tr><td>1.50</td><td>19.73</td><td>19.84</td><td>20.16</td><td>20.50</td><td>21.60</td></tr> <tr><td>2.00</td><td>26.42</td><td>26.50</td><td>26.78</td><td>27.16</td><td>28.35</td></tr> <tr><td>2.50</td><td>33.40</td><td>33.38</td><td>33.60</td><td>34.03</td><td>35.40</td></tr> <tr><td>2.75</td><td>37.00</td><td>36.91</td><td>37.20</td><td>37.61</td><td>39.40</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.72	0.86	1.16	1.45	2.24	0.50	6.89	7.04	7.36	7.67	8.59	1.00	13.22	13.36	13.67	14.02	15.03	1.50	19.73	19.84	20.16	20.50	21.60	2.00	26.42	26.50	26.78	27.16	28.35	2.50	33.40	33.38	33.60	34.03	35.40	2.75	37.00	36.91	37.20	37.61	39.40	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																				
0.00	0.72	0.86	1.16	1.45	2.24																																																																				
0.50	6.89	7.04	7.36	7.67	8.59																																																																				
1.00	13.22	13.36	13.67	14.02	15.03																																																																				
1.50	19.73	19.84	20.16	20.50	21.60																																																																				
2.00	26.42	26.50	26.78	27.16	28.35																																																																				
2.50	33.40	33.38	33.60	34.03	35.40																																																																				
2.75	37.00	36.91	37.20	37.61	39.40																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note:	Slanted line shows the range of the rated load current.																																																																								


Model	MGFS304812																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (10 to 90). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>17</td><td>91.3</td><td>89.4</td></tr> <tr><td>18</td><td>91.4</td><td>90.0</td></tr> <tr><td>24</td><td>90.8</td><td>90.1</td></tr> <tr><td>30</td><td>90.0</td><td>89.6</td></tr> <tr><td>36</td><td>89.0</td><td>89.5</td></tr> <tr><td>48</td><td>87.4</td><td>88.5</td></tr> <tr><td>60</td><td>85.4</td><td>86.9</td></tr> <tr><td>76</td><td>82.4</td><td>85.0</td></tr> <tr><td>80</td><td>81.7</td><td>84.0</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	17	91.3	89.4	18	91.4	90.0	24	90.8	90.1	30	90.0	89.6	36	89.0	89.5	48	87.4	88.5	60	85.4	86.9	76	82.4	85.0	80	81.7	84.0		
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
17	91.3	89.4																																
18	91.4	90.0																																
24	90.8	90.1																																
30	90.0	89.6																																
36	89.0	89.5																																
48	87.4	88.5																																
60	85.4	86.9																																
76	82.4	85.0																																
80	81.7	84.0																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>91.3</td><td>89.4</td></tr> <tr><td>18</td><td>91.4</td><td>90.0</td></tr> <tr><td>24</td><td>90.8</td><td>90.1</td></tr> <tr><td>30</td><td>90.0</td><td>89.6</td></tr> <tr><td>36</td><td>89.0</td><td>89.5</td></tr> <tr><td>48</td><td>87.4</td><td>88.5</td></tr> <tr><td>60</td><td>85.4</td><td>86.9</td></tr> <tr><td>76</td><td>82.4</td><td>85.0</td></tr> <tr><td>80</td><td>81.7</td><td>84.0</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	91.3	89.4	18	91.4	90.0	24	90.8	90.1	30	90.0	89.6	36	89.0	89.5	48	87.4	88.5	60	85.4	86.9	76	82.4	85.0	80	81.7	84.0
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	91.3	89.4																																
18	91.4	90.0																																
24	90.8	90.1																																
30	90.0	89.6																																
36	89.0	89.5																																
48	87.4	88.5																																
60	85.4	86.9																																
76	82.4	85.0																																
80	81.7	84.0																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	MGFS304812																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>The graph shows efficiency increasing with load current for all input voltages. A slanted line at approximately 2.2A indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.50</td><td>87.3</td><td>85.5</td><td>81.8</td><td>78.5</td><td>70.1</td></tr> <tr><td>1.00</td><td>91.1</td><td>90.2</td><td>88.1</td><td>85.9</td><td>80.2</td></tr> <tr><td>1.50</td><td>91.6</td><td>91.1</td><td>89.7</td><td>88.2</td><td>83.7</td></tr> <tr><td>2.00</td><td>91.2</td><td>90.9</td><td>90.0</td><td>88.7</td><td>85.0</td></tr> <tr><td>2.50</td><td>90.2</td><td>90.2</td><td>89.7</td><td>88.5</td><td>85.1</td></tr> <tr><td>2.75</td><td>89.5</td><td>89.8</td><td>89.1</td><td>88.1</td><td>84.1</td></tr> </tbody> </table>					Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.50	87.3	85.5	81.8	78.5	70.1	1.00	91.1	90.2	88.1	85.9	80.2	1.50	91.6	91.1	89.7	88.2	83.7	2.00	91.2	90.9	90.0	88.7	85.0	2.50	90.2	90.2	89.7	88.5	85.1	2.75	89.5	89.8	89.1	88.1	84.1																																			
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.50	87.3	85.5	81.8	78.5	70.1																																																																													
1.00	91.1	90.2	88.1	85.9	80.2																																																																													
1.50	91.6	91.1	89.7	88.2	83.7																																																																													
2.00	91.2	90.9	90.0	88.7	85.0																																																																													
2.50	90.2	90.2	89.7	88.5	85.1																																																																													
2.75	89.5	89.8	89.1	88.1	84.1																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>87.3</td><td>85.5</td><td>81.8</td><td>78.5</td><td>70.1</td></tr> <tr><td>1.00</td><td>91.1</td><td>90.2</td><td>88.1</td><td>85.9</td><td>80.2</td></tr> <tr><td>1.50</td><td>91.6</td><td>91.1</td><td>89.7</td><td>88.2</td><td>83.7</td></tr> <tr><td>2.00</td><td>91.2</td><td>90.9</td><td>90.0</td><td>88.7</td><td>85.0</td></tr> <tr><td>2.50</td><td>90.2</td><td>90.2</td><td>89.7</td><td>88.5</td><td>85.1</td></tr> <tr><td>2.75</td><td>89.5</td><td>89.8</td><td>89.1</td><td>88.1</td><td>84.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.50	87.3	85.5	81.8	78.5	70.1	1.00	91.1	90.2	88.1	85.9	80.2	1.50	91.6	91.1	89.7	88.2	83.7	2.00	91.2	90.9	90.0	88.7	85.0	2.50	90.2	90.2	89.7	88.5	85.1	2.75	89.5	89.8	89.1	88.1	84.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.50	87.3	85.5	81.8	78.5	70.1																																																																													
1.00	91.1	90.2	88.1	85.9	80.2																																																																													
1.50	91.6	91.1	89.7	88.2	83.7																																																																													
2.00	91.2	90.9	90.0	88.7	85.0																																																																													
2.50	90.2	90.2	89.7	88.5	85.1																																																																													
2.75	89.5	89.8	89.1	88.1	84.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	

Model	MGFS304812
Item	Line Regulation
Object	+12V2.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	12.018	12.017
18	12.018	12.018
24	12.018	12.018
30	12.018	12.018
36	12.018	12.018
48	12.017	12.018
60	12.017	12.017
76	12.017	12.017
80	12.017	12.017

Note: Slanted line shows the range of the rated input voltage.

Model	MGFS304812																																																																																	
Item	Load Regulation																																																																																	
Object	+12V2.5A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>12.020</td> <td>12.020</td> <td>12.020</td> <td>12.020</td> <td>12.020</td> </tr> <tr> <td>0.50</td> <td>12.019</td> <td>12.020</td> <td>12.020</td> <td>12.020</td> <td>12.020</td> </tr> <tr> <td>1.00</td> <td>12.019</td> <td>12.019</td> <td>12.019</td> <td>12.019</td> <td>12.019</td> </tr> <tr> <td>1.50</td> <td>12.018</td> <td>12.019</td> <td>12.019</td> <td>12.019</td> <td>12.018</td> </tr> <tr> <td>2.00</td> <td>12.018</td> <td>12.018</td> <td>12.018</td> <td>12.018</td> <td>12.018</td> </tr> <tr> <td>2.50</td> <td>12.017</td> <td>12.018</td> <td>12.018</td> <td>12.018</td> <td>12.017</td> </tr> <tr> <td>2.75</td> <td>12.017</td> <td>12.017</td> <td>12.017</td> <td>12.017</td> <td>12.017</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	12.020	12.020	12.020	12.020	12.020	0.50	12.019	12.020	12.020	12.020	12.020	1.00	12.019	12.019	12.019	12.019	12.019	1.50	12.018	12.019	12.019	12.019	12.018	2.00	12.018	12.018	12.018	12.018	12.018	2.50	12.017	12.018	12.018	12.018	12.017	2.75	12.017	12.017	12.017	12.017	12.017	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	12.020	12.020	12.020	12.020	12.020																																																																													
0.50	12.019	12.020	12.020	12.020	12.020																																																																													
1.00	12.019	12.019	12.019	12.019	12.019																																																																													
1.50	12.018	12.019	12.019	12.019	12.018																																																																													
2.00	12.018	12.018	12.018	12.018	12.018																																																																													
2.50	12.017	12.018	12.018	12.018	12.017																																																																													
2.75	12.017	12.017	12.017	12.017	12.017																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	

COSEL

COSEL


Model	MGFS304812																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	+12V2.5A																																						
1.Graph																																							
		2.Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>16</td><td>24</td></tr> <tr><td>0.50</td><td>15</td><td>24</td></tr> <tr><td>1.00</td><td>15</td><td>24</td></tr> <tr><td>1.50</td><td>15</td><td>24</td></tr> <tr><td>2.00</td><td>15</td><td>24</td></tr> <tr><td>2.50</td><td>15</td><td>24</td></tr> <tr><td>2.75</td><td>15</td><td>24</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	16	24	0.50	15	24	1.00	15	24	1.50	15	24	2.00	15	24	2.50	15	24	2.75	15	24	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 18 [V]	Input Volt. 76 [V]																																					
0.00	16	24																																					
0.50	15	24																																					
1.00	15	24																																					
1.50	15	24																																					
2.00	15	24																																					
2.50	15	24																																					
2.75	15	24																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																							
<p>Ripple [mVp-p]</p>																																							
Fig.Complex Ripple Wave Form																																							

Model	MGFS304812	Temperature	25°C																																			
Item	Ripple-Noise	Testing Circuitry	Figure B																																			
Object	+12V2.5A																																					
1.Graph			2.Values																																			
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 150 mV, and the X-axis ranges from 0.0 to 3.0 A. Two data series are plotted: Input Volt. 18V (triangles) and Input Volt. 76V (circles). Both series show a constant ripple voltage of approximately 25 mV across the load current range. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Voltage [mV] (Input Volt. 18V)</th> <th>Ripple-Voltage [mV] (Input Volt. 76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>25</td><td>25</td></tr> <tr><td>0.50</td><td>25</td><td>25</td></tr> <tr><td>1.00</td><td>25</td><td>25</td></tr> <tr><td>1.50</td><td>25</td><td>25</td></tr> <tr><td>2.00</td><td>25</td><td>25</td></tr> <tr><td>2.50</td><td>25</td><td>25</td></tr> <tr><td>2.75</td><td>25</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Voltage [mV] (Input Volt. 18V)	Ripple-Voltage [mV] (Input Volt. 76V)	0.0	25	25	0.50	25	25	1.00	25	25	1.50	25	25	2.00	25	25	2.50	25	25	2.75	25	25	--	-	-	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple-Voltage [mV] (Input Volt. 18V)	Ripple-Voltage [mV] (Input Volt. 76V)																																				
0.0	25	25																																				
0.50	25	25																																				
1.00	25	25																																				
1.50	25	25																																				
2.00	25	25																																				
2.50	25	25																																				
2.75	25	25																																				
--	-	-																																				
--	-	-																																				
--	-	-																																				
--	-	-																																				
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																						

COSEL

Model	MGFS304812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V2.5A

1. Graph



Testing Circuitry Figure B


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	36	37
-40	27	27
-20	18	18
0	18	18
25	18	18
60	17	18
65	17	18
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFS304812
Item	Ambient Temperature Drift
Object	+12V2.5A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	11.954	11.954	11.956	11.956	11.957
-40	11.977	11.977	11.978	11.978	11.979
-20	11.994	11.994	11.995	11.995	11.995
0	12.007	12.007	12.007	12.008	12.007
25	12.017	12.017	12.017	12.017	12.016
60	12.022	12.021	12.021	12.021	12.020
65	12.021	12.021	12.021	12.021	12.020
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS304812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V2.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 76V

Load Current : 0 - 2.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	36	0	12.025	±25	±0.2
Minimum Voltage	-40	76	0	11.976		

COSEL

Model	MGFS304812
Item	Time Lapse Drift
Object	+12V2.5A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Time since start [H]	Output Voltage [V]
0.0	12.017
0.5	12.026
1.0	12.026
2.0	12.026
3.0	12.026
4.0	12.026
5.0	12.026
6.0	12.026
7.0	12.026
8.0	12.026

COSEL

Model	MGFS304812
Item	Rise and Fall Time
Object	+12V2.5A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.2	9.1	10.3	3.2	1.1
100 %		1.2	9.2	10.4	1.6	0.4


[ms]



Model	MGFS304812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V2.5A

Testing Circuitry Figure A

1. Graph



2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.7	15.8
-40	15.7	15.8
-20	15.7	15.8
0	15.7	15.8
25	15.8	15.8
60	15.5	15.6
65	15.5	15.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFS304812	Temperature Testing Circuitry 25°C Figure A																																																																																							
Item	Overcurrent Protection																																																																																								
Object	+12V2.5A																																																																																								
1.Graph																																																																																									
		Note: Slanted line shows the range of the rated load current.																																																																																							
		Intermittent operation occurs when overcurrent protection is activated.																																																																																							
2.Values		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>12.0</td><td>3.208</td><td>3.365</td><td>3.521</td><td>3.465</td><td>3.202</td></tr> <tr> <td>11.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>10.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>9.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>7.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>4.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>3.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>2.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>1.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.0	3.208	3.365	3.521	3.465	3.202	11.4	-	-	-	-	-	10.8	-	-	-	-	-	9.6	-	-	-	-	-	8.4	-	-	-	-	-	7.2	-	-	-	-	-	6.0	-	-	-	-	-	4.8	-	-	-	-	-	3.6	-	-	-	-	-	2.4	-	-	-	-	-	1.2	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																																				
12.0	3.208	3.365	3.521	3.465	3.202																																																																																				
11.4	-	-	-	-	-																																																																																				
10.8	-	-	-	-	-																																																																																				
9.6	-	-	-	-	-																																																																																				
8.4	-	-	-	-	-																																																																																				
7.2	-	-	-	-	-																																																																																				
6.0	-	-	-	-	-																																																																																				
4.8	-	-	-	-	-																																																																																				
3.6	-	-	-	-	-																																																																																				
2.4	-	-	-	-	-																																																																																				
1.2	-	-	-	-	-																																																																																				
0.0	-	-	-	-	-																																																																																				

Model	MGFS304812
Item	Oversupply Protection
Object	+12V2.5A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-60	16.49	16.49
-40	16.58	16.58
-20	16.70	16.72
0	16.86	16.88
25	17.10	17.12
60	17.42	17.43
65	17.47	17.49
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)