

# TEST DATA OF MGFS400515

Regulated DC Power Supply  
November 29, 2018

Approved by : Junichi Hatagishi  
Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide  
Shohei Mukaide Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1  
 2.Input Current (by Load Current) . . . . . 2  
 3.Input Power (by Load Current) . . . . . 3  
 4.Efficiency (by Input Voltage) . . . . . 4  
 5.Efficiency (by Load Current) . . . . . 5  
 6.Line Regulation . . . . . 6  
 7.Load Regulation . . . . . 7  
 8.Dynamic Load Response . . . . . 8  
 9.Ripple Voltage (by Load Current) . . . . . 9  
 10.Ripple-Noise . . . . . 10  
 11.Ripple Voltage (by Ambient Temperature) . . . . . 11  
 12.Ambient Temperature Drift . . . . . 12  
 13.Output Voltage Accuracy . . . . . 13  
 14.Time Lapse Drift . . . . . 14  
 15.Rise and Fall Time . . . . . 15  
 16.Minimum Input Voltage for Regulated Output Voltage . . . . . 16  
 17.Overcurrent Protection . . . . . 17  
 18.Overvoltage Protection . . . . . 18  
 19.Switching frequency (by Load Current) . . . . . 19  
 20.Figure of Testing Circuitry . . . . . 20

(Final Page 20)



Model		MGFS400515		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object																																																																																				
1.Graph			2.Values																																																																																	
<p>Legend:          —△— Load 100%          - - - □ - - Load 50%          - · - ○ - · - Load 0%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.80</td><td>0.113</td><td>0.113</td><td>0.113</td></tr> <tr><td>3.90</td><td>0.111</td><td>4.454</td><td>9.343</td></tr> <tr><td>4.00</td><td>0.109</td><td>4.311</td><td>9.312</td></tr> <tr><td>4.10</td><td>0.107</td><td>4.183</td><td>8.917</td></tr> <tr><td>4.18</td><td>0.105</td><td>4.094</td><td>8.636</td></tr> <tr><td>4.20</td><td>0.105</td><td>4.074</td><td>8.589</td></tr> <tr><td>4.30</td><td>0.103</td><td>3.959</td><td>8.257</td></tr> <tr><td>4.40</td><td>0.102</td><td>3.853</td><td>8.037</td></tr> <tr><td>4.50</td><td>0.101</td><td>3.752</td><td>7.618</td></tr> <tr><td>5.00</td><td>0.093</td><td>3.414</td><td>6.830</td></tr> <tr><td>7.00</td><td>0.041</td><td>2.383</td><td>4.765</td></tr> <tr><td>9.00</td><td>0.032</td><td>1.881</td><td>3.687</td></tr> <tr><td>13.00</td><td>0.030</td><td>1.338</td><td>2.567</td></tr> <tr><td>15.00</td><td>0.030</td><td>1.185</td><td>2.247</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.00	0.000	0.000	0.000	3.80	0.113	0.113	0.113	3.90	0.111	4.454	9.343	4.00	0.109	4.311	9.312	4.10	0.107	4.183	8.917	4.18	0.105	4.094	8.636	4.20	0.105	4.074	8.589	4.30	0.103	3.959	8.257	4.40	0.102	3.853	8.037	4.50	0.101	3.752	7.618	5.00	0.093	3.414	6.830	7.00	0.041	2.383	4.765	9.00	0.032	1.881	3.687	13.00	0.030	1.338	2.567	15.00	0.030	1.185	2.247	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.00	0.000	0.000	0.000																																																																																	
3.80	0.113	0.113	0.113																																																																																	
3.90	0.111	4.454	9.343																																																																																	
4.00	0.109	4.311	9.312																																																																																	
4.10	0.107	4.183	8.917																																																																																	
4.18	0.105	4.094	8.636																																																																																	
4.20	0.105	4.074	8.589																																																																																	
4.30	0.103	3.959	8.257																																																																																	
4.40	0.102	3.853	8.037																																																																																	
4.50	0.101	3.752	7.618																																																																																	
5.00	0.093	3.414	6.830																																																																																	
7.00	0.041	2.383	4.765																																																																																	
9.00	0.032	1.881	3.687																																																																																	
13.00	0.030	1.338	2.567																																																																																	
15.00	0.030	1.185	2.247																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				




Model		MGFS400515		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> <li>—△— Input Volt. 4.5V</li> <li>---□--- Input Volt. 5V</li> <li>-·*·-·- Input Volt. 7V</li> <li>-·○·-·- Input Volt. 9V</li> <li>--◇-- Input Volt. 13V</li> </ul>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 7[V]</th> <th>Input Volt. 9[V]</th> <th>Input Volt. 13[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.101</td><td>0.093</td><td>0.041</td><td>0.032</td><td>0.030</td></tr> <tr><td>0.4</td><td>1.555</td><td>1.394</td><td>1.014</td><td>0.810</td><td>0.598</td></tr> <tr><td>0.8</td><td>2.995</td><td>2.674</td><td>1.926</td><td>1.523</td><td>1.082</td></tr> <tr><td>1.0</td><td>3.752</td><td>3.414</td><td>2.383</td><td>1.881</td><td>1.338</td></tr> <tr><td>1.2</td><td>4.529</td><td>4.011</td><td>2.840</td><td>2.233</td><td>1.588</td></tr> <tr><td>1.4</td><td>5.328</td><td>4.667</td><td>3.336</td><td>2.576</td><td>1.821</td></tr> <tr><td>1.6</td><td>6.083</td><td>5.354</td><td>3.794</td><td>2.954</td><td>2.073</td></tr> <tr><td>2.0</td><td>7.618</td><td>6.830</td><td>4.765</td><td>3.687</td><td>2.567</td></tr> <tr><td>2.2</td><td>8.686</td><td>7.700</td><td>5.246</td><td>4.082</td><td>2.829</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]					Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]	0.0	0.101	0.093	0.041	0.032	0.030	0.4	1.555	1.394	1.014	0.810	0.598	0.8	2.995	2.674	1.926	1.523	1.082	1.0	3.752	3.414	2.383	1.881	1.338	1.2	4.529	4.011	2.840	2.233	1.588	1.4	5.328	4.667	3.336	2.576	1.821	1.6	6.083	5.354	3.794	2.954	2.073	2.0	7.618	6.830	4.765	3.687	2.567	2.2	8.686	7.700	5.246	4.082	2.829	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]																																																																													
0.0	0.101	0.093	0.041	0.032	0.030																																																																													
0.4	1.555	1.394	1.014	0.810	0.598																																																																													
0.8	2.995	2.674	1.926	1.523	1.082																																																																													
1.0	3.752	3.414	2.383	1.881	1.338																																																																													
1.2	4.529	4.011	2.840	2.233	1.588																																																																													
1.4	5.328	4.667	3.336	2.576	1.821																																																																													
1.6	6.083	5.354	3.794	2.954	2.073																																																																													
2.0	7.618	6.830	4.765	3.687	2.567																																																																													
2.2	8.686	7.700	5.246	4.082	2.829																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



Model	MGFS400515
Item	Input Power (by Load Current)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A



Note: Slanted line shows the range of the rated load current.

2.Values


Load Current [A]	Input Power [W]				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]
0.0	0.45	0.47	0.29	0.29	0.39
0.4	7.00	7.01	7.16	7.34	7.83
0.8	13.63	13.59	13.61	13.70	14.11
1.0	16.80	16.68	16.66	16.70	17.03
1.2	20.36	20.23	20.08	20.17	20.63
1.4	23.91	23.69	23.41	23.43	23.83
1.6	27.52	27.24	26.78	26.73	27.05
2.0	35.03	34.58	33.68	33.45	33.61
2.2	39.19	38.47	37.23	36.88	36.94
--	-	-	-	-	-
--	-	-	-	-	-



Model	MGFS400515
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

1.Graph



Note: Slanted line shows the range of the rated input voltage.


2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.3	89.3	85.2
4.5	89.6	86.2
5.0	89.8	88.0
7.0	89.9	89.7
9.0	89.6	90.3
11.0	88.9	90.2
13.0	87.5	89.9
15.0	85.8	89.2
--	-	-



Model	MGFS400515
Item	Efficiency (by Load Current)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A



2.Values

Load Current [A]	Efficiency [%]				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]
0.0	-	-	-	-	-
0.4	86.8	86.8	85.1	83.0	77.7
0.8	88.8	89.1	89.1	88.4	85.9
1.0	89.6	89.8	89.9	89.6	87.5
1.2	89.2	89.7	90.3	90.0	88.0
1.4	88.5	89.4	90.4	90.4	88.8
1.6	87.9	88.9	90.3	90.5	89.3
2.0	86.2	88.0	89.7	90.3	89.9
2.2	84.8	86.8	89.3	90.1	89.9
--	-	-	-	-	-
--	-	-	-	-	-



<b>COSEL</b>																																			
Model	MGFS400515	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V2A																																		
<p>1.Graph</p> <div style="text-align: right;"> <p>---□--- Load 50%</p> <p>—△— Load 100%</p> </div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.3</td><td>15.109</td><td>15.106</td></tr> <tr><td>4.5</td><td>15.109</td><td>15.106</td></tr> <tr><td>5.0</td><td>15.107</td><td>15.106</td></tr> <tr><td>7.0</td><td>15.105</td><td>15.104</td></tr> <tr><td>9.0</td><td>15.102</td><td>15.102</td></tr> <tr><td>11.0</td><td>15.098</td><td>15.099</td></tr> <tr><td>13.0</td><td>15.096</td><td>15.095</td></tr> <tr><td>15.0</td><td>15.092</td><td>15.092</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.3	15.109	15.106	4.5	15.109	15.106	5.0	15.107	15.106	7.0	15.105	15.104	9.0	15.102	15.102	11.0	15.098	15.099	13.0	15.096	15.095	15.0	15.092	15.092	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
4.3	15.109	15.106																																	
4.5	15.109	15.106																																	
5.0	15.107	15.106																																	
7.0	15.105	15.104																																	
9.0	15.102	15.102																																	
11.0	15.098	15.099																																	
13.0	15.096	15.095																																	
15.0	15.092	15.092																																	
--	-	-																																	




<b>COSEL</b>																																																																																			
Model	MGFS400515	Temperature 25°C																																																																																	
Item	Load Regulation	Testing Circuitry Figure A																																																																																	
Object	+15V2A																																																																																		
1.Graph	<p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>-··*·-·- Input Volt. 7V</p> <p>-··○-·- Input Volt. 9V</p> <p>---◇--- Input Volt. 13V</p>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 7[V]</th> <th>Input Volt. 9[V]</th> <th>Input Volt. 13[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.112</td><td>15.109</td><td>15.113</td><td>15.114</td><td>15.114</td></tr> <tr><td>0.4</td><td>15.110</td><td>15.108</td><td>15.105</td><td>15.103</td><td>15.097</td></tr> <tr><td>0.8</td><td>15.109</td><td>15.107</td><td>15.105</td><td>15.102</td><td>15.097</td></tr> <tr><td>1.0</td><td>15.109</td><td>15.107</td><td>15.105</td><td>15.102</td><td>15.096</td></tr> <tr><td>1.2</td><td>15.109</td><td>15.107</td><td>15.105</td><td>15.102</td><td>15.096</td></tr> <tr><td>1.4</td><td>15.108</td><td>15.107</td><td>15.104</td><td>15.102</td><td>15.095</td></tr> <tr><td>1.6</td><td>15.107</td><td>15.106</td><td>15.104</td><td>15.102</td><td>15.095</td></tr> <tr><td>2.0</td><td>15.106</td><td>15.106</td><td>15.104</td><td>15.102</td><td>15.095</td></tr> <tr><td>2.2</td><td>15.106</td><td>15.105</td><td>15.104</td><td>15.102</td><td>15.095</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]	0.0	15.112	15.109	15.113	15.114	15.114	0.4	15.110	15.108	15.105	15.103	15.097	0.8	15.109	15.107	15.105	15.102	15.097	1.0	15.109	15.107	15.105	15.102	15.096	1.2	15.109	15.107	15.105	15.102	15.096	1.4	15.108	15.107	15.104	15.102	15.095	1.6	15.107	15.106	15.104	15.102	15.095	2.0	15.106	15.106	15.104	15.102	15.095	2.2	15.106	15.105	15.104	15.102	15.095	--	-	-	-	-	-	--	-	-	-	-	-
	Load Current [A]	Output Voltage [V]																																																																																	
		Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]																																																																													
	0.0	15.112	15.109	15.113	15.114	15.114																																																																													
	0.4	15.110	15.108	15.105	15.103	15.097																																																																													
	0.8	15.109	15.107	15.105	15.102	15.097																																																																													
	1.0	15.109	15.107	15.105	15.102	15.096																																																																													
	1.2	15.109	15.107	15.105	15.102	15.096																																																																													
	1.4	15.108	15.107	15.104	15.102	15.095																																																																													
	1.6	15.107	15.106	15.104	15.102	15.095																																																																													
	2.0	15.106	15.106	15.104	15.102	15.095																																																																													
	2.2	15.106	15.105	15.104	15.102	15.095																																																																													
	--	-	-	-	-	-																																																																													
	--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																			




Model		MGFS400515	
Item		Dynamic Load Response	
Object		+15V2A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 5 V  
Cycle 100 ms




Min.Load (0A) ←→  
Load 100% (2A)

200 mV/div




2 ms/div




2 ms/div

Min.Load (0A) ←→  
Load 50% (1A)

200 mV/div




2 ms/div




2 ms/div

Load 50% (1A) ←→  
Load 100% (2A)

200 mV/div



2 ms/div



2 ms/div



<p>Model MGFS400515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item</p>	<p>Ripple Voltage (by Load Current)</p>																																							
<p>Object</p>	<p>+15V2A</p>																																							
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 4.5V</p> <p>- - ○ - - Input Volt. 13V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>5</td><td>10</td></tr> <tr><td>0.8</td><td>5</td><td>15</td></tr> <tr><td>1.2</td><td>10</td><td>15</td></tr> <tr><td>1.6</td><td>20</td><td>10</td></tr> <tr><td>2.0</td><td>40</td><td>10</td></tr> <tr><td>2.2</td><td>65</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.0	5	5	0.4	5	10	0.8	5	15	1.2	10	15	1.6	20	10	2.0	40	10	2.2	65	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																						
0.0	5	5																																						
0.4	5	10																																						
0.8	5	15																																						
1.2	10	15																																						
1.6	20	10																																						
2.0	40	10																																						
2.2	65	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								




<p>Model MGFS400515</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +15V2A</p>																																								
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 4.5V</p> <p>-·-○-·- Input Volt. 13V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>10</td></tr> <tr><td>0.4</td><td>15</td><td>15</td></tr> <tr><td>0.8</td><td>15</td><td>20</td></tr> <tr><td>1.2</td><td>15</td><td>20</td></tr> <tr><td>1.6</td><td>25</td><td>20</td></tr> <tr><td>2.0</td><td>45</td><td>15</td></tr> <tr><td>2.2</td><td>70</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.0	15	10	0.4	15	15	0.8	15	20	1.2	15	20	1.6	25	20	2.0	45	15	2.2	70	15	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																						
0.0	15	10																																						
0.4	15	15																																						
0.8	15	20																																						
1.2	15	20																																						
1.6	25	20																																						
2.0	45	15																																						
2.2	70	15																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	MGFS400515
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V2A

Testing Circuitry Figure B

1. Graph



2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	55
-40	10	50
-20	10	40
25	10	35
60	5	30
85	5	25
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.  
 Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS400515
Item	Ambient Temperature Drift
Object	+15V2A

Testing Circuitry Figure A



Note: Slanted line shows the range of the rated ambient temperature.

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]
-60	14.999	15.002	15.004	15.004	14.998
-40	15.035	15.037	15.038	15.038	15.032
-20	15.063	15.065	15.065	15.064	15.059
0	15.084	15.085	15.085	15.084	15.078
25	15.101	15.102	15.102	15.100	15.095
55	15.111	15.112	15.111	15.110	15.104
65	15.111	15.111	15.111	15.109	15.104
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-



<b>COSEL</b>		Testing Circuitry Figure A
Model	MGFS400515	
Item	Output Voltage Accuracy	
Object	+15V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 4.5 - 13V

Load Current : 0 - 2A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ratio) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]		Ratio [%]
Maximum Voltage	55	13	0	15.121	±45	±0.3
Minimum Voltage	-40	13	2	15.032		




<b>COSEL</b>																								
Model	MGFS400515																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+15V2A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 5V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.102</td></tr> <tr><td>0.5</td><td>15.112</td></tr> <tr><td>1.0</td><td>15.112</td></tr> <tr><td>2.0</td><td>15.112</td></tr> <tr><td>3.0</td><td>15.112</td></tr> <tr><td>4.0</td><td>15.112</td></tr> <tr><td>5.0</td><td>15.112</td></tr> <tr><td>6.0</td><td>15.112</td></tr> <tr><td>7.0</td><td>15.112</td></tr> <tr><td>8.0</td><td>15.112</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.102	0.5	15.112	1.0	15.112	2.0	15.112	3.0	15.112	4.0	15.112	5.0	15.112	6.0	15.112	7.0	15.112	8.0	15.112
Time since start [H]	Output Voltage [V]																							
0.0	15.102																							
0.5	15.112																							
1.0	15.112																							
2.0	15.112																							
3.0	15.112																							
4.0	15.112																							
5.0	15.112																							
6.0	15.112																							
7.0	15.112																							
8.0	15.112																							



Model	MGFS400515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V2A		


1. Graph

Input Volt. 5 V



2. Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		7.5	4.6	12.1	0.4	8.1
100 %		7.5	5.1	12.6	0.3	3.3






Model	MGFS400515
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V2A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.6	3.7
-40	3.5	3.6
-20	3.5	3.6
0	3.4	3.6
25	3.4	3.7
55	3.4	3.6
65	3.3	3.6
--	-	-
--	-	-
--	-	-
--	-	-



<p>Model MGFS400515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																																																			
<p>Item Overcurrent Protection</p>																																																																																					
<p>Object +15V2A</p>																																																																																					
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>—△ Input Volt. 4.5V</p> <p>—□ Input Volt. 5V</p> <p>—* Input Volt. 7V</p> <p>—○ Input Volt. 9V</p> <p>—◇ Input Volt. 13V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 7[V]</th> <th>Input Volt. 9[V]</th> <th>Input Volt. 13[V]</th> </tr> </thead> <tbody> <tr> <td>15.0</td> <td>2.296</td> <td>2.380</td> <td>2.644</td> <td>2.728</td> <td>2.540</td> </tr> <tr> <td>14.3</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>13.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>10.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>9.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>7.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>6.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]	15.0	2.296	2.380	2.644	2.728	2.540	14.3	-	-	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	3.0	-	-	-	-	-	1.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 7[V]	Input Volt. 9[V]	Input Volt. 13[V]																																																																																
15.0	2.296	2.380	2.644	2.728	2.540																																																																																
14.3	-	-	-	-	-																																																																																
13.5	-	-	-	-	-																																																																																
12.0	-	-	-	-	-																																																																																
10.5	-	-	-	-	-																																																																																
9.0	-	-	-	-	-																																																																																
7.5	-	-	-	-	-																																																																																
6.0	-	-	-	-	-																																																																																
4.5	-	-	-	-	-																																																																																
3.0	-	-	-	-	-																																																																																
1.5	-	-	-	-	-																																																																																
0.0	-	-	-	-	-																																																																																



<p>Model MGFS400515</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item Overvoltage Protection</p>																																																					
<p>Object +15V2A</p>																																																					
<p>1.Graph</p> <p>                     —△— Input Volt. 4.5V                      ---□--- Input Volt. 5V                      -·-·*·-·- Input Volt. 13V                 </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Operating Point [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 13[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>135</td><td>135</td><td>137</td></tr> <tr><td>10</td><td>129</td><td>129</td><td>129</td></tr> <tr><td>20</td><td>130</td><td>130</td><td>130</td></tr> <tr><td>30</td><td>130</td><td>130</td><td>130</td></tr> <tr><td>40</td><td>130</td><td>131</td><td>131</td></tr> <tr><td>50</td><td>131</td><td>130</td><td>131</td></tr> <tr><td>60</td><td>130</td><td>131</td><td>130</td></tr> <tr><td>70</td><td>131</td><td>131</td><td>131</td></tr> <tr><td>80</td><td>132</td><td>130</td><td>131</td></tr> <tr><td>90</td><td>- ※</td><td>133</td><td>132</td></tr> <tr><td>100</td><td>- ※</td><td>- ※</td><td>132</td></tr> </tbody> </table> <p>※During this area, overcurrent protection activates.</p>	Load Ratio [%]	Operating Point [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]	0	135	135	137	10	129	129	129	20	130	130	130	30	130	130	130	40	130	131	131	50	131	130	131	60	130	131	130	70	131	131	131	80	132	130	131	90	- ※	133	132	100	- ※	- ※	132
Load Ratio [%]	Operating Point [%]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]																																																		
0	135	135	137																																																		
10	129	129	129																																																		
20	130	130	130																																																		
30	130	130	130																																																		
40	130	131	131																																																		
50	131	130	131																																																		
60	130	131	130																																																		
70	131	131	131																																																		
80	132	130	131																																																		
90	- ※	133	132																																																		
100	- ※	- ※	132																																																		




<b>COSEL</b>			
Model	MGFS400515	Temperature	25°C
Item	Switching frequency (by Load Current)	Testing Circuitry	Figure A
Object	15V2A		


1. Graph

———— Load Increase  
 - - - - - Load Decrease


Input Volt: 4.5V




Input Volt: 9V



Input Volt: 5V



Input Volt: 13V



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.  
 When load current is low, switching frequency becomes high and step down to low frequency at certain point.  
 There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.




Figure A




Figure B (Ripple and Ripple noise Characteristic)