

TEST DATA OF MGFS64812

Regulated DC Power Supply
December 6, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Current) 2

3.Input Power (by Load Current) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Current) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 9

10.Ripple-Noise 10

11.Ripple Voltage (by Ambient Temperature) 11

12.Ambient Temperature Drift 12

13.Output Voltage Accuracy 13

14.Time Lapse Drift 14

15.Rise and Fall Time 15

16.Minimum Input Voltage for Regulated Output Voltage 16

17.Overcurrent Protection 17

18.Switching frequency (by Load Current) 18

19.Figure of Testing Circuitry 19

(Final Page 19)



Model		MGFS64812		Temperature	25°C																																																																															
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																															
Object		_____																																																																																		
1.Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%	2.Values																																																																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>16.2</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>16.4</td><td>0.004</td><td>0.003</td><td>0.004</td></tr> <tr><td>16.6</td><td>0.003</td><td>0.004</td><td>0.003</td></tr> <tr><td>16.8</td><td>0.011</td><td>0.205</td><td>0.412</td></tr> <tr><td>17.0</td><td>0.010</td><td>0.204</td><td>0.406</td></tr> <tr><td>18.0</td><td>0.009</td><td>0.192</td><td>0.382</td></tr> <tr><td>24.0</td><td>0.008</td><td>0.144</td><td>0.283</td></tr> <tr><td>36.0</td><td>0.006</td><td>0.098</td><td>0.189</td></tr> <tr><td>48.0</td><td>0.005</td><td>0.074</td><td>0.141</td></tr> <tr><td>60.0</td><td>0.005</td><td>0.059</td><td>0.115</td></tr> <tr><td>76.0</td><td>0.003</td><td>0.048</td><td>0.091</td></tr> <tr><td>80.0</td><td>0.002</td><td>0.046</td><td>0.087</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	16.0	0.003	0.003	0.003	16.2	0.003	0.003	0.004	16.4	0.004	0.003	0.004	16.6	0.003	0.004	0.003	16.8	0.011	0.205	0.412	17.0	0.010	0.204	0.406	18.0	0.009	0.192	0.382	24.0	0.008	0.144	0.283	36.0	0.006	0.098	0.189	48.0	0.005	0.074	0.141	60.0	0.005	0.059	0.115	76.0	0.003	0.048	0.091	80.0	0.002	0.046	0.087	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
16.0	0.003	0.003	0.003																																																																																	
16.2	0.003	0.003	0.004																																																																																	
16.4	0.004	0.003	0.004																																																																																	
16.6	0.003	0.004	0.003																																																																																	
16.8	0.011	0.205	0.412																																																																																	
17.0	0.010	0.204	0.406																																																																																	
18.0	0.009	0.192	0.382																																																																																	
24.0	0.008	0.144	0.283																																																																																	
36.0	0.006	0.098	0.189																																																																																	
48.0	0.005	0.074	0.141																																																																																	
60.0	0.005	0.059	0.115																																																																																	
76.0	0.003	0.048	0.091																																																																																	
80.0	0.002	0.046	0.087																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		MGFS64812		Temperature 25°C																																																																													
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																													
Object		_____																																																																															
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V -·-·*·-·-·- Input Volt. 36V -·-·○-·-·- Input Volt. 48V -·-·◇-·-·- Input Volt. 76V 		2.Values																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.009</td><td>0.008</td><td>0.006</td><td>0.005</td><td>0.003</td></tr> <tr><td>0.10</td><td>0.082</td><td>0.062</td><td>0.043</td><td>0.033</td><td>0.022</td></tr> <tr><td>0.20</td><td>0.156</td><td>0.117</td><td>0.079</td><td>0.061</td><td>0.040</td></tr> <tr><td>0.30</td><td>0.230</td><td>0.172</td><td>0.114</td><td>0.087</td><td>0.057</td></tr> <tr><td>0.40</td><td>0.306</td><td>0.227</td><td>0.151</td><td>0.115</td><td>0.074</td></tr> <tr><td>0.50</td><td>0.382</td><td>0.283</td><td>0.189</td><td>0.141</td><td>0.091</td></tr> <tr><td>0.55</td><td>0.424</td><td>0.313</td><td>0.208</td><td>0.156</td><td>0.100</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.009	0.008	0.006	0.005	0.003	0.10	0.082	0.062	0.043	0.033	0.022	0.20	0.156	0.117	0.079	0.061	0.040	0.30	0.230	0.172	0.114	0.087	0.057	0.40	0.306	0.227	0.151	0.115	0.074	0.50	0.382	0.283	0.189	0.141	0.091	0.55	0.424	0.313	0.208	0.156	0.100	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Input Current [A]																																																																																
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																												
0.00	0.009	0.008	0.006	0.005	0.003																																																																												
0.10	0.082	0.062	0.043	0.033	0.022																																																																												
0.20	0.156	0.117	0.079	0.061	0.040																																																																												
0.30	0.230	0.172	0.114	0.087	0.057																																																																												
0.40	0.306	0.227	0.151	0.115	0.074																																																																												
0.50	0.382	0.283	0.189	0.141	0.091																																																																												
0.55	0.424	0.313	0.208	0.156	0.100																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												



Model		MGFS64812		Temperature 25°C																																																																														
Item		Input Power (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V ---*--- Input Volt. 36V ---○--- Input Volt. 48V ---◇--- Input Volt. 76V 		2.Values																																																																														
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.18</td><td>0.20</td><td>0.26</td><td>0.26</td><td>0.24</td></tr> <tr><td>0.10</td><td>1.48</td><td>1.49</td><td>1.55</td><td>1.57</td><td>1.64</td></tr> <tr><td>0.20</td><td>2.79</td><td>2.80</td><td>2.83</td><td>2.91</td><td>3.04</td></tr> <tr><td>0.30</td><td>4.13</td><td>4.12</td><td>4.13</td><td>4.18</td><td>4.35</td></tr> <tr><td>0.40</td><td>5.48</td><td>5.44</td><td>5.46</td><td>5.52</td><td>5.65</td></tr> <tr><td>0.50</td><td>6.87</td><td>6.80</td><td>6.81</td><td>6.82</td><td>6.94</td></tr> <tr><td>0.55</td><td>7.59</td><td>7.50</td><td>7.49</td><td>7.50</td><td>7.59</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.18	0.20	0.26	0.26	0.24	0.10	1.48	1.49	1.55	1.57	1.64	0.20	2.79	2.80	2.83	2.91	3.04	0.30	4.13	4.12	4.13	4.18	4.35	0.40	5.48	5.44	5.46	5.52	5.65	0.50	6.87	6.80	6.81	6.82	6.94	0.55	7.59	7.50	7.49	7.50	7.59	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	0.18	0.20	0.26	0.26	0.24																																																																													
0.10	1.48	1.49	1.55	1.57	1.64																																																																													
0.20	2.79	2.80	2.83	2.91	3.04																																																																													
0.30	4.13	4.12	4.13	4.18	4.35																																																																													
0.40	5.48	5.44	5.46	5.52	5.65																																																																													
0.50	6.87	6.80	6.81	6.82	6.94																																																																													
0.55	7.59	7.50	7.49	7.50	7.59																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



<p>Model MGFS64812</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item</p>	<p>Efficiency (by Input Voltage)</p>																																	
<p>Object</p>	<p>_____</p>																																	
<p>1.Graph</p>		<p>2.Values</p>																																
<p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>86.9</td><td>87.1</td></tr> <tr><td>18</td><td>87.0</td><td>87.6</td></tr> <tr><td>24</td><td>87.1</td><td>88.4</td></tr> <tr><td>30</td><td>86.4</td><td>88.6</td></tr> <tr><td>36</td><td>85.9</td><td>88.4</td></tr> <tr><td>48</td><td>84.8</td><td>88.3</td></tr> <tr><td>60</td><td>83.9</td><td>88.2</td></tr> <tr><td>76</td><td>82.3</td><td>87.3</td></tr> <tr><td>80</td><td>82.0</td><td>87.0</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	86.9	87.1	18	87.0	87.6	24	87.1	88.4	30	86.4	88.6	36	85.9	88.4	48	84.8	88.3	60	83.9	88.2	76	82.3	87.3	80	82.0	87.0
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	86.9	87.1																																
18	87.0	87.6																																
24	87.1	88.4																																
30	86.4	88.6																																
36	85.9	88.4																																
48	84.8	88.3																																
60	83.9	88.2																																
76	82.3	87.3																																
80	82.0	87.0																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



Model		MGFS64812		Temperature 25°C																																																																														
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<ul style="list-style-type: none"> —△— Input Volt. 18V ---□--- Input Volt. 24V ---*--- Input Volt. 36V ---○--- Input Volt. 48V ---◇--- Input Volt. 76V 		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.10</td><td>81.2</td><td>80.6</td><td>77.7</td><td>76.9</td><td>73.5</td></tr> <tr><td>0.20</td><td>86.0</td><td>85.8</td><td>85.0</td><td>82.9</td><td>79.3</td></tr> <tr><td>0.30</td><td>87.5</td><td>87.5</td><td>87.6</td><td>86.3</td><td>83.0</td></tr> <tr><td>0.40</td><td>87.9</td><td>88.5</td><td>88.3</td><td>87.2</td><td>85.2</td></tr> <tr><td>0.50</td><td>87.6</td><td>88.4</td><td>88.4</td><td>88.3</td><td>87.3</td></tr> <tr><td>0.55</td><td>87.2</td><td>88.3</td><td>88.4</td><td>88.3</td><td>87.3</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.10	81.2	80.6	77.7	76.9	73.5	0.20	86.0	85.8	85.0	82.9	79.3	0.30	87.5	87.5	87.6	86.3	83.0	0.40	87.9	88.5	88.3	87.2	85.2	0.50	87.6	88.4	88.4	88.3	87.3	0.55	87.2	88.3	88.4	88.3	87.3	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.10	81.2	80.6	77.7	76.9	73.5																																																																													
0.20	86.0	85.8	85.0	82.9	79.3																																																																													
0.30	87.5	87.5	87.6	86.3	83.0																																																																													
0.40	87.9	88.5	88.3	87.2	85.2																																																																													
0.50	87.6	88.4	88.4	88.3	87.3																																																																													
0.55	87.2	88.3	88.4	88.3	87.3																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



<p>Model MGFS64812</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
<p>Item Line Regulation</p>																																		
<p>Object +12V0.5A</p>																																		
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>11.998</td><td>11.999</td></tr> <tr><td>18</td><td>11.998</td><td>12.000</td></tr> <tr><td>24</td><td>11.998</td><td>12.000</td></tr> <tr><td>30</td><td>11.998</td><td>12.000</td></tr> <tr><td>36</td><td>11.998</td><td>12.000</td></tr> <tr><td>48</td><td>11.998</td><td>12.000</td></tr> <tr><td>60</td><td>11.997</td><td>12.000</td></tr> <tr><td>76</td><td>11.997</td><td>12.000</td></tr> <tr><td>80</td><td>11.997</td><td>12.000</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	11.998	11.999	18	11.998	12.000	24	11.998	12.000	30	11.998	12.000	36	11.998	12.000	48	11.998	12.000	60	11.997	12.000	76	11.997	12.000	80	11.997	12.000
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
17	11.998	11.999																																
18	11.998	12.000																																
24	11.998	12.000																																
30	11.998	12.000																																
36	11.998	12.000																																
48	11.998	12.000																																
60	11.997	12.000																																
76	11.997	12.000																																
80	11.997	12.000																																




Model		MGFS64812		Temperature 25°C																																																																														
Item		Load Regulation		Testing Circuitry Figure A																																																																														
Object		+12V0.5A																																																																																
1.Graph			—△— Input Volt. 18V	2.Values																																																																														
			---□--- Input Volt. 24V																																																																															
			---*--- Input Volt. 36V																																																																															
			---○--- Input Volt. 48V																																																																															
			---◇--- Input Volt. 76V																																																																															
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.010</td><td>12.009</td><td>12.009</td><td>12.008</td><td>12.010</td></tr> <tr><td>0.10</td><td>12.008</td><td>12.008</td><td>12.007</td><td>12.006</td><td>12.005</td></tr> <tr><td>0.20</td><td>12.007</td><td>12.006</td><td>12.005</td><td>12.005</td><td>12.004</td></tr> <tr><td>0.30</td><td>12.005</td><td>12.005</td><td>12.004</td><td>12.004</td><td>12.003</td></tr> <tr><td>0.40</td><td>12.004</td><td>12.004</td><td>12.003</td><td>12.003</td><td>12.002</td></tr> <tr><td>0.50</td><td>12.002</td><td>12.002</td><td>12.002</td><td>12.002</td><td>12.001</td></tr> <tr><td>0.55</td><td>12.001</td><td>12.002</td><td>12.001</td><td>12.001</td><td>12.000</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	12.010	12.009	12.009	12.008	12.010	0.10	12.008	12.008	12.007	12.006	12.005	0.20	12.007	12.006	12.005	12.005	12.004	0.30	12.005	12.005	12.004	12.004	12.003	0.40	12.004	12.004	12.003	12.003	12.002	0.50	12.002	12.002	12.002	12.002	12.001	0.55	12.001	12.002	12.001	12.001	12.000	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	12.010	12.009	12.009	12.008	12.010																																																																													
0.10	12.008	12.008	12.007	12.006	12.005																																																																													
0.20	12.007	12.006	12.005	12.005	12.004																																																																													
0.30	12.005	12.005	12.004	12.004	12.003																																																																													
0.40	12.004	12.004	12.003	12.003	12.002																																																																													
0.50	12.002	12.002	12.002	12.002	12.001																																																																													
0.55	12.001	12.002	12.001	12.001	12.000																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																		



Model		MGFS64812	
Item		Dynamic Load Response	
Object		+12V0.5A	
		Temperature	25°C
		Testing Circuitry	Figure A

Input Volt. 48 V
Cycle 100 ms


t1, t2 = 100 μs



Min. Load (0A) ←→
Load 100% (0.5A)

500 mV/div

2 ms/div





2 ms/div

Min. Load (0A) ←→
Load 50% (0.25A)

500 mV/div

2 ms/div





2 ms/div

Load 50% (0.25A) ←→
Load 100% (0.5A)

500 mV/div

2 ms/div



2 ms/div



COSEL																																								
Model	MGFS64812																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.5A																																							
<p>1.Graph</p> <p> —△— Input Volt. 18V - - ○ - - Input Volt. 76V </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>20</td></tr> <tr><td>0.10</td><td>5</td><td>5</td></tr> <tr><td>0.20</td><td>5</td><td>5</td></tr> <tr><td>0.30</td><td>5</td><td>5</td></tr> <tr><td>0.40</td><td>10</td><td>5</td></tr> <tr><td>0.50</td><td>15</td><td>5</td></tr> <tr><td>0.55</td><td>20</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	20	0.10	5	5	0.20	5	5	0.30	5	5	0.40	10	5	0.50	15	5	0.55	20	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	20																																						
0.10	5	5																																						
0.20	5	5																																						
0.30	5	5																																						
0.40	10	5																																						
0.50	15	5																																						
0.55	20	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGFS64812</p> <p>Item Ripple-Noise</p> <p>Object +12V0.5A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p> —△— Input Volt. 18V - - -○- - - Input Volt. 76V </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>20</td></tr> <tr><td>0.10</td><td>5</td><td>5</td></tr> <tr><td>0.20</td><td>5</td><td>10</td></tr> <tr><td>0.30</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.50</td><td>20</td><td>10</td></tr> <tr><td>0.55</td><td>25</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	20	0.10	5	5	0.20	5	10	0.30	10	10	0.40	10	10	0.50	20	10	0.55	25	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	20																																						
0.10	5	5																																						
0.20	5	10																																						
0.30	10	10																																						
0.40	10	10																																						
0.50	20	10																																						
0.55	25	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								




COSEL																																								
Model	MGFS64812																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+12V0.5A																																							
<p>1.Graph</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 48V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>5</td></tr> <tr><td>-40</td><td>5</td><td>5</td></tr> <tr><td>-20</td><td>5</td><td>5</td></tr> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>25</td><td>5</td><td>5</td></tr> <tr><td>80</td><td>5</td><td>5</td></tr> <tr><td>90</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	5	-40	5	5	-20	5	5	0	5	5	25	5	5	80	5	5	90	5	5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	5	5																																						
-40	5	5																																						
-20	5	5																																						
0	5	5																																						
25	5	5																																						
80	5	5																																						
90	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



Model	MGFS64812
Item	Ambient Temperature Drift
Object	+12V0.5A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	11.888	11.890	11.891	11.893	11.893
-40	11.923	11.925	11.926	11.928	11.928
-20	11.954	11.955	11.956	11.957	11.957
0	11.977	11.978	11.979	11.979	11.979
25	11.997	11.998	11.998	11.998	11.998
80	12.011	12.012	12.012	12.012	12.012
90	12.011	12.012	12.012	12.012	12.012
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL		
Model	MGFS64812	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V0.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 18 - 76V

Load Current : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	76	0	12.021	±49	±0.4
Minimum Voltage	-40	18	0.5	11.923		



COSEL																								
Model	MGFS64812																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+12V0.5A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.993</td></tr> <tr><td>0.5</td><td>12.000</td></tr> <tr><td>1.0</td><td>12.000</td></tr> <tr><td>2.0</td><td>12.000</td></tr> <tr><td>3.0</td><td>12.000</td></tr> <tr><td>4.0</td><td>12.000</td></tr> <tr><td>5.0</td><td>12.000</td></tr> <tr><td>6.0</td><td>12.000</td></tr> <tr><td>7.0</td><td>12.000</td></tr> <tr><td>8.0</td><td>12.000</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	11.993	0.5	12.000	1.0	12.000	2.0	12.000	3.0	12.000	4.0	12.000	5.0	12.000	6.0	12.000	7.0	12.000	8.0	12.000
Time since start [H]	Output Voltage [V]																							
0.0	11.993																							
0.5	12.000																							
1.0	12.000																							
2.0	12.000																							
3.0	12.000																							
4.0	12.000																							
5.0	12.000																							
6.0	12.000																							
7.0	12.000																							
8.0	12.000																							




Model		MGFS64812	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V0.5A		



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.4	0.4	1.8	0.2	3.7
100 %	1.4	0.6	2.0	0.1	1.9

[ms]





COSEL																																								
Model	MGFS64812																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+12V0.5A																																							
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>15.1</td><td>15.2</td></tr> <tr><td>-40</td><td>15.0</td><td>15.1</td></tr> <tr><td>-20</td><td>15.0</td><td>15.1</td></tr> <tr><td>0</td><td>14.9</td><td>15.0</td></tr> <tr><td>25</td><td>14.8</td><td>14.9</td></tr> <tr><td>80</td><td>14.4</td><td>14.5</td></tr> <tr><td>90</td><td>14.0</td><td>13.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	15.1	15.2	-40	15.0	15.1	-20	15.0	15.1	0	14.9	15.0	25	14.8	14.9	80	14.4	14.5	90	14.0	13.9	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	15.1	15.2																																						
-40	15.0	15.1																																						
-20	15.0	15.1																																						
0	14.9	15.0																																						
25	14.8	14.9																																						
80	14.4	14.5																																						
90	14.0	13.9																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model MGFS64812</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																																																			
<p>Item Overcurrent Protection</p>																																																																																					
<p>Object +12V0.5A</p>																																																																																					
<p>1.Graph</p> <div style="display: flex; align-items: flex-start;"> <div style="margin-right: 20px;"> <p>— Input Volt. 18V</p> <p>— Input Volt. 24V</p> <p>— Input Volt. 36V</p> <p>— Input Volt. 48V</p> <p>— Input Volt. 76V</p> </div> </div> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.639</td><td>0.640</td><td>0.644</td><td>0.668</td><td>0.722</td></tr> <tr><td>10.8</td><td>0.668</td><td>0.668</td><td>0.671</td><td>0.693</td><td>0.742</td></tr> <tr><td>9.6</td><td>0.734</td><td>0.725</td><td>0.729</td><td>0.744</td><td>0.781</td></tr> <tr><td>8.4</td><td>0.808</td><td>0.793</td><td>0.790</td><td>0.794</td><td>0.815</td></tr> <tr><td>7.2</td><td>0.895</td><td>0.870</td><td>0.852</td><td>0.850</td><td>0.864</td></tr> <tr><td>6.0</td><td>0.996</td><td>0.958</td><td>0.919</td><td>0.911</td><td>0.917</td></tr> <tr><td>4.8</td><td>1.102</td><td>1.051</td><td>0.995</td><td>0.978</td><td>0.974</td></tr> <tr><td>3.6</td><td>1.208</td><td>1.164</td><td>1.078</td><td>1.052</td><td>1.034</td></tr> <tr><td>2.4</td><td>1.376</td><td>1.305</td><td>1.175</td><td>1.130</td><td>1.092</td></tr> <tr><td>1.2</td><td>1.458</td><td>1.406</td><td>1.257</td><td>1.195</td><td>1.138</td></tr> <tr><td>0.0</td><td>1.813</td><td>1.600</td><td>1.386</td><td>1.247</td><td>1.129</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	11.4	0.639	0.640	0.644	0.668	0.722	10.8	0.668	0.668	0.671	0.693	0.742	9.6	0.734	0.725	0.729	0.744	0.781	8.4	0.808	0.793	0.790	0.794	0.815	7.2	0.895	0.870	0.852	0.850	0.864	6.0	0.996	0.958	0.919	0.911	0.917	4.8	1.102	1.051	0.995	0.978	0.974	3.6	1.208	1.164	1.078	1.052	1.034	2.4	1.376	1.305	1.175	1.130	1.092	1.2	1.458	1.406	1.257	1.195	1.138	0.0	1.813	1.600	1.386	1.247	1.129	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																																
11.4	0.639	0.640	0.644	0.668	0.722																																																																																
10.8	0.668	0.668	0.671	0.693	0.742																																																																																
9.6	0.734	0.725	0.729	0.744	0.781																																																																																
8.4	0.808	0.793	0.790	0.794	0.815																																																																																
7.2	0.895	0.870	0.852	0.850	0.864																																																																																
6.0	0.996	0.958	0.919	0.911	0.917																																																																																
4.8	1.102	1.051	0.995	0.978	0.974																																																																																
3.6	1.208	1.164	1.078	1.052	1.034																																																																																
2.4	1.376	1.305	1.175	1.130	1.092																																																																																
1.2	1.458	1.406	1.257	1.195	1.138																																																																																
0.0	1.813	1.600	1.386	1.247	1.129																																																																																
--	-	-	-	-	-																																																																																



<p>Model MGFS64812</p>		<p>Temperature 25°C</p>																																																																														
<p>Item Switching frequency (by Load Current)</p>		<p>Testing Circuitry Figure A</p>																																																																														
<p>Object +12V0.5A</p>																																																																																
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - Input Volt. 24V - · · * · · - · - Input Volt. 36V - · · ○ · · - · - Input Volt. 48V - - ◇ - - Input Volt. 76V </p> <p>Switching Frequency [kHz]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>504</td><td>579</td><td>673</td><td>728</td><td>777</td></tr> <tr><td>0.10</td><td>353</td><td>428</td><td>530</td><td>595</td><td>668</td></tr> <tr><td>0.20</td><td>270</td><td>340</td><td>436</td><td>498</td><td>575</td></tr> <tr><td>0.30</td><td>218</td><td>280</td><td>369</td><td>429</td><td>504</td></tr> <tr><td>0.40</td><td>183</td><td>238</td><td>320</td><td>377</td><td>449</td></tr> <tr><td>0.50</td><td>157</td><td>207</td><td>283</td><td>335</td><td>405</td></tr> <tr><td>0.55</td><td>147</td><td>195</td><td>267</td><td>317</td><td>386</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	504	579	673	728	777	0.10	353	428	530	595	668	0.20	270	340	436	498	575	0.30	218	280	369	429	504	0.40	183	238	320	377	449	0.50	157	207	283	335	405	0.55	147	195	267	317	386	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																											
0.00	504	579	673	728	777																																																																											
0.10	353	428	530	595	668																																																																											
0.20	270	340	436	498	575																																																																											
0.30	218	280	369	429	504																																																																											
0.40	183	238	320	377	449																																																																											
0.50	157	207	283	335	405																																																																											
0.55	147	195	267	317	386																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)