

TEST DATA OF MGFS802412

Regulated DC Power Supply
April 5, 2019

Approved by : Junichi Hatagishi
Junichi Hatagishi Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.




CONTENTS

| | |
|---|----|
| 1.Input Current (by Input Voltage) · · · · · | 1 |
| 2.Input Current (by Load Current) · · · · · | 2 |
| 3.Input Power (by Load Current) · · · · · | 3 |
| 4.Efficiency (by Input Voltage) · · · · · | 4 |
| 5.Efficiency (by Load Current) · · · · · | 5 |
| 6.Line Regulation · · · · · | 6 |
| 7.Load Regulation · · · · · | 7 |
| 8.Dynamic Load Response · · · · · | 8 |
| 9.Ripple Voltage (by Load Current) · · · · · | 9 |
| 10.Ripple-Noise · · · · · | 10 |
| 11.Ripple Voltage (by Ambient Temperature) · · · · · | 11 |
| 12.Ambient Temperature Drift · · · · · | 12 |
| 13.Output Voltage Accuracy · · · · · | 13 |
| 14.Time Lapse Drift · · · · · | 14 |
| 15.Rise and Fall Time · · · · · | 15 |
| 16.Minimum Input Voltage for Regulated Output Voltage · · · · · | 16 |
| 17.Overcurrent Protection · · · · · | 17 |
| 18.Overvoltage Protection · · · · · | 18 |
| 19.Switching frequency (by Load Current) · · · · · | 19 |
| 20.Figure of Testing Circuitry · · · · · | 20 |

(Final Page 20)

COSEL

| | |
|--------|----------------------------------|
| Model | MGFS802412 |
| Item | Input Current (by Input Voltage) |
| Object | _____ |



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

| Input Voltage [V] | Input Current [A] | | |
|-------------------|-------------------|----------|-----------|
| | Load 0% | Load 50% | Load 100% |
| 0.0 | 0.000 | 0.000 | 0.000 |
| 7.6 | 0.001 | 0.001 | -※ |
| 7.8 | 0.001 | 0.001 | -※ |
| 8.0 | 0.001 | 0.001 | -※ |
| 8.2 | 0.001 | 0.001 | -※ |
| 8.4 | 0.102 | 5.233 | -※ |
| 8.6 | 0.100 | 5.084 | -※ |
| 8.8 | 0.098 | 4.978 | -※ |
| 9.0 | 0.096 | 4.849 | -※ |
| 12.0 | 0.077 | 3.626 | -※ |
| 18.0 | 0.058 | 2.407 | 4.779 |
| 24.0 | 0.058 | 1.809 | 3.576 |
| 36.0 | 0.013 | 1.212 | 2.381 |
| 40.0 | 0.013 | 1.095 | 2.144 |
| -- | - | - | - |
| -- | - | - | - |
| -- | - | - | - |
| -- | - | - | - |

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

COSEL

| Model | MGFS802412 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|-------|-------|-------|-------|------------------|-------------------|-------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|-------|-------|-------|-------|-------|-----|-----|-------|-------|-------|-------|-----|-----|-------|-------|-------|----|----|---|---|---|---|----|----|---|---|---|---|----|---|---|---|---|---|
| Item | Input Current (by Load Current) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | <p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - -□-- Input Volt. 12V - ·*·— Input Volt. 18V - ·○·— Input Volt. 24V - ·◇·— Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.096</td><td>0.077</td><td>0.058</td><td>0.058</td><td>0.013</td></tr> <tr><td>1.3</td><td>1.899</td><td>1.424</td><td>0.963</td><td>0.730</td><td>0.496</td></tr> <tr><td>2.7</td><td>3.851</td><td>2.898</td><td>1.940</td><td>1.463</td><td>0.991</td></tr> <tr><td>4.0</td><td>5.749</td><td>4.265</td><td>2.845</td><td>2.147</td><td>1.442</td></tr> <tr><td>4.7</td><td>6.766</td><td>5.064</td><td>3.334</td><td>2.509</td><td>1.686</td></tr> <tr><td>5.4</td><td>-※1</td><td>5.808</td><td>3.828</td><td>2.874</td><td>1.927</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>4.779</td><td>3.576</td><td>2.381</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>5.277</td><td>3.938</td><td>2.630</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | | | | | Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | 0.096 | 0.077 | 0.058 | 0.058 | 0.013 | 1.3 | 1.899 | 1.424 | 0.963 | 0.730 | 0.496 | 2.7 | 3.851 | 2.898 | 1.940 | 1.463 | 0.991 | 4.0 | 5.749 | 4.265 | 2.845 | 2.147 | 1.442 | 4.7 | 6.766 | 5.064 | 3.334 | 2.509 | 1.686 | 5.4 | -※1 | 5.808 | 3.828 | 2.874 | 1.927 | 6.7 | -※1 | -※2 | 4.779 | 3.576 | 2.381 | 7.4 | -※1 | -※2 | 5.277 | 3.938 | 2.630 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - | | | | | |
| Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 0.096 | 0.077 | 0.058 | 0.058 | 0.013 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 1.899 | 1.424 | 0.963 | 0.730 | 0.496 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 3.851 | 2.898 | 1.940 | 1.463 | 0.991 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 5.749 | 4.265 | 2.845 | 2.147 | 1.442 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 6.766 | 5.064 | 3.334 | 2.509 | 1.686 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 5.808 | 3.828 | 2.874 | 1.927 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 4.779 | 3.576 | 2.381 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 5.277 | 3.938 | 2.630 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.096</td><td>0.077</td><td>0.058</td><td>0.058</td><td>0.013</td></tr> <tr><td>1.3</td><td>1.899</td><td>1.424</td><td>0.963</td><td>0.730</td><td>0.496</td></tr> <tr><td>2.7</td><td>3.851</td><td>2.898</td><td>1.940</td><td>1.463</td><td>0.991</td></tr> <tr><td>4.0</td><td>5.749</td><td>4.265</td><td>2.845</td><td>2.147</td><td>1.442</td></tr> <tr><td>4.7</td><td>6.766</td><td>5.064</td><td>3.334</td><td>2.509</td><td>1.686</td></tr> <tr><td>5.4</td><td>-※1</td><td>5.808</td><td>3.828</td><td>2.874</td><td>1.927</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>4.779</td><td>3.576</td><td>2.381</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>5.277</td><td>3.938</td><td>2.630</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | | | | | Load Current [A] | Input Current [A] | | | | | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | 0.096 | 0.077 | 0.058 | 0.058 | 0.013 | 1.3 | 1.899 | 1.424 | 0.963 | 0.730 | 0.496 | 2.7 | 3.851 | 2.898 | 1.940 | 1.463 | 0.991 | 4.0 | 5.749 | 4.265 | 2.845 | 2.147 | 1.442 | 4.7 | 6.766 | 5.064 | 3.334 | 2.509 | 1.686 | 5.4 | -※1 | 5.808 | 3.828 | 2.874 | 1.927 | 6.7 | -※1 | -※2 | 4.779 | 3.576 | 2.381 | 7.4 | -※1 | -※2 | 5.277 | 3.938 | 2.630 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - |
| Load Current [A] | Input Current [A] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 0.096 | 0.077 | 0.058 | 0.058 | 0.013 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 1.899 | 1.424 | 0.963 | 0.730 | 0.496 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 3.851 | 2.898 | 1.940 | 1.463 | 0.991 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 5.749 | 4.265 | 2.845 | 2.147 | 1.442 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 6.766 | 5.064 | 3.334 | 2.509 | 1.686 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 5.808 | 3.828 | 2.874 | 1.927 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 4.779 | 3.576 | 2.381 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 5.277 | 3.938 | 2.630 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: Slanted line shows the range of the rated load current. | <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL


| Model | MGFS802412 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------------|--|------------------|-------|-------|-------|-------|-------|-----|------|------|------|------|------|-----|-------|-------|-------|-------|-------|-----|-------|-------|-------|-------|-------|-----|-------|-------|-------|-------|-------|-----|-------|-------|-------|-------|-------|-----|-----|-------|-------|-------|-------|-----|-----|-----|-------|-------|-------|-----|-----|-----|-------|-------|-------|----|---|---|---|---|---|----|---|---|---|---|---|----|---|---|---|---|---|
| Item | Input Power (by Load Current) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.87</td><td>0.93</td><td>1.07</td><td>0.80</td><td>0.46</td></tr> <tr><td>1.3</td><td>17.18</td><td>17.22</td><td>17.38</td><td>17.53</td><td>17.90</td></tr> <tr><td>2.7</td><td>35.00</td><td>34.99</td><td>35.08</td><td>35.23</td><td>35.70</td></tr> <tr><td>4.0</td><td>51.75</td><td>51.49</td><td>51.47</td><td>51.60</td><td>52.06</td></tr> <tr><td>4.7</td><td>60.97</td><td>60.52</td><td>60.30</td><td>60.37</td><td>60.77</td></tr> <tr><td>5.4</td><td>-※1</td><td>69.62</td><td>69.19</td><td>69.20</td><td>69.52</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>85.88</td><td>85.72</td><td>85.89</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>95.02</td><td>94.68</td><td>94.77</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | 0.87 | 0.93 | 1.07 | 0.80 | 0.46 | 1.3 | 17.18 | 17.22 | 17.38 | 17.53 | 17.90 | 2.7 | 35.00 | 34.99 | 35.08 | 35.23 | 35.70 | 4.0 | 51.75 | 51.49 | 51.47 | 51.60 | 52.06 | 4.7 | 60.97 | 60.52 | 60.30 | 60.37 | 60.77 | 5.4 | -※1 | 69.62 | 69.19 | 69.20 | 69.52 | 6.7 | -※1 | -※2 | 85.88 | 85.72 | 85.89 | 7.4 | -※1 | -※2 | 95.02 | 94.68 | 94.77 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - |
| Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 0.87 | 0.93 | 1.07 | 0.80 | 0.46 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 17.18 | 17.22 | 17.38 | 17.53 | 17.90 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 35.00 | 34.99 | 35.08 | 35.23 | 35.70 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 51.75 | 51.49 | 51.47 | 51.60 | 52.06 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 60.97 | 60.52 | 60.30 | 60.37 | 60.77 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 69.62 | 69.19 | 69.20 | 69.52 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 85.88 | 85.72 | 85.89 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 95.02 | 94.68 | 94.77 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: | Slanted line shows the range of the rated load current. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ※1 | Maximum output current at minimum input Voltage is 70% of rated load current. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ※2 | Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL

| | |
|--------|-------------------------------|
| Model | MGFS802412 |
| Item | Efficiency (by Input Voltage) |
| Object | _____ |

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

| Input Voltage [V] | Efficiency [%] | |
|-------------------|----------------|-----------------|
| | Load 50% | Load 100% |
| 8.5 | 93.0 | 92.7 $\times 1$ |
| 9.0 | 93.2 | 92.9 $\times 1$ |
| 12.0 | 93.4 | 93.4 $\times 2$ |
| 15.0 | 93.3 | 93.6 |
| 18.0 | 93.2 | 94.0 |
| 24.0 | 92.8 | 94.1 |
| 30.0 | 92.4 | 94.1 |
| 36.0 | 92.2 | 94.0 |
| 40.0 | 91.9 | 93.8 |

 $\times 1$: Load 70% $\times 2$: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL


| Model | MGFS802412 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|------------------|-------|-------|-------|-------|-------|-----|---|---|---|---|---|-----|------|------|------|------|------|-----|------|------|------|------|------|-----|------|------|------|------|------|-----|------|------|------|------|------|-----|-----|------|------|------|------|-----|-----|-----|------|------|------|-----|-----|-----|------|------|------|----|---|---|---|---|---|----|---|---|---|---|---|----|---|---|---|---|---|
| Item | Efficiency (by Load Current) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.3</td><td>91.1</td><td>91.1</td><td>90.2</td><td>89.4</td><td>87.5</td></tr> <tr><td>2.7</td><td>92.9</td><td>93.0</td><td>92.7</td><td>92.3</td><td>91.1</td></tr> <tr><td>4.0</td><td>93.1</td><td>93.6</td><td>93.7</td><td>93.4</td><td>92.6</td></tr> <tr><td>4.7</td><td>92.9</td><td>93.5</td><td>93.9</td><td>93.8</td><td>93.2</td></tr> <tr><td>5.4</td><td>-※1</td><td>93.4</td><td>94.0</td><td>94.0</td><td>93.6</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>94.0</td><td>94.1</td><td>94.0</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>93.8</td><td>94.1</td><td>94.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | - | - | - | - | - | 1.3 | 91.1 | 91.1 | 90.2 | 89.4 | 87.5 | 2.7 | 92.9 | 93.0 | 92.7 | 92.3 | 91.1 | 4.0 | 93.1 | 93.6 | 93.7 | 93.4 | 92.6 | 4.7 | 92.9 | 93.5 | 93.9 | 93.8 | 93.2 | 5.4 | -※1 | 93.4 | 94.0 | 94.0 | 93.6 | 6.7 | -※1 | -※2 | 94.0 | 94.1 | 94.0 | 7.4 | -※1 | -※2 | 93.8 | 94.1 | 94.0 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - |
| Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 91.1 | 91.1 | 90.2 | 89.4 | 87.5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 92.9 | 93.0 | 92.7 | 92.3 | 91.1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 93.1 | 93.6 | 93.7 | 93.4 | 92.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 92.9 | 93.5 | 93.9 | 93.8 | 93.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 93.4 | 94.0 | 94.0 | 93.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 94.0 | 94.1 | 94.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 93.8 | 94.1 | 94.0 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: Slanted line shows the range of the rated load current. | <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL

| | |
|--------|-----------------|
| Model | MGFS802412 |
| Item | Line Regulation |
| Object | +12V6.7A |

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

| Input Voltage [V] | Output Voltage [V] | |
|-------------------|--------------------|-----------|
| | Load 50% | Load 100% |
| 8.5 | 12.049 | - |
| 9.0 | 12.049 | - |
| 12.0 | 12.050 | - |
| 15.0 | 12.051 | 12.049 |
| 18.0 | 12.051 | 12.048 |
| 24.0 | 12.051 | 12.047 |
| 30.0 | 12.051 | 12.048 |
| 36.0 | 12.050 | 12.048 |
| 40.0 | 12.051 | 12.048 |

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 12V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.


COSEL

| Model | MGFS802412 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------------|--|------------------|--------------------|--------|--------|-------|-------|------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|-----|--------|--------|--------|--------|--------|-----|-----|--------|--------|--------|--------|-----|-----|--------|--------|--------|----|----|---|---|---|---|----|----|---|---|---|---|----|---|---|---|---|---|
| Item | Load Regulation | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | +12V6.7A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | <p>—△— Input Volt. 9V - - □ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◇ - - Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.053</td><td>12.054</td><td>12.055</td><td>12.057</td><td>12.059</td></tr> <tr><td>1.3</td><td>12.050</td><td>12.051</td><td>12.052</td><td>12.053</td><td>12.055</td></tr> <tr><td>2.7</td><td>12.048</td><td>12.049</td><td>12.050</td><td>12.052</td><td>12.053</td></tr> <tr><td>4.0</td><td>12.048</td><td>12.047</td><td>12.050</td><td>12.051</td><td>12.052</td></tr> <tr><td>4.7</td><td>12.048</td><td>12.047</td><td>12.048</td><td>12.050</td><td>12.051</td></tr> <tr><td>5.4</td><td>-※1</td><td>12.048</td><td>12.047</td><td>12.049</td><td>12.051</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>12.048</td><td>12.047</td><td>12.048</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>12.047</td><td>12.046</td><td>12.048</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | 12.053 | 12.054 | 12.055 | 12.057 | 12.059 | 1.3 | 12.050 | 12.051 | 12.052 | 12.053 | 12.055 | 2.7 | 12.048 | 12.049 | 12.050 | 12.052 | 12.053 | 4.0 | 12.048 | 12.047 | 12.050 | 12.051 | 12.052 | 4.7 | 12.048 | 12.047 | 12.048 | 12.050 | 12.051 | 5.4 | -※1 | 12.048 | 12.047 | 12.049 | 12.051 | 6.7 | -※1 | -※2 | 12.048 | 12.047 | 12.048 | 7.4 | -※1 | -※2 | 12.047 | 12.046 | 12.048 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - | | | | | |
| Load Current [A] | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 12.053 | 12.054 | 12.055 | 12.057 | 12.059 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 12.050 | 12.051 | 12.052 | 12.053 | 12.055 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 12.048 | 12.049 | 12.050 | 12.052 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 12.048 | 12.047 | 12.050 | 12.051 | 12.052 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 12.048 | 12.047 | 12.048 | 12.050 | 12.051 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 12.048 | 12.047 | 12.049 | 12.051 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 12.048 | 12.047 | 12.048 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 12.047 | 12.046 | 12.048 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.053</td><td>12.054</td><td>12.055</td><td>12.057</td><td>12.059</td></tr> <tr><td>1.3</td><td>12.050</td><td>12.051</td><td>12.052</td><td>12.053</td><td>12.055</td></tr> <tr><td>2.7</td><td>12.048</td><td>12.049</td><td>12.050</td><td>12.052</td><td>12.053</td></tr> <tr><td>4.0</td><td>12.048</td><td>12.047</td><td>12.050</td><td>12.051</td><td>12.052</td></tr> <tr><td>4.7</td><td>12.048</td><td>12.047</td><td>12.048</td><td>12.050</td><td>12.051</td></tr> <tr><td>5.4</td><td>-※1</td><td>12.048</td><td>12.047</td><td>12.049</td><td>12.051</td></tr> <tr><td>6.7</td><td>-※1</td><td>-※2</td><td>12.048</td><td>12.047</td><td>12.048</td></tr> <tr><td>7.4</td><td>-※1</td><td>-※2</td><td>12.047</td><td>12.046</td><td>12.048</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | Load Current [A] | Output Voltage [V] | | | | | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | 0.0 | 12.053 | 12.054 | 12.055 | 12.057 | 12.059 | 1.3 | 12.050 | 12.051 | 12.052 | 12.053 | 12.055 | 2.7 | 12.048 | 12.049 | 12.050 | 12.052 | 12.053 | 4.0 | 12.048 | 12.047 | 12.050 | 12.051 | 12.052 | 4.7 | 12.048 | 12.047 | 12.048 | 12.050 | 12.051 | 5.4 | -※1 | 12.048 | 12.047 | 12.049 | 12.051 | 6.7 | -※1 | -※2 | 12.048 | 12.047 | 12.048 | 7.4 | -※1 | -※2 | 12.047 | 12.046 | 12.048 | -- | - | - | - | - | - | -- | - | - | - | - | - | -- | - | - | - | - | - |
| Load Current [A] | Output Voltage [V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 12.053 | 12.054 | 12.055 | 12.057 | 12.059 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.3 | 12.050 | 12.051 | 12.052 | 12.053 | 12.055 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.7 | 12.048 | 12.049 | 12.050 | 12.052 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 12.048 | 12.047 | 12.050 | 12.051 | 12.052 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.7 | 12.048 | 12.047 | 12.048 | 12.050 | 12.051 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.4 | -※1 | 12.048 | 12.047 | 12.049 | 12.051 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.7 | -※1 | -※2 | 12.048 | 12.047 | 12.048 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.4 | -※1 | -※2 | 12.047 | 12.046 | 12.048 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| -- | - | - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: | Slanted line shows the range of the rated load current. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | ※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |


COSEL

| | | |
|--------|-----------------------|--|
| Model | MGFS802412 | Temperature Testing Circuitry Figure A |
| Item | Dynamic Load Response | |
| Object | +12V6.7A | |


Input Volt. 24 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (6.7A)



Load 50% (3.35A)↔
 Load 100% (6.7A)




COSEL

| | |
|--------|----------------------------------|
| Model | MGFS802412 |
| Item | Ripple Voltage (by Load Current) |
| Object | +12V6.7A |

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

| Load Current [A] | Ripple Voltage [mV] | |
|------------------|---------------------|--------------------|
| | Input Volt. 9 [V] | Input Volt. 36 [V] |
| 0.0 | 15 | 25 |
| 1.3 | 5 | 5 |
| 2.7 | 10 | 5 |
| 4.0 | 15 | 5 |
| 4.7 | 25 | 5 |
| 5.4 | - | 5 |
| 6.7 | - | 5 |
| 7.4 | - | 10 |
| -- | - | - |
| -- | - | - |
| -- | - | - |

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

| | |
|--------|--------------|
| Model | MGFS802412 |
| Item | Ripple-Noise |
| Object | +12V6.7A |

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

| Load Current [A] | Ripple-Noise [mV] | |
|------------------|-------------------|--------------------|
| | Input Volt. 9 [V] | Input Volt. 36 [V] |
| 0.0 | 15 | 25 |
| 1.3 | 10 | 10 |
| 2.7 | 10 | 10 |
| 4.0 | 20 | 10 |
| 4.7 | 25 | 10 |
| 5.4 | - | 10 |
| 6.7 | - | 15 |
| 7.4 | - | 20 |
| -- | - | - |
| -- | - | - |
| -- | - | - |

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

| | |
|--------|-----------------------------------|
| Model | MGFS802412 |
| Item | Ripple Voltage (by Ambient Temp.) |
| Object | +12V6.7A |

Testing Circuitry Figure B

1. Graph



2. Values


| Ambient Temperature [°C] | Ripple Voltage [mV] | |
|--------------------------|---------------------|-----------|
| | Load 50% | Load 100% |
| -60 | 5 | 15 |
| -40 | 5 | 15 |
| -20 | 5 | 15 |
| 25 | 5 | 10 |
| 60 | 5 | 10 |
| 70 | 5 | 10 |
| -- | - | - |
| -- | - | - |
| -- | - | - |
| -- | - | - |
| -- | - | - |

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

| | |
|--------|---------------------------|
| Model | MGFS802412 |
| Item | Ambient Temperature Drift |
| Object | +12V6.7A |



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

| Ambient Temperature [°C] | Output Voltage [V] | | | | |
|--------------------------|--------------------|--------|--------|--------|--------|
| | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] |
| -60 | 11.950 | 11.949 | 11.947 | 11.947 | 11.949 |
| -40 | 11.984 | 11.983 | 11.982 | 11.983 | 11.985 |
| -20 | 12.011 | 12.010 | 12.008 | 12.008 | 12.010 |
| 0 | 12.032 | 12.031 | 12.029 | 12.029 | 12.030 |
| 25 | 12.049 | 12.050 | 12.048 | 12.047 | 12.048 |
| 60 | 12.062 | 12.061 | 12.057 | 12.058 | 12.058 |
| 70 | 12.063 | 12.062 | 12.058 | 12.059 | 12.059 |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |

Note: In case of input Volt.9V, Load 70%.
12V, Load 80%.
Other case Load 100%.



| | | |
|--------|-------------------------|-------------------------------|
| Model | MGFS802412 | Testing Circuitry Figure A |
| Item | Output Voltage Accuracy | |
| Object | +12V6.7A | |

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 36V

Load Current : 0 - 6.7A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

| Item | Temperature [°C] | Input Voltage[V] | Output | | Output Voltage Accuracy | |
|-----------------|---------------------|---------------------|------------|------------|-------------------------|-----------|
| | | | Current[A] | Voltage[V] | Value [mV] | Ratio [%] |
| Maximum Voltage | 60 | 24 | 0 | 12.071 | ±45 | ±0.4 |
| Minimum Voltage | -40 | 18 | 6.7 | 11.982 | | |


COSEL

| Model | MGFS802412 | Temperature | 25°C | | | | | | | | | | | | | | | | | | | | | | |
|---|-----------------------|-------------------|--|-------------------------|-----------------------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|-----|--------|
| Item | Time Lapse Drift | Testing Circuitry | Figure A | | | | | | | | | | | | | | | | | | | | | | |
| Object | +12V6.7A | | | | | | | | | | | | | | | | | | | | | | | | |
| 1. Graph | | | 2. Values | | | | | | | | | | | | | | | | | | | | | | |
| <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p> | | | <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.041</td></tr> <tr><td>0.5</td><td>12.053</td></tr> <tr><td>1.0</td><td>12.053</td></tr> <tr><td>2.0</td><td>12.053</td></tr> <tr><td>3.0</td><td>12.053</td></tr> <tr><td>4.0</td><td>12.053</td></tr> <tr><td>5.0</td><td>12.053</td></tr> <tr><td>6.0</td><td>12.053</td></tr> <tr><td>7.0</td><td>12.053</td></tr> <tr><td>8.0</td><td>12.053</td></tr> </tbody> </table> | Time since start [H] | Output Voltage [V] | 0.0 | 12.041 | 0.5 | 12.053 | 1.0 | 12.053 | 2.0 | 12.053 | 3.0 | 12.053 | 4.0 | 12.053 | 5.0 | 12.053 | 6.0 | 12.053 | 7.0 | 12.053 | 8.0 | 12.053 |
| Time since start [H] | Output Voltage [V] | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.0 | 12.041 | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.5 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 3.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 6.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 7.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |
| 8.0 | 12.053 | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL


| | | |
|--------|--------------------|--|
| Model | MGFS802412 | Temperature Testing Circuitry Figure A |
| Item | Rise and Fall Time | |
| Object | +12V6.7A | |

1. Graph



2. Values

| Load | Time | Td | Tr | Ts | Th | Tf | [ms] |
|-------|------|-----|-----|------|-----|-----|------|
| 50 % | | 6.3 | 3.4 | 9.7 | 0.2 | 1.4 | |
| 100 % | | 6.3 | 5.0 | 11.3 | 0.2 | 0.5 | |




COSEL

| | |
|--------|---|
| Model | MGFS802412 |
| Item | Minimum Input Voltage for Regulated Output Voltage |
| Object | +12V6.7A |

Testing Circuitry Figure A

1. Graph



2. Values

| Ambient Temperature [°C] | Input Voltage [V] | |
|-----------------------------|-------------------|-----------|
| | Load 50% | Load 100% |
| -60 | 7.5 | 7.5 |
| -40 | 7.5 | 7.5 |
| -20 | 7.4 | 7.4 |
| 0 | 7.4 | 7.4 |
| 25 | 7.6 | 7.6 |
| 60 | 7.4 | 7.5 |
| 70 | 7.4 | 7.5 |
| -- | - | - |
| -- | - | - |
| -- | - | - |
| -- | - | - |

Note: Slanted line shows the range of the rated ambient temperature.



| | |
|---|------------------------|
| Model | MGFS802412 |
| Item | Overcurrent Protection |
| Object | +12V6.7A |
| 1.Graph | |
| <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> | |
| <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p> | |

Temperature 25°C
Testing Circuitry Figure A

2.Values

| Output Voltage [V] | Load Current [A] | | | | |
|--------------------|------------------|-------|-------|-------|-------|
| | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] |
| 12.0 | 5.306 | 6.870 | 7.779 | 8.007 | 8.008 |
| 11.4 | -※1 | -※2 | - | - | - |
| 10.8 | - | - | - | - | - |
| 9.6 | - | - | - | - | - |
| 8.4 | - | - | - | - | - |
| 7.2 | - | - | - | - | - |
| 6.0 | - | - | - | - | - |
| 4.8 | - | - | - | - | - |
| 3.6 | - | - | - | - | - |
| 2.4 | - | - | - | - | - |
| 1.2 | - | - | - | - | - |
| 0.0 | - | - | - | - | - |


※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 12V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

| | |
|--------|------------------------|
| Model | MGFS802412 |
| Item | Overvoltage Protection |
| Object | +12V6.7A |



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values


| Ambient Temperature [°C] | Operating Point [%] | | | | |
|--------------------------|---------------------|-------|-------|-------|-------|
| | 9[V] | 12[V] | 18[V] | 24[V] | 36[V] |
| -60 | 123 | 123 | 123 | 123 | 123 |
| -40 | 124 | 124 | 124 | 124 | 123 |
| -20 | 124 | 124 | 124 | 124 | 124 |
| 0 | 124 | 124 | 124 | 124 | 124 |
| 25 | 124 | 124 | 124 | 124 | 124 |
| 60 | 125 | 125 | 125 | 125 | 124 |
| 70 | 125 | 125 | 125 | 125 | 124 |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |
| -- | - | - | - | - | - |

COSEL

| | |
|--------|---------------------------------------|
| Model | MGFS802412 |
| Item | Switching frequency (by Load Current) |
| Object | +12V6.7A |

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG80 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG80 operates intermittently, so switching frequency would not become constant.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

