

TEST DATA OF MGFW154815

Regulated DC Power Supply
September 8, 2010

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Yuichiro Ohashi
Yuichiro Ohashi Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Figure of Testing Circuitry · · · · ·	22

(Final Page 22)

Model	MGFW154815																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph	<p>—△— Load 100%</p> <p>- -□-- Load 50%</p> <p>- -○-- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>18</td><td>0.00</td><td>0.00</td><td>0.00</td></tr> <tr><td>20</td><td>0.00</td><td>0.00</td><td>1.00</td></tr> <tr><td>30</td><td>0.00</td><td>0.00</td><td>0.40</td></tr> <tr><td>40</td><td>0.00</td><td>0.00</td><td>0.25</td></tr> <tr><td>50</td><td>0.00</td><td>0.00</td><td>0.18</td></tr> <tr><td>70</td><td>0.00</td><td>0.00</td><td>0.15</td></tr> <tr><td>80</td><td>0.00</td><td>0.00</td><td>0.18</td></tr> </tbody> </table>			Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	18	0.00	0.00	0.00	20	0.00	0.00	1.00	30	0.00	0.00	0.40	40	0.00	0.00	0.25	50	0.00	0.00	0.18	70	0.00	0.00	0.15	80	0.00	0.00	0.18																																															
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
18	0.00	0.00	0.00																																																																															
20	0.00	0.00	1.00																																																																															
30	0.00	0.00	0.40																																																																															
40	0.00	0.00	0.25																																																																															
50	0.00	0.00	0.18																																																																															
70	0.00	0.00	0.15																																																																															
80	0.00	0.00	0.18																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.003</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.003</td><td>0.003</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.003</td><td>0.002</td><td>0.002</td></tr> <tr><td>17.0</td><td>0.026</td><td>0.502</td><td>1.032</td></tr> <tr><td>17.5</td><td>0.026</td><td>0.489</td><td>1.002</td></tr> <tr><td>18.0</td><td>0.026</td><td>0.477</td><td>0.974</td></tr> <tr><td>24.0</td><td>0.019</td><td>0.355</td><td>0.723</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.237</td><td>0.480</td></tr> <tr><td>48.0</td><td>0.011</td><td>0.183</td><td>0.357</td></tr> <tr><td>76.0</td><td>0.008</td><td>0.118</td><td>0.231</td></tr> <tr><td>80.0</td><td>0.008</td><td>0.113</td><td>0.220</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.002	0.002	0.002	10.0	0.002	0.002	0.002	15.0	0.002	0.003	0.002	16.0	0.003	0.003	0.002	16.5	0.003	0.002	0.002	17.0	0.026	0.502	1.032	17.5	0.026	0.489	1.002	18.0	0.026	0.477	0.974	24.0	0.019	0.355	0.723	36.0	0.015	0.237	0.480	48.0	0.011	0.183	0.357	76.0	0.008	0.118	0.231	80.0	0.008	0.113	0.220	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.002	0.002	0.002																																																																															
10.0	0.002	0.002	0.002																																																																															
15.0	0.002	0.003	0.002																																																																															
16.0	0.003	0.003	0.002																																																																															
16.5	0.003	0.002	0.002																																																																															
17.0	0.026	0.502	1.032																																																																															
17.5	0.026	0.489	1.002																																																																															
18.0	0.026	0.477	0.974																																																																															
24.0	0.019	0.355	0.723																																																																															
36.0	0.015	0.237	0.480																																																																															
48.0	0.011	0.183	0.357																																																																															
76.0	0.008	0.118	0.231																																																																															
80.0	0.008	0.113	0.220																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
Note:	Slanted line shows the range of the rated input voltage.																																																																																	

COSEL

Model	MGFW154815																																																																																
Item	Input Current (by Load Current)																																																																																
Object	_____																																																																																
1.Graph	—△— Input Volt. 18V - - -□- - Input Volt. 24V - - *- - Input Volt. 36V - - ○- - Input Volt. 48V - - ◇- - Input Volt. 76V																																																																																
2.Values																																																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.026</td> <td>0.019</td> <td>0.016</td> <td>0.012</td> <td>0.008</td> </tr> <tr> <td>20</td> <td>0.203</td> <td>0.156</td> <td>0.106</td> <td>0.079</td> <td>0.056</td> </tr> <tr> <td>40</td> <td>0.389</td> <td>0.294</td> <td>0.197</td> <td>0.146</td> <td>0.099</td> </tr> <tr> <td>60</td> <td>0.568</td> <td>0.429</td> <td>0.287</td> <td>0.215</td> <td>0.139</td> </tr> <tr> <td>80</td> <td>0.761</td> <td>0.566</td> <td>0.375</td> <td>0.287</td> <td>0.184</td> </tr> <tr> <td>100</td> <td>0.953</td> <td>0.708</td> <td>0.472</td> <td>0.351</td> <td>0.227</td> </tr> <tr> <td>110</td> <td>1.053</td> <td>0.787</td> <td>0.515</td> <td>0.389</td> <td>0.251</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ration [%]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.026	0.019	0.016	0.012	0.008	20	0.203	0.156	0.106	0.079	0.056	40	0.389	0.294	0.197	0.146	0.099	60	0.568	0.429	0.287	0.215	0.139	80	0.761	0.566	0.375	0.287	0.184	100	0.953	0.708	0.472	0.351	0.227	110	1.053	0.787	0.515	0.389	0.251	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																																																
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																												
0	0.026	0.019	0.016	0.012	0.008																																																																												
20	0.203	0.156	0.106	0.079	0.056																																																																												
40	0.389	0.294	0.197	0.146	0.099																																																																												
60	0.568	0.429	0.287	0.215	0.139																																																																												
80	0.761	0.566	0.375	0.287	0.184																																																																												
100	0.953	0.708	0.472	0.351	0.227																																																																												
110	1.053	0.787	0.515	0.389	0.251																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												

COSEL

Model	MGFW154815																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.47</td><td>0.45</td><td>0.56</td><td>0.56</td><td>0.64</td></tr> <tr><td>20</td><td>3.63</td><td>3.74</td><td>3.83</td><td>3.79</td><td>4.23</td></tr> <tr><td>40</td><td>6.99</td><td>7.03</td><td>7.09</td><td>7.00</td><td>7.51</td></tr> <tr><td>60</td><td>10.25</td><td>10.29</td><td>10.32</td><td>10.33</td><td>10.53</td></tr> <tr><td>80</td><td>13.69</td><td>13.50</td><td>13.47</td><td>13.74</td><td>13.98</td></tr> <tr><td>100</td><td>17.20</td><td>17.02</td><td>16.96</td><td>16.82</td><td>17.22</td></tr> <tr><td>110</td><td>19.01</td><td>18.73</td><td>18.47</td><td>18.62</td><td>19.06</td></tr> </tbody> </table>					Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]	0	0.47	0.45	0.56	0.56	0.64	20	3.63	3.74	3.83	3.79	4.23	40	6.99	7.03	7.09	7.00	7.51	60	10.25	10.29	10.32	10.33	10.53	80	13.69	13.50	13.47	13.74	13.98	100	17.20	17.02	16.96	16.82	17.22	110	19.01	18.73	18.47	18.62	19.06																													
Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.47	0.45	0.56	0.56	0.64																																																																													
20	3.63	3.74	3.83	3.79	4.23																																																																													
40	6.99	7.03	7.09	7.00	7.51																																																																													
60	10.25	10.29	10.32	10.33	10.53																																																																													
80	13.69	13.50	13.47	13.74	13.98																																																																													
100	17.20	17.02	16.96	16.82	17.22																																																																													
110	19.01	18.73	18.47	18.62	19.06																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.47</td><td>0.45</td><td>0.56</td><td>0.56</td><td>0.64</td></tr> <tr><td>20</td><td>3.63</td><td>3.74</td><td>3.83</td><td>3.79</td><td>4.23</td></tr> <tr><td>40</td><td>6.99</td><td>7.03</td><td>7.09</td><td>7.00</td><td>7.51</td></tr> <tr><td>60</td><td>10.25</td><td>10.29</td><td>10.32</td><td>10.33</td><td>10.53</td></tr> <tr><td>80</td><td>13.69</td><td>13.50</td><td>13.47</td><td>13.74</td><td>13.98</td></tr> <tr><td>100</td><td>17.20</td><td>17.02</td><td>16.96</td><td>16.82</td><td>17.22</td></tr> <tr><td>110</td><td>19.01</td><td>18.73</td><td>18.47</td><td>18.62</td><td>19.06</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.47	0.45	0.56	0.56	0.64	20	3.63	3.74	3.83	3.79	4.23	40	6.99	7.03	7.09	7.00	7.51	60	10.25	10.29	10.32	10.33	10.53	80	13.69	13.50	13.47	13.74	13.98	100	17.20	17.02	16.96	16.82	17.22	110	19.01	18.73	18.47	18.62	19.06	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.47	0.45	0.56	0.56	0.64																																																																													
20	3.63	3.74	3.83	3.79	4.23																																																																													
40	6.99	7.03	7.09	7.00	7.51																																																																													
60	10.25	10.29	10.32	10.33	10.53																																																																													
80	13.69	13.50	13.47	13.74	13.98																																																																													
100	17.20	17.02	16.96	16.82	17.22																																																																													
110	19.01	18.73	18.47	18.62	19.06																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													


Model	MGFW154815																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 90) against Input Voltage [V] on the x-axis (10 to 90). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>15</td><td>87.5</td><td>87.5</td></tr> <tr><td>30</td><td>86.5</td><td>89.0</td></tr> <tr><td>50</td><td>85.5</td><td>88.5</td></tr> <tr><td>70</td><td>84.5</td><td>87.5</td></tr> <tr><td>85</td><td>83.5</td><td>87.5</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	15	87.5	87.5	30	86.5	89.0	50	85.5	88.5	70	84.5	87.5	85	83.5	87.5														
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
15	87.5	87.5																																
30	86.5	89.0																																
50	85.5	88.5																																
70	84.5	87.5																																
85	83.5	87.5																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>87.3</td><td>86.7</td></tr> <tr><td>18</td><td>86.8</td><td>87.1</td></tr> <tr><td>24</td><td>87.6</td><td>88.0</td></tr> <tr><td>30</td><td>86.4</td><td>89.0</td></tr> <tr><td>36</td><td>87.7</td><td>88.3</td></tr> <tr><td>48</td><td>85.0</td><td>89.1</td></tr> <tr><td>60</td><td>85.7</td><td>87.3</td></tr> <tr><td>76</td><td>83.3</td><td>86.9</td></tr> <tr><td>80</td><td>82.4</td><td>87.0</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	87.3	86.7	18	86.8	87.1	24	87.6	88.0	30	86.4	89.0	36	87.7	88.3	48	85.0	89.1	60	85.7	87.3	76	83.3	86.9	80	82.4	87.0
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	87.3	86.7																																
18	86.8	87.1																																
24	87.6	88.0																																
30	86.4	89.0																																
36	87.7	88.3																																
48	85.0	89.1																																
60	85.7	87.3																																
76	83.3	86.9																																
80	82.4	87.0																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	MGFW154815																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>82.4</td><td>80.3</td><td>78.3</td><td>79.2</td><td>70.9</td></tr> <tr> <td>40</td><td>85.8</td><td>85.4</td><td>84.6</td><td>85.7</td><td>79.9</td></tr> <tr> <td>60</td><td>87.6</td><td>87.3</td><td>87.0</td><td>86.9</td><td>85.3</td></tr> <tr> <td>80</td><td>87.5</td><td>88.8</td><td>89.0</td><td>87.2</td><td>85.7</td></tr> <tr> <td>100</td><td>87.1</td><td>88.1</td><td>88.4</td><td>89.1</td><td>87.0</td></tr> <tr> <td>110</td><td>86.7</td><td>88.0</td><td>89.3</td><td>88.5</td><td>86.5</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	82.4	80.3	78.3	79.2	70.9	40	85.8	85.4	84.6	85.7	79.9	60	87.6	87.3	87.0	86.9	85.3	80	87.5	88.8	89.0	87.2	85.7	100	87.1	88.1	88.4	89.1	87.0	110	86.7	88.0	89.3	88.5	86.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0	-	-	-	-	-																																																																													
20	82.4	80.3	78.3	79.2	70.9																																																																													
40	85.8	85.4	84.6	85.7	79.9																																																																													
60	87.6	87.3	87.0	86.9	85.3																																																																													
80	87.5	88.8	89.0	87.2	85.7																																																																													
100	87.1	88.1	88.4	89.1	87.0																																																																													
110	86.7	88.0	89.3	88.5	86.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	MGFW154815
Item	Line Regulation
Object	+15V0.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	15.106	15.003
18	15.104	15.002
24	15.103	15.002
30	15.103	15.002
36	15.104	15.003
48	15.104	15.003
60	15.105	15.003
76	15.105	15.004
80	15.105	15.003

-15V: Rated output current

Object -15V0.5A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-15.100	-14.991
18	-15.098	-14.992
24	-15.096	-14.993
30	-15.096	-14.993
36	-15.096	-14.993
48	-15.095	-14.993
60	-15.095	-14.993
76	-15.095	-14.992
80	-15.095	-14.992

+15V: Rated output current


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFW154815	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Load Regulation																																																																																		
Object	+15V0.5A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15.550</td><td>15.544</td><td>15.539</td><td>15.541</td><td>15.548</td></tr> <tr><td>0.100</td><td>15.217</td><td>15.217</td><td>15.217</td><td>15.217</td><td>15.217</td></tr> <tr><td>0.200</td><td>15.136</td><td>15.136</td><td>15.136</td><td>15.136</td><td>15.137</td></tr> <tr><td>0.300</td><td>15.085</td><td>15.081</td><td>15.082</td><td>15.082</td><td>15.083</td></tr> <tr><td>0.400</td><td>15.043</td><td>15.039</td><td>15.039</td><td>15.039</td><td>15.040</td></tr> <tr><td>0.500</td><td>15.003</td><td>15.002</td><td>15.003</td><td>15.003</td><td>15.003</td></tr> <tr><td>0.550</td><td>14.983</td><td>14.985</td><td>14.986</td><td>14.986</td><td>14.987</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated output current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.000	15.550	15.544	15.539	15.541	15.548	0.100	15.217	15.217	15.217	15.217	15.217	0.200	15.136	15.136	15.136	15.136	15.137	0.300	15.085	15.081	15.082	15.082	15.083	0.400	15.043	15.039	15.039	15.039	15.040	0.500	15.003	15.002	15.003	15.003	15.003	0.550	14.983	14.985	14.986	14.986	14.987	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.000	15.550	15.544	15.539	15.541	15.548																																																																														
0.100	15.217	15.217	15.217	15.217	15.217																																																																														
0.200	15.136	15.136	15.136	15.136	15.137																																																																														
0.300	15.085	15.081	15.082	15.082	15.083																																																																														
0.400	15.043	15.039	15.039	15.039	15.040																																																																														
0.500	15.003	15.002	15.003	15.003	15.003																																																																														
0.550	14.983	14.985	14.986	14.986	14.987																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-15V0.5A	<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-15.527</td><td>-15.526</td><td>-15.522</td><td>-15.521</td><td>-15.525</td></tr> <tr><td>0.100</td><td>-15.200</td><td>-15.201</td><td>-15.201</td><td>-15.200</td><td>-15.199</td></tr> <tr><td>0.200</td><td>-15.124</td><td>-15.124</td><td>-15.124</td><td>-15.124</td><td>-15.123</td></tr> <tr><td>0.300</td><td>-15.074</td><td>-15.071</td><td>-15.071</td><td>-15.071</td><td>-15.070</td></tr> <tr><td>0.400</td><td>-15.032</td><td>-15.029</td><td>-15.029</td><td>-15.029</td><td>-15.028</td></tr> <tr><td>0.500</td><td>-14.991</td><td>-14.993</td><td>-14.993</td><td>-14.992</td><td>-14.992</td></tr> <tr><td>0.550</td><td>-14.971</td><td>-14.975</td><td>-14.976</td><td>-14.976</td><td>-14.976</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated output current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.000	-15.527	-15.526	-15.522	-15.521	-15.525	0.100	-15.200	-15.201	-15.201	-15.200	-15.199	0.200	-15.124	-15.124	-15.124	-15.124	-15.123	0.300	-15.074	-15.071	-15.071	-15.071	-15.070	0.400	-15.032	-15.029	-15.029	-15.029	-15.028	0.500	-14.991	-14.993	-14.993	-14.992	-14.992	0.550	-14.971	-14.975	-14.976	-14.976	-14.976	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.000	-15.527	-15.526	-15.522	-15.521	-15.525																																																																														
0.100	-15.200	-15.201	-15.201	-15.200	-15.199																																																																														
0.200	-15.124	-15.124	-15.124	-15.124	-15.123																																																																														
0.300	-15.074	-15.071	-15.071	-15.071	-15.070																																																																														
0.400	-15.032	-15.029	-15.029	-15.029	-15.028																																																																														
0.500	-14.991	-14.993	-14.993	-14.992	-14.992																																																																														
0.550	-14.971	-14.975	-14.976	-14.976	-14.976																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																			

COSEL

coSEL



Model	MGFW154815																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.5A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.10</td><td>12</td><td>12</td></tr> <tr><td>0.20</td><td>13</td><td>14</td></tr> <tr><td>0.30</td><td>15</td><td>15</td></tr> <tr><td>0.40</td><td>16</td><td>15</td></tr> <tr><td>0.50</td><td>16</td><td>16</td></tr> <tr><td>0.55</td><td>17</td><td>17</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated output current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	10	10	0.10	12	12	0.20	13	14	0.30	15	15	0.40	16	15	0.50	16	16	0.55	17	17	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	10	10																																						
0.10	12	12																																						
0.20	13	14																																						
0.30	15	15																																						
0.40	16	15																																						
0.50	16	16																																						
0.55	17	17																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								
- 10 -																																								
BC-10473																																								


Model	MGFW154815																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.5A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>7</td><td>7</td></tr> <tr> <td>0.10</td><td>8</td><td>9</td></tr> <tr> <td>0.20</td><td>12</td><td>13</td></tr> <tr> <td>0.30</td><td>15</td><td>16</td></tr> <tr> <td>0.40</td><td>18</td><td>17</td></tr> <tr> <td>0.50</td><td>19</td><td>19</td></tr> <tr> <td>0.55</td><td>20</td><td>21</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated output current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	7	7	0.10	8	9	0.20	12	13	0.30	15	16	0.40	18	17	0.50	19	19	0.55	20	21	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	7	7																																						
0.10	8	9																																						
0.20	12	13																																						
0.30	15	16																																						
0.40	18	17																																						
0.50	19	19																																						
0.55	20	21																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

Model	MGFW154815																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.5A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>11</td><td>10</td></tr> <tr><td>0.10</td><td>14</td><td>13</td></tr> <tr><td>0.20</td><td>15</td><td>15</td></tr> <tr><td>0.30</td><td>17</td><td>16</td></tr> <tr><td>0.40</td><td>18</td><td>17</td></tr> <tr><td>0.50</td><td>19</td><td>18</td></tr> <tr><td>0.55</td><td>20</td><td>19</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated output current</p>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	11	10	0.10	14	13	0.20	15	15	0.30	17	16	0.40	18	17	0.50	19	18	0.55	20	19	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	11	10																																						
0.10	14	13																																						
0.20	15	15																																						
0.30	17	16																																						
0.40	18	17																																						
0.50	19	18																																						
0.55	20	19																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

Model	MGFW154815																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.5A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>7</td><td>7</td></tr> <tr><td>0.10</td><td>9</td><td>9</td></tr> <tr><td>0.20</td><td>13</td><td>13</td></tr> <tr><td>0.30</td><td>16</td><td>16</td></tr> <tr><td>0.40</td><td>19</td><td>18</td></tr> <tr><td>0.50</td><td>21</td><td>21</td></tr> <tr><td>0.55</td><td>22</td><td>22</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated output current</p>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	7	7	0.10	9	9	0.20	13	13	0.30	16	16	0.40	19	18	0.50	21	21	0.55	22	22	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	7	7																																						
0.10	9	9																																						
0.20	13	13																																						
0.30	16	16																																						
0.40	19	18																																						
0.50	21	21																																						
0.55	22	22																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								

Model	MGFW154815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.5A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	13	19
-40	13	17
-20	17	18
0	16	19
25	18	20
60	16	19
65	16	19
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated output current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	23	29
-40	23	29
-20	21	28
0	20	27
25	18	25
60	16	23
65	15	23
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW154815	Testing Circuitry Figure A																																																																														
Item	Ambient Temperature Drift																																																																															
Object	+15V0.5A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> —△— Input Volt. 18V - -□-- Input Volt. 24V - -*-- Input Volt. 36V - -○-- Input Volt. 48V - -◇-- Input Volt. 76V 	2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.918</td><td>14.920</td><td>14.921</td><td>14.921</td><td>14.922</td></tr> <tr><td>-40</td><td>14.948</td><td>14.949</td><td>14.951</td><td>14.951</td><td>14.952</td></tr> <tr><td>-20</td><td>14.969</td><td>14.969</td><td>14.970</td><td>14.971</td><td>14.971</td></tr> <tr><td>0</td><td>14.987</td><td>14.987</td><td>14.988</td><td>14.989</td><td>14.989</td></tr> <tr><td>25</td><td>15.002</td><td>15.002</td><td>15.003</td><td>15.003</td><td>15.004</td></tr> <tr><td>60</td><td>15.012</td><td>15.012</td><td>15.013</td><td>15.013</td><td>15.014</td></tr> <tr><td>65</td><td>15.013</td><td>15.012</td><td>15.013</td><td>15.014</td><td>15.015</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-60	14.918	14.920	14.921	14.921	14.922	-40	14.948	14.949	14.951	14.951	14.952	-20	14.969	14.969	14.970	14.971	14.971	0	14.987	14.987	14.988	14.989	14.989	25	15.002	15.002	15.003	15.003	15.004	60	15.012	15.012	15.013	15.013	15.014	65	15.013	15.012	15.013	15.014	15.015	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Ambient Temperature [°C]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
-60	14.918	14.920	14.921	14.921	14.922																																																																											
-40	14.948	14.949	14.951	14.951	14.952																																																																											
-20	14.969	14.969	14.970	14.971	14.971																																																																											
0	14.987	14.987	14.988	14.989	14.989																																																																											
25	15.002	15.002	15.003	15.003	15.004																																																																											
60	15.012	15.012	15.013	15.013	15.014																																																																											
65	15.013	15.012	15.013	15.014	15.015																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Object	-15V0.5A	2.Values																																																																														
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> —△— Input Volt. 18V - -□-- Input Volt. 24V - -*-- Input Volt. 36V - -○-- Input Volt. 48V - -◇-- Input Volt. 76V 	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.912</td><td>-14.914</td><td>-14.914</td><td>-14.915</td><td>-14.915</td></tr> <tr><td>-40</td><td>-14.941</td><td>-14.943</td><td>-14.944</td><td>-14.944</td><td>-14.944</td></tr> <tr><td>-20</td><td>-14.961</td><td>-14.963</td><td>-14.963</td><td>-14.963</td><td>-14.963</td></tr> <tr><td>0</td><td>-14.978</td><td>-14.979</td><td>-14.980</td><td>-14.980</td><td>-14.980</td></tr> <tr><td>25</td><td>-14.991</td><td>-14.993</td><td>-14.993</td><td>-14.993</td><td>-14.993</td></tr> <tr><td>60</td><td>-14.999</td><td>-15.000</td><td>-15.001</td><td>-15.001</td><td>-15.000</td></tr> <tr><td>65</td><td>-14.999</td><td>-15.001</td><td>-15.001</td><td>-15.001</td><td>-15.000</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-60	-14.912	-14.914	-14.914	-14.915	-14.915	-40	-14.941	-14.943	-14.944	-14.944	-14.944	-20	-14.961	-14.963	-14.963	-14.963	-14.963	0	-14.978	-14.979	-14.980	-14.980	-14.980	25	-14.991	-14.993	-14.993	-14.993	-14.993	60	-14.999	-15.000	-15.001	-15.001	-15.000	65	-14.999	-15.001	-15.001	-15.001	-15.000	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Ambient Temperature [°C]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
-60	-14.912	-14.914	-14.914	-14.915	-14.915																																																																											
-40	-14.941	-14.943	-14.944	-14.944	-14.944																																																																											
-20	-14.961	-14.963	-14.963	-14.963	-14.963																																																																											
0	-14.978	-14.979	-14.980	-14.980	-14.980																																																																											
25	-14.991	-14.993	-14.993	-14.993	-14.993																																																																											
60	-14.999	-15.000	-15.001	-15.001	-15.000																																																																											
65	-14.999	-15.001	-15.001	-15.001	-15.000																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW154815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 0.5A (AVR 2) : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	76		0	15.580	
Minimum Voltage	-40	18	0.5	14.948	±316	±2.1

Object	-15V0.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18		0	-15.561	
Minimum Voltage	-40	18	0.5	-14.941	±310	±2.1

COSEL


Model	MGFW154815	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+15V0.5A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.991</td></tr> <tr><td>0.5</td><td>14.998</td></tr> <tr><td>1.0</td><td>14.998</td></tr> <tr><td>2.0</td><td>14.998</td></tr> <tr><td>3.0</td><td>14.998</td></tr> <tr><td>4.0</td><td>14.998</td></tr> <tr><td>5.0</td><td>14.999</td></tr> <tr><td>6.0</td><td>14.999</td></tr> <tr><td>7.0</td><td>14.999</td></tr> <tr><td>8.0</td><td>14.999</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	14.991	0.5	14.998	1.0	14.998	2.0	14.998	3.0	14.998	4.0	14.998	5.0	14.999	6.0	14.999	7.0	14.999	8.0	14.999
Time since start [H]	Output Voltage [V]																							
0.0	14.991																							
0.5	14.998																							
1.0	14.998																							
2.0	14.998																							
3.0	14.998																							
4.0	14.998																							
5.0	14.999																							
6.0	14.999																							
7.0	14.999																							
8.0	14.999																							
Object -15V0.5A		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.995</td></tr> <tr><td>0.5</td><td>-14.999</td></tr> <tr><td>1.0</td><td>-14.999</td></tr> <tr><td>2.0</td><td>-14.999</td></tr> <tr><td>3.0</td><td>-14.999</td></tr> <tr><td>4.0</td><td>-14.999</td></tr> <tr><td>5.0</td><td>-14.999</td></tr> <tr><td>6.0</td><td>-15.000</td></tr> <tr><td>7.0</td><td>-15.000</td></tr> <tr><td>8.0</td><td>-15.000</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-14.995	0.5	-14.999	1.0	-14.999	2.0	-14.999	3.0	-14.999	4.0	-14.999	5.0	-14.999	6.0	-15.000	7.0	-15.000	8.0	-15.000
Time since start [H]	Output Voltage [V]																							
0.0	-14.995																							
0.5	-14.999																							
1.0	-14.999																							
2.0	-14.999																							
3.0	-14.999																							
4.0	-14.999																							
5.0	-14.999																							
6.0	-15.000																							
7.0	-15.000																							
8.0	-15.000																							

COSEL

Model	MGFW154815
Item	Rise and Fall Time
Object	+15V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.1	4.8	5.9	0.4	10.0
100 %		1.1	4.9	6.0	0.3	4.9




COSEL

Model	MGFW154815
Item	Rise and Fall Time
Object	-15V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.1	4.7	5.8	0.4	10.3	
100 %		1.1	4.8	5.9	0.3	5.3	



Model	MGFW154815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.5A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	16.4	16.3
-40	16.5	16.4
-20	16.5	16.4
0	16.5	16.4
25	16.5	16.3
60	16.0	16.4
65	16.5	16.4
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.5A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	16.2	16.1
-40	16.3	16.1
-20	16.3	16.2
0	16.3	16.2
25	16.3	16.2
60	16.3	16.2
65	16.3	16.2
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW154815	Temperature 25°C Testing Circuitry Figure A														
Item	Overcurrent Protection															
Object	+15V0.5A															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 18V 24V 36V 48V 76V 	2.Values														
Object	-15V0.5A	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 18V 24V 36V 48V 76V 	2.Values													
Object	+15V0.5A	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 18V 24V 36V 48V 76V 	2.Values													
Note:	Slanted line shows the range of the rated load current.															
	Intermittent operation occurs when overcurrent protection is activated.															

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)