

TEST DATA OF MGFW302405

Regulated DC Power Supply
November 19, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Masashi Ueda
Masashi Ueda

Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Figure of Testing Circuitry	23

(Final Page 23)

Model	MGFW302405																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph	<p>—△— Load 100%</p> <p>- -□-- Load 50%</p> <p>- -○-- Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.4</td><td>0.031</td><td>1.382</td><td>2.980</td></tr> <tr><td>8.5</td><td>0.031</td><td>1.364</td><td>2.940</td></tr> <tr><td>9.0</td><td>0.031</td><td>1.288</td><td>2.763</td></tr> <tr><td>9.2</td><td>0.031</td><td>1.273</td><td>2.697</td></tr> <tr><td>12.0</td><td>0.023</td><td>0.976</td><td>2.060</td></tr> <tr><td>18.0</td><td>0.019</td><td>0.661</td><td>1.380</td></tr> <tr><td>24.0</td><td>0.017</td><td>0.504</td><td>1.038</td></tr> <tr><td>36.0</td><td>0.017</td><td>0.351</td><td>0.706</td></tr> <tr><td>40.0</td><td>0.017</td><td>0.321</td><td>0.642</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.002	0.002	0.002	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.002	8.4	0.031	1.382	2.980	8.5	0.031	1.364	2.940	9.0	0.031	1.288	2.763	9.2	0.031	1.273	2.697	12.0	0.023	0.976	2.060	18.0	0.019	0.661	1.380	24.0	0.017	0.504	1.038	36.0	0.017	0.351	0.706	40.0	0.017	0.321	0.642	--	-	-	-	--	-	-	-	--	-	-	-					
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
6.0	0.002	0.002	0.002																																																																															
7.0	0.002	0.002	0.002																																																																															
8.0	0.002	0.002	0.002																																																																															
8.4	0.031	1.382	2.980																																																																															
8.5	0.031	1.364	2.940																																																																															
9.0	0.031	1.288	2.763																																																																															
9.2	0.031	1.273	2.697																																																																															
12.0	0.023	0.976	2.060																																																																															
18.0	0.019	0.661	1.380																																																																															
24.0	0.017	0.504	1.038																																																																															
36.0	0.017	0.351	0.706																																																																															
40.0	0.017	0.321	0.642																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.4</td><td>0.031</td><td>1.382</td><td>2.980</td></tr> <tr><td>8.5</td><td>0.031</td><td>1.364</td><td>2.940</td></tr> <tr><td>9.0</td><td>0.031</td><td>1.288</td><td>2.763</td></tr> <tr><td>9.2</td><td>0.031</td><td>1.273</td><td>2.697</td></tr> <tr><td>12.0</td><td>0.023</td><td>0.976</td><td>2.060</td></tr> <tr><td>18.0</td><td>0.019</td><td>0.661</td><td>1.380</td></tr> <tr><td>24.0</td><td>0.017</td><td>0.504</td><td>1.038</td></tr> <tr><td>36.0</td><td>0.017</td><td>0.351</td><td>0.706</td></tr> <tr><td>40.0</td><td>0.017</td><td>0.321</td><td>0.642</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.002	0.002	0.002	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.002	8.4	0.031	1.382	2.980	8.5	0.031	1.364	2.940	9.0	0.031	1.288	2.763	9.2	0.031	1.273	2.697	12.0	0.023	0.976	2.060	18.0	0.019	0.661	1.380	24.0	0.017	0.504	1.038	36.0	0.017	0.351	0.706	40.0	0.017	0.321	0.642	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
2.0	0.000	0.000	0.000																																																																															
4.0	0.000	0.000	0.000																																																																															
6.0	0.002	0.002	0.002																																																																															
7.0	0.002	0.002	0.002																																																																															
8.0	0.002	0.002	0.002																																																																															
8.4	0.031	1.382	2.980																																																																															
8.5	0.031	1.364	2.940																																																																															
9.0	0.031	1.288	2.763																																																																															
9.2	0.031	1.273	2.697																																																																															
12.0	0.023	0.976	2.060																																																																															
18.0	0.019	0.661	1.380																																																																															
24.0	0.017	0.504	1.038																																																																															
36.0	0.017	0.351	0.706																																																																															
40.0	0.017	0.321	0.642																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

Model	MGFW302405																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.031</td> <td>0.025</td> <td>0.019</td> <td>0.018</td> <td>0.017</td> </tr> <tr> <td>20</td> <td>0.556</td> <td>0.419</td> <td>0.289</td> <td>0.225</td> <td>0.161</td> </tr> <tr> <td>40</td> <td>1.057</td> <td>0.799</td> <td>0.540</td> <td>0.415</td> <td>0.290</td> </tr> <tr> <td>60</td> <td>1.567</td> <td>1.180</td> <td>0.794</td> <td>0.603</td> <td>0.417</td> </tr> <tr> <td>80</td> <td>2.090</td> <td>1.564</td> <td>1.049</td> <td>0.796</td> <td>0.545</td> </tr> <tr> <td>100</td> <td>2.622</td> <td>1.974</td> <td>1.313</td> <td>0.993</td> <td>0.675</td> </tr> <tr> <td>110</td> <td>2.910</td> <td>2.164</td> <td>1.448</td> <td>1.088</td> <td>0.741</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ration [%]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.031	0.025	0.019	0.018	0.017	20	0.556	0.419	0.289	0.225	0.161	40	1.057	0.799	0.540	0.415	0.290	60	1.567	1.180	0.794	0.603	0.417	80	2.090	1.564	1.049	0.796	0.545	100	2.622	1.974	1.313	0.993	0.675	110	2.910	2.164	1.448	1.088	0.741	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.031	0.025	0.019	0.018	0.017																																																																													
20	0.556	0.419	0.289	0.225	0.161																																																																													
40	1.057	0.799	0.540	0.415	0.290																																																																													
60	1.567	1.180	0.794	0.603	0.417																																																																													
80	2.090	1.564	1.049	0.796	0.545																																																																													
100	2.622	1.974	1.313	0.993	0.675																																																																													
110	2.910	2.164	1.448	1.088	0.741																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	MGFW302405																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.28</td><td>0.29</td><td>0.35</td><td>0.43</td><td>0.61</td></tr> <tr><td>20</td><td>4.98</td><td>5.03</td><td>5.18</td><td>5.38</td><td>5.81</td></tr> <tr><td>40</td><td>9.47</td><td>9.53</td><td>9.71</td><td>9.91</td><td>10.44</td></tr> <tr><td>60</td><td>14.05</td><td>14.09</td><td>14.24</td><td>14.46</td><td>14.98</td></tr> <tr><td>80</td><td>18.75</td><td>18.73</td><td>18.86</td><td>19.04</td><td>19.58</td></tr> <tr><td>100</td><td>23.52</td><td>23.49</td><td>23.56</td><td>23.74</td><td>24.24</td></tr> <tr><td>110</td><td>25.95</td><td>25.91</td><td>25.94</td><td>26.11</td><td>26.59</td></tr> </tbody> </table>					Load Ration [%]	9[V]	12[V]	18[V]	24[V]	36[V]	0	0.28	0.29	0.35	0.43	0.61	20	4.98	5.03	5.18	5.38	5.81	40	9.47	9.53	9.71	9.91	10.44	60	14.05	14.09	14.24	14.46	14.98	80	18.75	18.73	18.86	19.04	19.58	100	23.52	23.49	23.56	23.74	24.24	110	25.95	25.91	25.94	26.11	26.59																													
Load Ration [%]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.28	0.29	0.35	0.43	0.61																																																																													
20	4.98	5.03	5.18	5.38	5.81																																																																													
40	9.47	9.53	9.71	9.91	10.44																																																																													
60	14.05	14.09	14.24	14.46	14.98																																																																													
80	18.75	18.73	18.86	19.04	19.58																																																																													
100	23.52	23.49	23.56	23.74	24.24																																																																													
110	25.95	25.91	25.94	26.11	26.59																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.28</td><td>0.29</td><td>0.35</td><td>0.43</td><td>0.61</td></tr> <tr><td>20</td><td>4.98</td><td>5.03</td><td>5.18</td><td>5.38</td><td>5.81</td></tr> <tr><td>40</td><td>9.47</td><td>9.53</td><td>9.71</td><td>9.91</td><td>10.44</td></tr> <tr><td>60</td><td>14.05</td><td>14.09</td><td>14.24</td><td>14.46</td><td>14.98</td></tr> <tr><td>80</td><td>18.75</td><td>18.73</td><td>18.86</td><td>19.04</td><td>19.58</td></tr> <tr><td>100</td><td>23.52</td><td>23.49</td><td>23.56</td><td>23.74</td><td>24.24</td></tr> <tr><td>110</td><td>25.95</td><td>25.91</td><td>25.94</td><td>26.11</td><td>26.59</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.28	0.29	0.35	0.43	0.61	20	4.98	5.03	5.18	5.38	5.81	40	9.47	9.53	9.71	9.91	10.44	60	14.05	14.09	14.24	14.46	14.98	80	18.75	18.73	18.86	19.04	19.58	100	23.52	23.49	23.56	23.74	24.24	110	25.95	25.91	25.94	26.11	26.59	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Input Power [W]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.28	0.29	0.35	0.43	0.61																																																																													
20	4.98	5.03	5.18	5.38	5.81																																																																													
40	9.47	9.53	9.71	9.91	10.44																																																																													
60	14.05	14.09	14.24	14.46	14.98																																																																													
80	18.75	18.73	18.86	19.04	19.58																																																																													
100	23.52	23.49	23.56	23.74	24.24																																																																													
110	25.95	25.91	25.94	26.11	26.59																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													


Model	MGFW302405																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (5 to 45). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight downward trend as input voltage increases. Two slanted lines on the graph indicate the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>10</td><td>86.3</td><td>86.0</td></tr> <tr><td>15</td><td>86.8</td><td>86.4</td></tr> <tr><td>20</td><td>86.3</td><td>86.5</td></tr> <tr><td>25</td><td>85.7</td><td>86.6</td></tr> <tr><td>30</td><td>84.9</td><td>86.3</td></tr> <tr><td>35</td><td>83.5</td><td>85.7</td></tr> <tr><td>40</td><td>81.9</td><td>84.9</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	10	86.3	86.0	15	86.8	86.4	20	86.3	86.5	25	85.7	86.6	30	84.9	86.3	35	83.5	85.7	40	81.9	84.9								
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
10	86.3	86.0																																
15	86.8	86.4																																
20	86.3	86.5																																
25	85.7	86.6																																
30	84.9	86.3																																
35	83.5	85.7																																
40	81.9	84.9																																
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>86.3</td><td>86.0</td></tr> <tr><td>9.0</td><td>86.8</td><td>86.4</td></tr> <tr><td>12.0</td><td>86.3</td><td>86.5</td></tr> <tr><td>15.0</td><td>85.7</td><td>86.6</td></tr> <tr><td>18.0</td><td>84.9</td><td>86.3</td></tr> <tr><td>24.0</td><td>83.5</td><td>85.7</td></tr> <tr><td>30.0</td><td>81.9</td><td>84.9</td></tr> <tr><td>36.0</td><td>80.0</td><td>83.9</td></tr> <tr><td>40.0</td><td>78.8</td><td>83.2</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	86.3	86.0	9.0	86.8	86.4	12.0	86.3	86.5	15.0	85.7	86.6	18.0	84.9	86.3	24.0	83.5	85.7	30.0	81.9	84.9	36.0	80.0	83.9	40.0	78.8	83.2
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	86.3	86.0																																
9.0	86.8	86.4																																
12.0	86.3	86.5																																
15.0	85.7	86.6																																
18.0	84.9	86.3																																
24.0	83.5	85.7																																
30.0	81.9	84.9																																
36.0	80.0	83.9																																
40.0	78.8	83.2																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		


Model	MGFW302405																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>9V</th> <th>12V</th> <th>18V</th> <th>24V</th> <th>36V</th> </tr> </thead> <tbody> <tr><td>20</td><td>81.5</td><td>80.7</td><td>78.4</td><td>75.5</td><td>69.9</td></tr> <tr><td>40</td><td>85.8</td><td>85.3</td><td>83.7</td><td>82.0</td><td>77.8</td></tr> <tr><td>60</td><td>86.8</td><td>86.5</td><td>85.6</td><td>84.3</td><td>81.4</td></tr> <tr><td>80</td><td>86.7</td><td>86.8</td><td>86.2</td><td>85.4</td><td>83.1</td></tr> <tr><td>100</td><td>86.4</td><td>86.5</td><td>86.3</td><td>85.6</td><td>83.8</td></tr> <tr><td>110</td><td>86.2</td><td>86.3</td><td>86.2</td><td>85.6</td><td>84.1</td></tr> </tbody> </table>					Load Ration [%]	9V	12V	18V	24V	36V	20	81.5	80.7	78.4	75.5	69.9	40	85.8	85.3	83.7	82.0	77.8	60	86.8	86.5	85.6	84.3	81.4	80	86.7	86.8	86.2	85.4	83.1	100	86.4	86.5	86.3	85.6	83.8	110	86.2	86.3	86.2	85.6	84.1																																			
Load Ration [%]	9V	12V	18V	24V	36V																																																																													
20	81.5	80.7	78.4	75.5	69.9																																																																													
40	85.8	85.3	83.7	82.0	77.8																																																																													
60	86.8	86.5	85.6	84.3	81.4																																																																													
80	86.7	86.8	86.2	85.4	83.1																																																																													
100	86.4	86.5	86.3	85.6	83.8																																																																													
110	86.2	86.3	86.2	85.6	84.1																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>81.5</td><td>80.7</td><td>78.4</td><td>75.5</td><td>69.9</td></tr> <tr><td>40</td><td>85.8</td><td>85.3</td><td>83.7</td><td>82.0</td><td>77.8</td></tr> <tr><td>60</td><td>86.8</td><td>86.5</td><td>85.6</td><td>84.3</td><td>81.4</td></tr> <tr><td>80</td><td>86.7</td><td>86.8</td><td>86.2</td><td>85.4</td><td>83.1</td></tr> <tr><td>100</td><td>86.4</td><td>86.5</td><td>86.3</td><td>85.6</td><td>83.8</td></tr> <tr><td>110</td><td>86.2</td><td>86.3</td><td>86.2</td><td>85.6</td><td>84.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Efficiency [%]					9[V]	12[V]	18[V]	24[V]	36[V]	0	-	-	-	-	-	20	81.5	80.7	78.4	75.5	69.9	40	85.8	85.3	83.7	82.0	77.8	60	86.8	86.5	85.6	84.3	81.4	80	86.7	86.8	86.2	85.4	83.1	100	86.4	86.5	86.3	85.6	83.8	110	86.2	86.3	86.2	85.6	84.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	-	-	-	-	-																																																																													
20	81.5	80.7	78.4	75.5	69.9																																																																													
40	85.8	85.3	83.7	82.0	77.8																																																																													
60	86.8	86.5	85.6	84.3	81.4																																																																													
80	86.7	86.8	86.2	85.4	83.1																																																																													
100	86.4	86.5	86.3	85.6	83.8																																																																													
110	86.2	86.3	86.2	85.6	84.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	MGFW302405	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+5V2A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>5.124</td><td>5.077</td></tr> <tr><td>9.0</td><td>5.124</td><td>5.077</td></tr> <tr><td>12.0</td><td>5.122</td><td>5.077</td></tr> <tr><td>15.0</td><td>5.121</td><td>5.077</td></tr> <tr><td>18.0</td><td>5.120</td><td>5.076</td></tr> <tr><td>24.0</td><td>5.119</td><td>5.076</td></tr> <tr><td>30.0</td><td>5.119</td><td>5.076</td></tr> <tr><td>36.0</td><td>5.119</td><td>5.076</td></tr> <tr><td>40.0</td><td>5.119</td><td>5.076</td></tr> </tbody> </table> <p>-5V: Rated output current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	5.124	5.077	9.0	5.124	5.077	12.0	5.122	5.077	15.0	5.121	5.077	18.0	5.120	5.076	24.0	5.119	5.076	30.0	5.119	5.076	36.0	5.119	5.076	40.0	5.119	5.076
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.5	5.124	5.077																																
9.0	5.124	5.077																																
12.0	5.122	5.077																																
15.0	5.121	5.077																																
18.0	5.120	5.076																																
24.0	5.119	5.076																																
30.0	5.119	5.076																																
36.0	5.119	5.076																																
40.0	5.119	5.076																																
Object	-5V2A	2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>-5.124</td><td>-5.071</td></tr> <tr><td>9.0</td><td>-5.124</td><td>-5.071</td></tr> <tr><td>12.0</td><td>-5.121</td><td>-5.072</td></tr> <tr><td>15.0</td><td>-5.120</td><td>-5.072</td></tr> <tr><td>18.0</td><td>-5.120</td><td>-5.072</td></tr> <tr><td>24.0</td><td>-5.119</td><td>-5.073</td></tr> <tr><td>30.0</td><td>-5.119</td><td>-5.073</td></tr> <tr><td>36.0</td><td>-5.119</td><td>-5.073</td></tr> <tr><td>40.0</td><td>-5.119</td><td>-5.073</td></tr> </tbody> </table> <p>+5V: Rated output current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	-5.124	-5.071	9.0	-5.124	-5.071	12.0	-5.121	-5.072	15.0	-5.120	-5.072	18.0	-5.120	-5.072	24.0	-5.119	-5.073	30.0	-5.119	-5.073	36.0	-5.119	-5.073	40.0	-5.119	-5.073
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.5	-5.124	-5.071																																
9.0	-5.124	-5.071																																
12.0	-5.121	-5.072																																
15.0	-5.120	-5.072																																
18.0	-5.120	-5.072																																
24.0	-5.119	-5.073																																
30.0	-5.119	-5.073																																
36.0	-5.119	-5.073																																
40.0	-5.119	-5.073																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	MGFW302405	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Load Regulation																																																																																		
Object	+5V2A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 9V 12V 18V 24V 36V 																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5.586</td><td>5.595</td><td>5.621</td><td>5.635</td><td>5.695</td></tr> <tr><td>0.100</td><td>5.210</td><td>5.209</td><td>5.188</td><td>5.184</td><td>5.181</td></tr> <tr><td>0.400</td><td>5.163</td><td>5.162</td><td>5.160</td><td>5.160</td><td>5.161</td></tr> <tr><td>0.800</td><td>5.136</td><td>5.135</td><td>5.132</td><td>5.131</td><td>5.132</td></tr> <tr><td>1.200</td><td>5.115</td><td>5.113</td><td>5.112</td><td>5.111</td><td>5.111</td></tr> <tr><td>1.600</td><td>5.095</td><td>5.095</td><td>5.093</td><td>5.092</td><td>5.092</td></tr> <tr><td>2.000</td><td>5.076</td><td>5.076</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.200</td><td>5.067</td><td>5.067</td><td>5.066</td><td>5.067</td><td>5.066</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>						Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	5.586	5.595	5.621	5.635	5.695	0.100	5.210	5.209	5.188	5.184	5.181	0.400	5.163	5.162	5.160	5.160	5.161	0.800	5.136	5.135	5.132	5.131	5.132	1.200	5.115	5.113	5.112	5.111	5.111	1.600	5.095	5.095	5.093	5.092	5.092	2.000	5.076	5.076	5.075	5.075	5.075	2.200	5.067	5.067	5.066	5.067	5.066	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.000	5.586	5.595	5.621	5.635	5.695																																																																														
0.100	5.210	5.209	5.188	5.184	5.181																																																																														
0.400	5.163	5.162	5.160	5.160	5.161																																																																														
0.800	5.136	5.135	5.132	5.131	5.132																																																																														
1.200	5.115	5.113	5.112	5.111	5.111																																																																														
1.600	5.095	5.095	5.093	5.092	5.092																																																																														
2.000	5.076	5.076	5.075	5.075	5.075																																																																														
2.200	5.067	5.067	5.066	5.067	5.066																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-5V2A	<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 9V 12V 18V 24V 36V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-5.541</td><td>-5.558</td><td>-5.587</td><td>-5.603</td><td>-5.685</td></tr> <tr><td>0.1</td><td>-5.203</td><td>-5.200</td><td>-5.184</td><td>-5.179</td><td>-5.174</td></tr> <tr><td>0.4</td><td>-5.165</td><td>-5.163</td><td>-5.162</td><td>-5.162</td><td>-5.163</td></tr> <tr><td>0.8</td><td>-5.135</td><td>-5.133</td><td>-5.131</td><td>-5.130</td><td>-5.130</td></tr> <tr><td>1.2</td><td>-5.112</td><td>-5.110</td><td>-5.109</td><td>-5.109</td><td>-5.109</td></tr> <tr><td>1.6</td><td>-5.091</td><td>-5.090</td><td>-5.090</td><td>-5.090</td><td>-5.090</td></tr> <tr><td>2.0</td><td>-5.070</td><td>-5.071</td><td>-5.071</td><td>-5.072</td><td>-5.072</td></tr> <tr><td>2.2</td><td>-5.061</td><td>-5.062</td><td>-5.063</td><td>-5.063</td><td>-5.064</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>						Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	-5.541	-5.558	-5.587	-5.603	-5.685	0.1	-5.203	-5.200	-5.184	-5.179	-5.174	0.4	-5.165	-5.163	-5.162	-5.162	-5.163	0.8	-5.135	-5.133	-5.131	-5.130	-5.130	1.2	-5.112	-5.110	-5.109	-5.109	-5.109	1.6	-5.091	-5.090	-5.090	-5.090	-5.090	2.0	-5.070	-5.071	-5.071	-5.072	-5.072	2.2	-5.061	-5.062	-5.063	-5.063	-5.064	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.000	-5.541	-5.558	-5.587	-5.603	-5.685																																																																														
0.1	-5.203	-5.200	-5.184	-5.179	-5.174																																																																														
0.4	-5.165	-5.163	-5.162	-5.162	-5.163																																																																														
0.8	-5.135	-5.133	-5.131	-5.130	-5.130																																																																														
1.2	-5.112	-5.110	-5.109	-5.109	-5.109																																																																														
1.6	-5.091	-5.090	-5.090	-5.090	-5.090																																																																														
2.0	-5.070	-5.071	-5.071	-5.072	-5.072																																																																														
2.2	-5.061	-5.062	-5.063	-5.063	-5.064																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																			





COSSEL

Model	MGFW302405																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+5V2A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 120 mV, and the X-axis ranges from 0.0 to 2.0 A. Two curves are shown: a solid line for 9V and a dashed line for 36V. Both curves remain near zero until approximately 1.2A, then rise sharply to about 110mV at 2.0A. A slanted line indicates the rated load current range.</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>2</td> <td>1</td> </tr> <tr> <td>0.4</td> <td>2</td> <td>3</td> </tr> <tr> <td>0.8</td> <td>2</td> <td>3</td> </tr> <tr> <td>1.2</td> <td>2</td> <td>3</td> </tr> <tr> <td>1.6</td> <td>3</td> <td>3</td> </tr> <tr> <td>2.0</td> <td>3</td> <td>3</td> </tr> <tr> <td>2.2</td> <td>3</td> <td>3</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	2	1	0.4	2	3	0.8	2	3	1.2	2	3	1.6	3	3	2.0	3	3	2.2	3	3	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.0	2	1																																						
0.4	2	3																																						
0.8	2	3																																						
1.2	2	3																																						
1.6	3	3																																						
2.0	3	3																																						
2.2	3	3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>-5V: Rated output current</p> <p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form</p>																																								

COSSEL

Model	MGFW302405																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-5V2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 120 mV, and the X-axis ranges from 0.0 to 2.0 A. Two curves are shown: one for Input Volt. 9V (solid line with open circles) and one for Input Volt. 36V (dashed line with open circles). Both curves show low ripple voltage (around 2-3 mV) across the load current range, with a slanted line indicating the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>2</td> <td>1</td> </tr> <tr> <td>0.4</td> <td>2</td> <td>4</td> </tr> <tr> <td>0.8</td> <td>2</td> <td>4</td> </tr> <tr> <td>1.2</td> <td>2</td> <td>4</td> </tr> <tr> <td>1.6</td> <td>3</td> <td>4</td> </tr> <tr> <td>2.0</td> <td>3</td> <td>4</td> </tr> <tr> <td>2.2</td> <td>3</td> <td>4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+5V: Rated output current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	2	1	0.4	2	4	0.8	2	4	1.2	2	4	1.6	3	4	2.0	3	4	2.2	3	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.0	2	1																																						
0.4	2	4																																						
0.8	2	4																																						
1.2	2	4																																						
1.6	3	4																																						
2.0	3	4																																						
2.2	3	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								


COSEL

Model	MGFW302405	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+5V2A	2. Values																																							
1. Graph																																									
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>5</td><td>10</td></tr> <tr><td>0.8</td><td>5</td><td>10</td></tr> <tr><td>1.2</td><td>5</td><td>10</td></tr> <tr><td>1.6</td><td>5</td><td>10</td></tr> <tr><td>2.0</td><td>5</td><td>10</td></tr> <tr><td>2.2</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	5	5	0.4	5	10	0.8	5	10	1.2	5	10	1.6	5	10	2.0	5	10	2.2	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.0	5	5																																							
0.4	5	10																																							
0.8	5	10																																							
1.2	5	10																																							
1.6	5	10																																							
2.0	5	10																																							
2.2	5	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Noise Wave Form</p>																																									

Model	MGFW302405																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-5V2A																																							
1. Graph																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>5</td><td>10</td></tr> <tr><td>0.8</td><td>5</td><td>10</td></tr> <tr><td>1.2</td><td>5</td><td>10</td></tr> <tr><td>1.6</td><td>5</td><td>10</td></tr> <tr><td>2.0</td><td>5</td><td>10</td></tr> <tr><td>2.2</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.0	5	5	0.4	5	10	0.8	5	10	1.2	5	10	1.6	5	10	2.0	5	10	2.2	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.0	5	5																																						
0.4	5	10																																						
0.8	5	10																																						
1.2	5	10																																						
1.6	5	10																																						
2.0	5	10																																						
2.2	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+5V: Rated output current																																								
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

Model	MGFW302405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	12	11
-40	7	8
-20	5	5
0	4	4
25	3	3
60	3	3
65	3	3
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	15	15
-40	10	10
-20	7	7
0	6	6
25	5	5
60	4	4
65	4	4
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW302405	Testing Circuitry Figure A																																																																																	
Item	Ambient Temperature Drift																																																																																		
Object	+5V2A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5.053</td><td>5.054</td><td>5.055</td><td>5.056</td><td>5.056</td></tr> <tr><td>-40</td><td>5.062</td><td>5.063</td><td>5.063</td><td>5.064</td><td>5.064</td></tr> <tr><td>-20</td><td>5.069</td><td>5.069</td><td>5.070</td><td>5.070</td><td>5.070</td></tr> <tr><td>0</td><td>5.074</td><td>5.074</td><td>5.074</td><td>5.074</td><td>5.074</td></tr> <tr><td>25</td><td>5.077</td><td>5.077</td><td>5.077</td><td>5.077</td><td>5.076</td></tr> <tr><td>60</td><td>5.078</td><td>5.078</td><td>5.077</td><td>5.077</td><td>5.076</td></tr> <tr><td>65</td><td>5.078</td><td>5.077</td><td>5.077</td><td>5.076</td><td>5.075</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	5.053	5.054	5.055	5.056	5.056	-40	5.062	5.063	5.063	5.064	5.064	-20	5.069	5.069	5.070	5.070	5.070	0	5.074	5.074	5.074	5.074	5.074	25	5.077	5.077	5.077	5.077	5.076	60	5.078	5.078	5.077	5.077	5.076	65	5.078	5.077	5.077	5.076	5.075	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
-60	5.053	5.054	5.055	5.056	5.056																																																																														
-40	5.062	5.063	5.063	5.064	5.064																																																																														
-20	5.069	5.069	5.070	5.070	5.070																																																																														
0	5.074	5.074	5.074	5.074	5.074																																																																														
25	5.077	5.077	5.077	5.077	5.076																																																																														
60	5.078	5.078	5.077	5.077	5.076																																																																														
65	5.078	5.077	5.077	5.076	5.075																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-5V2A	2.Values																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-5.046</td><td>-5.048</td><td>-5.049</td><td>-5.051</td><td>-5.051</td></tr> <tr><td>-40</td><td>-5.055</td><td>-5.057</td><td>-5.058</td><td>-5.059</td><td>-5.060</td></tr> <tr><td>-20</td><td>-5.062</td><td>-5.063</td><td>-5.064</td><td>-5.065</td><td>-5.066</td></tr> <tr><td>0</td><td>-5.067</td><td>-5.068</td><td>-5.068</td><td>-5.069</td><td>-5.070</td></tr> <tr><td>25</td><td>-5.070</td><td>-5.071</td><td>-5.072</td><td>-5.072</td><td>-5.073</td></tr> <tr><td>60</td><td>-5.071</td><td>-5.072</td><td>-5.073</td><td>-5.073</td><td>-5.073</td></tr> <tr><td>65</td><td>-5.071</td><td>-5.072</td><td>-5.072</td><td>-5.073</td><td>-5.073</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	-5.046	-5.048	-5.049	-5.051	-5.051	-40	-5.055	-5.057	-5.058	-5.059	-5.060	-20	-5.062	-5.063	-5.064	-5.065	-5.066	0	-5.067	-5.068	-5.068	-5.069	-5.070	25	-5.070	-5.071	-5.072	-5.072	-5.073	60	-5.071	-5.072	-5.073	-5.073	-5.073	65	-5.071	-5.072	-5.072	-5.073	-5.073	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
-60	-5.046	-5.048	-5.049	-5.051	-5.051																																																																														
-40	-5.055	-5.057	-5.058	-5.059	-5.060																																																																														
-20	-5.062	-5.063	-5.064	-5.065	-5.066																																																																														
0	-5.067	-5.068	-5.068	-5.069	-5.070																																																																														
25	-5.070	-5.071	-5.072	-5.072	-5.073																																																																														
60	-5.071	-5.072	-5.073	-5.073	-5.073																																																																														
65	-5.071	-5.072	-5.072	-5.073	-5.073																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																	



Model	MGFW302405	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 2A (AVR 2) : 0 - 2A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36		0	5.706	±322
Minimum Voltage	-40	9	2	5.062		±6.4

Object	-5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	36		0	-5.697	±321
Minimum Voltage	-40	9	2	-5.055		±6.4


COSEL

Model	MGFW302405
-------	------------

Item	Time Lapse Drift
------	------------------

Object	+5V2A
--------	-------


1.Graph



Input Volt. 24V
Load 100%

Object	-5V2A
--------	-------

1.Graph



Input Volt. 24V
Load 100%

Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	5.075
0.5	5.077
1.0	5.077
2.0	5.077
3.0	5.077
4.0	5.077
5.0	5.077
6.0	5.077
7.0	5.077
8.0	5.077

2.Values


Time since start [H]	Output Voltage [V]
0.0	-5.072
0.5	-5.079
1.0	-5.079
2.0	-5.079
3.0	-5.079
4.0	-5.079
5.0	-5.079
6.0	-5.079
7.0	-5.079
8.0	-5.079

COSEL

Model	MGFW302405
Item	Rise and Fall Time
Object	+5V2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.1	8.4	10.5	1.3	0.8	
100 %		2.1	8.5	10.6	0.6	0.5	




COSEL

Model	MGFW302405
Item	Rise and Fall Time
Object	-5V2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.1	8.5	10.6	1.3	1.0	
100 %		2.1	8.4	10.5	0.6	0.6	



Model	MGFW302405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.2	8.1
-40	8.2	8.3
-20	8.2	8.2
0	8.2	8.1
25	8.2	8.1
60	8.2	8.1
65	8.0	8.1
--	-	-
--	-	-
--	-	-
--	-	-

Object	-5V2A
--------	-------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.1	8.0
-40	8.1	8.2
-20	8.1	8.0
0	8.1	8.0
25	8.1	8.0
60	8.1	8.0
65	7.9	8.0
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW302405	Temperature 25°C Testing Circuitry Figure A																																																																																							
Item	Overcurrent Protection																																																																																								
Object	+5V2A																																																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 9V —□— Input Volt. 12V —*— Input Volt. 18V —○— Input Volt. 24V —◇— Input Volt. 36V 																																																																																								
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>2.993</td><td>3.551</td><td>3.989</td><td>3.964</td><td>3.445</td></tr> <tr><td>4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	5.00	2.993	3.551	3.989	3.964	3.445	4.75	-	-	-	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																								
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																				
5.00	2.993	3.551	3.989	3.964	3.445																																																																																				
4.75	-	-	-	-	-																																																																																				
4.50	-	-	-	-	-																																																																																				
4.00	-	-	-	-	-																																																																																				
3.50	-	-	-	-	-																																																																																				
3.00	-	-	-	-	-																																																																																				
2.50	-	-	-	-	-																																																																																				
2.00	-	-	-	-	-																																																																																				
1.50	-	-	-	-	-																																																																																				
1.00	-	-	-	-	-																																																																																				
0.50	-	-	-	-	-																																																																																				
0.00	-	-	-	-	-																																																																																				
Object	-5V2A	<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 9V —□— Input Volt. 12V —*— Input Volt. 18V —○— Input Volt. 24V —◇— Input Volt. 36V 																																																																																							
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-5.00</td><td>2.928</td><td>3.521</td><td>3.967</td><td>3.967</td><td>3.441</td></tr> <tr><td>-4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	-5.00	2.928	3.521	3.967	3.967	3.441	-4.75	-	-	-	-	-	-4.50	-	-	-	-	-	-4.00	-	-	-	-	-	-3.50	-	-	-	-	-	-3.00	-	-	-	-	-	-2.50	-	-	-	-	-	-2.00	-	-	-	-	-	-1.50	-	-	-	-	-	-1.00	-	-	-	-	-	-0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																								
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																				
-5.00	2.928	3.521	3.967	3.967	3.441																																																																																				
-4.75	-	-	-	-	-																																																																																				
-4.50	-	-	-	-	-																																																																																				
-4.00	-	-	-	-	-																																																																																				
-3.50	-	-	-	-	-																																																																																				
-3.00	-	-	-	-	-																																																																																				
-2.50	-	-	-	-	-																																																																																				
-2.00	-	-	-	-	-																																																																																				
-1.50	-	-	-	-	-																																																																																				
-1.00	-	-	-	-	-																																																																																				
-0.50	-	-	-	-	-																																																																																				
0.00	-	-	-	-	-																																																																																				
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																																																									

Model	MGFW302405
Item	Oversupply Protection
Object	+10V2.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-60	13.41	13.42
-40	13.48	13.49
-20	13.63	13.64
0	13.77	13.78
25	13.98	14.00
60	14.20	14.29
65	14.28	14.29
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+10V).

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)