

# TEST DATA OF MGFW304805

Regulated DC Power Supply  
December 25, 2010

Approved by : Kazunari Asano  
Kazunari Asano

Design Manager

Prepared by : Masashi Ueda  
Masashi Ueda

Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)

Model	MGFW304805																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph	<p>—△— Load 100%</p> <p>- - -□-- Load 50%</p> <p>- -○-- Load 0%</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.001</td><td>0.001</td><td>0.002</td></tr> <tr><td>10.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>15.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.5</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>17.0</td><td>0.016</td><td>0.711</td><td>1.476</td></tr> <tr><td>17.5</td><td>0.016</td><td>0.670</td><td>1.439</td></tr> <tr><td>18.0</td><td>0.015</td><td>0.652</td><td>1.397</td></tr> <tr><td>24.0</td><td>0.013</td><td>0.491</td><td>1.043</td></tr> <tr><td>36.0</td><td>0.012</td><td>0.334</td><td>0.702</td></tr> <tr><td>48.0</td><td>0.012</td><td>0.255</td><td>0.531</td></tr> <tr><td>76.0</td><td>0.012</td><td>0.171</td><td>0.348</td></tr> <tr><td>80.0</td><td>0.012</td><td>0.164</td><td>0.332</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.001	0.001	0.002	10.0	0.002	0.002	0.002	15.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.5	0.002	0.002	0.002	17.0	0.016	0.711	1.476	17.5	0.016	0.670	1.439	18.0	0.015	0.652	1.397	24.0	0.013	0.491	1.043	36.0	0.012	0.334	0.702	48.0	0.012	0.255	0.531	76.0	0.012	0.171	0.348	80.0	0.012	0.164	0.332	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.001	0.001	0.002																																																																															
10.0	0.002	0.002	0.002																																																																															
15.0	0.002	0.002	0.002																																																																															
16.0	0.002	0.002	0.002																																																																															
16.5	0.002	0.002	0.002																																																																															
17.0	0.016	0.711	1.476																																																																															
17.5	0.016	0.670	1.439																																																																															
18.0	0.015	0.652	1.397																																																																															
24.0	0.013	0.491	1.043																																																																															
36.0	0.012	0.334	0.702																																																																															
48.0	0.012	0.255	0.531																																																																															
76.0	0.012	0.171	0.348																																																																															
80.0	0.012	0.164	0.332																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Note: Slanted line shows the range of the rated input voltage.

Model	MGFW304805																																																																								
Item	Input Current (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.015</td><td>0.013</td><td>0.012</td><td>0.012</td><td>0.012</td></tr> <tr><td>20</td><td>0.277</td><td>0.211</td><td>0.144</td><td>0.112</td><td>0.079</td></tr> <tr><td>40</td><td>0.527</td><td>0.401</td><td>0.272</td><td>0.209</td><td>0.141</td></tr> <tr><td>60</td><td>0.786</td><td>0.593</td><td>0.401</td><td>0.306</td><td>0.203</td></tr> <tr><td>80</td><td>1.052</td><td>0.789</td><td>0.533</td><td>0.404</td><td>0.266</td></tr> <tr><td>100</td><td>1.320</td><td>0.992</td><td>0.666</td><td>0.505</td><td>0.331</td></tr> <tr><td>110</td><td>1.461</td><td>1.096</td><td>0.736</td><td>0.556</td><td>0.364</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]	0	0.015	0.013	0.012	0.012	0.012	20	0.277	0.211	0.144	0.112	0.079	40	0.527	0.401	0.272	0.209	0.141	60	0.786	0.593	0.401	0.306	0.203	80	1.052	0.789	0.533	0.404	0.266	100	1.320	0.992	0.666	0.505	0.331	110	1.461	1.096	0.736	0.556	0.364	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																				
0	0.015	0.013	0.012	0.012	0.012																																																																				
20	0.277	0.211	0.144	0.112	0.079																																																																				
40	0.527	0.401	0.272	0.209	0.141																																																																				
60	0.786	0.593	0.401	0.306	0.203																																																																				
80	1.052	0.789	0.533	0.404	0.266																																																																				
100	1.320	0.992	0.666	0.505	0.331																																																																				
110	1.461	1.096	0.736	0.556	0.364																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									

Model	MGFW304805																																																																												
Item	Input Power (by Load Current)																																																																												
Object	_____																																																																												
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.28</td><td>0.32</td><td>0.43</td><td>0.59</td><td>0.93</td></tr> <tr><td>20</td><td>4.98</td><td>5.06</td><td>5.19</td><td>5.39</td><td>5.99</td></tr> <tr><td>40</td><td>9.51</td><td>9.58</td><td>9.78</td><td>10.02</td><td>10.74</td></tr> <tr><td>60</td><td>14.15</td><td>14.21</td><td>14.41</td><td>14.65</td><td>15.45</td></tr> <tr><td>80</td><td>18.91</td><td>18.93</td><td>19.13</td><td>19.37</td><td>20.23</td></tr> <tr><td>100</td><td>23.78</td><td>23.77</td><td>23.93</td><td>24.19</td><td>25.15</td></tr> <tr><td>110</td><td>26.28</td><td>26.28</td><td>26.38</td><td>26.67</td><td>27.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]	0	0.28	0.32	0.43	0.59	0.93	20	4.98	5.06	5.19	5.39	5.99	40	9.51	9.58	9.78	10.02	10.74	60	14.15	14.21	14.41	14.65	15.45	80	18.91	18.93	19.13	19.37	20.23	100	23.78	23.77	23.93	24.19	25.15	110	26.28	26.28	26.38	26.67	27.65	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																								
0	0.28	0.32	0.43	0.59	0.93																																																																								
20	4.98	5.06	5.19	5.39	5.99																																																																								
40	9.51	9.58	9.78	10.02	10.74																																																																								
60	14.15	14.21	14.41	14.65	15.45																																																																								
80	18.91	18.93	19.13	19.37	20.23																																																																								
100	23.78	23.77	23.93	24.19	25.15																																																																								
110	26.28	26.28	26.38	26.67	27.65																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
2.Values																																																																													

Load Ration [%]	Input Power [W]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.28	0.32	0.43	0.59	0.93
20	4.98	5.06	5.19	5.39	5.99
40	9.51	9.58	9.78	10.02	10.74
60	14.15	14.21	14.41	14.65	15.45
80	18.91	18.93	19.13	19.37	20.23
100	23.78	23.77	23.93	24.19	25.15
110	26.28	26.28	26.38	26.67	27.65
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


Model	MGFW304805																																
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry      25°C      Figure A																															
Object	—	—																															
1. Graph																																	
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (10 to 90). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. A slanted line on the graph indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>15</td><td>86.2</td><td>85.0</td></tr> <tr><td>30</td><td>86.2</td><td>85.3</td></tr> <tr><td>50</td><td>85.6</td><td>85.4</td></tr> <tr><td>70</td><td>85.0</td><td>85.2</td></tr> <tr><td>80</td><td>84.2</td><td>84.9</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	15	86.2	85.0	30	86.2	85.3	50	85.6	85.4	70	85.0	85.2	80	84.2	84.9														
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
15	86.2	85.0																															
30	86.2	85.3																															
50	85.6	85.4																															
70	85.0	85.2																															
80	84.2	84.9																															
2. Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>86.2</td><td>85.0</td></tr> <tr><td>18</td><td>86.2</td><td>85.3</td></tr> <tr><td>24</td><td>85.6</td><td>85.4</td></tr> <tr><td>30</td><td>85.0</td><td>85.2</td></tr> <tr><td>36</td><td>84.2</td><td>84.9</td></tr> <tr><td>48</td><td>82.4</td><td>83.9</td></tr> <tr><td>60</td><td>80.5</td><td>82.7</td></tr> <tr><td>76</td><td>77.7</td><td>80.8</td></tr> <tr><td>80</td><td>77.1</td><td>80.2</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	86.2	85.0	18	86.2	85.3	24	85.6	85.4	30	85.0	85.2	36	84.2	84.9	48	82.4	83.9	60	80.5	82.7	76	77.7	80.8	80	77.1	80.2
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
17	86.2	85.0																															
18	86.2	85.3																															
24	85.6	85.4																															
30	85.0	85.2																															
36	84.2	84.9																															
48	82.4	83.9																															
60	80.5	82.7																															
76	77.7	80.8																															
80	77.1	80.2																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

Model	MGFW304805																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>81.4</td><td>80.1</td><td>78.2</td><td>75.2</td><td>67.7</td></tr> <tr> <td>40</td><td>85.4</td><td>84.7</td><td>83.0</td><td>81.1</td><td>75.6</td></tr> <tr> <td>60</td><td>86.1</td><td>85.8</td><td>84.6</td><td>83.2</td><td>78.9</td></tr> <tr> <td>80</td><td>85.9</td><td>85.9</td><td>85.0</td><td>83.9</td><td>80.4</td></tr> <tr> <td>100</td><td>85.4</td><td>85.5</td><td>84.9</td><td>84.0</td><td>80.8</td></tr> <tr> <td>110</td><td>85.1</td><td>85.1</td><td>84.8</td><td>83.8</td><td>80.9</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ration [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	81.4	80.1	78.2	75.2	67.7	40	85.4	84.7	83.0	81.1	75.6	60	86.1	85.8	84.6	83.2	78.9	80	85.9	85.9	85.0	83.9	80.4	100	85.4	85.5	84.9	84.0	80.8	110	85.1	85.1	84.8	83.8	80.9	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ration [%]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0	-	-	-	-	-																																																																													
20	81.4	80.1	78.2	75.2	67.7																																																																													
40	85.4	84.7	83.0	81.1	75.6																																																																													
60	86.1	85.8	84.6	83.2	78.9																																																																													
80	85.9	85.9	85.0	83.9	80.4																																																																													
100	85.4	85.5	84.9	84.0	80.8																																																																													
110	85.1	85.1	84.8	83.8	80.9																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model	MGFW304805
Item	Line Regulation
Object	+5V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	5.130	5.079
18	5.129	5.080
24	5.126	5.078
30	5.125	5.078
36	5.124	5.077
48	5.122	5.076
60	5.122	5.076
76	5.122	5.076
80	5.122	5.076

-5V: Rated output current

## Object -5V2A

## 1.Graph



## 2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-5.131	-5.076
18	-5.130	-5.076
24	-5.129	-5.078
30	-5.128	-5.079
36	-5.128	-5.079
48	-5.127	-5.080
60	-5.127	-5.081
76	-5.127	-5.081
80	-5.127	-5.081


+5V: Rated output current

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MGFW304805	Temperature	25°C																																																																													
Item	Load Regulation	Testing Circuitry	Figure A																																																																													
Object	+5V2A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 18V</li> <li>- - -□- - Input Volt. 24V</li> <li>- · · * · - Input Volt. 36V</li> <li>- · -○- - Input Volt. 48V</li> <li>- - ◇ - - Input Volt. 76V</li> </ul>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.572</td><td>5.591</td><td>5.657</td><td>5.688</td><td>5.710</td></tr> <tr><td>0.1</td><td>5.231</td><td>5.240</td><td>5.249</td><td>5.250</td><td>5.258</td></tr> <tr><td>0.4</td><td>5.176</td><td>5.178</td><td>5.180</td><td>5.182</td><td>5.184</td></tr> <tr><td>0.8</td><td>5.144</td><td>5.142</td><td>5.140</td><td>5.139</td><td>5.139</td></tr> <tr><td>1.2</td><td>5.121</td><td>5.119</td><td>5.116</td><td>5.115</td><td>5.115</td></tr> <tr><td>1.6</td><td>5.100</td><td>5.098</td><td>5.096</td><td>5.095</td><td>5.094</td></tr> <tr><td>2.0</td><td>5.080</td><td>5.078</td><td>5.076</td><td>5.076</td><td>5.075</td></tr> <tr><td>2.2</td><td>5.070</td><td>5.068</td><td>5.067</td><td>5.067</td><td>5.066</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	5.572	5.591	5.657	5.688	5.710	0.1	5.231	5.240	5.249	5.250	5.258	0.4	5.176	5.178	5.180	5.182	5.184	0.8	5.144	5.142	5.140	5.139	5.139	1.2	5.121	5.119	5.116	5.115	5.115	1.6	5.100	5.098	5.096	5.095	5.094	2.0	5.080	5.078	5.076	5.076	5.075	2.2	5.070	5.068	5.067	5.067	5.066	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	5.572	5.591	5.657	5.688	5.710																																																																											
0.1	5.231	5.240	5.249	5.250	5.258																																																																											
0.4	5.176	5.178	5.180	5.182	5.184																																																																											
0.8	5.144	5.142	5.140	5.139	5.139																																																																											
1.2	5.121	5.119	5.116	5.115	5.115																																																																											
1.6	5.100	5.098	5.096	5.095	5.094																																																																											
2.0	5.080	5.078	5.076	5.076	5.075																																																																											
2.2	5.070	5.068	5.067	5.067	5.066																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Object	-5V2A	2.Values																																																																														
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 18V</li> <li>- - -□- - Input Volt. 24V</li> <li>- · · * · - Input Volt. 36V</li> <li>- · -○- - Input Volt. 48V</li> <li>- - ◇ - - Input Volt. 76V</li> </ul>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.534</td><td>-5.550</td><td>-5.607</td><td>-5.623</td><td>-5.598</td></tr> <tr><td>0.1</td><td>-5.217</td><td>-5.214</td><td>-5.215</td><td>-5.217</td><td>-5.219</td></tr> <tr><td>0.4</td><td>-5.173</td><td>-5.171</td><td>-5.169</td><td>-5.169</td><td>-5.169</td></tr> <tr><td>0.8</td><td>-5.144</td><td>-5.142</td><td>-5.141</td><td>-5.141</td><td>-5.141</td></tr> <tr><td>1.2</td><td>-5.120</td><td>-5.119</td><td>-5.119</td><td>-5.119</td><td>-5.119</td></tr> <tr><td>1.6</td><td>-5.098</td><td>-5.098</td><td>-5.099</td><td>-5.099</td><td>-5.100</td></tr> <tr><td>2.0</td><td>-5.076</td><td>-5.077</td><td>-5.079</td><td>-5.080</td><td>-5.081</td></tr> <tr><td>2.2</td><td>-5.065</td><td>-5.068</td><td>-5.069</td><td>-5.071</td><td>-5.072</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	-5.534	-5.550	-5.607	-5.623	-5.598	0.1	-5.217	-5.214	-5.215	-5.217	-5.219	0.4	-5.173	-5.171	-5.169	-5.169	-5.169	0.8	-5.144	-5.142	-5.141	-5.141	-5.141	1.2	-5.120	-5.119	-5.119	-5.119	-5.119	1.6	-5.098	-5.098	-5.099	-5.099	-5.100	2.0	-5.076	-5.077	-5.079	-5.080	-5.081	2.2	-5.065	-5.068	-5.069	-5.071	-5.072	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	-5.534	-5.550	-5.607	-5.623	-5.598																																																																											
0.1	-5.217	-5.214	-5.215	-5.217	-5.219																																																																											
0.4	-5.173	-5.171	-5.169	-5.169	-5.169																																																																											
0.8	-5.144	-5.142	-5.141	-5.141	-5.141																																																																											
1.2	-5.120	-5.119	-5.119	-5.119	-5.119																																																																											
1.6	-5.098	-5.098	-5.099	-5.099	-5.100																																																																											
2.0	-5.076	-5.077	-5.079	-5.080	-5.081																																																																											
2.2	-5.065	-5.068	-5.069	-5.071	-5.072																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																

**COSEL**



**COSSEL**

Model	MGFW304805																																							
Item	Ripple Voltage (by Load Current)	Temperature      25°C Testing Circuitry      Figure B																																						
Object	+5V2A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>4</td><td>5</td></tr> <tr><td>0.4</td><td>3</td><td>3</td></tr> <tr><td>0.8</td><td>3</td><td>3</td></tr> <tr><td>1.2</td><td>3</td><td>3</td></tr> <tr><td>1.6</td><td>2</td><td>3</td></tr> <tr><td>2.0</td><td>2</td><td>3</td></tr> <tr><td>2.2</td><td>2</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	4	5	0.4	3	3	0.8	3	3	1.2	3	3	1.6	2	3	2.0	2	3	2.2	2	3	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	4	5																																						
0.4	3	3																																						
0.8	3	3																																						
1.2	3	3																																						
1.6	2	3																																						
2.0	2	3																																						
2.2	2	3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

**COSSEL**

Model	MGFW304805																																							
Item	Ripple Voltage (by Load Current)	Temperature      25°C Testing Circuitry      Figure B																																						
Object	-5V2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 18V (solid line with triangle markers) and Input Volt. 76V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.0 to 2.0. The y-axis represents Ripple Voltage [mV] from 0 to 120. Both curves show a slight increase in ripple voltage as load current increases, with the 18V curve generally higher than the 76V curve.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>1</td> <td>2</td> </tr> <tr> <td>0.4</td> <td>2</td> <td>4</td> </tr> <tr> <td>0.8</td> <td>2</td> <td>4</td> </tr> <tr> <td>1.2</td> <td>2</td> <td>4</td> </tr> <tr> <td>1.6</td> <td>3</td> <td>4</td> </tr> <tr> <td>2.0</td> <td>3</td> <td>4</td> </tr> <tr> <td>2.2</td> <td>3</td> <td>4</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+5V: Rated output current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	1	2	0.4	2	4	0.8	2	4	1.2	2	4	1.6	3	4	2.0	3	4	2.2	3	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	1	2																																						
0.4	2	4																																						
0.8	2	4																																						
1.2	2	4																																						
1.6	3	4																																						
2.0	3	4																																						
2.2	3	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Wave Form</p>																																								


**COSEL**

Model	MGFW304805																																							
Item	Ripple-Noise	Temperature      25°C Testing Circuitry      Figure B																																						
Object	+5V2A																																							
1. Graph																																								
<p>Input Volt. 18V Input Volt. 76V</p>																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.4</td><td>5</td><td>10</td></tr> <tr><td>0.8</td><td>5</td><td>10</td></tr> <tr><td>1.2</td><td>5</td><td>10</td></tr> <tr><td>1.6</td><td>5</td><td>10</td></tr> <tr><td>2.0</td><td>5</td><td>10</td></tr> <tr><td>2.2</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	10	10	0.4	5	10	0.8	5	10	1.2	5	10	1.6	5	10	2.0	5	10	2.2	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	10	10																																						
0.4	5	10																																						
0.8	5	10																																						
1.2	5	10																																						
1.6	5	10																																						
2.0	5	10																																						
2.2	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-5V: Rated output current																																								
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

Model	MGFW304805																																							
Item	Ripple-Noise	Temperature      25°C Testing Circuitry      Figure B																																						
Object	-5V2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>5</td><td>10</td></tr> <tr><td>0.8</td><td>5</td><td>10</td></tr> <tr><td>1.2</td><td>5</td><td>10</td></tr> <tr><td>1.6</td><td>10</td><td>10</td></tr> <tr><td>2.0</td><td>10</td><td>10</td></tr> <tr><td>2.2</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	5	5	0.4	5	10	0.8	5	10	1.2	5	10	1.6	10	10	2.0	10	10	2.2	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	5	5																																						
0.4	5	10																																						
0.8	5	10																																						
1.2	5	10																																						
1.6	10	10																																						
2.0	10	10																																						
2.2	10	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+5V: Rated output current																																								
<p>Ripple-Noise is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Noise Wave Form																																								

Model	MGFW304805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	11	11
-40	9	9
-20	6	6
0	5	5
25	3	4
60	3	3
65	3	3
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

## Object -5V2A



## 2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	15	15
-40	12	12
-20	8	8
0	7	7
25	5	5
60	4	4
65	4	4
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGFW304805
Item	Ambient Temperature Drift
Object	+5V2A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	5.054	5.054	5.054	5.054	5.054
-40	5.063	5.063	5.062	5.062	5.062
-20	5.070	5.070	5.069	5.069	5.069
0	5.076	5.075	5.074	5.074	5.073
25	5.081	5.079	5.078	5.078	5.077
60	5.084	5.082	5.081	5.080	5.079
65	5.084	5.082	5.080	5.079	5.079
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	-5.048	-5.050	-5.053	-5.054	-5.056
-40	-5.057	-5.060	-5.062	-5.063	-5.064
-20	-5.065	-5.067	-5.069	-5.070	-5.071
0	-5.070	-5.072	-5.074	-5.075	-5.076
25	-5.075	-5.077	-5.078	-5.079	-5.080
60	-5.078	-5.080	-5.082	-5.083	-5.083
65	-5.078	-5.080	-5.082	-5.083	-5.083
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW304805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 2A (AVR 2) : 0 - 2A

\* Other Output : Rated Load

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Object	+5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	76		0	5.976	$\pm 457$
Minimum Voltage	-40	76	2	5.062		$\pm 9.1$

Object	-5V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	48		0	-5.673	$\pm 308$
Minimum Voltage	-40	18	2	-5.057		$\pm 6.2$

**COSEL**

Model	MGFW304805
Item	Time Lapse Drift
Object	+5V2A


1.Graph



Input Volt. 48V  
Load 100%

Object	-5V2A
--------	-------

1.Graph



Input Volt. 48V  
Load 100%

Temperature 25°C  
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	5.076
0.5	5.081
1.0	5.080
2.0	5.080
3.0	5.080
4.0	5.080
5.0	5.080
6.0	5.080
7.0	5.080
8.0	5.080

2.Values


Time since start [H]	Output Voltage [V]
0.0	-5.080
0.5	-5.091
1.0	-5.091
2.0	-5.090
3.0	-5.090
4.0	-5.090
5.0	-5.090
6.0	-5.090
7.0	-5.090
8.0	-5.090

**COSEL**

Model	MGFW304805
Item	Rise and Fall Time
Object	+5V2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.1	7.9	10.0	0.2	0.8	
100 %		2.1	8.2	10.3	0.2	0.5	




**COSEL**

Model	MGFW304805
Item	Rise and Fall Time
Object	-5V2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.1	7.9	10.0	0.2	0.9	
100 %		2.1	8.0	10.1	0.2	0.5	



Model	MGFW304805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	16.4	16.3
-40	16.4	16.3
-20	16.4	16.3
0	16.0	16.3
25	16.0	16.3
60	16.0	16.3
65	16.0	15.9
--	-	-
--	-	-
--	-	-
--	-	-

Object	-5V2A
--------	-------

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	16.3	16.1
-40	16.3	16.1
-20	16.3	16.2
0	15.9	16.1
25	15.8	16.1
60	15.8	16.1
65	15.8	16.1
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW304805	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+5V2A																																																																																					
1.Graph		2.Values																																																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>3.339</td><td>3.818</td><td>4.176</td><td>4.224</td><td>3.877</td></tr> <tr><td>4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	5.00	3.339	3.818	4.176	4.224	3.877	4.75	-	-	-	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
5.00	3.339	3.818	4.176	4.224	3.877																																																																																	
4.75	-	-	-	-	-																																																																																	
4.50	-	-	-	-	-																																																																																	
4.00	-	-	-	-	-																																																																																	
3.50	-	-	-	-	-																																																																																	
3.00	-	-	-	-	-																																																																																	
2.50	-	-	-	-	-																																																																																	
2.00	-	-	-	-	-																																																																																	
1.50	-	-	-	-	-																																																																																	
1.00	-	-	-	-	-																																																																																	
0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	
1.Graph		2.Values																																																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-5.00</td><td>3.289</td><td>3.775</td><td>4.155</td><td>4.204</td><td>3.886</td></tr> <tr><td>-4.75</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-5.00	3.289	3.775	4.155	4.204	3.886	-4.75	-	-	-	-	-	-4.50	-	-	-	-	-	-4.00	-	-	-	-	-	-3.50	-	-	-	-	-	-3.00	-	-	-	-	-	-2.50	-	-	-	-	-	-2.00	-	-	-	-	-	-1.50	-	-	-	-	-	-1.00	-	-	-	-	-	-0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
-5.00	3.289	3.775	4.155	4.204	3.886																																																																																	
-4.75	-	-	-	-	-																																																																																	
-4.50	-	-	-	-	-																																																																																	
-4.00	-	-	-	-	-																																																																																	
-3.50	-	-	-	-	-																																																																																	
-3.00	-	-	-	-	-																																																																																	
-2.50	-	-	-	-	-																																																																																	
-2.00	-	-	-	-	-																																																																																	
-1.50	-	-	-	-	-																																																																																	
-1.00	-	-	-	-	-																																																																																	
-0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	


Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Model	MGFW304805
Item	Oversupply Protection
Object	+10V2.5A

Testing Circuitry Figure A

## 1. Graph



## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-60	13.37	13.37
-40	13.44	13.44
-20	13.59	13.59
0	13.73	13.73
25	13.94	13.94
60	14.16	14.23
65	14.23	14.23
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+10V).

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)