

TEST DATA OF MGFW400512

Regulated DC Power Supply

November 28, 2018

Approved by : Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide Design Engineer




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Switching frequency (by Load Current)	23
20.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	MGFW400512
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
3.8	0.133	0.004	0.004
3.9	0.115	4.673	10.498
4.0	0.128	4.503	9.995
4.1	0.126	4.030	9.546
4.2	0.110	4.269	9.146
4.3	0.121	4.267	8.807
4.4	0.119	4.155	8.536
4.5	0.116	4.026	8.223
5.0	0.095	3.557	7.318
7.0	0.049	2.525	5.009
9.0	0.040	1.962	3.904
13.0	0.035	1.399	2.705
15.0	0.035	1.234	2.400
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGFW400512
Item	Input Current (by Load Current)
Object	_____



 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0	0.116	0.095	0.049	0.040	0.035
20	1.609	1.441	1.032	0.819	0.600
40	3.112	2.779	1.995	1.576	1.118
60	4.715	4.177	2.957	2.318	1.646
80	6.338	5.706	4.018	3.083	2.163
100	8.223	7.318	5.009	3.904	2.705
110	9.111	8.072	5.580	4.274	2.963
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL

Model	MGFW400512
Item	Input Power (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Ratio [%]	Input Power [W]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0	0.53	0.48	0.35	0.36	0.45
20	7.26	7.26	7.32	7.45	7.82
40	14.23	14.18	14.15	14.23	14.62
60	21.35	21.20	20.99	21.03	21.44
80	28.96	28.69	28.14	28.01	28.27
100	37.15	36.58	35.50	35.19	35.24
110	41.51	40.69	39.29	38.83	38.80
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL

Model	MGFW400512
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.3	88.4	84.7
4.5	88.5	84.5
5.0	89.0	86.0
7.0	89.4	88.4
9.0	88.8	89.2
11.0	87.9	89.1
13.0	86.5	89.1
15.0	84.9	88.4
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFW400512
Item	Efficiency (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Ratio [%]	Efficiency [%]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0	-	-	-	-	-
20	86.1	86.1	85.6	84.1	79.9
40	87.9	88.0	88.4	87.9	85.5
60	88.2	88.6	89.6	89.4	87.7
80	86.6	87.4	89.2	89.6	88.7
100	84.5	86.0	88.4	89.2	89.1
110	83.2	84.8	87.9	88.9	88.9
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL

Model	MGFW400512
Item	Line Regulation
Object	+12V1.3A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	12.181	12.108
4.5	12.181	12.108
5.0	12.178	12.109
7.0	12.169	12.110
9.0	12.165	12.110
11.0	12.163	12.110
13.0	12.161	12.110
15.0	12.160	12.110
--	-	-

-12V: Rated Load Current

Object -12V1.3A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	-12.191	-12.116
4.5	-12.189	-12.116
5.0	-12.186	-12.116
7.0	-12.177	-12.115
9.0	-12.173	-12.115
11.0	-12.171	-12.115
13.0	-12.169	-12.115
15.0	-12.167	-12.115
--	-	-

+12V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFW400512	Temperature 25°C Testing Circuitry Figure A																																																																																	
Item	Load Regulation																																																																																		
Object	+12V1.3A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 4.5V - -□-- Input Volt. 5V - -★-- Input Volt. 7V - -○-- Input Volt. 9V - -◇-- Input Volt. 13V 																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.409</td><td>12.403</td><td>12.384</td><td>12.357</td><td>12.351</td></tr> <tr><td>0.26</td><td>12.225</td><td>12.226</td><td>12.222</td><td>12.214</td><td>12.209</td></tr> <tr><td>0.52</td><td>12.195</td><td>12.193</td><td>12.183</td><td>12.180</td><td>12.173</td></tr> <tr><td>0.65</td><td>12.181</td><td>12.178</td><td>12.169</td><td>12.165</td><td>12.161</td></tr> <tr><td>0.78</td><td>12.166</td><td>12.164</td><td>12.156</td><td>12.153</td><td>12.149</td></tr> <tr><td>0.91</td><td>12.152</td><td>12.150</td><td>12.144</td><td>12.142</td><td>12.138</td></tr> <tr><td>1.04</td><td>12.138</td><td>12.137</td><td>12.133</td><td>12.131</td><td>12.129</td></tr> <tr><td>1.30</td><td>12.108</td><td>12.109</td><td>12.110</td><td>12.110</td><td>12.110</td></tr> <tr><td>1.43</td><td>12.091</td><td>12.094</td><td>12.098</td><td>12.099</td><td>12.100</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0.00	12.409	12.403	12.384	12.357	12.351	0.26	12.225	12.226	12.222	12.214	12.209	0.52	12.195	12.193	12.183	12.180	12.173	0.65	12.181	12.178	12.169	12.165	12.161	0.78	12.166	12.164	12.156	12.153	12.149	0.91	12.152	12.150	12.144	12.142	12.138	1.04	12.138	12.137	12.133	12.131	12.129	1.30	12.108	12.109	12.110	12.110	12.110	1.43	12.091	12.094	12.098	12.099	12.100	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
0.00	12.409	12.403	12.384	12.357	12.351																																																																														
0.26	12.225	12.226	12.222	12.214	12.209																																																																														
0.52	12.195	12.193	12.183	12.180	12.173																																																																														
0.65	12.181	12.178	12.169	12.165	12.161																																																																														
0.78	12.166	12.164	12.156	12.153	12.149																																																																														
0.91	12.152	12.150	12.144	12.142	12.138																																																																														
1.04	12.138	12.137	12.133	12.131	12.129																																																																														
1.30	12.108	12.109	12.110	12.110	12.110																																																																														
1.43	12.091	12.094	12.098	12.099	12.100																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-12V1.3A	<p>1.Graph</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 4.5V - -□-- Input Volt. 5V - -★-- Input Volt. 7V - -○-- Input Volt. 9V - -◇-- Input Volt. 13V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-12.425</td><td>-12.415</td><td>-12.387</td><td>-12.364</td><td>-12.350</td></tr> <tr><td>0.26</td><td>-12.243</td><td>-12.242</td><td>-12.231</td><td>-12.228</td><td>-12.224</td></tr> <tr><td>0.52</td><td>-12.205</td><td>-12.201</td><td>-12.193</td><td>-12.187</td><td>-12.183</td></tr> <tr><td>0.65</td><td>-12.189</td><td>-12.186</td><td>-12.177</td><td>-12.173</td><td>-12.169</td></tr> <tr><td>0.78</td><td>-12.175</td><td>-12.172</td><td>-12.164</td><td>-12.160</td><td>-12.157</td></tr> <tr><td>0.91</td><td>-12.161</td><td>-12.157</td><td>-12.151</td><td>-12.148</td><td>-12.145</td></tr> <tr><td>1.04</td><td>-12.146</td><td>-12.143</td><td>-12.139</td><td>-12.137</td><td>-12.134</td></tr> <tr><td>1.30</td><td>-12.116</td><td>-12.116</td><td>-12.115</td><td>-12.115</td><td>-12.115</td></tr> <tr><td>1.43</td><td>-12.100</td><td>-12.101</td><td>-12.103</td><td>-12.105</td><td>-12.104</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0.00	-12.425	-12.415	-12.387	-12.364	-12.350	0.26	-12.243	-12.242	-12.231	-12.228	-12.224	0.52	-12.205	-12.201	-12.193	-12.187	-12.183	0.65	-12.189	-12.186	-12.177	-12.173	-12.169	0.78	-12.175	-12.172	-12.164	-12.160	-12.157	0.91	-12.161	-12.157	-12.151	-12.148	-12.145	1.04	-12.146	-12.143	-12.139	-12.137	-12.134	1.30	-12.116	-12.116	-12.115	-12.115	-12.115	1.43	-12.100	-12.101	-12.103	-12.105	-12.104	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
0.00	-12.425	-12.415	-12.387	-12.364	-12.350																																																																														
0.26	-12.243	-12.242	-12.231	-12.228	-12.224																																																																														
0.52	-12.205	-12.201	-12.193	-12.187	-12.183																																																																														
0.65	-12.189	-12.186	-12.177	-12.173	-12.169																																																																														
0.78	-12.175	-12.172	-12.164	-12.160	-12.157																																																																														
0.91	-12.161	-12.157	-12.151	-12.148	-12.145																																																																														
1.04	-12.146	-12.143	-12.139	-12.137	-12.134																																																																														
1.30	-12.116	-12.116	-12.115	-12.115	-12.115																																																																														
1.43	-12.100	-12.101	-12.103	-12.105	-12.104																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																			


COSEL

Model	MGFW400512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V1.3A		

Input Volt. 5 V

-12V:rated load current.


Cycle 100 ms

 $t_1, t_2 = 100 \mu s$ 

Min.Load (0A)↔
Load 100% (1.3A)

200 mV/div


2 ms/div



Min.Load (0A)↔
Load 50% (0.65A)

200 mV/div


2 ms/div



Load 50% (0.65A)↔
Load 100% (1.3A)

200 mV/div

2 ms/div



COSEL


Model	MGFW400512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V1.3A		

Input Volt. 5 V

+12V:rated load current.

Cycle 100 ms


 $t_1, t_2 = 100 \mu s$

Load Current


Min.Load (0A)↔
Load 100% (1.3A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (0.65A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (0.65A)↔
Load 100% (1.3A)

200 mV/div

2 ms/div




2 ms/div

COSEL

Model	MGFW400512
Item	Ripple Voltage (by Load Current)
Object	+12V1.3A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.00	5	25
0.26	20	20
0.52	20	30
0.78	20	35
1.04	25	40
1.30	35	35
1.43	40	35
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form

COSEL


Model	MGFW400512																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-12V1.3A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0.0 to 1.5 A. Two curves are plotted: one for Input Volt. 4.5V (solid line with triangle markers) and one for Input Volt. 13V (dashed line with circle markers). Both curves show an increase in ripple voltage as load current increases. A slanted line on the graph indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 13V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>25</td></tr> <tr><td>0.26</td><td>20</td><td>20</td></tr> <tr><td>0.52</td><td>20</td><td>30</td></tr> <tr><td>0.78</td><td>20</td><td>35</td></tr> <tr><td>1.04</td><td>25</td><td>40</td></tr> <tr><td>1.30</td><td>35</td><td>35</td></tr> <tr><td>1.43</td><td>40</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)	0.00	5	25	0.26	20	20	0.52	20	30	0.78	20	35	1.04	25	40	1.30	35	35	1.43	40	35	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)																																						
0.00	5	25																																						
0.26	20	20																																						
0.52	20	30																																						
0.78	20	35																																						
1.04	25	40																																						
1.30	35	35																																						
1.43	40	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>25</td></tr> <tr><td>0.26</td><td>20</td><td>20</td></tr> <tr><td>0.52</td><td>20</td><td>30</td></tr> <tr><td>0.78</td><td>20</td><td>35</td></tr> <tr><td>1.04</td><td>25</td><td>40</td></tr> <tr><td>1.30</td><td>35</td><td>35</td></tr> <tr><td>1.43</td><td>40</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.00	5	25	0.26	20	20	0.52	20	30	0.78	20	35	1.04	25	40	1.30	35	35	1.43	40	35	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																						
0.00	5	25																																						
0.26	20	20																																						
0.52	20	30																																						
0.78	20	35																																						
1.04	25	40																																						
1.30	35	35																																						
1.43	40	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+12V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGFW400512
Item	Ripple-Noise
Object	+12V1.3A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.00	10	30
0.26	20	20
0.52	20	35
0.78	25	40
1.04	25	40
1.30	35	40
1.43	45	40
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFW400512
Item	Ripple-Noise
Object	-12V1.3A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.00	5	25
0.26	20	20
0.52	20	30
0.78	20	35
1.04	25	40
1.30	35	35
1.43	40	35
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form



Model	MGFW400512
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.3A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	20	35
-40	20	35
-20	20	30
25	20	30
60	20	35
85	30	40
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	20	35
-40	20	35
-20	20	30
25	20	30
60	20	35
85	30	40
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFW400512	Testing Circuitry Figure A																																																																																	
Item	Ambient Temperature Drift																																																																																		
Object	+12V1.3A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.052</td><td>12.055</td><td>12.056</td><td>12.057</td><td>12.057</td></tr> <tr><td>-40</td><td>12.073</td><td>12.075</td><td>12.076</td><td>12.077</td><td>12.077</td></tr> <tr><td>-20</td><td>12.090</td><td>12.091</td><td>12.092</td><td>12.093</td><td>12.093</td></tr> <tr><td>0</td><td>12.101</td><td>12.102</td><td>12.103</td><td>12.104</td><td>12.104</td></tr> <tr><td>25</td><td>12.109</td><td>12.110</td><td>12.111</td><td>12.112</td><td>12.111</td></tr> <tr><td>50</td><td>12.112</td><td>12.112</td><td>12.114</td><td>12.114</td><td>12.114</td></tr> <tr><td>60</td><td>12.111</td><td>12.112</td><td>12.113</td><td>12.113</td><td>12.113</td></tr> <tr><td>65</td><td>12.108</td><td>12.109</td><td>12.110</td><td>12.110</td><td>12.110</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-60	12.052	12.055	12.056	12.057	12.057	-40	12.073	12.075	12.076	12.077	12.077	-20	12.090	12.091	12.092	12.093	12.093	0	12.101	12.102	12.103	12.104	12.104	25	12.109	12.110	12.111	12.112	12.111	50	12.112	12.112	12.114	12.114	12.114	60	12.111	12.112	12.113	12.113	12.113	65	12.108	12.109	12.110	12.110	12.110	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
-60	12.052	12.055	12.056	12.057	12.057																																																																														
-40	12.073	12.075	12.076	12.077	12.077																																																																														
-20	12.090	12.091	12.092	12.093	12.093																																																																														
0	12.101	12.102	12.103	12.104	12.104																																																																														
25	12.109	12.110	12.111	12.112	12.111																																																																														
50	12.112	12.112	12.114	12.114	12.114																																																																														
60	12.111	12.112	12.113	12.113	12.113																																																																														
65	12.108	12.109	12.110	12.110	12.110																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		-12V: Rated Load Current																																																																																	
Object	-12V1.3A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.053</td><td>-12.055</td><td>-12.056</td><td>-12.056</td><td>-12.056</td></tr> <tr><td>-40</td><td>-12.075</td><td>-12.077</td><td>-12.078</td><td>-12.078</td><td>-12.078</td></tr> <tr><td>-20</td><td>-12.093</td><td>-12.094</td><td>-12.095</td><td>-12.095</td><td>-12.095</td></tr> <tr><td>0</td><td>-12.106</td><td>-12.106</td><td>-12.107</td><td>-12.107</td><td>-12.107</td></tr> <tr><td>25</td><td>-12.116</td><td>-12.116</td><td>-12.116</td><td>-12.117</td><td>-12.116</td></tr> <tr><td>50</td><td>-12.120</td><td>-12.120</td><td>-12.120</td><td>-12.120</td><td>-12.119</td></tr> <tr><td>60</td><td>-12.120</td><td>-12.120</td><td>-12.120</td><td>-12.120</td><td>-12.119</td></tr> <tr><td>65</td><td>-12.117</td><td>-12.117</td><td>-12.117</td><td>-12.117</td><td>-12.116</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-60	-12.053	-12.055	-12.056	-12.056	-12.056	-40	-12.075	-12.077	-12.078	-12.078	-12.078	-20	-12.093	-12.094	-12.095	-12.095	-12.095	0	-12.106	-12.106	-12.107	-12.107	-12.107	25	-12.116	-12.116	-12.116	-12.117	-12.116	50	-12.120	-12.120	-12.120	-12.120	-12.119	60	-12.120	-12.120	-12.120	-12.120	-12.119	65	-12.117	-12.117	-12.117	-12.117	-12.116	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
-60	-12.053	-12.055	-12.056	-12.056	-12.056																																																																														
-40	-12.075	-12.077	-12.078	-12.078	-12.078																																																																														
-20	-12.093	-12.094	-12.095	-12.095	-12.095																																																																														
0	-12.106	-12.106	-12.107	-12.107	-12.107																																																																														
25	-12.116	-12.116	-12.116	-12.117	-12.116																																																																														
50	-12.120	-12.120	-12.120	-12.120	-12.119																																																																														
60	-12.120	-12.120	-12.120	-12.120	-12.119																																																																														
65	-12.117	-12.117	-12.117	-12.117	-12.116																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		+12V: Rated Load Current																																																																																	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																			



Model	MGFW400512	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 4.5 - 13V

Load Current (AVR 1) : 0 - 1.3A (AVR 2) : 0 - 1.3A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+12V1.3A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	12.424	± 333	± 2.8
Minimum Voltage	-40	13	0	11.759		

Object	-12V1.3A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	-12.439	± 317	± 2.6
Minimum Voltage	-40	4.5	1.3	-11.805		


COSEL

Model	MGFW400512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.3A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.110</td></tr> <tr><td>0.5</td><td>12.112</td></tr> <tr><td>1.0</td><td>12.112</td></tr> <tr><td>2.0</td><td>12.112</td></tr> <tr><td>3.0</td><td>12.112</td></tr> <tr><td>4.0</td><td>12.112</td></tr> <tr><td>5.0</td><td>12.112</td></tr> <tr><td>6.0</td><td>12.112</td></tr> <tr><td>7.0</td><td>12.112</td></tr> <tr><td>8.0</td><td>12.112</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	12.110	0.5	12.112	1.0	12.112	2.0	12.112	3.0	12.112	4.0	12.112	5.0	12.112	6.0	12.112	7.0	12.112	8.0	12.112
Time since start [H]	Output Voltage [V]																								
0.0	12.110																								
0.5	12.112																								
1.0	12.112																								
2.0	12.112																								
3.0	12.112																								
4.0	12.112																								
5.0	12.112																								
6.0	12.112																								
7.0	12.112																								
8.0	12.112																								
Object			2.Values																						
1.Graph			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.120</td></tr> <tr><td>0.5</td><td>-12.120</td></tr> <tr><td>1.0</td><td>-12.120</td></tr> <tr><td>2.0</td><td>-12.120</td></tr> <tr><td>3.0</td><td>-12.120</td></tr> <tr><td>4.0</td><td>-12.120</td></tr> <tr><td>5.0</td><td>-12.120</td></tr> <tr><td>6.0</td><td>-12.120</td></tr> <tr><td>7.0</td><td>-12.120</td></tr> <tr><td>8.0</td><td>-12.120</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-12.120	0.5	-12.120	1.0	-12.120	2.0	-12.120	3.0	-12.120	4.0	-12.120	5.0	-12.120	6.0	-12.120	7.0	-12.120	8.0	-12.120
Time since start [H]	Output Voltage [V]																								
0.0	-12.120																								
0.5	-12.120																								
1.0	-12.120																								
2.0	-12.120																								
3.0	-12.120																								
4.0	-12.120																								
5.0	-12.120																								
6.0	-12.120																								
7.0	-12.120																								
8.0	-12.120																								

COSEL


Model	MGFW400512	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V1.3A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		7.9	1.8	9.7	0.3	2.8	
100 %		7.4	4.0	11.4	0.2	1.0	



COSEL


Model	MGFW400512	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V1.3A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		7.9	1.8	9.7	0.3	3.0	
100 %		7.4	4.0	11.4	0.2	1.1	




COSEL

Model	MGFW400512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1.3A

Testing Circuitry Figure A

1.Graph

--- □ --- Load 50%
 —△— Load 100%



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.5	3.8
-40	3.6	3.7
-20	3.5	3.6
0	3.8	3.8
25	3.8	3.8
50	3.7	3.8
60	3.7	3.8
65	3.7	3.8
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Object	-12V1.3A
--------	----------

1.Graph

--- □ --- Load 50%
 —△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.5	3.8
-40	3.5	3.7
-20	3.5	3.6
0	3.7	3.8
25	3.7	3.7
50	3.7	3.8
60	3.7	3.7
65	3.7	3.8
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current


Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW400512	Temperature Testing Circuitry	25°C Figure A																																																																								
Item	Overcurrent Protection																																																																										
Object	+12V1.3A																																																																										
1.Graph		2.Values																																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>12.000</td><td>1.780</td><td>1.928</td><td>2.298</td><td>2.426</td><td>2.223</td></tr> <tr><td>11.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	12.000	1.780	1.928	2.298	2.426	2.223	11.400	-	-	-	-	-	10.800	-	-	-	-	-	9.600	-	-	-	-	-	8.400	-	-	-	-	-	7.200	-	-	-	-	-	6.000	-	-	-	-	-	4.800	-	-	-	-	-	3.600	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																										
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																						
12.000	1.780	1.928	2.298	2.426	2.223																																																																						
11.400	-	-	-	-	-																																																																						
10.800	-	-	-	-	-																																																																						
9.600	-	-	-	-	-																																																																						
8.400	-	-	-	-	-																																																																						
7.200	-	-	-	-	-																																																																						
6.000	-	-	-	-	-																																																																						
4.800	-	-	-	-	-																																																																						
3.600	-	-	-	-	-																																																																						
0.000	-	-	-	-	-																																																																						
		-12V: Rated Load Current																																																																									
Object		2.Values																																																																									
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-12.000</td><td>1.761</td><td>1.928</td><td>2.312</td><td>2.430</td><td>2.220</td></tr> <tr><td>-11.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-12.000	1.761	1.928	2.312	2.430	2.220	-11.400	-	-	-	-	-	-10.800	-	-	-	-	-	-9.600	-	-	-	-	-	-8.400	-	-	-	-	-	-7.200	-	-	-	-	-	-6.000	-	-	-	-	-	-4.800	-	-	-	-	-	-3.600	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																										
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																						
-12.000	1.761	1.928	2.312	2.430	2.220																																																																						
-11.400	-	-	-	-	-																																																																						
-10.800	-	-	-	-	-																																																																						
-9.600	-	-	-	-	-																																																																						
-8.400	-	-	-	-	-																																																																						
-7.200	-	-	-	-	-																																																																						
-6.000	-	-	-	-	-																																																																						
-4.800	-	-	-	-	-																																																																						
-3.600	-	-	-	-	-																																																																						
0.000	-	-	-	-	-																																																																						
		+12V: Rated Load Current																																																																									
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>																																																																											

COSEL

Model	MGFW400512
Item	Overvoltage Protection
Object	+24V1.3A



Measured as a single output(+24V).

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Operating Point [%]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]
0	131	131	133
10	126	126	127
20	127	127	128
30	127	127	128
40	128	127	128
50	127	127	129
60	129	128	128
70	129	129	128
80	130	130	129
90	131	130	130
100	- ※	129	130


※During this area, overcurrent protection activates.

COSEL

Model	MGFW400512
Item	Switching frequency (by Load Current)
Object	+/-12V1.3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)