

TEST DATA OF MGFW400515

Regulated DC Power Supply

November 28, 2018

Approved by : Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	10
10.Ripple-Noise · · · · ·	12
11.Ripple Voltage (by Ambient Temperature) · · · · ·	14
12.Ambient Temperature Drift · · · · ·	15
13.Output Voltage Accuracy · · · · ·	16
14.Time Lapse Drift · · · · ·	17
15.Rise and Fall Time · · · · ·	18
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	20
17.Overcurrent Protection · · · · ·	21
18.Overvoltage Protection · · · · ·	22
19.Switching frequency (by Load Current) · · · · ·	23
20.Figure of Testing Circuitry · · · · ·	24

(Final Page 24)

COSEL

Model	MGFW400515
Item	Input Current (by Input Voltage)
Object	_____




Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
3.8	0.145	0.141	0.135
3.9	0.144	4.384	9.824
4.0	0.142	4.255	9.361
4.1	0.139	4.147	8.961
4.2	0.136	4.045	8.622
4.3	0.134	3.937	8.322
4.4	0.131	3.938	8.050
4.5	0.129	3.838	7.747
5.0	0.118	3.393	6.926
7.0	0.069	2.412	4.726
9.0	0.049	1.873	3.702
13.0	0.041	1.338	2.570
15.0	0.040	1.182	2.280
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]				
	4.5[V]	5[V]	7[V]	9[V]	13[V]
0	0.129	0.118	0.069	0.049	0.041
20	1.537	1.376	0.992	0.787	0.578
40	2.963	2.695	1.906	1.506	1.070
60	4.476	3.962	2.819	2.213	1.571
80	5.996	5.413	3.757	2.932	2.059
100	7.747	6.926	4.726	3.702	2.570
110	8.570	7.625	5.282	4.047	2.810
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL


Model	MGFW400515	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Power (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 4.5V - -□--- Input Volt. 5V - ·*--- Input Volt. 7V - ·○--- Input Volt. 9V - ·◇--- Input Volt. 13V																																																																														
		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.58</td> <td>0.60</td> <td>0.49</td> <td>0.44</td> <td>0.53</td> </tr> <tr> <td>20</td> <td>6.96</td> <td>6.96</td> <td>7.02</td> <td>7.16</td> <td>7.53</td> </tr> <tr> <td>40</td> <td>13.54</td> <td>13.50</td> <td>13.49</td> <td>13.58</td> <td>13.98</td> </tr> <tr> <td>60</td> <td>20.25</td> <td>20.13</td> <td>19.97</td> <td>20.03</td> <td>20.44</td> </tr> <tr> <td>80</td> <td>27.39</td> <td>27.17</td> <td>26.66</td> <td>26.60</td> <td>26.90</td> </tr> <tr> <td>100</td> <td>34.98</td> <td>34.53</td> <td>33.56</td> <td>33.34</td> <td>33.46</td> </tr> <tr> <td>110</td> <td>38.99</td> <td>38.33</td> <td>37.14</td> <td>36.75</td> <td>36.80</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Ratio [%]	Input Power [W]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0	0.58	0.60	0.49	0.44	0.53	20	6.96	6.96	7.02	7.16	7.53	40	13.54	13.50	13.49	13.58	13.98	60	20.25	20.13	19.97	20.03	20.44	80	27.39	27.17	26.66	26.60	26.90	100	34.98	34.53	33.56	33.34	33.46	110	38.99	38.33	37.14	36.75	36.80	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																															
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																											
0	0.58	0.60	0.49	0.44	0.53																																																																											
20	6.96	6.96	7.02	7.16	7.53																																																																											
40	13.54	13.50	13.49	13.58	13.98																																																																											
60	20.25	20.13	19.97	20.03	20.44																																																																											
80	27.39	27.17	26.66	26.60	26.90																																																																											
100	34.98	34.53	33.56	33.34	33.46																																																																											
110	38.99	38.33	37.14	36.75	36.80																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

COSEL

Model	MGFW400515
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
4.3	88.6	84.6
4.5	88.7	85.4
5.0	89.1	87.0
7.0	89.3	89.0
9.0	88.7	89.7
11.0	87.6	89.5
13.0	86.2	89.3
15.0	84.5	88.6
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFW400515
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values


Load Ratio [%]	Efficiency [%]				
	Input Volt. [V]				
0	-	-	-	-	-
20	85.5	85.7	85.0	83.3	78.9
40	87.9	88.1	88.3	87.5	85.3
60	88.3	89.0	89.6	89.3	87.6
80	87.3	87.9	89.5	89.8	88.8
100	85.4	87.0	89.0	89.7	89.3
110	84.3	85.7	88.5	89.4	89.2
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

COSEL

Model	MGFW400515
Item	Line Regulation
Object	+15V1A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	15.062	14.986
4.5	15.061	14.987
5.0	15.057	14.988
7.0	15.049	14.989
9.0	15.045	14.989
11.0	15.042	14.989
13.0	15.040	14.989
15.0	15.038	14.989
--	-	-

-15V: Rated Load Current

Object -15V1A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	-15.067	-14.991
4.5	-15.066	-14.991
5.0	-15.063	-14.991
7.0	-15.055	-14.991
9.0	-15.050	-14.990
11.0	-15.046	-14.990
13.0	-15.044	-14.990
15.0	-15.042	-14.989
--	-	-

+15V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGFW400515	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+15V1A																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 4.5V - -□-- Input Volt. 5V - -★-- Input Volt. 7V - -○-- Input Volt. 9V - -◇-- Input Volt. 13V 																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.287</td><td>15.279</td><td>15.253</td><td>15.231</td><td>15.224</td></tr> <tr><td>0.2</td><td>15.118</td><td>15.116</td><td>15.104</td><td>15.100</td><td>15.097</td></tr> <tr><td>0.4</td><td>15.076</td><td>15.072</td><td>15.065</td><td>15.058</td><td>15.053</td></tr> <tr><td>0.5</td><td>15.061</td><td>15.057</td><td>15.049</td><td>15.045</td><td>15.040</td></tr> <tr><td>0.6</td><td>15.046</td><td>15.043</td><td>15.036</td><td>15.032</td><td>15.028</td></tr> <tr><td>0.7</td><td>15.031</td><td>15.029</td><td>15.023</td><td>15.021</td><td>15.017</td></tr> <tr><td>0.8</td><td>15.016</td><td>15.014</td><td>15.011</td><td>15.010</td><td>15.007</td></tr> <tr><td>1.0</td><td>14.987</td><td>14.988</td><td>14.989</td><td>14.989</td><td>14.989</td></tr> <tr><td>1.1</td><td>14.971</td><td>14.973</td><td>14.977</td><td>14.978</td><td>14.978</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0.0	15.287	15.279	15.253	15.231	15.224	0.2	15.118	15.116	15.104	15.100	15.097	0.4	15.076	15.072	15.065	15.058	15.053	0.5	15.061	15.057	15.049	15.045	15.040	0.6	15.046	15.043	15.036	15.032	15.028	0.7	15.031	15.029	15.023	15.021	15.017	0.8	15.016	15.014	15.011	15.010	15.007	1.0	14.987	14.988	14.989	14.989	14.989	1.1	14.971	14.973	14.977	14.978	14.978	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																			
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																															
0.0	15.287	15.279	15.253	15.231	15.224																																																																															
0.2	15.118	15.116	15.104	15.100	15.097																																																																															
0.4	15.076	15.072	15.065	15.058	15.053																																																																															
0.5	15.061	15.057	15.049	15.045	15.040																																																																															
0.6	15.046	15.043	15.036	15.032	15.028																																																																															
0.7	15.031	15.029	15.023	15.021	15.017																																																																															
0.8	15.016	15.014	15.011	15.010	15.007																																																																															
1.0	14.987	14.988	14.989	14.989	14.989																																																																															
1.1	14.971	14.973	14.977	14.978	14.978																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-15V1A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.295</td><td>-15.285</td><td>-15.256</td><td>-15.237</td><td>-15.214</td></tr> <tr><td>0.2</td><td>-15.129</td><td>-15.123</td><td>-15.114</td><td>-15.111</td><td>-15.103</td></tr> <tr><td>0.4</td><td>-15.081</td><td>-15.080</td><td>-15.069</td><td>-15.066</td><td>-15.061</td></tr> <tr><td>0.5</td><td>-15.066</td><td>-15.063</td><td>-15.055</td><td>-15.050</td><td>-15.044</td></tr> <tr><td>0.6</td><td>-15.050</td><td>-15.048</td><td>-15.040</td><td>-15.037</td><td>-15.033</td></tr> <tr><td>0.7</td><td>-15.036</td><td>-15.033</td><td>-15.027</td><td>-15.024</td><td>-15.021</td></tr> <tr><td>0.8</td><td>-15.021</td><td>-15.019</td><td>-15.015</td><td>-15.013</td><td>-15.010</td></tr> <tr><td>1.0</td><td>-14.991</td><td>-14.991</td><td>-14.991</td><td>-14.990</td><td>-14.990</td></tr> <tr><td>1.1</td><td>-14.976</td><td>-14.977</td><td>-14.979</td><td>-14.980</td><td>-14.980</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	0.0	-15.295	-15.285	-15.256	-15.237	-15.214	0.2	-15.129	-15.123	-15.114	-15.111	-15.103	0.4	-15.081	-15.080	-15.069	-15.066	-15.061	0.5	-15.066	-15.063	-15.055	-15.050	-15.044	0.6	-15.050	-15.048	-15.040	-15.037	-15.033	0.7	-15.036	-15.033	-15.027	-15.024	-15.021	0.8	-15.021	-15.019	-15.015	-15.013	-15.010	1.0	-14.991	-14.991	-14.991	-14.990	-14.990	1.1	-14.976	-14.977	-14.979	-14.980	-14.980	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																															
0.0	-15.295	-15.285	-15.256	-15.237	-15.214																																																																															
0.2	-15.129	-15.123	-15.114	-15.111	-15.103																																																																															
0.4	-15.081	-15.080	-15.069	-15.066	-15.061																																																																															
0.5	-15.066	-15.063	-15.055	-15.050	-15.044																																																																															
0.6	-15.050	-15.048	-15.040	-15.037	-15.033																																																																															
0.7	-15.036	-15.033	-15.027	-15.024	-15.021																																																																															
0.8	-15.021	-15.019	-15.015	-15.013	-15.010																																																																															
1.0	-14.991	-14.991	-14.991	-14.990	-14.990																																																																															
1.1	-14.976	-14.977	-14.979	-14.980	-14.980																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																				


COSEL

Model	MGFW400515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V1A		

Input Volt. 5 V

-15V:rated load current.


Cycle 100 ms

 $t_1, t_2 = 100 \mu s$ 

Min.Load (0A)↔
Load 100% (1A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (0.5A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (0.5A)↔
Load 100% (1A)

200 mV/div

2 ms/div



2 ms/div


COSEL

Model	MGFW400515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V1A		

Input Volt. 5 V



+15V:rated load current.

Cycle 100 ms

 $t_1, t_2 = 100 \mu s$ Min.Load (0A)↔
Load 100% (1A)



200 mV/div

2 ms/div

Min.Load (0A)↔
Load 50% (0.5A)



200 mV/div

2 ms/div

Load 50% (0.5A)↔
Load 100% (1A)

200 mV/div

2 ms/div



COSEL

Model	MGFW400515																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	+15V1A																																						
1.Graph																																							
<p>Legend: —△— Input Volt. 4.5V —○— Input Volt. 13V </p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 13V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>0.2</td><td>15</td><td>20</td></tr> <tr><td>0.4</td><td>15</td><td>25</td></tr> <tr><td>0.6</td><td>15</td><td>25</td></tr> <tr><td>0.8</td><td>15</td><td>25</td></tr> <tr><td>1.0</td><td>20</td><td>25</td></tr> <tr><td>1.1</td><td>20</td><td>25</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)	0.0	15	20	0.2	15	20	0.4	15	25	0.6	15	25	0.8	15	25	1.0	20	25	1.1	20	25														
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)																																					
0.0	15	20																																					
0.2	15	20																																					
0.4	15	25																																					
0.6	15	25																																					
0.8	15	25																																					
1.0	20	25																																					
1.1	20	25																																					
2.Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>0.2</td><td>15</td><td>20</td></tr> <tr><td>0.4</td><td>15</td><td>25</td></tr> <tr><td>0.6</td><td>15</td><td>25</td></tr> <tr><td>0.8</td><td>15</td><td>25</td></tr> <tr><td>1.0</td><td>20</td><td>25</td></tr> <tr><td>1.1</td><td>20</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.0	15	20	0.2	15	20	0.4	15	25	0.6	15	25	0.8	15	25	1.0	20	25	1.1	20	25	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																					
0.0	15	20																																					
0.2	15	20																																					
0.4	15	25																																					
0.6	15	25																																					
0.8	15	25																																					
1.0	20	25																																					
1.1	20	25																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
-15V: Rated Load Current																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Ripple [mVp-p]</p>																																							
<p>Fig.Complex Ripple Wave Form</p>																																							

COSEL


Model	MGFW400515																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	-15V1A																																						
1.Graph																																							
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph displays two sets of data points for Input Volt. 4.5V (solid line with triangle markers) and Input Volt. 13V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.0 to 1.5. The y-axis represents Ripple Voltage [mV] from 0 to 200. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 4.5V)</th> <th>Ripple Voltage [mV] (Input Volt. 13V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>~15</td><td>~15</td></tr> <tr><td>0.2</td><td>~15</td><td>~20</td></tr> <tr><td>0.4</td><td>~15</td><td>~25</td></tr> <tr><td>0.6</td><td>~15</td><td>~25</td></tr> <tr><td>0.8</td><td>~15</td><td>~25</td></tr> <tr><td>1.0</td><td>~20</td><td>~25</td></tr> <tr><td>1.1</td><td>~20</td><td>~25</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)	0.0	~15	~15	0.2	~15	~20	0.4	~15	~25	0.6	~15	~25	0.8	~15	~25	1.0	~20	~25	1.1	~20	~25														
Load Current [A]	Ripple Voltage [mV] (Input Volt. 4.5V)	Ripple Voltage [mV] (Input Volt. 13V)																																					
0.0	~15	~15																																					
0.2	~15	~20																																					
0.4	~15	~25																																					
0.6	~15	~25																																					
0.8	~15	~25																																					
1.0	~20	~25																																					
1.1	~20	~25																																					
2.Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 13 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>0.2</td><td>15</td><td>20</td></tr> <tr><td>0.4</td><td>15</td><td>25</td></tr> <tr><td>0.6</td><td>15</td><td>25</td></tr> <tr><td>0.8</td><td>15</td><td>25</td></tr> <tr><td>1.0</td><td>20</td><td>25</td></tr> <tr><td>1.1</td><td>20</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 13 [V]	0.0	15	20	0.2	15	20	0.4	15	25	0.6	15	25	0.8	15	25	1.0	20	25	1.1	20	25	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 4.5 [V]	Input Volt. 13 [V]																																					
0.0	15	20																																					
0.2	15	20																																					
0.4	15	25																																					
0.6	15	25																																					
0.8	15	25																																					
1.0	20	25																																					
1.1	20	25																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
+15V: Rated Load Current																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																							

COSEL

Model	MGFW400515
Item	Ripple-Noise
Object	+15V1A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.0	60	65
0.2	45	50
0.4	45	55
0.6	40	60
0.8	45	60
1.0	55	60
1.1	55	60
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFW400515
Item	Ripple-Noise
Object	-15V1A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 13 [V]
0.0	60	65
0.2	45	50
0.4	45	55
0.6	40	60
0.8	45	60
1.0	55	60
1.1	55	60
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFW400515
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V1A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	15
-40	10	15
-20	15	20
25	15	20
60	15	20
85	30	25
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	15
-40	10	15
-20	15	20
25	15	20
60	15	20
85	30	25
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFW400515	Testing Circuitry Figure A																																																																																	
Item	Ambient Temperature Drift																																																																																		
Object	+15V1A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 4.5V Input Volt. 5V Input Volt. 7V Input Volt. 9V Input Volt. 13V 	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.921</td><td>14.922</td><td>14.924</td><td>14.926</td><td>14.925</td></tr> <tr><td>-40</td><td>14.947</td><td>14.949</td><td>14.950</td><td>14.952</td><td>14.952</td></tr> <tr><td>-20</td><td>14.966</td><td>14.967</td><td>14.969</td><td>14.970</td><td>14.969</td></tr> <tr><td>0</td><td>14.979</td><td>14.980</td><td>14.982</td><td>14.982</td><td>14.981</td></tr> <tr><td>25</td><td>14.987</td><td>14.988</td><td>14.990</td><td>14.990</td><td>14.989</td></tr> <tr><td>50</td><td>14.988</td><td>14.989</td><td>14.990</td><td>14.991</td><td>14.990</td></tr> <tr><td>60</td><td>14.987</td><td>14.988</td><td>14.989</td><td>14.990</td><td>14.989</td></tr> <tr><td>65</td><td>14.983</td><td>14.984</td><td>14.986</td><td>14.986</td><td>14.985</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-60	14.921	14.922	14.924	14.926	14.925	-40	14.947	14.949	14.950	14.952	14.952	-20	14.966	14.967	14.969	14.970	14.969	0	14.979	14.980	14.982	14.982	14.981	25	14.987	14.988	14.990	14.990	14.989	50	14.988	14.989	14.990	14.991	14.990	60	14.987	14.988	14.989	14.990	14.989	65	14.983	14.984	14.986	14.986	14.985	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
-60	14.921	14.922	14.924	14.926	14.925																																																																														
-40	14.947	14.949	14.950	14.952	14.952																																																																														
-20	14.966	14.967	14.969	14.970	14.969																																																																														
0	14.979	14.980	14.982	14.982	14.981																																																																														
25	14.987	14.988	14.990	14.990	14.989																																																																														
50	14.988	14.989	14.990	14.991	14.990																																																																														
60	14.987	14.988	14.989	14.990	14.989																																																																														
65	14.983	14.984	14.986	14.986	14.985																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		-15V: Rated Load Current																																																																																	
Object	-15V1A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 4.5V Input Volt. 5V Input Volt. 7V Input Volt. 9V Input Volt. 13V 	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.916</td><td>-14.919</td><td>-14.920</td><td>-14.921</td><td>-14.921</td></tr> <tr><td>-40</td><td>-14.945</td><td>-14.946</td><td>-14.948</td><td>-14.949</td><td>-14.948</td></tr> <tr><td>-20</td><td>-14.965</td><td>-14.967</td><td>-14.968</td><td>-14.968</td><td>-14.968</td></tr> <tr><td>0</td><td>-14.980</td><td>-14.981</td><td>-14.981</td><td>-14.982</td><td>-14.981</td></tr> <tr><td>25</td><td>-14.990</td><td>-14.990</td><td>-14.991</td><td>-14.991</td><td>-14.990</td></tr> <tr><td>50</td><td>-14.993</td><td>-14.993</td><td>-14.993</td><td>-14.993</td><td>-14.992</td></tr> <tr><td>60</td><td>-14.993</td><td>-14.993</td><td>-14.993</td><td>-14.993</td><td>-14.991</td></tr> <tr><td>65</td><td>-14.989</td><td>-14.989</td><td>-14.990</td><td>-14.989</td><td>-14.988</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-60	-14.916	-14.919	-14.920	-14.921	-14.921	-40	-14.945	-14.946	-14.948	-14.949	-14.948	-20	-14.965	-14.967	-14.968	-14.968	-14.968	0	-14.980	-14.981	-14.981	-14.982	-14.981	25	-14.990	-14.990	-14.991	-14.991	-14.990	50	-14.993	-14.993	-14.993	-14.993	-14.992	60	-14.993	-14.993	-14.993	-14.993	-14.991	65	-14.989	-14.989	-14.990	-14.989	-14.988	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																														
-60	-14.916	-14.919	-14.920	-14.921	-14.921																																																																														
-40	-14.945	-14.946	-14.948	-14.949	-14.948																																																																														
-20	-14.965	-14.967	-14.968	-14.968	-14.968																																																																														
0	-14.980	-14.981	-14.981	-14.982	-14.981																																																																														
25	-14.990	-14.990	-14.991	-14.991	-14.990																																																																														
50	-14.993	-14.993	-14.993	-14.993	-14.992																																																																														
60	-14.993	-14.993	-14.993	-14.993	-14.991																																																																														
65	-14.989	-14.989	-14.990	-14.989	-14.988																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		+15V: Rated Load Current																																																																																	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																																																			



Model	MGFW400515	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 4.5 - 13V

Load Current (AVR 1) : 0 - 1A (AVR 2) : 0 - 1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	15.295	±313	±2.1
Minimum Voltage	-40	4.5	1	14.670		

Object	-15V1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	-15.306	±319	±2.1
Minimum Voltage	-40	4.5	1	-14.669		


COSEL

Model	MGFW400515	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V1A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.988</td></tr> <tr><td>0.5</td><td>14.989</td></tr> <tr><td>1.0</td><td>14.989</td></tr> <tr><td>2.0</td><td>14.989</td></tr> <tr><td>3.0</td><td>14.989</td></tr> <tr><td>4.0</td><td>14.989</td></tr> <tr><td>5.0</td><td>14.989</td></tr> <tr><td>6.0</td><td>14.989</td></tr> <tr><td>7.0</td><td>14.989</td></tr> <tr><td>8.0</td><td>14.989</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	14.988	0.5	14.989	1.0	14.989	2.0	14.989	3.0	14.989	4.0	14.989	5.0	14.989	6.0	14.989	7.0	14.989	8.0	14.989
Time since start [H]	Output Voltage [V]																								
0.0	14.988																								
0.5	14.989																								
1.0	14.989																								
2.0	14.989																								
3.0	14.989																								
4.0	14.989																								
5.0	14.989																								
6.0	14.989																								
7.0	14.989																								
8.0	14.989																								
Object	-15V1A	2.Values																							
1.Graph			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.990</td></tr> <tr><td>0.5</td><td>-14.993</td></tr> <tr><td>1.0</td><td>-14.993</td></tr> <tr><td>2.0</td><td>-14.993</td></tr> <tr><td>3.0</td><td>-14.993</td></tr> <tr><td>4.0</td><td>-14.993</td></tr> <tr><td>5.0</td><td>-14.993</td></tr> <tr><td>6.0</td><td>-14.993</td></tr> <tr><td>7.0</td><td>-14.993</td></tr> <tr><td>8.0</td><td>-14.993</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-14.990	0.5	-14.993	1.0	-14.993	2.0	-14.993	3.0	-14.993	4.0	-14.993	5.0	-14.993	6.0	-14.993	7.0	-14.993	8.0	-14.993
Time since start [H]	Output Voltage [V]																								
0.0	-14.990																								
0.5	-14.993																								
1.0	-14.993																								
2.0	-14.993																								
3.0	-14.993																								
4.0	-14.993																								
5.0	-14.993																								
6.0	-14.993																								
7.0	-14.993																								
8.0	-14.993																								
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 5V Load 100%</p>																									

COSEL


Model	MGFW400515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V1A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		8.1	3.7	11.8	0.4	8.4	
100 %		7.5	4.7	12.2	0.3	3.5	



COSEL


Model	MGFW400515	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V1A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		8.1	3.6	11.7	0.5	8.7	
100 %		7.5	4.7	12.2	0.3	3.7	




COSEL

Model	MGFW400515
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.5	3.8
-40	3.7	3.8
-20	3.5	3.7
0	3.5	3.5
25	3.5	3.6
50	3.4	3.7
60	3.4	3.6
65	3.3	3.5
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

Object -15V1A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.5	3.8
-40	3.6	3.7
-20	3.5	3.7
0	3.5	3.5
25	3.4	3.5
50	3.3	3.7
60	3.3	3.6
65	3.3	3.6
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFW400515	Temperature Testing Circuitry	25°C Figure A																																																																							
Item	Overcurrent Protection																																																																									
Object	+15V1A																																																																									
1.Graph		2.Values																																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>1.301</td><td>1.413</td><td>1.662</td><td>1.747</td><td>1.598</td></tr> <tr><td>14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-15V: Rated Load Current</p>		Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	15.0	1.301	1.413	1.662	1.747	1.598	14.3	-	-	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																									
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																					
15.0	1.301	1.413	1.662	1.747	1.598																																																																					
14.3	-	-	-	-	-																																																																					
13.5	-	-	-	-	-																																																																					
12.0	-	-	-	-	-																																																																					
10.5	-	-	-	-	-																																																																					
9.0	-	-	-	-	-																																																																					
7.5	-	-	-	-	-																																																																					
6.0	-	-	-	-	-																																																																					
4.5	-	-	-	-	-																																																																					
0.0	-	-	-	-	-																																																																					
Object		2.Values																																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>7[V]</th> <th>9[V]</th> <th>13[V]</th> </tr> </thead> <tbody> <tr><td>-15.0</td><td>1.304</td><td>1.414</td><td>1.660</td><td>1.740</td><td>1.583</td></tr> <tr><td>-14.3</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+15V: Rated Load Current</p>		Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	7[V]	9[V]	13[V]	-15.0	1.304	1.414	1.660	1.740	1.583	-14.3	-	-	-	-	-	-13.5	-	-	-	-	-	-12.0	-	-	-	-	-	-10.5	-	-	-	-	-	-9.0	-	-	-	-	-	-7.5	-	-	-	-	-	-6.0	-	-	-	-	-	-4.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																									
	4.5[V]	5[V]	7[V]	9[V]	13[V]																																																																					
-15.0	1.304	1.414	1.660	1.740	1.583																																																																					
-14.3	-	-	-	-	-																																																																					
-13.5	-	-	-	-	-																																																																					
-12.0	-	-	-	-	-																																																																					
-10.5	-	-	-	-	-																																																																					
-9.0	-	-	-	-	-																																																																					
-7.5	-	-	-	-	-																																																																					
-6.0	-	-	-	-	-																																																																					
-4.5	-	-	-	-	-																																																																					
0.0	-	-	-	-	-																																																																					
Note: Slanted line shows the range of the rated load current. Intermittent operation activates when overcurrent protection is activated.																																																																										

COSEL

Model	MGFW400515
Item	Overvoltage Protection
Object	+30V1A



Measured as a single output(+30V).

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Operating Point [%]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 13[V]
0	130	130	134
10	125	125	126
20	125	125	126
30	125	125	126
40	125	125	127
50	126	126	127
60	127	126	126
70	127	127	126
80	128	127	127
90	129	128	128
100	- ※	126	128


※During this area, overcurrent protection activates.

COSEL

Model	MGFW400515
Item	Switching frequency (by Load Current)
Object	+/-15V1A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)