

TEST DATA OF MGFW402415

Regulated DC Power Supply
November 29, 2018

Approved by : Junichi Idatagishi
Design Manager

Prepared by : Shohei Mukaiide
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Switching frequency (by Load Current)	23
20.Figure of Testing Circuitry	24


(Final Page 24)

COSEL

Model	MGFW402415																																																																																	
Item	Input Current (by Input Voltage)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
	<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values																																																																																		
	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.6</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>7.8</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>8.0</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>8.2</td><td>0.078</td><td>2.862</td><td>- ✕</td></tr> <tr><td>8.4</td><td>0.075</td><td>2.861</td><td>- ✕</td></tr> <tr><td>8.6</td><td>0.075</td><td>2.783</td><td>- ✕</td></tr> <tr><td>8.8</td><td>0.073</td><td>2.711</td><td>- ✕</td></tr> <tr><td>9.0</td><td>0.072</td><td>2.641</td><td>- ✕</td></tr> <tr><td>12.0</td><td>0.057</td><td>1.929</td><td>- ✕</td></tr> <tr><td>18.0</td><td>0.043</td><td>1.272</td><td>2.557</td></tr> <tr><td>24.0</td><td>0.036</td><td>0.968</td><td>1.915</td></tr> <tr><td>36.0</td><td>0.019</td><td>0.651</td><td>1.277</td></tr> <tr><td>40.0</td><td>0.018</td><td>0.589</td><td>1.156</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	7.6	0.004	0.004	- ✕	7.8	0.004	0.004	- ✕	8.0	0.004	0.004	- ✕	8.2	0.078	2.862	- ✕	8.4	0.075	2.861	- ✕	8.6	0.075	2.783	- ✕	8.8	0.073	2.711	- ✕	9.0	0.072	2.641	- ✕	12.0	0.057	1.929	- ✕	18.0	0.043	1.272	2.557	24.0	0.036	0.968	1.915	36.0	0.019	0.651	1.277	40.0	0.018	0.589	1.156	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
7.6	0.004	0.004	- ✕																																																																															
7.8	0.004	0.004	- ✕																																																																															
8.0	0.004	0.004	- ✕																																																																															
8.2	0.078	2.862	- ✕																																																																															
8.4	0.075	2.861	- ✕																																																																															
8.6	0.075	2.783	- ✕																																																																															
8.8	0.073	2.711	- ✕																																																																															
9.0	0.072	2.641	- ✕																																																																															
12.0	0.057	1.929	- ✕																																																																															
18.0	0.043	1.272	2.557																																																																															
24.0	0.036	0.968	1.915																																																																															
36.0	0.019	0.651	1.277																																																																															
40.0	0.018	0.589	1.156																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
	<p>※During this area, overcurrent protection activates and power supply operates in hiccup mode.</p>																																																																																	

COSEL

Model	MGFW402415
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
0	0.072	0.057	0.043	0.036	0.019
20	1.070	0.802	0.540	0.410	0.281
40	2.080	1.552	1.044	0.788	0.533
60	3.111	2.304	1.540	1.156	0.777
80	-※1	3.106	2.038	1.532	1.026
100	-※1	-※2	2.557	1.915	1.277
110	-※1	-※2	2.832	2.104	1.406
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 12V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFW402415																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>9V</th> <th>12V</th> <th>18V</th> <th>24V</th> <th>36V</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.66</td> <td>0.70</td> <td>0.78</td> <td>0.93</td> <td>0.68</td> </tr> <tr> <td>20</td> <td>9.67</td> <td>9.70</td> <td>9.77</td> <td>9.85</td> <td>10.16</td> </tr> <tr> <td>40</td> <td>18.79</td> <td>18.74</td> <td>18.82</td> <td>18.91</td> <td>19.23</td> </tr> <tr> <td>60</td> <td>28.15</td> <td>27.86</td> <td>27.72</td> <td>27.77</td> <td>28.03</td> </tr> <tr> <td>80</td> <td>-</td> <td>37.28</td> <td>36.86</td> <td>36.79</td> <td>36.97</td> </tr> <tr> <td>100</td> <td>-</td> <td>-</td> <td>46.21</td> <td>46.02</td> <td>46.06</td> </tr> <tr> <td>110</td> <td>-</td> <td>-</td> <td>51.00</td> <td>50.69</td> <td>50.67</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ratio [%]	9V	12V	18V	24V	36V	0	0.66	0.70	0.78	0.93	0.68	20	9.67	9.70	9.77	9.85	10.16	40	18.79	18.74	18.82	18.91	19.23	60	28.15	27.86	27.72	27.77	28.03	80	-	37.28	36.86	36.79	36.97	100	-	-	46.21	46.02	46.06	110	-	-	51.00	50.69	50.67	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	9V	12V	18V	24V	36V																																																																													
0	0.66	0.70	0.78	0.93	0.68																																																																													
20	9.67	9.70	9.77	9.85	10.16																																																																													
40	18.79	18.74	18.82	18.91	19.23																																																																													
60	28.15	27.86	27.72	27.77	28.03																																																																													
80	-	37.28	36.86	36.79	36.97																																																																													
100	-	-	46.21	46.02	46.06																																																																													
110	-	-	51.00	50.69	50.67																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.66</td> <td>0.70</td> <td>0.78</td> <td>0.93</td> <td>0.68</td> </tr> <tr> <td>20</td> <td>9.67</td> <td>9.70</td> <td>9.77</td> <td>9.85</td> <td>10.16</td> </tr> <tr> <td>40</td> <td>18.79</td> <td>18.74</td> <td>18.82</td> <td>18.91</td> <td>19.23</td> </tr> <tr> <td>60</td> <td>28.15</td> <td>27.86</td> <td>27.72</td> <td>27.77</td> <td>28.03</td> </tr> <tr> <td>80</td> <td>-</td> <td>37.28</td> <td>36.86</td> <td>36.79</td> <td>36.97</td> </tr> <tr> <td>100</td> <td>-</td> <td>-</td> <td>46.21</td> <td>46.02</td> <td>46.06</td> </tr> <tr> <td>110</td> <td>-</td> <td>-</td> <td>51.00</td> <td>50.69</td> <td>50.67</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.66	0.70	0.78	0.93	0.68	20	9.67	9.70	9.77	9.85	10.16	40	18.79	18.74	18.82	18.91	19.23	60	28.15	27.86	27.72	27.77	28.03	80	-	37.28	36.86	36.79	36.97	100	-	-	46.21	46.02	46.06	110	-	-	51.00	50.69	50.67	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.66	0.70	0.78	0.93	0.68																																																																													
20	9.67	9.70	9.77	9.85	10.16																																																																													
40	18.79	18.74	18.82	18.91	19.23																																																																													
60	28.15	27.86	27.72	27.77	28.03																																																																													
80	-	37.28	36.86	36.79	36.97																																																																													
100	-	-	46.21	46.02	46.06																																																																													
110	-	-	51.00	50.69	50.67																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		

COSEL

Model	MGFW402415																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>89.9</td><td>89.0 ※1</td></tr> <tr><td>9.0</td><td>90.0</td><td>89.5 ※1</td></tr> <tr><td>12.0</td><td>90.6</td><td>90.3 ※2</td></tr> <tr><td>15.0</td><td>90.9</td><td>90.6</td></tr> <tr><td>18.0</td><td>90.8</td><td>91.1</td></tr> <tr><td>24.0</td><td>90.5</td><td>91.5</td></tr> <tr><td>30.0</td><td>90.0</td><td>91.5</td></tr> <tr><td>36.0</td><td>89.4</td><td>91.4</td></tr> <tr><td>40.0</td><td>88.9</td><td>91.1</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	89.9	89.0 ※1	9.0	90.0	89.5 ※1	12.0	90.6	90.3 ※2	15.0	90.9	90.6	18.0	90.8	91.1	24.0	90.5	91.5	30.0	90.0	91.5	36.0	89.4	91.4	40.0	88.9	91.1
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	89.9	89.0 ※1																																
9.0	90.0	89.5 ※1																																
12.0	90.6	90.3 ※2																																
15.0	90.9	90.6																																
18.0	90.8	91.1																																
24.0	90.5	91.5																																
30.0	90.0	91.5																																
36.0	89.4	91.4																																
40.0	88.9	91.1																																
※1: Load 70% ※2: Load 80%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL


Model	MGFW402415																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Ratio [%]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 9V - - ■ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◇ - - Input Volt. 36V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>86.9</td><td>86.8</td><td>86.1</td><td>85.3</td><td>83.0</td></tr> <tr> <td>40</td><td>89.9</td><td>90.3</td><td>89.8</td><td>89.4</td><td>87.9</td></tr> <tr> <td>60</td><td>89.8</td><td>90.8</td><td>91.2</td><td>91.1</td><td>90.3</td></tr> <tr> <td>80</td><td>-※1</td><td>90.3</td><td>91.4</td><td>91.6</td><td>91.1</td></tr> <tr> <td>100</td><td>-※1</td><td>-※2</td><td>91.1</td><td>91.5</td><td>91.4</td></tr> <tr> <td>110</td><td>-※1</td><td>-※2</td><td>90.7</td><td>91.3</td><td>91.3</td></tr> <tr> <td>--</td><td></td><td></td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td></td><td></td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	-	-	20	86.9	86.8	86.1	85.3	83.0	40	89.9	90.3	89.8	89.4	87.9	60	89.8	90.8	91.2	91.1	90.3	80	-※1	90.3	91.4	91.6	91.1	100	-※1	-※2	91.1	91.5	91.4	110	-※1	-※2	90.7	91.3	91.3	--			-	-	-	--			-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	-	-	-	-	-																																																																													
20	86.9	86.8	86.1	85.3	83.0																																																																													
40	89.9	90.3	89.8	89.4	87.9																																																																													
60	89.8	90.8	91.2	91.1	90.3																																																																													
80	-※1	90.3	91.4	91.6	91.1																																																																													
100	-※1	-※2	91.1	91.5	91.4																																																																													
110	-※1	-※2	90.7	91.3	91.3																																																																													
--			-	-	-																																																																													
--			-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFW402415
Item	Line Regulation
Object	+15V1.4A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	15.090	- ⋆1
9.0	15.087	- ⋆1
12.0	15.070	- ⋆2
15.0	15.062	15.002
18.0	15.061	15.003
24.0	15.056	15.003
30.0	15.051	15.003
36.0	15.052	15.003
40.0	15.048	15.003

-15V: Rated Load Current

Object -15V1.4A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	-15.102	- ⋆1
9.0	-15.096	- ⋆1
12.0	-15.077	- ⋆2
15.0	-15.070	-14.994
18.0	-15.066	-14.995
24.0	-15.061	-14.995
30.0	-15.057	-14.995
36.0	-15.055	-14.995
40.0	-15.054	-14.995

+15V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

⋆1 Maximum output current at minimum input Voltage is 70% of rated load current.
 ⋆2 Maximum output current at 12V input Voltage is 80% of rated load current.
 Refer to instruction manuals for details of input derating.

COSEL

Model	MGFW402415	Temperature	25°C																																																																														
Item	Load Regulation	Testing Circuitry	Figure A																																																																														
Object	+15V1.4A																																																																																
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.306</td><td>15.298</td><td>15.303</td><td>15.275</td><td>15.281</td></tr> <tr><td>0.28</td><td>15.079</td><td>15.085</td><td>15.105</td><td>15.102</td><td>15.102</td></tr> <tr><td>0.56</td><td>15.063</td><td>15.063</td><td>15.075</td><td>15.068</td><td>15.067</td></tr> <tr><td>0.70</td><td>15.087</td><td>15.070</td><td>15.061</td><td>15.056</td><td>15.052</td></tr> <tr><td>0.84</td><td>15.027</td><td>15.032</td><td>15.048</td><td>15.045</td><td>15.040</td></tr> <tr><td>0.98</td><td>15.001</td><td>15.018</td><td>15.036</td><td>15.033</td><td>15.030</td></tr> <tr><td>1.12</td><td>-※1</td><td>15.002</td><td>15.023</td><td>15.022</td><td>15.019</td></tr> <tr><td>1.40</td><td>-※1</td><td>-※2</td><td>15.003</td><td>15.003</td><td>15.003</td></tr> <tr><td>1.54</td><td>-※1</td><td>-※2</td><td>14.989</td><td>14.990</td><td>14.991</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	15.306	15.298	15.303	15.275	15.281	0.28	15.079	15.085	15.105	15.102	15.102	0.56	15.063	15.063	15.075	15.068	15.067	0.70	15.087	15.070	15.061	15.056	15.052	0.84	15.027	15.032	15.048	15.045	15.040	0.98	15.001	15.018	15.036	15.033	15.030	1.12	-※1	15.002	15.023	15.022	15.019	1.40	-※1	-※2	15.003	15.003	15.003	1.54	-※1	-※2	14.989	14.990	14.991	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	15.306	15.298	15.303	15.275	15.281																																																																												
0.28	15.079	15.085	15.105	15.102	15.102																																																																												
0.56	15.063	15.063	15.075	15.068	15.067																																																																												
0.70	15.087	15.070	15.061	15.056	15.052																																																																												
0.84	15.027	15.032	15.048	15.045	15.040																																																																												
0.98	15.001	15.018	15.036	15.033	15.030																																																																												
1.12	-※1	15.002	15.023	15.022	15.019																																																																												
1.40	-※1	-※2	15.003	15.003	15.003																																																																												
1.54	-※1	-※2	14.989	14.990	14.991																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
Object	-15V1.4A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.303</td><td>-15.301</td><td>-15.310</td><td>-15.284</td><td>-15.272</td></tr> <tr><td>0.28</td><td>-15.065</td><td>-15.090</td><td>-15.111</td><td>-15.116</td><td>-15.112</td></tr> <tr><td>0.56</td><td>-15.049</td><td>-15.054</td><td>-15.075</td><td>-15.075</td><td>-15.065</td></tr> <tr><td>0.70</td><td>-15.096</td><td>-15.077</td><td>-15.066</td><td>-15.061</td><td>-15.055</td></tr> <tr><td>0.84</td><td>-15.010</td><td>-15.025</td><td>-15.049</td><td>-15.046</td><td>-15.042</td></tr> <tr><td>0.98</td><td>-14.992</td><td>-15.009</td><td>-15.035</td><td>-15.033</td><td>-15.030</td></tr> <tr><td>1.12</td><td>-※1</td><td>-14.993</td><td>-15.023</td><td>-15.021</td><td>-15.018</td></tr> <tr><td>1.40</td><td>-※1</td><td>-※2</td><td>-14.995</td><td>-14.995</td><td>-14.995</td></tr> <tr><td>1.54</td><td>-※1</td><td>-※2</td><td>-14.982</td><td>-14.984</td><td>-14.984</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-15.303	-15.301	-15.310	-15.284	-15.272	0.28	-15.065	-15.090	-15.111	-15.116	-15.112	0.56	-15.049	-15.054	-15.075	-15.075	-15.065	0.70	-15.096	-15.077	-15.066	-15.061	-15.055	0.84	-15.010	-15.025	-15.049	-15.046	-15.042	0.98	-14.992	-15.009	-15.035	-15.033	-15.030	1.12	-※1	-14.993	-15.023	-15.021	-15.018	1.40	-※1	-※2	-14.995	-14.995	-14.995	1.54	-※1	-※2	-14.982	-14.984	-14.984	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	-15.303	-15.301	-15.310	-15.284	-15.272																																																																												
0.28	-15.065	-15.090	-15.111	-15.116	-15.112																																																																												
0.56	-15.049	-15.054	-15.075	-15.075	-15.065																																																																												
0.70	-15.096	-15.077	-15.066	-15.061	-15.055																																																																												
0.84	-15.010	-15.025	-15.049	-15.046	-15.042																																																																												
0.98	-14.992	-15.009	-15.035	-15.033	-15.030																																																																												
1.12	-※1	-14.993	-15.023	-15.021	-15.018																																																																												
1.40	-※1	-※2	-14.995	-14.995	-14.995																																																																												
1.54	-※1	-※2	-14.982	-14.984	-14.984																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
<p>Note: Slanted line shows the range of the rated load current.</p>			<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																														

COSEL

Model	MGFW402415
Item	Dynamic Load Response
Object	+15V1.4A


Temperature 25°C
Testing Circuitry Figure A

Input Volt. 24 V

-15V:rated load current.

Cycle 100 ms

t1,t2 = 100 μ s

Min.Load (0A)↔
Load 100% (1.4A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (0.7A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (0.7A)↔
Load 100% (1.4A)

200 mV/div

2 ms/div



2 ms/div


COSEL

Model	MGFW402415	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V1.4A		

Input Volt. 24 V

+15V:rated load current.


Cycle 100 ms

t1,t2 = 100 μ s

Min.Load (0A)↔
Load 100% (1.4A)

200 mV/div


2 ms/div



Min.Load (0A)↔
Load 50% (0.7A)

200 mV/div


2 ms/div



Load 50% (0.7A)↔
Load 100% (1.4A)

200 mV/div

2 ms/div



COSEL

Model	MGFW402415																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V1.4A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0.0 to 2.0 A. Two curves are plotted: one for Input Volt. 9V (solid line with triangle markers) and one for Input Volt. 36V (dashed line with circle markers). A vertical slanted line at approximately 1.4A indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (9V)</th> <th>Ripple Voltage [mV] (36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>35</td></tr> <tr><td>0.28</td><td>20</td><td>30</td></tr> <tr><td>0.56</td><td>25</td><td>35</td></tr> <tr><td>0.84</td><td>30</td><td>40</td></tr> <tr><td>1.12</td><td>-</td><td>45</td></tr> <tr><td>1.40</td><td>-</td><td>50</td></tr> <tr><td>1.54</td><td>-</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (9V)	Ripple Voltage [mV] (36V)	0.00	20	35	0.28	20	30	0.56	25	35	0.84	30	40	1.12	-	45	1.40	-	50	1.54	-	50	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (9V)	Ripple Voltage [mV] (36V)																																						
0.00	20	35																																						
0.28	20	30																																						
0.56	25	35																																						
0.84	30	40																																						
1.12	-	45																																						
1.40	-	50																																						
1.54	-	50																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>35</td></tr> <tr><td>0.28</td><td>20</td><td>30</td></tr> <tr><td>0.56</td><td>25</td><td>35</td></tr> <tr><td>0.84</td><td>30</td><td>40</td></tr> <tr><td>1.12</td><td>-</td><td>45</td></tr> <tr><td>1.40</td><td>-</td><td>50</td></tr> <tr><td>1.54</td><td>-</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	20	35	0.28	20	30	0.56	25	35	0.84	30	40	1.12	-	45	1.40	-	50	1.54	-	50	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	20	35																																						
0.28	20	30																																						
0.56	25	35																																						
0.84	30	40																																						
1.12	-	45																																						
1.40	-	50																																						
1.54	-	50																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								

COSEL

Model	MGFW402415																																								
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																							
Object	-15V1.4A																																								
1.Graph																																									
		2.Values																																							
<p>Input Volt. 9V Input Volt. 36V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>35</td></tr> <tr><td>0.28</td><td>20</td><td>30</td></tr> <tr><td>0.56</td><td>25</td><td>35</td></tr> <tr><td>0.84</td><td>30</td><td>40</td></tr> <tr><td>1.12</td><td>-※</td><td>45</td></tr> <tr><td>1.40</td><td>-※</td><td>50</td></tr> <tr><td>1.54</td><td>-※</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	20	35	0.28	20	30	0.56	25	35	0.84	30	40	1.12	-※	45	1.40	-※	50	1.54	-※	50	--	-	-	--	-	-	--	-	-	--	-	-	+15V: Rated Load Current
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.00	20	35																																							
0.28	20	30																																							
0.56	25	35																																							
0.84	30	40																																							
1.12	-※	45																																							
1.40	-※	50																																							
1.54	-※	50																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																							
<p>Ripple [mVp-p]</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									


COSEL

Model MGFW402415

Item Ripple-Noise

Object +15V1.4A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.00	20	35
0.28	30	40
0.56	35	40
0.84	40	50
1.12	-	65
1.40	-	75
1.54	-	80
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.


COSEL

Model MGFW402415

Item Ripple-Noise

Object -15V1.4A

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.00	20	35
0.28	30	40
0.56	35	40
0.84	40	50
1.12	-	65
1.40	-	75
1.54	-	80
--	-	-
--	-	-
--	-	-
--	-	-


+15V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFW402415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V1.4A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	50	45
-40	45	45
-20	40	45
25	35	40
60	30	40
85	35	45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	50	45
-40	45	45
-20	40	45
25	35	40
60	30	40
85	35	45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFW402415
Item	Ambient Temperature Drift
Object	+15V1.4A




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	14.950	14.952	14.946	14.948	14.948
-40	14.970	14.971	14.967	14.969	14.970
-20	14.984	14.986	14.984	14.985	14.985
0	14.995	14.996	14.995	14.995	14.995
25	15.001	15.002	15.003	15.003	15.003
65	14.999	15.001	14.999	14.999	14.999
75	14.998	15.001	14.997	14.997	14.997
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-15V: Rated Load Current



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	-14.907	-14.909	-14.911	-14.914	-14.917
-40	-14.938	-14.940	-14.943	-14.945	-14.947
-20	-14.963	-14.964	-14.967	-14.968	-14.970
0	-14.980	-14.981	-14.983	-14.984	-14.984
25	-14.992	-14.993	-14.995	-14.995	-14.995
65	-14.996	-14.998	-14.996	-14.996	-14.995
75	-14.997	-14.998	-14.995	-14.995	-14.994
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

+15V: Rated Load Current

Note: In case of input Volt.9V, Load 70%.

12V, Load 80%.

Other case Load 100%.

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW402415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 65°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 1.4A (AVR 2) : 0 - 1.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V1.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	65	9	0	15.367	±357	±2.4
Minimum Voltage	-40	18	1.4	14.653		

Object	-15V1.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	65	18	0	-15.325	±370	±2.5
Minimum Voltage	-40	9	1.4	-14.585		

COSEL


Model	MGFW402415	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V1.4A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.002</td></tr> <tr><td>0.5</td><td>14.999</td></tr> <tr><td>1.0</td><td>14.999</td></tr> <tr><td>2.0</td><td>14.999</td></tr> <tr><td>3.0</td><td>14.999</td></tr> <tr><td>4.0</td><td>14.999</td></tr> <tr><td>5.0</td><td>14.999</td></tr> <tr><td>6.0</td><td>14.999</td></tr> <tr><td>7.0</td><td>14.999</td></tr> <tr><td>8.0</td><td>14.999</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	15.002	0.5	14.999	1.0	14.999	2.0	14.999	3.0	14.999	4.0	14.999	5.0	14.999	6.0	14.999	7.0	14.999	8.0	14.999
Time since start [H]	Output Voltage [V]																								
0.0	15.002																								
0.5	14.999																								
1.0	14.999																								
2.0	14.999																								
3.0	14.999																								
4.0	14.999																								
5.0	14.999																								
6.0	14.999																								
7.0	14.999																								
8.0	14.999																								
Object -15V1.4A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.995</td></tr> <tr><td>0.5</td><td>-14.996</td></tr> <tr><td>1.0</td><td>-14.996</td></tr> <tr><td>2.0</td><td>-14.996</td></tr> <tr><td>3.0</td><td>-14.996</td></tr> <tr><td>4.0</td><td>-14.996</td></tr> <tr><td>5.0</td><td>-14.996</td></tr> <tr><td>6.0</td><td>-14.996</td></tr> <tr><td>7.0</td><td>-14.996</td></tr> <tr><td>8.0</td><td>-14.996</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-14.995	0.5	-14.996	1.0	-14.996	2.0	-14.996	3.0	-14.996	4.0	-14.996	5.0	-14.996	6.0	-14.996	7.0	-14.996	8.0	-14.996
Time since start [H]	Output Voltage [V]																								
0.0	-14.995																								
0.5	-14.996																								
1.0	-14.996																								
2.0	-14.996																								
3.0	-14.996																								
4.0	-14.996																								
5.0	-14.996																								
6.0	-14.996																								
7.0	-14.996																								
8.0	-14.996																								

COSEL

Model	MGFW402415
Item	Rise and Fall Time
Object	+15V1.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.8	4.1	10.9	0.5	3.1	
100 %		6.8	5.7	12.5	0.4	1.0	




COSEL

Model	MGFW402415
Item	Rise and Fall Time
Object	-15V1.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		6.8	4.1	10.9	0.5	3.1
100 %		6.8	5.7	12.5	0.4	1.0




COSEL

Model	MGFW402415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1.4A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	7.7	8.0
-40	7.5	7.8
-20	7.4	7.5
0	7.4	7.5
25	7.4	7.5
65	7.5	7.4
75	7.5	7.4
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Load Current is same as well as +15V

Object	-15V1.4A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	7.7	8.0
-40	7.5	7.9
-20	7.4	7.5
0	7.4	7.5
25	7.4	7.5
65	7.5	7.4
75	7.5	7.4
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Load Current is same as well as -15V

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFW402415	Temperature Testing Circuitry	25°C Figure A																																																																							
Item	Overcurrent Protection																																																																									
Object	+15V1.4A																																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>15.0</td> <td>1.366</td> <td>1.676</td> <td>1.945</td> <td>1.925</td> <td>1.915</td> </tr> <tr> <td>14.3</td> <td>-※1</td> <td>-※2</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>13.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>12.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>10.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>9.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>7.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>6.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>-15V: Rated Load Current</p>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	15.0	1.366	1.676	1.945	1.925	1.915	14.3	-※1	-※2	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																									
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																					
15.0	1.366	1.676	1.945	1.925	1.915																																																																					
14.3	-※1	-※2	-	-	-																																																																					
13.5	-	-	-	-	-																																																																					
12.0	-	-	-	-	-																																																																					
10.5	-	-	-	-	-																																																																					
9.0	-	-	-	-	-																																																																					
7.5	-	-	-	-	-																																																																					
6.0	-	-	-	-	-																																																																					
4.5	-	-	-	-	-																																																																					
0.0	-	-	-	-	-																																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>-15.0</td> <td>1.377</td> <td>1.676</td> <td>1.945</td> <td>1.925</td> <td>1.925</td> </tr> <tr> <td>-14.3</td> <td>-※1</td> <td>-※2</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-13.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-12.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-10.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-9.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-7.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-6.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-4.5</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+15V: Rated Load Current</p> <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	-15.0	1.377	1.676	1.945	1.925	1.925	-14.3	-※1	-※2	-	-	-	-13.5	-	-	-	-	-	-12.0	-	-	-	-	-	-10.5	-	-	-	-	-	-9.0	-	-	-	-	-	-7.5	-	-	-	-	-	-6.0	-	-	-	-	-	-4.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																									
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																					
-15.0	1.377	1.676	1.945	1.925	1.925																																																																					
-14.3	-※1	-※2	-	-	-																																																																					
-13.5	-	-	-	-	-																																																																					
-12.0	-	-	-	-	-																																																																					
-10.5	-	-	-	-	-																																																																					
-9.0	-	-	-	-	-																																																																					
-7.5	-	-	-	-	-																																																																					
-6.0	-	-	-	-	-																																																																					
-4.5	-	-	-	-	-																																																																					
0.0	-	-	-	-	-																																																																					
Note:	Slanted line shows the range of the rated load current. Intermittent operation activates when overcurrent protection is activated.																																																																									

COSEL

Model	MGFW402415																																																					
Item	Overvoltage Protection																																																					
Object	+30V1.4A																																																					
1.Graph	—△— Input Volt. 9V ---□--- Input Volt. 24V -·-*-- Input Volt. 36V	Temperature 25°C Testing Circuitry Figure A	2.Values																																																			
	<p>Operating Point [%]</p> <p>Load Ratio [%]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Operating Point [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>132</td><td>131</td><td>132</td></tr> <tr><td>10</td><td>126</td><td>126</td><td>126</td></tr> <tr><td>20</td><td>126</td><td>126</td><td>125</td></tr> <tr><td>30</td><td>126</td><td>126</td><td>125</td></tr> <tr><td>40</td><td>126</td><td>125</td><td>125</td></tr> <tr><td>50</td><td>126</td><td>126</td><td>125</td></tr> <tr><td>60</td><td>127</td><td>126</td><td>126</td></tr> <tr><td>70</td><td>125</td><td>126</td><td>126</td></tr> <tr><td>80</td><td>-</td><td>126</td><td>126</td></tr> <tr><td>90</td><td>-</td><td>126</td><td>126</td></tr> <tr><td>100</td><td>-</td><td>126</td><td>126</td></tr> </tbody> </table>	Load Ratio [%]	Operating Point [%]			Input Volt. 9[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	132	131	132	10	126	126	126	20	126	126	125	30	126	126	125	40	126	125	125	50	126	126	125	60	127	126	126	70	125	126	126	80	-	126	126	90	-	126	126	100	-	126	126	
Load Ratio [%]	Operating Point [%]																																																					
	Input Volt. 9[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	132	131	132																																																			
10	126	126	126																																																			
20	126	126	125																																																			
30	126	126	125																																																			
40	126	125	125																																																			
50	126	126	125																																																			
60	127	126	126																																																			
70	125	126	126																																																			
80	-	126	126																																																			
90	-	126	126																																																			
100	-	126	126																																																			

Measured as a single output(+30V).


※During this area, overcurrent protection activates.

COSEL

Model	MGFW402415
Item	Switching frequency (by Load Current)
Object	+/-15V1.4A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)