

# TEST DATA OF MGFW404812

Regulated DC Power Supply

Approved by : Junichi Hatagishi  
Junichi Hatagishi                                  Design Manager

Prepared by : Shohei Mukaiide  
Shohei Mukaiide                                  Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Switching frequency (by Load Current) . . . . .	23
20.Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	MGFW404812																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____	_____	_____																																																																															
1.Graph	<p style="text-align: center;">—△— Load 100%        - - □ - - Load 50%        - - ○ - - Load 0%</p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>	2.Values																																																																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.2</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>15.6</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.0</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.4</td><td>0.030</td><td>1.384</td><td>-※</td></tr> <tr><td>16.8</td><td>0.029</td><td>1.349</td><td>-※</td></tr> <tr><td>17.2</td><td>0.029</td><td>1.316</td><td>-※</td></tr> <tr><td>17.6</td><td>0.028</td><td>1.285</td><td>-※</td></tr> <tr><td>18.0</td><td>0.028</td><td>1.255</td><td>-※</td></tr> <tr><td>24.0</td><td>0.023</td><td>0.935</td><td>-※</td></tr> <tr><td>36.0</td><td>0.018</td><td>0.621</td><td>1.257</td></tr> <tr><td>48.0</td><td>0.016</td><td>0.470</td><td>0.941</td></tr> <tr><td>76.0</td><td>0.011</td><td>0.304</td><td>0.600</td></tr> <tr><td>80.0</td><td>0.011</td><td>0.291</td><td>0.575</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	15.2	0.004	0.004	-※	15.6	0.004	0.004	-※	16.0	0.004	0.004	-※	16.4	0.030	1.384	-※	16.8	0.029	1.349	-※	17.2	0.029	1.316	-※	17.6	0.028	1.285	-※	18.0	0.028	1.255	-※	24.0	0.023	0.935	-※	36.0	0.018	0.621	1.257	48.0	0.016	0.470	0.941	76.0	0.011	0.304	0.600	80.0	0.011	0.291	0.575	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
15.2	0.004	0.004	-※																																																																															
15.6	0.004	0.004	-※																																																																															
16.0	0.004	0.004	-※																																																																															
16.4	0.030	1.384	-※																																																																															
16.8	0.029	1.349	-※																																																																															
17.2	0.029	1.316	-※																																																																															
17.6	0.028	1.285	-※																																																																															
18.0	0.028	1.255	-※																																																																															
24.0	0.023	0.935	-※																																																																															
36.0	0.018	0.621	1.257																																																																															
48.0	0.016	0.470	0.941																																																																															
76.0	0.011	0.304	0.600																																																																															
80.0	0.011	0.291	0.575																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

**COSEL**

Model	MGFW404812																																																																																	
Item	Input Current (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.028</td><td>0.023</td><td>0.018</td><td>0.016</td><td>0.011</td></tr> <tr><td>20</td><td>0.517</td><td>0.390</td><td>0.262</td><td>0.199</td><td>0.133</td></tr> <tr><td>40</td><td>1.008</td><td>0.756</td><td>0.505</td><td>0.382</td><td>0.250</td></tr> <tr><td>60</td><td>1.517</td><td>1.133</td><td>0.751</td><td>0.566</td><td>0.364</td></tr> <tr><td>80</td><td>-※1</td><td>1.510</td><td>1.003</td><td>0.752</td><td>0.481</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>1.257</td><td>0.941</td><td>0.600</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>1.388</td><td>1.038</td><td>0.659</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.028	0.023	0.018	0.016	0.011	20	0.517	0.390	0.262	0.199	0.133	40	1.008	0.756	0.505	0.382	0.250	60	1.517	1.133	0.751	0.566	0.364	80	-※1	1.510	1.003	0.752	0.481	100	-※1	-※2	1.257	0.941	0.600	110	-※1	-※2	1.388	1.038	0.659	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.028	0.023	0.018	0.016	0.011																																																																													
20	0.517	0.390	0.262	0.199	0.133																																																																													
40	1.008	0.756	0.505	0.382	0.250																																																																													
60	1.517	1.133	0.751	0.566	0.364																																																																													
80	-※1	1.510	1.003	0.752	0.481																																																																													
100	-※1	-※2	1.257	0.941	0.600																																																																													
110	-※1	-※2	1.388	1.038	0.659																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**

Model	MGFW404812																																																																																	
Item	Input Power (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object																																																																																		
1.Graph	<p>Input Power [W]</p> <p>Load Ratio [%]</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.50</td><td>0.55</td><td>0.64</td><td>0.77</td><td>0.83</td></tr> <tr><td>20</td><td>9.33</td><td>9.37</td><td>9.45</td><td>9.58</td><td>10.11</td></tr> <tr><td>40</td><td>18.23</td><td>18.19</td><td>18.22</td><td>18.38</td><td>19.01</td></tr> <tr><td>60</td><td>27.37</td><td>27.19</td><td>27.08</td><td>27.17</td><td>27.71</td></tr> <tr><td>80</td><td>-※1</td><td>36.37</td><td>36.15</td><td>36.16</td><td>36.58</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>45.31</td><td>45.26</td><td>45.58</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>49.99</td><td>49.87</td><td>50.13</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.50	0.55	0.64	0.77	0.83	20	9.33	9.37	9.45	9.58	10.11	40	18.23	18.19	18.22	18.38	19.01	60	27.37	27.19	27.08	27.17	27.71	80	-※1	36.37	36.15	36.16	36.58	100	-※1	-※2	45.31	45.26	45.58	110	-※1	-※2	49.99	49.87	50.13	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.50	0.55	0.64	0.77	0.83																																																																													
20	9.33	9.37	9.45	9.58	10.11																																																																													
40	18.23	18.19	18.22	18.38	19.01																																																																													
60	27.37	27.19	27.08	27.17	27.71																																																																													
80	-※1	36.37	36.15	36.16	36.58																																																																													
100	-※1	-※2	45.31	45.26	45.58																																																																													
110	-※1	-※2	49.99	49.87	50.13																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

Model	MGFW404812																																
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry      25°C Figure A																															
Object																																	
1.Graph																																	
		2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>90.4</td> <td>89.4 ※1</td> </tr> <tr> <td>18</td> <td>90.4</td> <td>90.0 ※1</td> </tr> <tr> <td>24</td> <td>90.9</td> <td>90.5 ※2</td> </tr> <tr> <td>30</td> <td>91.1</td> <td>90.3</td> </tr> <tr> <td>36</td> <td>91.1</td> <td>90.7</td> </tr> <tr> <td>48</td> <td>90.6</td> <td>91.0</td> </tr> <tr> <td>60</td> <td>89.7</td> <td>90.5</td> </tr> <tr> <td>76</td> <td>88.0</td> <td>90.0</td> </tr> <tr> <td>80</td> <td>87.6</td> <td>89.8</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	90.4	89.4 ※1	18	90.4	90.0 ※1	24	90.9	90.5 ※2	30	91.1	90.3	36	91.1	90.7	48	90.6	91.0	60	89.7	90.5	76	88.0	90.0	80	87.6	89.8
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
17	90.4	89.4 ※1																															
18	90.4	90.0 ※1																															
24	90.9	90.5 ※2																															
30	91.1	90.3																															
36	91.1	90.7																															
48	90.6	91.0																															
60	89.7	90.5																															
76	88.0	90.0																															
80	87.6	89.8																															
		※1: Load 70% ※2: Load 80%																															
Note: Slanted line shows the range of the rated input voltage.																																	

**COSEL**


Model	MGFW404812																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18V</th> <th>24V</th> <th>36V</th> <th>48V</th> <th>76V</th> </tr> </thead> <tbody> <tr><td>20</td><td>84.0</td><td>85.5</td><td>86.0</td><td>86.5</td><td>87.0</td></tr> <tr><td>40</td><td>86.0</td><td>87.5</td><td>88.0</td><td>88.5</td><td>89.0</td></tr> <tr><td>60</td><td>87.0</td><td>88.5</td><td>89.0</td><td>89.5</td><td>90.0</td></tr> <tr><td>80</td><td>88.0</td><td>89.5</td><td>90.0</td><td>90.5</td><td>91.0</td></tr> <tr><td>100</td><td>89.0</td><td>90.5</td><td>91.0</td><td>91.5</td><td>92.0</td></tr> </tbody> </table>					Load Ratio [%]	18V	24V	36V	48V	76V	20	84.0	85.5	86.0	86.5	87.0	40	86.0	87.5	88.0	88.5	89.0	60	87.0	88.5	89.0	89.5	90.0	80	88.0	89.5	90.0	90.5	91.0	100	89.0	90.5	91.0	91.5	92.0																																									
Load Ratio [%]	18V	24V	36V	48V	76V																																																																													
20	84.0	85.5	86.0	86.5	87.0																																																																													
40	86.0	87.5	88.0	88.5	89.0																																																																													
60	87.0	88.5	89.0	89.5	90.0																																																																													
80	88.0	89.5	90.0	90.5	91.0																																																																													
100	89.0	90.5	91.0	91.5	92.0																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>88.5</td><td>88.1</td><td>87.2</td><td>86.3</td><td>81.3</td></tr> <tr><td>40</td><td>90.6</td><td>90.9</td><td>90.6</td><td>89.7</td><td>86.7</td></tr> <tr><td>60</td><td>90.4</td><td>90.8</td><td>91.2</td><td>90.9</td><td>89.2</td></tr> <tr><td>80</td><td>-※1</td><td>90.5</td><td>91.1</td><td>91.0</td><td>89.8</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>90.7</td><td>91.0</td><td>90.0</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>90.5</td><td>90.6</td><td>90.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0	-	-	-	-	-	20	88.5	88.1	87.2	86.3	81.3	40	90.6	90.9	90.6	89.7	86.7	60	90.4	90.8	91.2	90.9	89.2	80	-※1	90.5	91.1	91.0	89.8	100	-※1	-※2	90.7	91.0	90.0	110	-※1	-※2	90.5	90.6	90.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	-	-	-	-	-																																																																													
20	88.5	88.1	87.2	86.3	81.3																																																																													
40	90.6	90.9	90.6	89.7	86.7																																																																													
60	90.4	90.8	91.2	90.9	89.2																																																																													
80	-※1	90.5	91.1	91.0	89.8																																																																													
100	-※1	-※2	90.7	91.0	90.0																																																																													
110	-※1	-※2	90.5	90.6	90.1																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

Model	MGFW404812	Temperature Testing Circuitry	25°C Figure A																																
Item	Line Regulation																																		
Object	+12V1.7A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>12.186</td><td>-</td></tr> <tr><td>18</td><td>12.182</td><td>-</td></tr> <tr><td>24</td><td>12.167</td><td>-</td></tr> <tr><td>30</td><td>12.160</td><td>12.083</td></tr> <tr><td>36</td><td>12.156</td><td>12.084</td></tr> <tr><td>48</td><td>12.151</td><td>12.084</td></tr> <tr><td>60</td><td>12.148</td><td>12.084</td></tr> <tr><td>76</td><td>12.146</td><td>12.084</td></tr> <tr><td>80</td><td>12.146</td><td>12.084</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	12.186	-	18	12.182	-	24	12.167	-	30	12.160	12.083	36	12.156	12.084	48	12.151	12.084	60	12.148	12.084	76	12.146	12.084	80	12.146	12.084
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	12.186	-																																	
18	12.182	-																																	
24	12.167	-																																	
30	12.160	12.083																																	
36	12.156	12.084																																	
48	12.151	12.084																																	
60	12.148	12.084																																	
76	12.146	12.084																																	
80	12.146	12.084																																	
Object	-12V1.7A	2.Values																																	
1.Graph			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-12.198</td><td>-</td></tr> <tr><td>18</td><td>-12.193</td><td>-</td></tr> <tr><td>24</td><td>-12.175</td><td>-</td></tr> <tr><td>30</td><td>-12.168</td><td>-12.083</td></tr> <tr><td>36</td><td>-12.163</td><td>-12.083</td></tr> <tr><td>48</td><td>-12.157</td><td>-12.083</td></tr> <tr><td>60</td><td>-12.155</td><td>-12.083</td></tr> <tr><td>76</td><td>-12.152</td><td>-12.083</td></tr> <tr><td>80</td><td>-12.151</td><td>-12.083</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-12.198	-	18	-12.193	-	24	-12.175	-	30	-12.168	-12.083	36	-12.163	-12.083	48	-12.157	-12.083	60	-12.155	-12.083	76	-12.152	-12.083	80	-12.151	-12.083
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-12.198	-																																	
18	-12.193	-																																	
24	-12.175	-																																	
30	-12.168	-12.083																																	
36	-12.163	-12.083																																	
48	-12.157	-12.083																																	
60	-12.155	-12.083																																	
76	-12.152	-12.083																																	
80	-12.151	-12.083																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.      ※2 Maximum output current at 24V input Voltage is 80% of rated load current.      Refer to instruction manuals for details of input derating.</p>																																

**COSEL**

Model	MGFW404812																																																																																	
Item	Load Regulation																																																																																	
Object	+12V1.7A																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.431</td><td>12.411</td><td>12.392</td><td>12.382</td><td>12.370</td></tr> <tr><td>0.34</td><td>12.245</td><td>12.221</td><td>12.211</td><td>12.208</td><td>12.205</td></tr> <tr><td>0.68</td><td>12.207</td><td>12.186</td><td>12.173</td><td>12.170</td><td>12.164</td></tr> <tr><td>0.85</td><td>12.187</td><td>12.168</td><td>12.158</td><td>12.154</td><td>12.148</td></tr> <tr><td>1.02</td><td>12.168</td><td>12.152</td><td>12.142</td><td>12.138</td><td>12.134</td></tr> <tr><td>1.19</td><td>12.148</td><td>12.135</td><td>12.127</td><td>12.124</td><td>12.121</td></tr> <tr><td>1.36</td><td>-※1</td><td>12.118</td><td>12.112</td><td>12.111</td><td>12.108</td></tr> <tr><td>1.70</td><td>-※1</td><td>-※2</td><td>12.084</td><td>12.084</td><td>12.084</td></tr> <tr><td>1.87</td><td>-※1</td><td>-※2</td><td>12.068</td><td>12.070</td><td>12.071</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	12.431	12.411	12.392	12.382	12.370	0.34	12.245	12.221	12.211	12.208	12.205	0.68	12.207	12.186	12.173	12.170	12.164	0.85	12.187	12.168	12.158	12.154	12.148	1.02	12.168	12.152	12.142	12.138	12.134	1.19	12.148	12.135	12.127	12.124	12.121	1.36	-※1	12.118	12.112	12.111	12.108	1.70	-※1	-※2	12.084	12.084	12.084	1.87	-※1	-※2	12.068	12.070	12.071	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	12.431	12.411	12.392	12.382	12.370																																																																													
0.34	12.245	12.221	12.211	12.208	12.205																																																																													
0.68	12.207	12.186	12.173	12.170	12.164																																																																													
0.85	12.187	12.168	12.158	12.154	12.148																																																																													
1.02	12.168	12.152	12.142	12.138	12.134																																																																													
1.19	12.148	12.135	12.127	12.124	12.121																																																																													
1.36	-※1	12.118	12.112	12.111	12.108																																																																													
1.70	-※1	-※2	12.084	12.084	12.084																																																																													
1.87	-※1	-※2	12.068	12.070	12.071																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Object	-12V1.7A																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-12.461</td><td>-12.429</td><td>-12.400</td><td>-12.395</td><td>-12.363</td></tr> <tr><td>0.34</td><td>-12.257</td><td>-12.231</td><td>-12.220</td><td>-12.221</td><td>-12.215</td></tr> <tr><td>0.68</td><td>-12.215</td><td>-12.190</td><td>-12.177</td><td>-12.173</td><td>-12.169</td></tr> <tr><td>0.85</td><td>-12.194</td><td>-12.172</td><td>-12.160</td><td>-12.156</td><td>-12.152</td></tr> <tr><td>1.02</td><td>-12.174</td><td>-12.154</td><td>-12.144</td><td>-12.140</td><td>-12.137</td></tr> <tr><td>1.19</td><td>-12.158</td><td>-12.137</td><td>-12.128</td><td>-12.126</td><td>-12.123</td></tr> <tr><td>1.36</td><td>-※1</td><td>-12.119</td><td>-12.113</td><td>-12.111</td><td>-12.109</td></tr> <tr><td>1.70</td><td>-※1</td><td>-※2</td><td>-12.083</td><td>-12.083</td><td>-12.083</td></tr> <tr><td>1.87</td><td>-※1</td><td>-※2</td><td>-12.068</td><td>-12.069</td><td>-12.071</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-12.461	-12.429	-12.400	-12.395	-12.363	0.34	-12.257	-12.231	-12.220	-12.221	-12.215	0.68	-12.215	-12.190	-12.177	-12.173	-12.169	0.85	-12.194	-12.172	-12.160	-12.156	-12.152	1.02	-12.174	-12.154	-12.144	-12.140	-12.137	1.19	-12.158	-12.137	-12.128	-12.126	-12.123	1.36	-※1	-12.119	-12.113	-12.111	-12.109	1.70	-※1	-※2	-12.083	-12.083	-12.083	1.87	-※1	-※2	-12.068	-12.069	-12.071	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	-12.461	-12.429	-12.400	-12.395	-12.363																																																																													
0.34	-12.257	-12.231	-12.220	-12.221	-12.215																																																																													
0.68	-12.215	-12.190	-12.177	-12.173	-12.169																																																																													
0.85	-12.194	-12.172	-12.160	-12.156	-12.152																																																																													
1.02	-12.174	-12.154	-12.144	-12.140	-12.137																																																																													
1.19	-12.158	-12.137	-12.128	-12.126	-12.123																																																																													
1.36	-※1	-12.119	-12.113	-12.111	-12.109																																																																													
1.70	-※1	-※2	-12.083	-12.083	-12.083																																																																													
1.87	-※1	-※2	-12.068	-12.069	-12.071																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current.																																																																																		
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

**COSEL**

Model	MGFW404812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V1.7A		

Input Volt. 48 V

+12V:rated load current.


Cycle 100 ms

t<sub>1</sub>,t<sub>2</sub> = 100 μ s


Load Current  
t<sub>1</sub>

t<sub>2</sub>

Min.Load (0A)↔  
Load 100% (1.7A)




2 ms/div




2 ms/div

Min.Load (0A)↔  
Load 50% (0.85A)




2 ms/div




2 ms/div

Load 50% (0.85A)↔  
Load 100% (1.7A)



2 ms/div




2 ms/div

**COSEL**

Model	MGFW404812
Item	Ripple Voltage (by Load Current)
Object	+12V1.7A

## 1.Graph



Measured by 100 MHz Oscilloscope.  
Ripple Voltage is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	15	30
0.34	30	25
0.68	20	50
1.02	35	50
1.19	35	45
1.36	-	45
1.70	-	55
1.87	-	70
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

\* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**COSEL**

Model	MGFW404812
Item	Ripple Voltage (by Load Current)
Object	-12V1.7A

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	15	30
0.34	30	25
0.68	20	50
1.02	35	50
1.19	35	45
1.36	-	45
1.70	-	55
1.87	-	70
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**COSEL**

Model	MGFW404812
Item	Ripple-Noise
Object	+12V1.7A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.  
Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	20	30
0.34	35	30
0.68	25	55
1.02	35	55
1.19	40	50
1.36	-	45
1.70	-	60
1.87	-	75
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current


※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFW404812
Item	Ripple-Noise
Object	-12V1.7A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.  
Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	20	30
0.34	35	30
0.68	25	55
1.02	35	55
1.19	40	50
1.36	-	45
1.70	-	60
1.87	-	75
--	-	-
--	-	-
--	-	-


+12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFW404812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.7A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	35	50
-40	35	45
-20	35	45
25	40	50
60	40	50
85	40	50
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	35	50
-40	35	45
-20	35	45
25	40	50
60	40	50
85	40	50
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFW404812
Item	Ambient Temperature Drift
Object	+12V1.7A




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	12.019	12.021	12.021	12.024	12.025
-40	12.041	12.043	12.045	12.046	12.047
-20	12.058	12.059	12.061	12.062	12.062
0	12.070	12.071	12.074	12.075	12.075
25	12.078	12.080	12.083	12.083	12.082
65	12.082	12.084	12.085	12.085	12.085
75	12.084	12.086	12.085	12.085	12.085
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-12V: Rated Load Current



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	-12.013	-12.014	-12.015	-12.018	-12.020
-40	-12.036	-12.038	-12.040	-12.042	-12.044
-20	-12.054	-12.056	-12.057	-12.059	-12.060
0	-12.068	-12.069	-12.072	-12.073	-12.074
25	-12.078	-12.079	-12.082	-12.082	-12.082
65	-12.084	-12.085	-12.086	-12.086	-12.086
75	-12.086	-12.087	-12.086	-12.085	-12.086
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

+12V: Rated Load Current

Note: In case of input Volt.18V, Load 70%.

24V, Load 80%.

Other case Load 100%.

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW404812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 65°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 1.7A (AVR 2) : 0 - 1.7A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object		+12V1.7A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ratio [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	65	18	0	12.455	$\pm 350$	$\pm 2.9$	
Minimum Voltage	65	76	1.7	11.755			

Object		-12V1.7A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ratio [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	65	36	0	-12.425	$\pm 353$	$\pm 2.9$	
Minimum Voltage	65	18	1.7	-11.720			

**COSEL**


Model	MGFW404812	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.7A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.083</td></tr> <tr><td>0.5</td><td>12.085</td></tr> <tr><td>1.0</td><td>12.085</td></tr> <tr><td>2.0</td><td>12.085</td></tr> <tr><td>3.0</td><td>12.085</td></tr> <tr><td>4.0</td><td>12.085</td></tr> <tr><td>5.0</td><td>12.085</td></tr> <tr><td>6.0</td><td>12.085</td></tr> <tr><td>7.0</td><td>12.085</td></tr> <tr><td>8.0</td><td>12.085</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	12.083	0.5	12.085	1.0	12.085	2.0	12.085	3.0	12.085	4.0	12.085	5.0	12.085	6.0	12.085	7.0	12.085	8.0	12.085
Time since start [H]	Output Voltage [V]																								
0.0	12.083																								
0.5	12.085																								
1.0	12.085																								
2.0	12.085																								
3.0	12.085																								
4.0	12.085																								
5.0	12.085																								
6.0	12.085																								
7.0	12.085																								
8.0	12.085																								
Object -12V1.7A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.082</td></tr> <tr><td>0.5</td><td>-12.086</td></tr> <tr><td>1.0</td><td>-12.086</td></tr> <tr><td>2.0</td><td>-12.086</td></tr> <tr><td>3.0</td><td>-12.086</td></tr> <tr><td>4.0</td><td>-12.086</td></tr> <tr><td>5.0</td><td>-12.086</td></tr> <tr><td>6.0</td><td>-12.086</td></tr> <tr><td>7.0</td><td>-12.086</td></tr> <tr><td>8.0</td><td>-12.086</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-12.082	0.5	-12.086	1.0	-12.086	2.0	-12.086	3.0	-12.086	4.0	-12.086	5.0	-12.086	6.0	-12.086	7.0	-12.086	8.0	-12.086
Time since start [H]	Output Voltage [V]																								
0.0	-12.082																								
0.5	-12.086																								
1.0	-12.086																								
2.0	-12.086																								
3.0	-12.086																								
4.0	-12.086																								
5.0	-12.086																								
6.0	-12.086																								
7.0	-12.086																								
8.0	-12.086																								

**COSEL**

Model	MGFW404812
Item	Rise and Fall Time
Object	+12V1.7A


Temperature  
Testing Circuitry      25°C  
Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.7	4.2	10.9	1.6	3.4	
100 %		6.7	5.7	12.4	1.2	1.1	



**COSEL**


Model	MGFW404812	Temperature Testing Circuitry	25°C
Item	Rise and Fall Time	Figure A	
Object	-12V1.7A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.7	4.2	10.9	1.6	3.4	
100 %		6.7	5.7	12.4	1.2	1.1	



**COSEL**

Model	MGFW404812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1.7A

## 1.Graph



Testing Circuitry Figure A


## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.3	15.3
-40	15.2	15.2
-20	15.1	15.1
0	15.1	15.0
25	15.2	15.1
65	15.1	15.1
75	15.0	15.0
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Load Current is same as well as +12V

## Object -12V1.7A

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.3	15.3
-40	15.2	15.2
-20	15.1	15.1
0	15.1	15.0
25	15.2	15.1
65	15.1	15.1
75	15.0	15.0
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Load Current is same as well as -12V


Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW404812	Temperature Testing Circuitry	25°C Figure A																																																																						
Item	Overcurrent Protection																																																																								
Object	+12V1.7A																																																																								
1.Graph	<p>—△ Input Volt. 18V            —□ Input Volt. 24V            —* Input Volt. 36V            —○ Input Volt. 48V            —◇ Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>12.000</td><td>1.621</td><td>2.048</td><td>2.335</td><td>2.354</td><td>2.429</td></tr> <tr><td>11.400</td><td>-※1</td><td>-※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	12.000	1.621	2.048	2.335	2.354	2.429	11.400	-※1	-※2	-	-	-	10.800	-	-	-	-	-	9.600	-	-	-	-	-	8.400	-	-	-	-	-	7.200	-	-	-	-	-	6.000	-	-	-	-	-	4.800	-	-	-	-	-	3.600	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																								
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																				
12.000	1.621	2.048	2.335	2.354	2.429																																																																				
11.400	-※1	-※2	-	-	-																																																																				
10.800	-	-	-	-	-																																																																				
9.600	-	-	-	-	-																																																																				
8.400	-	-	-	-	-																																																																				
7.200	-	-	-	-	-																																																																				
6.000	-	-	-	-	-																																																																				
4.800	-	-	-	-	-																																																																				
3.600	-	-	-	-	-																																																																				
0.000	-	-	-	-	-																																																																				
			-12V: Rated Load Current																																																																						
Object	-12V1.7A	2.Values																																																																							
1.Graph	<p>—△ Input Volt. 18V            —□ Input Volt. 24V            —* Input Volt. 36V            —○ Input Volt. 48V            —◇ Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-12.000</td><td>1.634</td><td>2.048</td><td>2.335</td><td>2.354</td><td>2.448</td></tr> <tr><td>-11.400</td><td>-※1</td><td>-※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-12.000	1.634	2.048	2.335	2.354	2.448	-11.400	-※1	-※2	-	-	-	-10.800	-	-	-	-	-	-9.600	-	-	-	-	-	-8.400	-	-	-	-	-	-7.200	-	-	-	-	-	-6.000	-	-	-	-	-	-4.800	-	-	-	-	-	-3.600	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																								
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																				
-12.000	1.634	2.048	2.335	2.354	2.448																																																																				
-11.400	-※1	-※2	-	-	-																																																																				
-10.800	-	-	-	-	-																																																																				
-9.600	-	-	-	-	-																																																																				
-8.400	-	-	-	-	-																																																																				
-7.200	-	-	-	-	-																																																																				
-6.000	-	-	-	-	-																																																																				
-4.800	-	-	-	-	-																																																																				
-3.600	-	-	-	-	-																																																																				
0.000	-	-	-	-	-																																																																				
			+12V: Rated Load Current																																																																						
Note:	Slanted line shows the range of the rated load current.		※1 Maximum output current at minimum input Voltage is 70% of rated load current.																																																																						
	Intermittent operation activates when overcurrent protection is activated.		※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																						

**COSEL**

Model	MGFW404812
Item	Ovvoltage Protection
Object	+24V1.7A



Measured as a single output(+24V).

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Ratio [%]	Operating Point [%]		
	Input Volt. 18[V]	Input Volt. 48[V]	Input Volt. 76[V]
0	134	133	134
10	128	128	128
20	127	128	127
30	128	127	127
40	128	127	126
50	128	127	127
60	128	127	127
70	127	127	127
80	- ※	127	127
90	- ※	127	127
100	- ※	126	126


※During this area, overcurrent protection activates.

# COSEL

Model	MGFW404812
Item	Switching frequency (by Load Current)
Object	+/-12V1.7A

Temperature 25°C  
Testing Circuitry Figure A

### 1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.




Figure A




Figure B (Ripple and Ripple noise Characteristic)