

TEST DATA OF MGFW62412

Regulated DC Power Supply
December 22, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage) 1

2.Input Current (by Load Ratio) 2

3.Input Power (by Load Ratio) 3

4.Efficiency (by Input Voltage) 4

5.Efficiency (by Load Ratio) 5

6.Line Regulation 6

7.Load Regulation 7

8.Dynamic Load Response 8

9.Ripple Voltage (by Load Current) 10

10.Ripple-Noise 12

11.Ripple Voltage (by Ambient Temperature) 14

12.Ambient Temperature Drift 15

13.Output Voltage Accuracy 16

14.Time Lapse Drift 17

15.Rise and Fall Time 18

16.Minimum Input Voltage for Regulated Output Voltage 20

17.Overcurrent Protection 21

18.Switching frequency (by Load Current) 22


19.Figure of Testing Circuitry 23

(Final Page 23)



Model	MGFW62412
Item	Input Current (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
6.0	0.003	0.003	0.003
8.0	0.003	0.003	0.003
8.2	0.004	0.003	0.003
8.4	0.003	0.003	0.004
8.6	0.030	0.414	0.818
8.8	0.028	0.403	0.816
9.0	0.028	0.396	0.796
12.0	0.023	0.295	0.585
18.0	0.017	0.198	0.387
24.0	0.014	0.150	0.290
30.0	0.006	0.121	0.233
36.0	0.005	0.103	0.195
40.0	0.005	0.093	0.177
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model		MGFW62412		Temperature	25°C																																																																													
Item		Input Current (by Load Ratio)		Testing Circuitry	Figure A																																																																													
Object		_____																																																																																
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · - Input Volt. 18V - · - ○ - · - - Input Volt. 24V - - ◇ - - - Input Volt. 36V </p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.028</td><td>0.023</td><td>0.017</td><td>0.014</td><td>0.005</td></tr> <tr><td>20</td><td>0.172</td><td>0.131</td><td>0.090</td><td>0.069</td><td>0.049</td></tr> <tr><td>40</td><td>0.314</td><td>0.240</td><td>0.162</td><td>0.122</td><td>0.084</td></tr> <tr><td>60</td><td>0.472</td><td>0.347</td><td>0.233</td><td>0.177</td><td>0.121</td></tr> <tr><td>80</td><td>0.615</td><td>0.465</td><td>0.310</td><td>0.233</td><td>0.158</td></tr> <tr><td>100</td><td>0.796</td><td>0.585</td><td>0.387</td><td>0.290</td><td>0.195</td></tr> <tr><td>110</td><td>0.856</td><td>0.640</td><td>0.423</td><td>0.317</td><td>0.213</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.028	0.023	0.017	0.014	0.005	20	0.172	0.131	0.090	0.069	0.049	40	0.314	0.240	0.162	0.122	0.084	60	0.472	0.347	0.233	0.177	0.121	80	0.615	0.465	0.310	0.233	0.158	100	0.796	0.585	0.387	0.290	0.195	110	0.856	0.640	0.423	0.317	0.213	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Ratio [%]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	0.028	0.023	0.017	0.014	0.005																																																																													
20	0.172	0.131	0.090	0.069	0.049																																																																													
40	0.314	0.240	0.162	0.122	0.084																																																																													
60	0.472	0.347	0.233	0.177	0.121																																																																													
80	0.615	0.465	0.310	0.233	0.158																																																																													
100	0.796	0.585	0.387	0.290	0.195																																																																													
110	0.856	0.640	0.423	0.317	0.213																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model		MGFW62412		Temperature 25°C																																																																														
Item		Input Power (by Load Ratio)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>---*--- Input Volt. 18V</p> <p>---○--- Input Volt. 24V</p> <p>---◇--- Input Volt. 36V</p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.25</td><td>0.28</td><td>0.31</td><td>0.32</td><td>0.19</td></tr> <tr><td>20</td><td>1.53</td><td>1.57</td><td>1.61</td><td>1.65</td><td>1.75</td></tr> <tr><td>40</td><td>2.85</td><td>2.86</td><td>2.91</td><td>2.93</td><td>3.04</td></tr> <tr><td>60</td><td>4.18</td><td>4.19</td><td>4.22</td><td>4.24</td><td>4.34</td></tr> <tr><td>80</td><td>5.55</td><td>5.52</td><td>5.54</td><td>5.57</td><td>5.67</td></tr> <tr><td>100</td><td>6.96</td><td>6.88</td><td>6.87</td><td>6.88</td><td>7.00</td></tr> <tr><td>110</td><td>7.68</td><td>7.58</td><td>7.54</td><td>7.56</td><td>7.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ratio [%]	Input Power [W]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.25	0.28	0.31	0.32	0.19	20	1.53	1.57	1.61	1.65	1.75	40	2.85	2.86	2.91	2.93	3.04	60	4.18	4.19	4.22	4.24	4.34	80	5.55	5.52	5.54	5.57	5.67	100	6.96	6.88	6.87	6.88	7.00	110	7.68	7.58	7.54	7.56	7.65	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	0.25	0.28	0.31	0.32	0.19																																																																													
20	1.53	1.57	1.61	1.65	1.75																																																																													
40	2.85	2.86	2.91	2.93	3.04																																																																													
60	4.18	4.19	4.22	4.24	4.34																																																																													
80	5.55	5.52	5.54	5.57	5.67																																																																													
100	6.96	6.88	6.87	6.88	7.00																																																																													
110	7.68	7.58	7.54	7.56	7.65																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model		MGFW62412		Temperature	25°C																																
Item		Efficiency (by Input Voltage)		Testing Circuitry	Figure A																																
Object		_____																																			
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.6</td><td>85.8</td><td>86.6</td></tr> <tr><td>9.0</td><td>85.7</td><td>86.8</td></tr> <tr><td>12.0</td><td>85.5</td><td>87.6</td></tr> <tr><td>15.0</td><td>85.4</td><td>88.0</td></tr> <tr><td>18.0</td><td>84.9</td><td>87.8</td></tr> <tr><td>24.0</td><td>84.3</td><td>87.6</td></tr> <tr><td>30.0</td><td>83.2</td><td>87.0</td></tr> <tr><td>36.0</td><td>81.3</td><td>86.4</td></tr> <tr><td>40.0</td><td>80.8</td><td>85.8</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	85.8	86.6	9.0	85.7	86.8	12.0	85.5	87.6	15.0	85.4	88.0	18.0	84.9	87.8	24.0	84.3	87.6	30.0	83.2	87.0	36.0	81.3	86.4	40.0	80.8	85.8
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
8.6	85.8	86.6																																			
9.0	85.7	86.8																																			
12.0	85.5	87.6																																			
15.0	85.4	88.0																																			
18.0	84.9	87.8																																			
24.0	84.3	87.6																																			
30.0	83.2	87.0																																			
36.0	81.3	86.4																																			
40.0	80.8	85.8																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					




Model		MGFW62412		Temperature 25°C																																																																														
Item		Efficiency (by Load Ratio)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · · - Input Volt. 18V - · · ○ · · - · · - Input Volt. 24V - - ◇ - - - Input Volt. 36V </p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>78.9</td><td>76.4</td><td>74.3</td><td>73.3</td><td>68.3</td></tr> <tr><td>40</td><td>84.7</td><td>84.3</td><td>82.6</td><td>82.1</td><td>79.2</td></tr> <tr><td>60</td><td>86.5</td><td>86.5</td><td>85.8</td><td>85.4</td><td>83.4</td></tr> <tr><td>80</td><td>87.0</td><td>87.5</td><td>87.2</td><td>86.6</td><td>85.0</td></tr> <tr><td>100</td><td>86.8</td><td>87.6</td><td>87.8</td><td>87.6</td><td>86.4</td></tr> <tr><td>110</td><td>86.5</td><td>87.6</td><td>88.1</td><td>87.8</td><td>86.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	-	-	20	78.9	76.4	74.3	73.3	68.3	40	84.7	84.3	82.6	82.1	79.2	60	86.5	86.5	85.8	85.4	83.4	80	87.0	87.5	87.2	86.6	85.0	100	86.8	87.6	87.8	87.6	86.4	110	86.5	87.6	88.1	87.8	86.8	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Ratio [%]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	-	-	-	-	-																																																																													
20	78.9	76.4	74.3	73.3	68.3																																																																													
40	84.7	84.3	82.6	82.1	79.2																																																																													
60	86.5	86.5	85.8	85.4	83.4																																																																													
80	87.0	87.5	87.2	86.6	85.0																																																																													
100	86.8	87.6	87.8	87.6	86.4																																																																													
110	86.5	87.6	88.1	87.8	86.8																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model	MGFW62412
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	12.133	12.062
9.0	12.132	12.063
12.0	12.128	12.064
15.0	12.125	12.064
18.0	12.122	12.064
24.0	12.119	12.063
30.0	12.116	12.062
36.0	12.115	12.061
40.0	12.114	12.061

-12V : Rated Load Current

Object	-12V0.25A
--------	-----------

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	-12.151	-12.078
9.0	-12.150	-12.078
12.0	-12.145	-12.078
15.0	-12.141	-12.078
18.0	-12.139	-12.077
24.0	-12.138	-12.078
30.0	-12.138	-12.078
36.0	-12.137	-12.079
40.0	-12.137	-12.079

+12V : Rated Load Current

Note: Slanted line shows the range of the rated input voltage.




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	12.278	12.261	12.245	12.236	12.226
0.050	12.191	12.183	12.173	12.167	12.161
0.100	12.150	12.145	12.138	12.134	12.129
0.150	12.118	12.115	12.110	12.107	12.104
0.200	12.089	12.088	12.086	12.084	12.081
0.250	12.063	12.064	12.064	12.063	12.061
0.275	12.048	12.051	12.052	12.052	12.051
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-12V : Rated Load Current



2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	-12.306	-12.287	-12.274	-12.265	-12.252
0.050	-12.213	-12.202	-12.194	-12.190	-12.185
0.100	-12.168	-12.161	-12.155	-12.154	-12.152
0.150	-12.134	-12.129	-12.125	-12.125	-12.124
0.200	-12.105	-12.102	-12.100	-12.100	-12.100
0.250	-12.078	-12.078	-12.077	-12.078	-12.079
0.275	-12.064	-12.065	-12.066	-12.067	-12.068
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

+12V : Rated Load Current



Model	MGFW62412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.25A		

Input Volt. 24 V
 -12V:rated load current.
 Cycle 100 ms



t1,t2 = 100 μs



Min.Load (0A) ←→
 Load 100% (0.25A)

200 mV/div

4 ms/div





4 ms/div

Min.Load (0A) ←→
 Load 50% (0.125A)

200 mV/div

4 ms/div





4 ms/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

200 mV/div

4 ms/div




4 ms/div



Model	MGFW62412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.25A		


Input Volt. 24 V
 +12V:rated load current.
 Cycle 100 ms

t1,t2 = 100 μs




Min.Load (0A) ←→
 Load 100% (0.25A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→
 Load 50% (0.125A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

200 mV/div



4 ms/div



4 ms/div



COSEL																																									
Model	MGFW62412	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+12V0.25A																																								
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>5</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>15</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	5	5	0.200	10	5	0.250	15	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.000	5	5																																							
0.050	5	5																																							
0.100	5	5																																							
0.150	5	5																																							
0.200	10	5																																							
0.250	15	5																																							
0.275	15	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									



COSEL																																									
Model	MGFW62412	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	-12V0.25A																																								
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>5</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>15</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	5	5	0.200	10	5	0.250	15	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 36 [V]																																							
0.000	5	5																																							
0.050	5	5																																							
0.100	5	5																																							
0.150	5	5																																							
0.200	10	5																																							
0.250	15	5																																							
0.275	15	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Ripple [mVp-p]</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									



<p>Model MGFW62412</p> <p>Item Ripple-Noise</p> <p>Object +12V0.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>10</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>15</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	10	5	0.200	10	5	0.250	15	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	10	5																																						
0.200	10	5																																						
0.250	15	5																																						
0.275	15	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								




<p>Model MGFW62412</p> <p>Item Ripple-Noise</p> <p>Object -12V0.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>10</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>15</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	10	5	0.200	10	5	0.250	15	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	10	5																																						
0.200	10	5																																						
0.250	15	5																																						
0.275	15	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



Model	MGFW62412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.25A

Testing Circuitry Figure B

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
80	5	5
90	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Object	-12V0.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
80	5	5
90	5	5
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



Model		MGFW62412		Testing Circuitry Figure A																																																																														
Item		Ambient Temperature Drift																																																																																
Object		+12V0.25A																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-·-·*·-·- Input Volt. 18V</p> <p>-·-·○-·- Input Volt. 24V</p> <p>-·-·◇-·- Input Volt. 36V</p>		2.Values																																																																														
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.001</td><td>12.002</td><td>12.002</td><td>12.002</td><td>11.999</td></tr> <tr><td>-40</td><td>12.024</td><td>12.025</td><td>12.025</td><td>12.024</td><td>12.022</td></tr> <tr><td>-20</td><td>12.042</td><td>12.042</td><td>12.043</td><td>12.042</td><td>12.039</td></tr> <tr><td>0</td><td>12.054</td><td>12.055</td><td>12.055</td><td>12.054</td><td>12.052</td></tr> <tr><td>25</td><td>12.063</td><td>12.064</td><td>12.064</td><td>12.063</td><td>12.061</td></tr> <tr><td>80</td><td>12.061</td><td>12.062</td><td>12.062</td><td>12.062</td><td>12.061</td></tr> <tr><td>90</td><td>12.059</td><td>12.061</td><td>12.061</td><td>12.061</td><td>12.060</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V : Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	12.001	12.002	12.002	12.002	11.999	-40	12.024	12.025	12.025	12.024	12.022	-20	12.042	12.042	12.043	12.042	12.039	0	12.054	12.055	12.055	12.054	12.052	25	12.063	12.064	12.064	12.063	12.061	80	12.061	12.062	12.062	12.062	12.061	90	12.059	12.061	12.061	12.061	12.060	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
-60	12.001	12.002	12.002	12.002	11.999																																																																													
-40	12.024	12.025	12.025	12.024	12.022																																																																													
-20	12.042	12.042	12.043	12.042	12.039																																																																													
0	12.054	12.055	12.055	12.054	12.052																																																																													
25	12.063	12.064	12.064	12.063	12.061																																																																													
80	12.061	12.062	12.062	12.062	12.061																																																																													
90	12.059	12.061	12.061	12.061	12.060																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Object		-12V0.25A																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-·-·*·-·- Input Volt. 18V</p> <p>-·-·○-·- Input Volt. 24V</p> <p>-·-·◇-·- Input Volt. 36V</p>		2.Values																																																																														
<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.008</td><td>-12.009</td><td>-12.009</td><td>-12.009</td><td>-12.012</td></tr> <tr><td>-40</td><td>-12.033</td><td>-12.034</td><td>-12.034</td><td>-12.034</td><td>-12.037</td></tr> <tr><td>-20</td><td>-12.053</td><td>-12.053</td><td>-12.053</td><td>-12.054</td><td>-12.056</td></tr> <tr><td>0</td><td>-12.067</td><td>-12.067</td><td>-12.067</td><td>-12.068</td><td>-12.069</td></tr> <tr><td>25</td><td>-12.078</td><td>-12.078</td><td>-12.077</td><td>-12.078</td><td>-12.079</td></tr> <tr><td>80</td><td>-12.079</td><td>-12.079</td><td>-12.079</td><td>-12.079</td><td>-12.080</td></tr> <tr><td>90</td><td>-12.078</td><td>-12.078</td><td>-12.077</td><td>-12.078</td><td>-12.079</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V : Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	-12.008	-12.009	-12.009	-12.009	-12.012	-40	-12.033	-12.034	-12.034	-12.034	-12.037	-20	-12.053	-12.053	-12.053	-12.054	-12.056	0	-12.067	-12.067	-12.067	-12.068	-12.069	25	-12.078	-12.078	-12.077	-12.078	-12.079	80	-12.079	-12.079	-12.079	-12.079	-12.080	90	-12.078	-12.078	-12.077	-12.078	-12.079	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Ambient Temperature [°C]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
-60	-12.008	-12.009	-12.009	-12.009	-12.012																																																																													
-40	-12.033	-12.034	-12.034	-12.034	-12.037																																																																													
-20	-12.053	-12.053	-12.053	-12.054	-12.056																																																																													
0	-12.067	-12.067	-12.067	-12.068	-12.069																																																																													
25	-12.078	-12.078	-12.077	-12.078	-12.079																																																																													
80	-12.079	-12.079	-12.079	-12.079	-12.080																																																																													
90	-12.078	-12.078	-12.077	-12.078	-12.079																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated ambient temperature.																																																																																		



COSEL		Testing Circuitry Figure A
Model	MGFW62412	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 0.25A (AVR 2) : 0 - 0.25A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	9	0	12.301	±238	±2.0
Minimum Voltage	75	9	0.25	11.826		


Object		-12V0.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	9	0	-12.327	±238	±2.0
Minimum Voltage	75	9	0.25	-11.852		



COSEL																									
Model	MGFW62412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.058</td></tr> <tr><td>0.5</td><td>12.062</td></tr> <tr><td>1.0</td><td>12.062</td></tr> <tr><td>2.0</td><td>12.062</td></tr> <tr><td>3.0</td><td>12.062</td></tr> <tr><td>4.0</td><td>12.062</td></tr> <tr><td>5.0</td><td>12.062</td></tr> <tr><td>6.0</td><td>12.062</td></tr> <tr><td>7.0</td><td>12.062</td></tr> <tr><td>8.0</td><td>12.062</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	12.058	0.5	12.062	1.0	12.062	2.0	12.062	3.0	12.062	4.0	12.062	5.0	12.062	6.0	12.062	7.0	12.062	8.0	12.062
Time since start [H]	Output Voltage [V]																								
0.0	12.058																								
0.5	12.062																								
1.0	12.062																								
2.0	12.062																								
3.0	12.062																								
4.0	12.062																								
5.0	12.062																								
6.0	12.062																								
7.0	12.062																								
8.0	12.062																								
Object	-12V0.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.076</td></tr> <tr><td>0.5</td><td>-12.079</td></tr> <tr><td>1.0</td><td>-12.079</td></tr> <tr><td>2.0</td><td>-12.079</td></tr> <tr><td>3.0</td><td>-12.080</td></tr> <tr><td>4.0</td><td>-12.080</td></tr> <tr><td>5.0</td><td>-12.079</td></tr> <tr><td>6.0</td><td>-12.080</td></tr> <tr><td>7.0</td><td>-12.080</td></tr> <tr><td>8.0</td><td>-12.079</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	-12.076	0.5	-12.079	1.0	-12.079	2.0	-12.079	3.0	-12.080	4.0	-12.080	5.0	-12.079	6.0	-12.080	7.0	-12.080	8.0	-12.079
Time since start [H]	Output Voltage [V]																								
0.0	-12.076																								
0.5	-12.079																								
1.0	-12.079																								
2.0	-12.079																								
3.0	-12.080																								
4.0	-12.080																								
5.0	-12.079																								
6.0	-12.080																								
7.0	-12.080																								
8.0	-12.079																								




Model		MGFW62412	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V0.25A		



2.Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.5	0.5	2.0	0.3	3.9
100 %		1.5	0.7	2.2	0.2	1.9

[ms]






Model	MGFW62412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.25A		



2.Values

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.5	0.5	2.0	0.3	4.6
100 %	1.5	0.7	2.2	0.2	2.2


[ms]





Model	MGFW62412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A


Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.6	7.7
-40	7.5	7.6
-20	7.5	7.6
0	7.5	7.6
25	7.4	7.5
80	7.3	7.4
90	7.3	7.4
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------



2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.6	7.7
-40	7.5	7.6
-20	7.5	7.6
0	7.5	7.6
25	7.4	7.5
80	7.3	7.4
90	7.3	7.4
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW62412
Item	Overcurrent Protection
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure A




2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
11.4	0.391	0.414	0.408	0.406	0.408
10.8	0.426	0.450	0.441	0.436	0.434
9.6	0.500	0.526	0.513	0.496	0.484
8.4	0.583	0.611	0.586	0.558	0.537
7.2	0.676	0.696	0.656	0.622	0.596
6.0	0.782	0.790	0.730	0.688	0.656
4.8	0.896	0.886	0.810	0.760	0.719
3.6	1.023	0.993	0.895	0.836	0.783
2.4	1.152	1.114	0.985	0.914	0.850
1.2	1.286	1.239	1.082	0.991	0.911
0.0	1.359	1.235	1.013	0.897	0.809
--	-	-	-	-	-

-12V: Rated Load Current

Object	-12V0.25A
--------	-----------



2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-11.4	0.391	0.417	0.408	0.407	0.409
-10.8	0.427	0.451	0.441	0.437	0.434
-9.6	0.502	0.527	0.514	0.499	0.483
-8.4	0.587	0.613	0.587	0.561	0.538
-7.2	0.682	0.702	0.657	0.625	0.598
-6.0	0.785	0.795	0.733	0.693	0.658
-4.8	0.902	0.893	0.813	0.764	0.722
-3.6	1.033	1.001	0.901	0.841	0.788
-2.4	1.162	1.125	0.993	0.921	0.856
-1.2	1.308	1.256	1.093	1.001	0.920
0.0	1.359	1.219	1.012	0.906	0.856
--	-	-	-	-	-

+12V: Rated Load Current

Note: Slanted line shows the range of the rated load current.



Model		MGFW62412		Temperature 25°C																																																																														
Item		Switching frequency (by Load Current)		Testing Circuitry Figure A																																																																														
Object		+/-12V0.25A																																																																																
1.Graph		<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · - Input Volt. 18V - · · ○ · · - · - Input Volt. 24V - - ◇ - - - Input Volt. 36V </p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>770</td><td>880</td><td>1020</td><td>1105</td><td>1230</td></tr> <tr><td>0.050</td><td>462</td><td>573</td><td>720</td><td>810</td><td>902</td></tr> <tr><td>0.100</td><td>331</td><td>424</td><td>558</td><td>644</td><td>739</td></tr> <tr><td>0.150</td><td>257</td><td>338</td><td>455</td><td>534</td><td>625</td></tr> <tr><td>0.200</td><td>208</td><td>280</td><td>384</td><td>456</td><td>542</td></tr> <tr><td>0.250</td><td>175</td><td>238</td><td>332</td><td>398</td><td>479</td></tr> <tr><td>0.275</td><td>162</td><td>221</td><td>310</td><td>375</td><td>452</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	770	880	1020	1105	1230	0.050	462	573	720	810	902	0.100	331	424	558	644	739	0.150	257	338	455	534	625	0.200	208	280	384	456	542	0.250	175	238	332	398	479	0.275	162	221	310	375	452	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.000	770	880	1020	1105	1230																																																																													
0.050	462	573	720	810	902																																																																													
0.100	331	424	558	644	739																																																																													
0.150	257	338	455	534	625																																																																													
0.200	208	280	384	456	542																																																																													
0.250	175	238	332	398	479																																																																													
0.275	162	221	310	375	452																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																																																		




Figure A




Figure B (Ripple and Ripple noise Characteristic)