

# TEST DATA OF MGFW64815

Regulated DC Power Supply  
December 20, 2016

Approved by :

Takayuki Fukuda

Design Manager

Prepared by :

Takaaki Sekiguchi

Takaaki Sekiguchi

Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Ratio) . . . . .	2
3.Input Power (by Load Ratio) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Ratio) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Switching frequency (by Load Current) . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)


**COSEL**

Model MGFW64815

Item Input Current (by Input Voltage)

Object \_\_\_\_\_

1.Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C  
 Testing Circuitry Figure A

2.Values


Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
16.0	0.004	0.004	0.003
16.2	0.003	0.004	0.003
16.4	0.003	0.004	0.004
16.6	0.003	0.003	0.003
16.8	0.012	0.208	0.417
17.0	0.013	0.206	0.412
18.0	0.012	0.194	0.388
24.0	0.010	0.145	0.286
36.0	0.007	0.097	0.191
48.0	0.006	0.074	0.143
60.0	0.005	0.060	0.115
76.0	0.004	0.048	0.092
80.0	0.004	0.046	0.087
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model MGFW64815

Item Input Current (by Load Ratio)

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Load Ratio [%]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.012	0.010	0.007	0.006	0.004
20	0.084	0.063	0.044	0.033	0.022
40	0.157	0.117	0.080	0.060	0.040
60	0.230	0.173	0.116	0.088	0.057
80	0.310	0.229	0.153	0.114	0.074
100	0.388	0.286	0.191	0.143	0.092
110	0.428	0.315	0.208	0.157	0.100
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

**COSEL**

Model MGFW64815

Item Input Power (by Load Ratio)

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Ratio [%]	Input Power [W]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.22	0.24	0.27	0.27	0.26
20	1.50	1.52	1.57	1.60	1.69
40	2.82	2.82	2.86	2.90	3.01
60	4.15	4.14	4.17	4.20	4.33
80	5.53	5.48	5.50	5.49	5.62
100	6.91	6.83	6.81	6.84	6.96
110	7.63	7.52	7.48	7.52	7.61
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


**COSEL**

Model MGFW64815

Item Efficiency (by Input Voltage)

Object \_\_\_\_\_

## 1.Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	86.8	87.0
18	86.7	87.3
24	86.5	88.3
30	86.2	88.7
36	85.7	88.7
48	84.8	88.5
60	83.2	87.7
76	81.5	86.7
80	81.1	86.3

**COSEL**

Model MGFW64815

Item Efficiency (by Load Ratio)

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Efficiency [%]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0	-	-	-	-	-
20	79.9	79.1	77.2	75.3	70.9
40	85.6	86.0	84.2	82.8	79.9
60	87.3	87.5	86.8	86.1	83.7
80	87.4	88.1	87.7	87.8	85.8
100	87.3	88.3	88.7	88.5	86.7
110	87.0	88.1	88.7	88.3	87.3
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

**COSEL**

Model	MGFW64815	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+15V0.2A																																		
1.Graph		2.Values																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>15.144</td><td>15.055</td></tr> <tr><td>18</td><td>15.141</td><td>15.055</td></tr> <tr><td>24</td><td>15.135</td><td>15.058</td></tr> <tr><td>30</td><td>15.132</td><td>15.059</td></tr> <tr><td>36</td><td>15.129</td><td>15.060</td></tr> <tr><td>48</td><td>15.125</td><td>15.060</td></tr> <tr><td>60</td><td>15.124</td><td>15.060</td></tr> <tr><td>76</td><td>15.122</td><td>15.060</td></tr> <tr><td>80</td><td>15.122</td><td>15.060</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	15.144	15.055	18	15.141	15.055	24	15.135	15.058	30	15.132	15.059	36	15.129	15.060	48	15.125	15.060	60	15.124	15.060	76	15.122	15.060	80	15.122	15.060
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	15.144	15.055																																	
18	15.141	15.055																																	
24	15.135	15.058																																	
30	15.132	15.059																																	
36	15.129	15.060																																	
48	15.125	15.060																																	
60	15.124	15.060																																	
76	15.122	15.060																																	
80	15.122	15.060																																	
Object		2.Values																																	
1.Graph		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-15.180</td><td>-15.091</td></tr> <tr><td>18</td><td>-15.176</td><td>-15.091</td></tr> <tr><td>24</td><td>-15.166</td><td>-15.089</td></tr> <tr><td>30</td><td>-15.161</td><td>-15.087</td></tr> <tr><td>36</td><td>-15.158</td><td>-15.087</td></tr> <tr><td>48</td><td>-15.154</td><td>-15.087</td></tr> <tr><td>60</td><td>-15.151</td><td>-15.087</td></tr> <tr><td>76</td><td>-15.149</td><td>-15.086</td></tr> <tr><td>80</td><td>-15.149</td><td>-15.086</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-15.180	-15.091	18	-15.176	-15.091	24	-15.166	-15.089	30	-15.161	-15.087	36	-15.158	-15.087	48	-15.154	-15.087	60	-15.151	-15.087	76	-15.149	-15.086	80	-15.149	-15.086
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-15.180	-15.091																																	
18	-15.176	-15.091																																	
24	-15.166	-15.089																																	
30	-15.161	-15.087																																	
36	-15.158	-15.087																																	
48	-15.154	-15.087																																	
60	-15.151	-15.087																																	
76	-15.149	-15.086																																	
80	-15.149	-15.086																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

**COSEL**

Model	MGFW64815	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+15V0.2A																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.311</td><td>15.288</td><td>15.266</td><td>15.255</td><td>15.243</td></tr> <tr><td>0.04</td><td>15.216</td><td>15.204</td><td>15.190</td><td>15.183</td><td>15.176</td></tr> <tr><td>0.08</td><td>15.167</td><td>15.159</td><td>15.150</td><td>15.145</td><td>15.140</td></tr> <tr><td>0.12</td><td>15.127</td><td>15.122</td><td>15.117</td><td>15.114</td><td>15.111</td></tr> <tr><td>0.16</td><td>15.091</td><td>15.090</td><td>15.087</td><td>15.086</td><td>15.085</td></tr> <tr><td>0.20</td><td>15.055</td><td>15.058</td><td>15.060</td><td>15.060</td><td>15.060</td></tr> <tr><td>0.22</td><td>15.039</td><td>15.043</td><td>15.047</td><td>15.048</td><td>15.048</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	15.311	15.288	15.266	15.255	15.243	0.04	15.216	15.204	15.190	15.183	15.176	0.08	15.167	15.159	15.150	15.145	15.140	0.12	15.127	15.122	15.117	15.114	15.111	0.16	15.091	15.090	15.087	15.086	15.085	0.20	15.055	15.058	15.060	15.060	15.060	0.22	15.039	15.043	15.047	15.048	15.048	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	15.311	15.288	15.266	15.255	15.243																																																																															
0.04	15.216	15.204	15.190	15.183	15.176																																																																															
0.08	15.167	15.159	15.150	15.145	15.140																																																																															
0.12	15.127	15.122	15.117	15.114	15.111																																																																															
0.16	15.091	15.090	15.087	15.086	15.085																																																																															
0.20	15.055	15.058	15.060	15.060	15.060																																																																															
0.22	15.039	15.043	15.047	15.048	15.048																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-15V0.2A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.345</td><td>-15.318</td><td>-15.293</td><td>-15.281</td><td>-15.268</td></tr> <tr><td>0.04</td><td>-15.250</td><td>-15.233</td><td>-15.217</td><td>-15.210</td><td>-15.201</td></tr> <tr><td>0.08</td><td>-15.198</td><td>-15.187</td><td>-15.176</td><td>-15.171</td><td>-15.166</td></tr> <tr><td>0.12</td><td>-15.158</td><td>-15.150</td><td>-15.143</td><td>-15.140</td><td>-15.136</td></tr> <tr><td>0.16</td><td>-15.123</td><td>-15.118</td><td>-15.113</td><td>-15.112</td><td>-15.110</td></tr> <tr><td>0.20</td><td>-15.091</td><td>-15.089</td><td>-15.087</td><td>-15.087</td><td>-15.086</td></tr> <tr><td>0.22</td><td>-15.075</td><td>-15.074</td><td>-15.074</td><td>-15.074</td><td>-15.075</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-15.345	-15.318	-15.293	-15.281	-15.268	0.04	-15.250	-15.233	-15.217	-15.210	-15.201	0.08	-15.198	-15.187	-15.176	-15.171	-15.166	0.12	-15.158	-15.150	-15.143	-15.140	-15.136	0.16	-15.123	-15.118	-15.113	-15.112	-15.110	0.20	-15.091	-15.089	-15.087	-15.087	-15.086	0.22	-15.075	-15.074	-15.074	-15.074	-15.075	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	-15.345	-15.318	-15.293	-15.281	-15.268																																																																															
0.04	-15.250	-15.233	-15.217	-15.210	-15.201																																																																															
0.08	-15.198	-15.187	-15.176	-15.171	-15.166																																																																															
0.12	-15.158	-15.150	-15.143	-15.140	-15.136																																																																															
0.16	-15.123	-15.118	-15.113	-15.112	-15.110																																																																															
0.20	-15.091	-15.089	-15.087	-15.087	-15.086																																																																															
0.22	-15.075	-15.074	-15.074	-15.074	-15.075																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Note:	Slanted line shows the range of the rated load current.																																																																																			

**COSEL**


Model	MGFW64815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.2A		


Input Volt. 48 V

-15V:rated load current.

Cycle 100 ms

t<sub>1</sub>,t<sub>2</sub> = 100 μ s

Load Current  




Min.Load (0A)↔  
Load 100% (0.2A)

200 mV/div

4 ms/div

4 ms/div

Min.Load (0A)↔  
Load 50% (0.1A)

200 mV/div

4 ms/div

4 ms/div

Load 50% (0.1A)↔  
Load 100% (0.2A)

200 mV/div

4 ms/div

4 ms/div

**COSEL**

Model	MGFW64815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V0.2A		

Input Volt. 48 V

+15V:rated load current.


Cycle 100 ms

t<sub>1</sub>,t<sub>2</sub> = 100 μ s


Load Current  
t<sub>1</sub>

t<sub>2</sub>


Min.Load (0A)↔  
Load 100% (0.2A)




4 ms/div




Min.Load (0A)↔  
Load 50% (0.1A)




4 ms/div



Load 50% (0.1A)↔  
Load 100% (0.2A)



4 ms/div



**COSEL**

Model	MGFW64815																																							
Item	Ripple Voltage (by Load Current)	Temperature      25°C Testing Circuitry      Figure B																																						
Object	+15V0.2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>10</td><td>5</td></tr> <tr><td>0.16</td><td>15</td><td>5</td></tr> <tr><td>0.20</td><td>25</td><td>5</td></tr> <tr><td>0.22</td><td>30</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	10	5	0.16	15	5	0.20	25	5	0.22	30	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	5																																						
0.04	5	5																																						
0.08	5	5																																						
0.12	10	5																																						
0.16	15	5																																						
0.20	25	5																																						
0.22	30	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope.      Ripple Voltage is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

**COSEL**

Model	MGFW64815																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>10</td><td>5</td></tr> <tr><td>0.16</td><td>15</td><td>5</td></tr> <tr><td>0.20</td><td>25</td><td>5</td></tr> <tr><td>0.22</td><td>30</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	10	5	0.16	15	5	0.20	25	5	0.22	30	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	5																																						
0.04	5	5																																						
0.08	5	5																																						
0.12	10	5																																						
0.16	15	5																																						
0.20	25	5																																						
0.22	30	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope.      Ripple Voltage is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

**COSEL**

Model	MGFW64815																																							
Item	Ripple-Noise	Temperature      25°C Testing Circuitry      Figure B																																						
Object	+15V0.2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>10</td></tr> <tr><td>0.04</td><td>5</td><td>10</td></tr> <tr><td>0.08</td><td>10</td><td>10</td></tr> <tr><td>0.12</td><td>10</td><td>10</td></tr> <tr><td>0.16</td><td>20</td><td>10</td></tr> <tr><td>0.20</td><td>25</td><td>10</td></tr> <tr><td>0.22</td><td>30</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	10	0.04	5	10	0.08	10	10	0.12	10	10	0.16	20	10	0.20	25	10	0.22	30	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	10																																						
0.04	5	10																																						
0.08	10	10																																						
0.12	10	10																																						
0.16	20	10																																						
0.20	25	10																																						
0.22	30	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope.      Ripple-Noise is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								


**COSEL**

Model	MGFW64815																																							
Item	Ripple-Noise	Temperature      25°C Testing Circuitry      Figure B																																						
Object	-15V0.2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>10</td></tr> <tr><td>0.04</td><td>5</td><td>10</td></tr> <tr><td>0.08</td><td>10</td><td>10</td></tr> <tr><td>0.12</td><td>10</td><td>10</td></tr> <tr><td>0.16</td><td>20</td><td>10</td></tr> <tr><td>0.20</td><td>25</td><td>10</td></tr> <tr><td>0.22</td><td>30</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	5	10	0.04	5	10	0.08	10	10	0.12	10	10	0.16	20	10	0.20	25	10	0.22	30	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	5	10																																						
0.04	5	10																																						
0.08	10	10																																						
0.12	10	10																																						
0.16	20	10																																						
0.20	25	10																																						
0.22	30	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope.      Ripple-Noise is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

**COSSEL**

Model	MGFW64815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
75	5	5
85	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
75	5	5
85	5	5
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model MGFW64815

Item Ambient Temperature Drift

Object +15V0.2A




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	14.947	14.949	14.951	14.951	14.950
-40	14.986	14.988	14.990	14.990	14.989
-20	15.018	15.020	15.021	15.022	15.021
0	15.041	15.043	15.045	15.045	15.044
25	15.055	15.058	15.060	15.060	15.060
75	15.057	15.060	15.062	15.064	15.065
85	15.055	15.058	15.060	15.062	15.063
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-15V: Rated Load Current



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	-14.969	-14.970	-14.970	-14.970	-14.971
-40	-15.012	-15.012	-15.011	-15.012	-15.012
-20	-15.046	-15.046	-15.045	-15.045	-15.046
0	-15.071	-15.071	-15.070	-15.070	-15.070
25	-15.091	-15.089	-15.087	-15.087	-15.086
75	-15.095	-15.093	-15.091	-15.091	-15.090
85	-15.093	-15.092	-15.090	-15.089	-15.089
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

+15V: Rated Load Current

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW64815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 75°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 0.2A (AVR 2) : 0 - 0.2A

\* Output Voltage Accuracy =  $\pm$ (Maximum of Output Voltage - Minimum of Output Voltage) / 2



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	18	0	15.329	±280	±1.9
Minimum Voltage	-40	18	0.2	14.769		

Object	-15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	18	0	-15.363	±281	±1.9
Minimum Voltage	-40	18	0.2	-14.802		


**COSEL**

Model	MGFW64815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V0.2A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.054</td></tr> <tr><td>0.5</td><td>15.060</td></tr> <tr><td>1.0</td><td>15.060</td></tr> <tr><td>2.0</td><td>15.060</td></tr> <tr><td>3.0</td><td>15.060</td></tr> <tr><td>4.0</td><td>15.060</td></tr> <tr><td>5.0</td><td>15.059</td></tr> <tr><td>6.0</td><td>15.060</td></tr> <tr><td>7.0</td><td>15.060</td></tr> <tr><td>8.0</td><td>15.060</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	15.054	0.5	15.060	1.0	15.060	2.0	15.060	3.0	15.060	4.0	15.060	5.0	15.059	6.0	15.060	7.0	15.060	8.0	15.060
Time since start [H]	Output Voltage [V]																								
0.0	15.054																								
0.5	15.060																								
1.0	15.060																								
2.0	15.060																								
3.0	15.060																								
4.0	15.060																								
5.0	15.059																								
6.0	15.060																								
7.0	15.060																								
8.0	15.060																								
Object -15V0.2A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.083</td></tr> <tr><td>0.5</td><td>-15.089</td></tr> <tr><td>1.0</td><td>-15.089</td></tr> <tr><td>2.0</td><td>-15.089</td></tr> <tr><td>3.0</td><td>-15.089</td></tr> <tr><td>4.0</td><td>-15.089</td></tr> <tr><td>5.0</td><td>-15.089</td></tr> <tr><td>6.0</td><td>-15.089</td></tr> <tr><td>7.0</td><td>-15.089</td></tr> <tr><td>8.0</td><td>-15.089</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-15.083	0.5	-15.089	1.0	-15.089	2.0	-15.089	3.0	-15.089	4.0	-15.089	5.0	-15.089	6.0	-15.089	7.0	-15.089	8.0	-15.089
Time since start [H]	Output Voltage [V]																								
0.0	-15.083																								
0.5	-15.089																								
1.0	-15.089																								
2.0	-15.089																								
3.0	-15.089																								
4.0	-15.089																								
5.0	-15.089																								
6.0	-15.089																								
7.0	-15.089																								
8.0	-15.089																								

**COSEL**


Model	MGFW64815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.2A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.5	0.6	2.1	1.3	5.0	
100 %		1.5	0.7	2.2	1.2	2.5	



**COSEL**


Model	MGFW64815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V0.2A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.5	0.6	2.1	1.4	5.9	
100 %		1.5	0.7	2.2	1.2	2.8	



**COSEL**

Model	MGFW64815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.1	15.2
-40	15.0	15.1
-20	15.0	15.1
0	14.9	15.0
25	14.8	14.9
75	14.4	14.5
85	14.0	13.9
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.1	15.2
-40	15.0	15.1
-20	15.0	15.1
0	14.9	15.0
25	14.8	14.9
75	14.4	14.5
85	14.0	13.9
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFW64815	Temperature Testing Circuitry	25°C Figure A																																																																																		
Item	Overcurrent Protection																																																																																				
Object	+15V0.2A																																																																																				
1.Graph		2.Values																																																																																			
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>0.313</td><td>0.325</td><td>0.326</td><td>0.340</td><td>0.369</td></tr> <tr><td>13.5</td><td>0.344</td><td>0.355</td><td>0.355</td><td>0.369</td><td>0.393</td></tr> <tr><td>12.0</td><td>0.411</td><td>0.419</td><td>0.420</td><td>0.426</td><td>0.440</td></tr> <tr><td>10.5</td><td>0.488</td><td>0.491</td><td>0.488</td><td>0.485</td><td>0.492</td></tr> <tr><td>9.0</td><td>0.572</td><td>0.568</td><td>0.552</td><td>0.548</td><td>0.552</td></tr> <tr><td>7.5</td><td>0.665</td><td>0.654</td><td>0.622</td><td>0.612</td><td>0.610</td></tr> <tr><td>6.0</td><td>0.756</td><td>0.741</td><td>0.699</td><td>0.683</td><td>0.672</td></tr> <tr><td>4.5</td><td>0.846</td><td>0.845</td><td>0.780</td><td>0.757</td><td>0.737</td></tr> <tr><td>3.0</td><td>0.978</td><td>0.958</td><td>0.869</td><td>0.836</td><td>0.800</td></tr> <tr><td>1.5</td><td>1.090</td><td>1.042</td><td>0.940</td><td>0.895</td><td>0.847</td></tr> <tr><td>0.0</td><td>1.124</td><td>1.026</td><td>0.888</td><td>0.829</td><td>0.768</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	14.3	0.313	0.325	0.326	0.340	0.369	13.5	0.344	0.355	0.355	0.369	0.393	12.0	0.411	0.419	0.420	0.426	0.440	10.5	0.488	0.491	0.488	0.485	0.492	9.0	0.572	0.568	0.552	0.548	0.552	7.5	0.665	0.654	0.622	0.612	0.610	6.0	0.756	0.741	0.699	0.683	0.672	4.5	0.846	0.845	0.780	0.757	0.737	3.0	0.978	0.958	0.869	0.836	0.800	1.5	1.090	1.042	0.940	0.895	0.847	0.0	1.124	1.026	0.888	0.829	0.768	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																
14.3	0.313	0.325	0.326	0.340	0.369																																																																																
13.5	0.344	0.355	0.355	0.369	0.393																																																																																
12.0	0.411	0.419	0.420	0.426	0.440																																																																																
10.5	0.488	0.491	0.488	0.485	0.492																																																																																
9.0	0.572	0.568	0.552	0.548	0.552																																																																																
7.5	0.665	0.654	0.622	0.612	0.610																																																																																
6.0	0.756	0.741	0.699	0.683	0.672																																																																																
4.5	0.846	0.845	0.780	0.757	0.737																																																																																
3.0	0.978	0.958	0.869	0.836	0.800																																																																																
1.5	1.090	1.042	0.940	0.895	0.847																																																																																
0.0	1.124	1.026	0.888	0.829	0.768																																																																																
--	-	-	-	-	-																																																																																
		-15V : Rated Load Current																																																																																			
Object		2.Values																																																																																			
<p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-14.3</td><td>0.315</td><td>0.327</td><td>0.327</td><td>0.342</td><td>0.371</td></tr> <tr><td>-13.5</td><td>0.347</td><td>0.356</td><td>0.356</td><td>0.370</td><td>0.395</td></tr> <tr><td>-12.0</td><td>0.416</td><td>0.420</td><td>0.421</td><td>0.429</td><td>0.441</td></tr> <tr><td>-10.5</td><td>0.492</td><td>0.493</td><td>0.489</td><td>0.489</td><td>0.494</td></tr> <tr><td>-9.0</td><td>0.575</td><td>0.571</td><td>0.554</td><td>0.550</td><td>0.554</td></tr> <tr><td>-7.5</td><td>0.672</td><td>0.656</td><td>0.626</td><td>0.617</td><td>0.613</td></tr> <tr><td>-6.0</td><td>0.753</td><td>0.748</td><td>0.702</td><td>0.686</td><td>0.675</td></tr> <tr><td>-4.5</td><td>0.856</td><td>0.855</td><td>0.784</td><td>0.761</td><td>0.740</td></tr> <tr><td>-3.0</td><td>0.993</td><td>0.965</td><td>0.878</td><td>0.843</td><td>0.806</td></tr> <tr><td>-1.5</td><td>1.120</td><td>1.062</td><td>0.953</td><td>0.905</td><td>0.856</td></tr> <tr><td>0.0</td><td>1.163</td><td>1.049</td><td>0.906</td><td>0.853</td><td>0.790</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-14.3	0.315	0.327	0.327	0.342	0.371	-13.5	0.347	0.356	0.356	0.370	0.395	-12.0	0.416	0.420	0.421	0.429	0.441	-10.5	0.492	0.493	0.489	0.489	0.494	-9.0	0.575	0.571	0.554	0.550	0.554	-7.5	0.672	0.656	0.626	0.617	0.613	-6.0	0.753	0.748	0.702	0.686	0.675	-4.5	0.856	0.855	0.784	0.761	0.740	-3.0	0.993	0.965	0.878	0.843	0.806	-1.5	1.120	1.062	0.953	0.905	0.856	0.0	1.163	1.049	0.906	0.853	0.790	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																
-14.3	0.315	0.327	0.327	0.342	0.371																																																																																
-13.5	0.347	0.356	0.356	0.370	0.395																																																																																
-12.0	0.416	0.420	0.421	0.429	0.441																																																																																
-10.5	0.492	0.493	0.489	0.489	0.494																																																																																
-9.0	0.575	0.571	0.554	0.550	0.554																																																																																
-7.5	0.672	0.656	0.626	0.617	0.613																																																																																
-6.0	0.753	0.748	0.702	0.686	0.675																																																																																
-4.5	0.856	0.855	0.784	0.761	0.740																																																																																
-3.0	0.993	0.965	0.878	0.843	0.806																																																																																
-1.5	1.120	1.062	0.953	0.905	0.856																																																																																
0.0	1.163	1.049	0.906	0.853	0.790																																																																																
--	-	-	-	-	-																																																																																
		+15V : Rated Load Current																																																																																			
Note: Slanted line shows the range of the rated load current.																																																																																					

**COSEL**

Model	MGFW64815
Item	Switching frequency (by Load Current)
Object	+/-15V0.2A


 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Load Current [A]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.00	468	541	623	671	714
0.04	329	398	489	545	610
0.08	252	316	402	457	524
0.12	205	261	341	393	459
0.16	171	222	296	346	410
0.20	147	193	261	308	370
0.22	138	182	247	292	352
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: Slanted line shows the range of the rated load current.

When load current is low, MG operates intermittently, so switching frequency would not become constant.




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)