

# TEST DATA OF MGFW804815

Regulated DC Power Supply  
April 12, 2019

Approved by : Junichi Hatagishi  
Junichi Hatagishi                                  Design Manager

Prepared by : Satoshi Kinoshita  
Satoshi Kinoshita                                  Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Switching frequency (by Load Current) . . . . .	23
20.Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	MGFW804815
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.00	0	0	0
15.20	0.001	0.001	-※
15.60	0.001	0.001	-※
16.00	0.001	0.001	-※
16.40	0.001	0.001	-※
16.80	0.045	2.560	-※
17.20	0.044	2.496	-※
17.60	0.044	2.436	-※
18.00	0.043	2.379	-※
23.68	0.035	1.807	-※
24.00	0.035	1.783	3.635
36.00	0.028	1.185	2.391
48.00	0.026	0.897	1.793
76.00	0.012	0.582	1.142
80.00	0.012	0.556	1.087
--	-	-	-
--	-	-	-
--	-	-	-

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

**COSEL**

Model	MGFW804815																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.043</td> <td>0.035</td> <td>0.028</td> <td>0.026</td> <td>0.012</td> </tr> <tr> <td>20</td> <td>0.975</td> <td>0.733</td> <td>0.492</td> <td>0.375</td> <td>0.249</td> </tr> <tr> <td>40</td> <td>1.914</td> <td>1.441</td> <td>0.963</td> <td>0.727</td> <td>0.471</td> </tr> <tr> <td>60</td> <td>2.873</td> <td>2.149</td> <td>1.431</td> <td>1.078</td> <td>0.694</td> </tr> <tr> <td>80</td> <td>-※1</td> <td>2.876</td> <td>1.908</td> <td>1.432</td> <td>0.915</td> </tr> <tr> <td>100</td> <td>-※1</td> <td>-※2</td> <td>2.391</td> <td>1.793</td> <td>1.142</td> </tr> <tr> <td>110</td> <td>-※1</td> <td>-※2</td> <td>2.630</td> <td>1.970</td> <td>1.252</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ratio [%]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.043	0.035	0.028	0.026	0.012	20	0.975	0.733	0.492	0.375	0.249	40	1.914	1.441	0.963	0.727	0.471	60	2.873	2.149	1.431	1.078	0.694	80	-※1	2.876	1.908	1.432	0.915	100	-※1	-※2	2.391	1.793	1.142	110	-※1	-※2	2.630	1.970	1.252	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.043	0.035	0.028	0.026	0.012																																																																													
20	0.975	0.733	0.492	0.375	0.249																																																																													
40	1.914	1.441	0.963	0.727	0.471																																																																													
60	2.873	2.149	1.431	1.078	0.694																																																																													
80	-※1	2.876	1.908	1.432	0.915																																																																													
100	-※1	-※2	2.391	1.793	1.142																																																																													
110	-※1	-※2	2.630	1.970	1.252																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**


Model	MGFW804815																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18V</th> <th>24V</th> <th>36V</th> <th>48V</th> <th>76V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.78</td><td>0.84</td><td>1.01</td><td>1.26</td><td>0.95</td></tr> <tr><td>20</td><td>17.60</td><td>17.62</td><td>17.71</td><td>18.03</td><td>18.91</td></tr> <tr><td>40</td><td>34.59</td><td>34.67</td><td>34.72</td><td>34.91</td><td>35.82</td></tr> <tr><td>60</td><td>51.92</td><td>51.66</td><td>51.58</td><td>51.78</td><td>52.80</td></tr> <tr><td>80</td><td>-※1</td><td>69.07</td><td>68.72</td><td>68.80</td><td>69.64</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>86.11</td><td>86.02</td><td>86.71</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>94.89</td><td>94.72</td><td>95.31</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	18V	24V	36V	48V	76V	0	0.78	0.84	1.01	1.26	0.95	20	17.60	17.62	17.71	18.03	18.91	40	34.59	34.67	34.72	34.91	35.82	60	51.92	51.66	51.58	51.78	52.80	80	-※1	69.07	68.72	68.80	69.64	100	-※1	-※2	86.11	86.02	86.71	110	-※1	-※2	94.89	94.72	95.31	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	18V	24V	36V	48V	76V																																																																													
0	0.78	0.84	1.01	1.26	0.95																																																																													
20	17.60	17.62	17.71	18.03	18.91																																																																													
40	34.59	34.67	34.72	34.91	35.82																																																																													
60	51.92	51.66	51.58	51.78	52.80																																																																													
80	-※1	69.07	68.72	68.80	69.64																																																																													
100	-※1	-※2	86.11	86.02	86.71																																																																													
110	-※1	-※2	94.89	94.72	95.31																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.78</td><td>0.84</td><td>1.01</td><td>1.26</td><td>0.95</td></tr> <tr><td>20</td><td>17.60</td><td>17.62</td><td>17.71</td><td>18.03</td><td>18.91</td></tr> <tr><td>40</td><td>34.59</td><td>34.67</td><td>34.72</td><td>34.91</td><td>35.82</td></tr> <tr><td>60</td><td>51.92</td><td>51.66</td><td>51.58</td><td>51.78</td><td>52.80</td></tr> <tr><td>80</td><td>-※1</td><td>69.07</td><td>68.72</td><td>68.80</td><td>69.64</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>86.11</td><td>86.02</td><td>86.71</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>94.89</td><td>94.72</td><td>95.31</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.78	0.84	1.01	1.26	0.95	20	17.60	17.62	17.71	18.03	18.91	40	34.59	34.67	34.72	34.91	35.82	60	51.92	51.66	51.58	51.78	52.80	80	-※1	69.07	68.72	68.80	69.64	100	-※1	-※2	86.11	86.02	86.71	110	-※1	-※2	94.89	94.72	95.31	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.78	0.84	1.01	1.26	0.95																																																																													
20	17.60	17.62	17.71	18.03	18.91																																																																													
40	34.59	34.67	34.72	34.91	35.82																																																																													
60	51.92	51.66	51.58	51.78	52.80																																																																													
80	-※1	69.07	68.72	68.80	69.64																																																																													
100	-※1	-※2	86.11	86.02	86.71																																																																													
110	-※1	-※2	94.89	94.72	95.31																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**

Model	MGFW804815
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	93.6	93.0 ※1
18	93.6	93.2 ※1
24	94.0	93.6 ※2
30	94.0	93.7
36	93.9	94.0
48	93.5	94.1
60	92.6	93.8
76	90.9	93.3
80	90.4	93.1

※1: Load 70%

※2: Load 80%

Note: Slanted line shows the range of the rated input voltage.


**COSEL**

Model	MGFW804815																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18V</th> <th>24V</th> <th>36V</th> <th>48V</th> <th>76V</th> </tr> </thead> <tbody> <tr><td>20</td><td>92.0</td><td>92.0</td><td>92.0</td><td>92.0</td><td>85.0</td></tr> <tr><td>40</td><td>93.0</td><td>93.0</td><td>93.0</td><td>93.0</td><td>91.0</td></tr> <tr><td>60</td><td>93.5</td><td>93.5</td><td>93.5</td><td>93.5</td><td>92.0</td></tr> <tr><td>80</td><td>93.8</td><td>93.8</td><td>93.8</td><td>93.8</td><td>92.5</td></tr> <tr><td>100</td><td>93.8</td><td>93.8</td><td>93.8</td><td>93.8</td><td>92.5</td></tr> <tr><td>120</td><td>93.8</td><td>93.8</td><td>93.8</td><td>93.8</td><td>92.5</td></tr> </tbody> </table>					Load Ratio [%]	18V	24V	36V	48V	76V	20	92.0	92.0	92.0	92.0	85.0	40	93.0	93.0	93.0	93.0	91.0	60	93.5	93.5	93.5	93.5	92.0	80	93.8	93.8	93.8	93.8	92.5	100	93.8	93.8	93.8	93.8	92.5	120	93.8	93.8	93.8	93.8	92.5																																			
Load Ratio [%]	18V	24V	36V	48V	76V																																																																													
20	92.0	92.0	92.0	92.0	85.0																																																																													
40	93.0	93.0	93.0	93.0	91.0																																																																													
60	93.5	93.5	93.5	93.5	92.0																																																																													
80	93.8	93.8	93.8	93.8	92.5																																																																													
100	93.8	93.8	93.8	93.8	92.5																																																																													
120	93.8	93.8	93.8	93.8	92.5																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>91.9</td><td>91.9</td><td>91.3</td><td>89.8</td><td>85.5</td></tr> <tr><td>40</td><td>93.6</td><td>93.4</td><td>93.2</td><td>92.7</td><td>90.4</td></tr> <tr><td>60</td><td>93.5</td><td>94.0</td><td>94.1</td><td>93.8</td><td>91.9</td></tr> <tr><td>80</td><td>-※1</td><td>93.7</td><td>94.2</td><td>94.1</td><td>93.0</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>94.0</td><td>94.1</td><td>93.3</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>93.8</td><td>93.9</td><td>93.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0	-	-	-	-	-	20	91.9	91.9	91.3	89.8	85.5	40	93.6	93.4	93.2	92.7	90.4	60	93.5	94.0	94.1	93.8	91.9	80	-※1	93.7	94.2	94.1	93.0	100	-※1	-※2	94.0	94.1	93.3	110	-※1	-※2	93.8	93.9	93.4	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	-	-	-	-	-																																																																													
20	91.9	91.9	91.3	89.8	85.5																																																																													
40	93.6	93.4	93.2	92.7	90.4																																																																													
60	93.5	94.0	94.1	93.8	91.9																																																																													
80	-※1	93.7	94.2	94.1	93.0																																																																													
100	-※1	-※2	94.0	94.1	93.3																																																																													
110	-※1	-※2	93.8	93.9	93.4																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

Model	MGFW804815
Item	Line Regulation
Object	+15V2.7A

## 1.Graph

Temperature 25°C  
Testing Circuitry Figure A


## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	15.061	-
18	15.059	-
24	15.049	-
30	15.046	14.988
36	15.042	14.990
48	15.039	14.992
60	15.037	14.993
76	15.036	14.994
80	15.036	14.994

-15V: Rated Load Current

Object	-15V2.7A
--------	----------

## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-15.097	-
18	-15.091	-
24	-15.072	-
30	-15.061	-15.006
36	-15.054	-15.005
48	-15.048	-15.002
60	-15.045	-15.000
76	-15.043	-15.000
80	-15.043	-15.000

+15V: Rated Load Current

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MGFW804815																																																																																	
Item	Load Regulation																																																																																	
Object	+15V2.7A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> <li>18V</li> <li>24V</li> <li>36V</li> <li>48V</li> <li>76V</li> </ul>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.089</td><td>15.093</td><td>15.111</td><td>15.115</td><td>15.106</td></tr> <tr><td>0.5</td><td>15.050</td><td>15.053</td><td>15.073</td><td>15.070</td><td>15.067</td></tr> <tr><td>1.1</td><td>15.027</td><td>15.034</td><td>15.053</td><td>15.049</td><td>15.046</td></tr> <tr><td>1.6</td><td>14.999</td><td>15.010</td><td>15.033</td><td>15.032</td><td>15.030</td></tr> <tr><td>1.9</td><td>14.984</td><td>14.998</td><td>15.022</td><td>15.021</td><td>15.020</td></tr> <tr><td>2.2</td><td>-※1</td><td>14.985</td><td>15.010</td><td>15.009</td><td>15.010</td></tr> <tr><td>2.7</td><td>-※1</td><td>-※2</td><td>14.989</td><td>14.991</td><td>14.994</td></tr> <tr><td>3.0</td><td>-※1</td><td>-※2</td><td>14.976</td><td>14.980</td><td>14.983</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	15.089	15.093	15.111	15.115	15.106	0.5	15.050	15.053	15.073	15.070	15.067	1.1	15.027	15.034	15.053	15.049	15.046	1.6	14.999	15.010	15.033	15.032	15.030	1.9	14.984	14.998	15.022	15.021	15.020	2.2	-※1	14.985	15.010	15.009	15.010	2.7	-※1	-※2	14.989	14.991	14.994	3.0	-※1	-※2	14.976	14.980	14.983	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	15.089	15.093	15.111	15.115	15.106																																																																													
0.5	15.050	15.053	15.073	15.070	15.067																																																																													
1.1	15.027	15.034	15.053	15.049	15.046																																																																													
1.6	14.999	15.010	15.033	15.032	15.030																																																																													
1.9	14.984	14.998	15.022	15.021	15.020																																																																													
2.2	-※1	14.985	15.010	15.009	15.010																																																																													
2.7	-※1	-※2	14.989	14.991	14.994																																																																													
3.0	-※1	-※2	14.976	14.980	14.983																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Object	-15V2.7A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> <li>18V</li> <li>24V</li> <li>36V</li> <li>48V</li> <li>76V</li> </ul>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.102</td><td>-15.106</td><td>-15.127</td><td>-15.128</td><td>-15.127</td></tr> <tr><td>0.5</td><td>-15.057</td><td>-15.058</td><td>-15.080</td><td>-15.076</td><td>-15.077</td></tr> <tr><td>1.1</td><td>-15.040</td><td>-15.041</td><td>-15.060</td><td>-15.055</td><td>-15.052</td></tr> <tr><td>1.6</td><td>-15.016</td><td>-15.023</td><td>-15.045</td><td>-15.039</td><td>-15.035</td></tr> <tr><td>1.9</td><td>-15.003</td><td>-15.012</td><td>-15.034</td><td>-15.028</td><td>-15.025</td></tr> <tr><td>2.2</td><td>-※1</td><td>-15.000</td><td>-15.023</td><td>-15.019</td><td>-15.016</td></tr> <tr><td>2.7</td><td>-※1</td><td>-※2</td><td>-15.004</td><td>-15.001</td><td>-15.000</td></tr> <tr><td>3.0</td><td>-※1</td><td>-※2</td><td>-14.992</td><td>-14.991</td><td>-14.990</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	-15.102	-15.106	-15.127	-15.128	-15.127	0.5	-15.057	-15.058	-15.080	-15.076	-15.077	1.1	-15.040	-15.041	-15.060	-15.055	-15.052	1.6	-15.016	-15.023	-15.045	-15.039	-15.035	1.9	-15.003	-15.012	-15.034	-15.028	-15.025	2.2	-※1	-15.000	-15.023	-15.019	-15.016	2.7	-※1	-※2	-15.004	-15.001	-15.000	3.0	-※1	-※2	-14.992	-14.991	-14.990	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	-15.102	-15.106	-15.127	-15.128	-15.127																																																																													
0.5	-15.057	-15.058	-15.080	-15.076	-15.077																																																																													
1.1	-15.040	-15.041	-15.060	-15.055	-15.052																																																																													
1.6	-15.016	-15.023	-15.045	-15.039	-15.035																																																																													
1.9	-15.003	-15.012	-15.034	-15.028	-15.025																																																																													
2.2	-※1	-15.000	-15.023	-15.019	-15.016																																																																													
2.7	-※1	-※2	-15.004	-15.001	-15.000																																																																													
3.0	-※1	-※2	-14.992	-14.991	-14.990																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>*1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>*2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		
-																																																																																		
7																																																																																		
BC-11378																																																																																		


**COSEL**

Model	MGFW804815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V2.7A		

Input Volt. 48 V

-15V:rated load current.


Cycle 100 ms

t1,t2 = 100  $\mu$ s

Min.Load (0A)↔  
Load 100% (2.7A)

200 mV/div


2 ms/div



Min.Load (0A)↔  
Load 50% (1.35A)

200 mV/div


2 ms/div



Load 50% (1.35A)↔  
Load 100% (2.7A)

200 mV/div

2 ms/div




**COSEL**

Model	MGFW804815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V2.7A		

Input Volt. 48 V

+15V:rated load current.


Cycle 100 ms

t1,t2 = 100  $\mu$ s

Min.Load (0A)↔  
Load 100% (2.7A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔  
Load 50% (1.35A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (1.35A)↔  
Load 100% (2.7A)

200 mV/div

2 ms/div



2 ms/div

**COSEL**

Model	MGFW804815																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V2.7A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two curves: one for Input Volt. 18V (solid line with triangle markers) and one for Input Volt. 76V (dashed line with circle markers). The x-axis is Load Current [A] from 0.0 to 4.0. The y-axis is Ripple Voltage [mV] from 0 to 200. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (18V)</th> <th>Ripple Voltage [mV] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>40</td></tr> <tr><td>0.5</td><td>5</td><td>5</td></tr> <tr><td>1.1</td><td>5</td><td>5</td></tr> <tr><td>1.6</td><td>10</td><td>5</td></tr> <tr><td>1.9</td><td>15</td><td>5</td></tr> <tr><td>2.2</td><td>-</td><td>5</td></tr> <tr><td>2.7</td><td>-</td><td>5</td></tr> <tr><td>3.0</td><td>-</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)	0.0	15	40	0.5	5	5	1.1	5	5	1.6	10	5	1.9	15	5	2.2	-	5	2.7	-	5	3.0	-	10	--	-	-	--	-	-	--	-	-				
Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)																																						
0.0	15	40																																						
0.5	5	5																																						
1.1	5	5																																						
1.6	10	5																																						
1.9	15	5																																						
2.2	-	5																																						
2.7	-	5																																						
3.0	-	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>40</td></tr> <tr><td>0.5</td><td>5</td><td>5</td></tr> <tr><td>1.1</td><td>5</td><td>5</td></tr> <tr><td>1.6</td><td>10</td><td>5</td></tr> <tr><td>1.9</td><td>15</td><td>5</td></tr> <tr><td>2.2</td><td>-</td><td>5</td></tr> <tr><td>2.7</td><td>-</td><td>5</td></tr> <tr><td>3.0</td><td>-</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	15	40	0.5	5	5	1.1	5	5	1.6	10	5	1.9	15	5	2.2	-	5	2.7	-	5	3.0	-	10	--	-	-	--	-	-	--	-	-		
Load Current [A]		Ripple Voltage [mV]																																						
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.0	15	40																																						
0.5	5	5																																						
1.1	5	5																																						
1.6	10	5																																						
1.9	15	5																																						
2.2	-	5																																						
2.7	-	5																																						
3.0	-	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								

**COSEL**

Model	MGFW804815																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	-15V2.7A																																						
1.Graph																																							
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two curves: one for Input Volt. 18V (solid line with triangle markers) and one for Input Volt. 76V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.0 to 4.0. The y-axis represents Ripple Voltage [mV] from 0 to 200. Both curves show a minimum ripple voltage around 1.0 A and then increase as load current increases. A slanted line is drawn across the graph, starting from approximately (0.5, 10) and ending at (2.7, 10), indicating the rated load current range.</p>																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>15</td> <td>40</td> </tr> <tr> <td>0.5</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.1</td> <td>5</td> <td>5</td> </tr> <tr> <td>1.6</td> <td>10</td> <td>5</td> </tr> <tr> <td>1.9</td> <td>15</td> <td>5</td> </tr> <tr> <td>2.2</td> <td>-※</td> <td>5</td> </tr> <tr> <td>2.7</td> <td>-※</td> <td>5</td> </tr> <tr> <td>3.0</td> <td>-※</td> <td>10</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.0	15	40	0.5	5	5	1.1	5	5	1.6	10	5	1.9	15	5	2.2	-※	5	2.7	-※	5	3.0	-※	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 18 [V]	Input Volt. 76 [V]																																					
0.0	15	40																																					
0.5	5	5																																					
1.1	5	5																																					
1.6	10	5																																					
1.9	15	5																																					
2.2	-※	5																																					
2.7	-※	5																																					
3.0	-※	10																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		+15V: Rated Load Current																																					
<p>Fig.Complex Ripple Wave Form</p>																																							
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																							


**COSEL**

Model MGFW804815

Item Ripple-Noise

Object +15V2.7A

## 1. Graph



Measured by 100 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C  
Testing Circuitry Figure B

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	15	40
0.5	10	15
1.1	20	15
1.6	15	15
1.9	25	20
2.2	-	20
2.7	-	20
3.0	-	25
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.


**COSEL**

Model MGFW804815

Item Ripple-Noise

Object -15V2.7A

## 1. Graph



Measured by 100 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

Temperature 25°C  
Testing Circuitry Figure B

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	15	40
0.5	10	15
1.1	20	15
1.6	15	15
1.9	25	20
2.2	-	20
2.7	-	20
3.0	-	25
--	-	-
--	-	-
--	-	-


+15V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFW804815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V2.7A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	10
25	5	10
60	5	10
70	5	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	10
25	5	10
60	5	10
70	5	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFW804815	Testing Circuitry Figure A																																																																																	
Item	Ambient Temperature Drift																																																																																		
Object	+15V2.7A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.898</td><td>14.904</td><td>14.908</td><td>14.910</td><td>14.914</td></tr> <tr><td>-40</td><td>14.928</td><td>14.934</td><td>14.936</td><td>14.939</td><td>14.942</td></tr> <tr><td>-20</td><td>14.952</td><td>14.957</td><td>14.959</td><td>14.962</td><td>14.965</td></tr> <tr><td>0</td><td>14.970</td><td>14.975</td><td>14.976</td><td>14.978</td><td>14.981</td></tr> <tr><td>25</td><td>14.985</td><td>14.990</td><td>14.989</td><td>14.991</td><td>14.993</td></tr> <tr><td>60</td><td>14.992</td><td>14.998</td><td>14.995</td><td>14.996</td><td>14.998</td></tr> <tr><td>70</td><td>14.992</td><td>14.998</td><td>14.995</td><td>14.996</td><td>14.997</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-60	14.898	14.904	14.908	14.910	14.914	-40	14.928	14.934	14.936	14.939	14.942	-20	14.952	14.957	14.959	14.962	14.965	0	14.970	14.975	14.976	14.978	14.981	25	14.985	14.990	14.989	14.991	14.993	60	14.992	14.998	14.995	14.996	14.998	70	14.992	14.998	14.995	14.996	14.997	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
-60	14.898	14.904	14.908	14.910	14.914																																																																														
-40	14.928	14.934	14.936	14.939	14.942																																																																														
-20	14.952	14.957	14.959	14.962	14.965																																																																														
0	14.970	14.975	14.976	14.978	14.981																																																																														
25	14.985	14.990	14.989	14.991	14.993																																																																														
60	14.992	14.998	14.995	14.996	14.998																																																																														
70	14.992	14.998	14.995	14.996	14.997																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Object	-15V2.7A	2.Values																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-14.923</td><td>-14.921</td><td>-14.921</td><td>-14.921</td><td>-14.920</td></tr> <tr><td>-40</td><td>-14.952</td><td>-14.950</td><td>-14.950</td><td>-14.949</td><td>-14.948</td></tr> <tr><td>-20</td><td>-14.975</td><td>-14.974</td><td>-14.973</td><td>-14.971</td><td>-14.970</td></tr> <tr><td>0</td><td>-14.991</td><td>-14.990</td><td>-14.990</td><td>-14.987</td><td>-14.986</td></tr> <tr><td>25</td><td>-15.005</td><td>-15.003</td><td>-15.003</td><td>-15.000</td><td>-14.998</td></tr> <tr><td>60</td><td>-15.012</td><td>-15.011</td><td>-15.009</td><td>-15.006</td><td>-15.004</td></tr> <tr><td>70</td><td>-15.012</td><td>-15.011</td><td>-15.008</td><td>-15.006</td><td>-15.004</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	-60	-14.923	-14.921	-14.921	-14.921	-14.920	-40	-14.952	-14.950	-14.950	-14.949	-14.948	-20	-14.975	-14.974	-14.973	-14.971	-14.970	0	-14.991	-14.990	-14.990	-14.987	-14.986	25	-15.005	-15.003	-15.003	-15.000	-14.998	60	-15.012	-15.011	-15.009	-15.006	-15.004	70	-15.012	-15.011	-15.008	-15.006	-15.004	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
-60	-14.923	-14.921	-14.921	-14.921	-14.920																																																																														
-40	-14.952	-14.950	-14.950	-14.949	-14.948																																																																														
-20	-14.975	-14.974	-14.973	-14.971	-14.970																																																																														
0	-14.991	-14.990	-14.990	-14.987	-14.986																																																																														
25	-15.005	-15.003	-15.003	-15.000	-14.998																																																																														
60	-15.012	-15.011	-15.009	-15.006	-15.004																																																																														
70	-15.012	-15.011	-15.008	-15.006	-15.004																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		<p>Note: In case of input Volt.18V, Load 70%.</p> <p>24V, Load 80%.</p> <p>Other case Load 100%.</p>																																																																																	
Note: Slanted line shows the range of the rated ambient temperature.																																																																																			



Model	MGFW804815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 2.7A (AVR 2) : 0 - 2.7A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+15V2.7A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	24	0	15.136	±104	±0.7
Minimum Voltage	-40	18	2.4	14.928		

Object	-15V2.7A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	36	0	-15.151	±102	±0.7
Minimum Voltage	-40	76	2.7	-14.948		


**COSEL**

Model	MGFW804815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V2.7A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>14.982</td></tr> <tr><td>0.5</td><td>14.990</td></tr> <tr><td>1.0</td><td>14.991</td></tr> <tr><td>2.0</td><td>14.990</td></tr> <tr><td>3.0</td><td>14.990</td></tr> <tr><td>4.0</td><td>14.990</td></tr> <tr><td>5.0</td><td>14.990</td></tr> <tr><td>6.0</td><td>14.990</td></tr> <tr><td>7.0</td><td>14.990</td></tr> <tr><td>8.0</td><td>14.990</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	14.982	0.5	14.990	1.0	14.991	2.0	14.990	3.0	14.990	4.0	14.990	5.0	14.990	6.0	14.990	7.0	14.990	8.0	14.990
Time since start [H]	Output Voltage [V]																								
0.0	14.982																								
0.5	14.990																								
1.0	14.991																								
2.0	14.990																								
3.0	14.990																								
4.0	14.990																								
5.0	14.990																								
6.0	14.990																								
7.0	14.990																								
8.0	14.990																								
Object -15V2.7A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-14.993</td></tr> <tr><td>0.5</td><td>-15.004</td></tr> <tr><td>1.0</td><td>-15.004</td></tr> <tr><td>2.0</td><td>-15.004</td></tr> <tr><td>3.0</td><td>-15.004</td></tr> <tr><td>4.0</td><td>-15.004</td></tr> <tr><td>5.0</td><td>-15.004</td></tr> <tr><td>6.0</td><td>-15.004</td></tr> <tr><td>7.0</td><td>-15.004</td></tr> <tr><td>8.0</td><td>-15.004</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-14.993	0.5	-15.004	1.0	-15.004	2.0	-15.004	3.0	-15.004	4.0	-15.004	5.0	-15.004	6.0	-15.004	7.0	-15.004	8.0	-15.004
Time since start [H]	Output Voltage [V]																								
0.0	-14.993																								
0.5	-15.004																								
1.0	-15.004																								
2.0	-15.004																								
3.0	-15.004																								
4.0	-15.004																								
5.0	-15.004																								
6.0	-15.004																								
7.0	-15.004																								
8.0	-15.004																								

**COSEL**


Model	MGFW804815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V2.7A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.7	4.0	10.7	0.3	2.4	
100 %		6.7	5.5	12.2	0.3	0.8	




**COSEL**

Model	MGFW804815
Item	Rise and Fall Time
Object	-15V2.7A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.7	4.0	10.7	0.4	2.7	
100 %		6.7	5.5	12.2	0.3	0.9	




**COSEL**

Model	MGFW804815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1.89A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.3	15.4
-40	15.2	15.3
-20	15.2	15.3
0	15.2	15.1
25	15.2	15.3
60	15.2	15.2
70	15.2	15.2
--	-	-
--	-	-
--	-	-
--	-	-

## Object

-15V1.89A


## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.3	15.4
-40	15.2	15.3
-20	15.2	15.3
0	15.2	15.1
25	15.2	15.3
60	15.2	15.2
70	15.2	15.2
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

 Temperature 25°C  
 Testing Circuitry Figure A

## 2.Values

Output Voltage [V]	Load Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
15.0	2.905	3.625	3.694	3.757	3.817
14.3	-※1	-※2	-	-	-
13.5	-	-	-	-	-
12.0	-	-	-	-	-
10.5	-	-	-	-	-
9.0	-	-	-	-	-
7.5	-	-	-	-	-
6.0	-	-	-	-	-
4.5	-	-	-	-	-
0.0	-	-	-	-	-

-15V: Rated Load Current



## 2.Values

Output Voltage [V]	Load Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-15.0	2.945	3.606	3.660	3.660	3.784
-14.3	-※1	-※2	-	-	-
-13.5	-	-	-	-	-
-12.0	-	-	-	-	-
-10.5	-	-	-	-	-
-9.0	-	-	-	-	-
-7.5	-	-	-	-	-
-6.0	-	-	-	-	-
-4.5	-	-	-	-	-
0.0	-	-	-	-	-

+15V: Rated Load Current

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at V input Voltage is 80% of rated load current.


Refer to instruction manuals for details of input derating.

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

**COSEL**

Model	MGFW804815
Item	Overvoltage Protection
Object	+30V1.89A



Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output (+30V).

### Testing Circuitry Figure A

#### 2.Values


Ambient Temperature [°C]	Operating Point [%]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	118	118	118	118	118
-40	119	119	119	119	119
-20	121	121	121	121	121
0	122	122	122	122	122
25	124	124	124	124	124
60	127	127	127	127	127
70	128	128	128	128	128
0	-	-	-	-	-
0	-	-	-	-	-
0	-	-	-	-	-
0	-	-	-	-	-

# COSEL

Model	MGFW804815
Item	Switching frequency (by Load Current)
Object	+/-15V2.7A

Temperature 25°C  
Testing Circuitry Figure A

### 1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG80 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG80 operates intermittently, so switching frequency would not become constant.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)