



TEST DATA OF MGS1R50512

Regulated DC Power Supply
March 31, 2016

Approved by : Takayuki Fukuda _____
Takayuki Fukuda Design Manager

Prepared by : Shohei Mukaiide _____
Shohei Mukaiide Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching Frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGS1R50512																																																																																	
Item	Input Current (by Input Voltage)	Temperature	25°C																																																																															
Object		Testing Circuitry	Figure A																																																																															
1.Graph																																																																																		
			2.Values																																																																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>3.7</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>3.8</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>3.9</td><td>0.028</td><td>0.244</td><td>0.479</td></tr> <tr><td>4.0</td><td>0.028</td><td>0.237</td><td>0.465</td></tr> <tr><td>4.2</td><td>0.027</td><td>0.225</td><td>0.441</td></tr> <tr><td>4.5</td><td>0.025</td><td>0.211</td><td>0.411</td></tr> <tr><td>5.0</td><td>0.024</td><td>0.191</td><td>0.370</td></tr> <tr><td>6.0</td><td>0.020</td><td>0.161</td><td>0.307</td></tr> <tr><td>7.0</td><td>0.016</td><td>0.142</td><td>0.264</td></tr> <tr><td>8.0</td><td>0.014</td><td>0.127</td><td>0.233</td></tr> <tr><td>9.0</td><td>0.013</td><td>0.116</td><td>0.210</td></tr> <tr><td>10.0</td><td>0.012</td><td>0.107</td><td>0.191</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.002	0.002	0.002	3.7	0.003	0.003	0.003	3.8	0.003	0.003	0.003	3.9	0.028	0.244	0.479	4.0	0.028	0.237	0.465	4.2	0.027	0.225	0.441	4.5	0.025	0.211	0.411	5.0	0.024	0.191	0.370	6.0	0.020	0.161	0.307	7.0	0.016	0.142	0.264	8.0	0.014	0.127	0.233	9.0	0.013	0.116	0.210	10.0	0.012	0.107	0.191	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
3.0	0.002	0.002	0.002																																																																															
3.7	0.003	0.003	0.003																																																																															
3.8	0.003	0.003	0.003																																																																															
3.9	0.028	0.244	0.479																																																																															
4.0	0.028	0.237	0.465																																																																															
4.2	0.027	0.225	0.441																																																																															
4.5	0.025	0.211	0.411																																																																															
5.0	0.024	0.191	0.370																																																																															
6.0	0.020	0.161	0.307																																																																															
7.0	0.016	0.142	0.264																																																																															
8.0	0.014	0.127	0.233																																																																															
9.0	0.013	0.116	0.210																																																																															
10.0	0.012	0.107	0.191																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		

COSEL

Model	MGS1R50512																																																				
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																			
Object																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 4.5V ---□--- Input Volt. 5V ---○--- Input Volt. 9V </p>  <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.025</td><td>0.024</td><td>0.013</td></tr> <tr><td>0.026</td><td>0.099</td><td>0.091</td><td>0.061</td></tr> <tr><td>0.052</td><td>0.174</td><td>0.158</td><td>0.097</td></tr> <tr><td>0.078</td><td>0.251</td><td>0.227</td><td>0.134</td></tr> <tr><td>0.104</td><td>0.331</td><td>0.298</td><td>0.172</td></tr> <tr><td>0.130</td><td>0.411</td><td>0.370</td><td>0.210</td></tr> <tr><td>0.143</td><td>0.455</td><td>0.408</td><td>0.230</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	0.025	0.024	0.013	0.026	0.099	0.091	0.061	0.052	0.174	0.158	0.097	0.078	0.251	0.227	0.134	0.104	0.331	0.298	0.172	0.130	0.411	0.370	0.210	0.143	0.455	0.408	0.230	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																				
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																		
0.000	0.025	0.024	0.013																																																		
0.026	0.099	0.091	0.061																																																		
0.052	0.174	0.158	0.097																																																		
0.078	0.251	0.227	0.134																																																		
0.104	0.331	0.298	0.172																																																		
0.130	0.411	0.370	0.210																																																		
0.143	0.455	0.408	0.230																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

COSEL


Model MGS1R50512

Item Input Power (by Load Current)

Object _____

1.Graph

—△— Input Volt. 4.5V
 - -□--- Input Volt. 5V
 - -○--- Input Volt. 9V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	0.12	0.12	0.12
0.026	0.46	0.46	0.56
0.052	0.79	0.80	0.88
0.078	1.14	1.14	1.22
0.104	1.50	1.50	1.56
0.130	1.86	1.85	1.90
0.143	2.05	2.04	2.08
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL


Model	MGS1R50512																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.4</td><td>81.4</td><td>85.1</td> </tr> <tr> <td>4.5</td><td>81.4</td><td>85.1</td> </tr> <tr> <td>4.8</td><td>81.5</td><td>85.2</td> </tr> <tr> <td>5.0</td><td>81.6</td><td>85.2</td> </tr> <tr> <td>7.0</td><td>78.7</td><td>84.1</td> </tr> <tr> <td>9.0</td><td>74.6</td><td>82.9</td> </tr> <tr> <td>10.0</td><td>71.9</td><td>81.3</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.4	81.4	85.1	4.5	81.4	85.1	4.8	81.5	85.2	5.0	81.6	85.2	7.0	78.7	84.1	9.0	74.6	82.9	10.0	71.9	81.3	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.4	81.4	85.1																																
4.5	81.4	85.1																																
4.8	81.5	85.2																																
5.0	81.6	85.2																																
7.0	78.7	84.1																																
9.0	74.6	82.9																																
10.0	71.9	81.3																																
--	-	-																																
--	-	-																																

COSEL

Model	MGS1R50512	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Graph showing Efficiency [%] vs Load Current [A] for MGS1R50512 at 25°C. The graph plots efficiency against load current for three input voltages: 4.5V (solid line with triangles), 5V (dashed line with squares), and 9V (dash-dot line with circles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 4.5V [%]</th> <th>Input Volt. 5V [%]</th> <th>Input Volt. 9V [%]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.026</td><td>68.9</td><td>68.0</td><td>55.2</td></tr> <tr><td>0.052</td><td>79.2</td><td>78.7</td><td>71.3</td></tr> <tr><td>0.078</td><td>82.9</td><td>82.8</td><td>77.9</td></tr> <tr><td>0.104</td><td>84.8</td><td>84.8</td><td>80.7</td></tr> <tr><td>0.130</td><td>85.1</td><td>85.2</td><td>82.9</td></tr> <tr><td>0.143</td><td>85.2</td><td>85.3</td><td>83.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 4.5V [%]	Input Volt. 5V [%]	Input Volt. 9V [%]	0.000	-	-	-	0.026	68.9	68.0	55.2	0.052	79.2	78.7	71.3	0.078	82.9	82.8	77.9	0.104	84.8	84.8	80.7	0.130	85.1	85.2	82.9	0.143	85.2	85.3	83.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Volt. 4.5V [%]	Input Volt. 5V [%]	Input Volt. 9V [%]																																																			
0.000	-	-	-																																																			
0.026	68.9	68.0	55.2																																																			
0.052	79.2	78.7	71.3																																																			
0.078	82.9	82.8	77.9																																																			
0.104	84.8	84.8	80.7																																																			
0.130	85.1	85.2	82.9																																																			
0.143	85.2	85.3	83.1																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.026</td><td>68.9</td><td>68.0</td><td>55.2</td></tr> <tr><td>0.052</td><td>79.2</td><td>78.7</td><td>71.3</td></tr> <tr><td>0.078</td><td>82.9</td><td>82.8</td><td>77.9</td></tr> <tr><td>0.104</td><td>84.8</td><td>84.8</td><td>80.7</td></tr> <tr><td>0.130</td><td>85.1</td><td>85.2</td><td>82.9</td></tr> <tr><td>0.143</td><td>85.2</td><td>85.3</td><td>83.1</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-	-	-	0.026	68.9	68.0	55.2	0.052	79.2	78.7	71.3	0.078	82.9	82.8	77.9	0.104	84.8	84.8	80.7	0.130	85.1	85.2	82.9	0.143	85.2	85.3	83.1	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.000	-	-	-																																																			
0.026	68.9	68.0	55.2																																																			
0.052	79.2	78.7	71.3																																																			
0.078	82.9	82.8	77.9																																																			
0.104	84.8	84.8	80.7																																																			
0.130	85.1	85.2	82.9																																																			
0.143	85.2	85.3	83.1																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS1R50512
Item	Line Regulation
Object	+12V0.13A

1.Graph


Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.4	12.017	12.015
4.5	12.017	12.015
4.8	12.017	12.015
5.0	12.017	12.015
7.0	12.017	12.015
9.0	12.017	12.015
10.0	12.017	12.015
--	-	-
--	-	-

COSEL


Model MGS1R50512

Item Load Regulation

Object +12V0.13A

1.Graph

—△— Input Volt. 4.5V
 - - - □ - - Input Volt. 5V
 - - ○ - - Input Volt. 9V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A




2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	12.021	12.021	12.021
0.026	12.019	12.019	12.019
0.052	12.018	12.018	12.018
0.078	12.017	12.017	12.016
0.104	12.016	12.016	12.016
0.130	12.015	12.015	12.015
0.143	12.014	12.014	12.014
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGS1R50512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.13A		

Input Volt. 5 V
 Cycle 1000 ms




COSEL

Model	MGS1R50512
Item	Ripple Voltage (by Load Current)
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	10	20
0.026	15	20
0.052	20	20
0.078	35	25
0.104	50	35
0.130	60	45
0.143	80	50
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	MGS1R50512
Item	Ripple-Noise
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 4.5 [V]	Input Volt. 9 [V]
0.000	15	25
0.026	20	25
0.052	25	25
0.078	40	30
0.104	60	40
0.130	70	50
0.143	85	55
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form


COSEL

Model MGS1R50512

Item Ripple Voltage (by Ambient Temp.)

Object +12V0.13A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	40	75
-40	40	75
-20	40	70
0	30	55
25	30	55
75	30	65
85	30	65
90	30	65
--	-	-
--	-	-
--	-	-

COSEL


Model MGS1R50512

Item Ambient Temperature Drift

Object +12V0.13A

1.Graph

—△— Input Volt. 4.5V
 - - -□--- Input Volt. 5V
 - - -○--- Input Volt. 9V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	11.934	11.934	11.934
-40	11.956	11.957	11.957
-20	11.979	11.980	11.980
0	11.996	11.997	11.997
25	12.015	12.015	12.015
75	12.019	12.019	12.019
85	12.018	12.018	12.018
90	12.017	12.017	12.018
--	-	-	-
--	-	-	-
--	-	-	-



Model	MGS1R50512	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.13A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 4.5 - 9V

Load Current : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	9	0	12.027	± 36	± 0.3
Minimum Voltage	-40	4.5	0.13	11.956		

COSEL

Model	MGS1R50512
Item	Time Lapse Drift
Object	+12V0.13A

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



Input Volt. 5V
 Load 100%

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.013
0.5	12.014
1.0	12.014
2.0	12.014
3.0	12.014
4.0	12.014
5.0	12.014
6.0	12.014
7.0	12.013
8.0	12.014

COSEL


Model MGS1R50512

Item Rise and Fall Time

Object +12V0.13A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	0.4	1.1	0.3	4.1	
100 %		0.7	0.6	1.3	0.2	2.0	




COSEL

Model MGS1R50512

Item Minimum Input Voltage
for Regulated Output Voltage

Object +12V0.13A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.7	3.7
-40	3.6	3.7
-20	3.6	3.6
0	3.6	3.6
25	3.6	3.6
75	3.5	3.6
85	3.5	3.6
90	3.5	3.6
--	-	-
--	-	-
--	-	-

COSEL

Model	MGS1R50512
Item	Overcurrent Protection
Object	+12V0.13A

1.Graph



Note: Slanted line shows the range of the rated load current.


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
12.0	0.13	0.13	0.13
11.4	0.18	0.18	0.18
10.8	0.19	0.19	0.19
9.6	0.20	0.20	0.20
8.4	0.21	0.21	0.21
7.2	0.22	0.22	0.22
6.0	0.24	0.24	0.23
4.8	0.25	0.25	0.24
3.6	0.27	0.27	0.25
2.4	0.30	0.29	0.27
1.2	0.32	0.31	0.28
0.0	0.41	0.39	0.32

COSEL

Model	MGS1R50512
Item	Switching Frequency (by Load Current)
Object	+12V0.13A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Frequency [kHz]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.000	966	1000	1100
0.026	675	706	844
0.052	501	532	677
0.078	396	424	563
0.104	327	355	484
0.130	279	303	422
0.143	266	290	406
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

When load current is low, MG operates intermittently, so switching frequency would not become constant.

