

TEST DATA OF MGS302405

Regulated DC Power Supply

November 25, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Sho Saito
Sho Saito


Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19

(Final Page 19)

Model	MGS302405	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;"> △ Load 100% □ Load 50% ○ Load 0% </p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.6</td><td>0.064</td><td>1.001</td><td>1.994</td></tr> <tr><td>17.0</td><td>0.058</td><td>0.982</td><td>1.928</td></tr> <tr><td>18.0</td><td>0.049</td><td>0.921</td><td>1.810</td></tr> <tr><td>20.0</td><td>0.040</td><td>0.824</td><td>1.632</td></tr> <tr><td>22.0</td><td>0.038</td><td>0.750</td><td>1.481</td></tr> <tr><td>24.0</td><td>0.037</td><td>0.693</td><td>1.363</td></tr> <tr><td>28.0</td><td>0.037</td><td>0.599</td><td>1.171</td></tr> <tr><td>30.0</td><td>0.036</td><td>0.559</td><td>1.095</td></tr> <tr><td>32.0</td><td>0.036</td><td>0.527</td><td>1.028</td></tr> <tr><td>36.0</td><td>0.036</td><td>0.474</td><td>0.920</td></tr> <tr><td>40.0</td><td>0.035</td><td>0.430</td><td>0.832</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.001	0.001	0.001	8.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.6	0.064	1.001	1.994	17.0	0.058	0.982	1.928	18.0	0.049	0.921	1.810	20.0	0.040	0.824	1.632	22.0	0.038	0.750	1.481	24.0	0.037	0.693	1.363	28.0	0.037	0.599	1.171	30.0	0.036	0.559	1.095	32.0	0.036	0.527	1.028	36.0	0.036	0.474	0.920	40.0	0.035	0.430	0.832	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
4.0	0.001	0.001	0.001																																																																																
8.0	0.002	0.002	0.002																																																																																
16.0	0.002	0.002	0.002																																																																																
16.6	0.064	1.001	1.994																																																																																
17.0	0.058	0.982	1.928																																																																																
18.0	0.049	0.921	1.810																																																																																
20.0	0.040	0.824	1.632																																																																																
22.0	0.038	0.750	1.481																																																																																
24.0	0.037	0.693	1.363																																																																																
28.0	0.037	0.599	1.171																																																																																
30.0	0.036	0.559	1.095																																																																																
32.0	0.036	0.527	1.028																																																																																
36.0	0.036	0.474	0.920																																																																																
40.0	0.035	0.430	0.832																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																


Model	MGS302405																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (18V)</th> <th>Input Current [A] (24V)</th> <th>Input Current [A] (36V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.050</td><td>0.038</td><td>0.035</td></tr> <tr><td>1.2</td><td>0.395</td><td>0.300</td><td>0.211</td></tr> <tr><td>2.4</td><td>0.747</td><td>0.560</td><td>0.387</td></tr> <tr><td>3.6</td><td>1.093</td><td>0.824</td><td>0.562</td></tr> <tr><td>4.8</td><td>1.445</td><td>1.093</td><td>0.739</td></tr> <tr><td>6.0</td><td>1.813</td><td>1.360</td><td>0.920</td></tr> <tr><td>6.6</td><td>2.000</td><td>1.498</td><td>1.010</td></tr> </tbody> </table>			Load Current [A]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)	0.0	0.050	0.038	0.035	1.2	0.395	0.300	0.211	2.4	0.747	0.560	0.387	3.6	1.093	0.824	0.562	4.8	1.445	1.093	0.739	6.0	1.813	1.360	0.920	6.6	2.000	1.498	1.010																			
Load Current [A]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)																																																			
0.0	0.050	0.038	0.035																																																			
1.2	0.395	0.300	0.211																																																			
2.4	0.747	0.560	0.387																																																			
3.6	1.093	0.824	0.562																																																			
4.8	1.445	1.093	0.739																																																			
6.0	1.813	1.360	0.920																																																			
6.6	2.000	1.498	1.010																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.050</td><td>0.038</td><td>0.035</td></tr> <tr><td>1.2</td><td>0.395</td><td>0.300</td><td>0.211</td></tr> <tr><td>2.4</td><td>0.747</td><td>0.560</td><td>0.387</td></tr> <tr><td>3.6</td><td>1.093</td><td>0.824</td><td>0.562</td></tr> <tr><td>4.8</td><td>1.445</td><td>1.093</td><td>0.739</td></tr> <tr><td>6.0</td><td>1.813</td><td>1.360</td><td>0.920</td></tr> <tr><td>6.6</td><td>2.000</td><td>1.498</td><td>1.010</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.050	0.038	0.035	1.2	0.395	0.300	0.211	2.4	0.747	0.560	0.387	3.6	1.093	0.824	0.562	4.8	1.445	1.093	0.739	6.0	1.813	1.360	0.920	6.6	2.000	1.498	1.010	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	0.050	0.038	0.035																																																			
1.2	0.395	0.300	0.211																																																			
2.4	0.747	0.560	0.387																																																			
3.6	1.093	0.824	0.562																																																			
4.8	1.445	1.093	0.739																																																			
6.0	1.813	1.360	0.920																																																			
6.6	2.000	1.498	1.010																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS302405																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0.0 to 6.0). Three data series are shown for input voltages of 18V, 24V, and 36V. Each series consists of data points connected by straight lines. A slanted line is drawn across the graph, starting from approximately (0.5, 2) and ending at (6.0, 36), representing the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.90</td><td>0.91</td><td>1.27</td></tr> <tr><td>1.2</td><td>7.11</td><td>7.16</td><td>7.60</td></tr> <tr><td>2.4</td><td>13.41</td><td>13.46</td><td>13.90</td></tr> <tr><td>3.6</td><td>19.69</td><td>19.74</td><td>20.19</td></tr> <tr><td>4.8</td><td>26.11</td><td>26.17</td><td>26.62</td></tr> <tr><td>6.0</td><td>32.64</td><td>32.62</td><td>33.07</td></tr> <tr><td>6.6</td><td>35.95</td><td>35.87</td><td>36.35</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.90	0.91	1.27	1.2	7.11	7.16	7.60	2.4	13.41	13.46	13.90	3.6	19.69	19.74	20.19	4.8	26.11	26.17	26.62	6.0	32.64	32.62	33.07	6.6	35.95	35.87	36.35	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	0.90	0.91	1.27																																																			
1.2	7.11	7.16	7.60																																																			
2.4	13.41	13.46	13.90																																																			
3.6	19.69	19.74	20.19																																																			
4.8	26.11	26.17	26.62																																																			
6.0	32.64	32.62	33.07																																																			
6.6	35.95	35.87	36.35																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS302405
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	90.9	92.2
18	91.5	92.6
20	91.9	92.8
24	91.2	92.8
30	90.0	92.2
36	88.8	91.5
40	87.9	91.0
--	-	-
--	-	-


Note: Slanted line shows the range of the rated input voltage.


Model	MGS302405	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [18V] [%]</th> <th>Efficiency [24V] [%]</th> <th>Efficiency [36V] [%]</th> </tr> </thead> <tbody> <tr><td>1.2</td><td>85.3</td><td>84.7</td><td>79.8</td></tr> <tr><td>2.4</td><td>90.4</td><td>90.1</td><td>87.3</td></tr> <tr><td>3.6</td><td>92.1</td><td>91.8</td><td>89.8</td></tr> <tr><td>4.8</td><td>92.7</td><td>92.5</td><td>90.9</td></tr> <tr><td>6.0</td><td>92.7</td><td>92.8</td><td>91.5</td></tr> <tr><td>6.6</td><td>92.6</td><td>92.8</td><td>91.6</td></tr> </tbody> </table>	Load Current [A]	Efficiency [18V] [%]	Efficiency [24V] [%]	Efficiency [36V] [%]	1.2	85.3	84.7	79.8	2.4	90.4	90.1	87.3	3.6	92.1	91.8	89.8	4.8	92.7	92.5	90.9	6.0	92.7	92.8	91.5	6.6	92.6	92.8	91.6																								
Load Current [A]	Efficiency [18V] [%]	Efficiency [24V] [%]	Efficiency [36V] [%]																																																		
1.2	85.3	84.7	79.8																																																		
2.4	90.4	90.1	87.3																																																		
3.6	92.1	91.8	89.8																																																		
4.8	92.7	92.5	90.9																																																		
6.0	92.7	92.8	91.5																																																		
6.6	92.6	92.8	91.6																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>85.3</td><td>84.7</td><td>79.8</td></tr> <tr><td>2.4</td><td>90.4</td><td>90.1</td><td>87.3</td></tr> <tr><td>3.6</td><td>92.1</td><td>91.8</td><td>89.8</td></tr> <tr><td>4.8</td><td>92.7</td><td>92.5</td><td>90.9</td></tr> <tr><td>6.0</td><td>92.7</td><td>92.8</td><td>91.5</td></tr> <tr><td>6.6</td><td>92.6</td><td>92.8</td><td>91.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	-	-	-	1.2	85.3	84.7	79.8	2.4	90.4	90.1	87.3	3.6	92.1	91.8	89.8	4.8	92.7	92.5	90.9	6.0	92.7	92.8	91.5	6.6	92.6	92.8	91.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Efficiency [%]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.0	-	-	-																																																		
1.2	85.3	84.7	79.8																																																		
2.4	90.4	90.1	87.3																																																		
3.6	92.1	91.8	89.8																																																		
4.8	92.7	92.5	90.9																																																		
6.0	92.7	92.8	91.5																																																		
6.6	92.6	92.8	91.6																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

Model	MGS302405	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+5V6A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: - - - □ - - Load 50% — △ — Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>18</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>20</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>24</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>30</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>36</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>40</td> <td>5.054</td> <td>5.052</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	5.054	5.052	18	5.054	5.052	20	5.054	5.052	24	5.054	5.052	30	5.054	5.052	36	5.054	5.052	40	5.054	5.052	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
17	5.054	5.052																																
18	5.054	5.052																																
20	5.054	5.052																																
24	5.054	5.052																																
30	5.054	5.052																																
36	5.054	5.052																																
40	5.054	5.052																																
--	-	-																																
--	-	-																																

Note: Slanted line shows the range of the rated input voltage.

Model	MGS302405	Temperature Testing Circuitry 25°C Figure A																																																					
Item	Load Regulation																																																						
Object	+5V6A																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - -○--- Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>1.2</td><td>5.055</td><td>5.055</td><td>5.055</td></tr> <tr><td>2.4</td><td>5.055</td><td>5.054</td><td>5.054</td></tr> <tr><td>3.6</td><td>5.054</td><td>5.054</td><td>5.054</td></tr> <tr><td>4.8</td><td>5.053</td><td>5.053</td><td>5.053</td></tr> <tr><td>6.0</td><td>5.052</td><td>5.052</td><td>5.052</td></tr> <tr><td>6.6</td><td>5.052</td><td>5.052</td><td>5.052</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	5.056	5.056	5.056	1.2	5.055	5.055	5.055	2.4	5.055	5.054	5.054	3.6	5.054	5.054	5.054	4.8	5.053	5.053	5.053	6.0	5.052	5.052	5.052	6.6	5.052	5.052	5.052	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0.0	5.056	5.056	5.056																																																				
1.2	5.055	5.055	5.055																																																				
2.4	5.055	5.054	5.054																																																				
3.6	5.054	5.054	5.054																																																				
4.8	5.053	5.053	5.053																																																				
6.0	5.052	5.052	5.052																																																				
6.6	5.052	5.052	5.052																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated load current.																																																							

COSEL

COSSEL

Model	MGS302405	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+5V6A																																							
1.Graph		2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>7</td></tr> <tr><td>1.2</td><td>5</td><td>7</td></tr> <tr><td>2.4</td><td>5</td><td>7</td></tr> <tr><td>3.6</td><td>5</td><td>7</td></tr> <tr><td>4.8</td><td>5</td><td>7</td></tr> <tr><td>6.0</td><td>5</td><td>7</td></tr> <tr><td>6.6</td><td>5</td><td>7</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	5	7	1.2	5	7	2.4	5	7	3.6	5	7	4.8	5	7	6.0	5	7	6.6	5	7	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	5	7																																						
1.2	5	7																																						
2.4	5	7																																						
3.6	5	7																																						
4.8	5	7																																						
6.0	5	7																																						
6.6	5	7																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
Fig.Complex Ripple Wave Form																																								


COSEL

Model	MGS302405	Temperature	25°C																																								
Item	Ripple-Noise	Testing Circuitry	Figure B																																								
Object	+5V6A	2. Values																																									
1. Graph																																											
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>2.4</td><td>10</td><td>10</td></tr> <tr><td>3.6</td><td>10</td><td>10</td></tr> <tr><td>4.8</td><td>10</td><td>10</td></tr> <tr><td>6.0</td><td>10</td><td>10</td></tr> <tr><td>6.6</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	10	10	1.2	10	10	2.4	10	10	3.6	10	10	4.8	10	10	6.0	10	10	6.6	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 18 [V]	Input Volt. 36 [V]																																									
0.0	10	10																																									
1.2	10	10																																									
2.4	10	10																																									
3.6	10	10																																									
4.8	10	10																																									
6.0	10	10																																									
6.6	10	10																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Fig.Complex Ripple Noise Wave Form</p>																																											

COSEL

Model	MGS302405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V6A

1. Graph



Testing Circuitry Figure B


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	17	17
-40	11	11
-20	9	9
0	8	8
25	6	6
60	5	5
65	5	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS302405
Item	Ambient Temperature Drift
Object	+5V6A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	5.019	5.020	5.021
-40	5.031	5.032	5.032
-20	5.040	5.040	5.041
0	5.047	5.047	5.047
25	5.052	5.052	5.052
60	5.053	5.053	5.052
65	5.053	5.052	5.052
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	MGS302405	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 36V

Load Current : 0 - 6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	18	0	5.056	±13	±0.3
Minimum Voltage	-40	18	6	5.031		

COSEL

Model	MGS302405
Item	Time Lapse Drift
Object	+5V6A

1. Graph



Temperature 25°C
Testing Circuitry Figure A

2. Values


Time since start [H]	Output Voltage [V]
0.0	5.052
0.5	5.056
1.0	5.056
2.0	5.056
3.0	5.056
4.0	5.056
5.0	5.056
6.0	5.056
7.0	5.055
8.0	5.055

COSEL

Model	MGS302405
Item	Rise and Fall Time
Object	+5V6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		2.7	2.0	4.7	0.1	0.5
100 %		2.7	3.3	6.0	0.1	0.2



Model	MGS302405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V6A

Testing Circuitry Figure A


1. Graph



Note: Slanted line shows the range of the rated ambient temperature.


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.7	15.7
-40	15.7	15.7
-20	15.7	15.7
0	15.6	15.6
25	15.6	15.7
60	15.6	15.6
65	15.6	15.6
--	-	-
--	-	-
--	-	-
--	-	-

Model	MGS302405	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overshoot Protection																																																								
Object	+5V6A																																																								
1. Graph	<p>—△— Input Volt. 18V —□— Input Volt. 24V —○— Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2. Values																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overshoot protection is activated.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>5</td><td>7.34</td><td>7.28</td><td>7.23</td></tr> <tr><td>5</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>5</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	5	7.34	7.28	7.23	5	-	-	-	5	-	-	-	4	-	-	-	4	-	-	-	3	-	-	-	3	-	-	-	2	-	-	-	2	-	-	-	1	-	-	-	1	-	-	-	0	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
5	7.34	7.28	7.23																																																						
5	-	-	-																																																						
5	-	-	-																																																						
4	-	-	-																																																						
4	-	-	-																																																						
3	-	-	-																																																						
3	-	-	-																																																						
2	-	-	-																																																						
2	-	-	-																																																						
1	-	-	-																																																						
1	-	-	-																																																						
0	-	-	-																																																						

Model	MGS302405
Item	Oversupply Protection
Object	+5V6A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-60	6.99	6.99
-40	6.97	6.97
-20	6.96	6.96
0	6.95	6.95
25	6.95	6.95
60	6.95	6.95
65	6.95	6.95
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)