

TEST DATA OF MGS304805

Regulated DC Power Supply

November 24, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Sho Saito
Sho Saito

Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Overvoltage Protection	18
19. Figure of Testing Circuitry	19


(Final Page 19)

Model	MGS304805	Temperature Testing Circuitry 25°C Figure A																																																																																		
Item	Input Current (by Input Voltage)																																																																																			
Object	_____	2.Values																																																																																		
1.Graph	<p style="text-align: center;"> —△— Load 100% ---□--- Load 50% ---○--- Load 0% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.001</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>24.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>32.0</td><td>0.002</td><td>0.003</td><td>0.003</td></tr> <tr><td>33.2</td><td>0.031</td><td>0.500</td><td>0.991</td></tr> <tr><td>34.0</td><td>0.027</td><td>0.486</td><td>0.966</td></tr> <tr><td>36.0</td><td>0.024</td><td>0.458</td><td>0.908</td></tr> <tr><td>40.0</td><td>0.021</td><td>0.410</td><td>0.816</td></tr> <tr><td>48.0</td><td>0.019</td><td>0.344</td><td>0.679</td></tr> <tr><td>60.0</td><td>0.019</td><td>0.278</td><td>0.545</td></tr> <tr><td>70.0</td><td>0.019</td><td>0.241</td><td>0.471</td></tr> <tr><td>76.0</td><td>0.019</td><td>0.224</td><td>0.434</td></tr> <tr><td>80.0</td><td>0.019</td><td>0.213</td><td>0.414</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.001	0.002	0.002	16.0	0.002	0.002	0.002	24.0	0.002	0.002	0.002	32.0	0.002	0.003	0.003	33.2	0.031	0.500	0.991	34.0	0.027	0.486	0.966	36.0	0.024	0.458	0.908	40.0	0.021	0.410	0.816	48.0	0.019	0.344	0.679	60.0	0.019	0.278	0.545	70.0	0.019	0.241	0.471	76.0	0.019	0.224	0.434	80.0	0.019	0.213	0.414	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
8.0	0.001	0.002	0.002																																																																																	
16.0	0.002	0.002	0.002																																																																																	
24.0	0.002	0.002	0.002																																																																																	
32.0	0.002	0.003	0.003																																																																																	
33.2	0.031	0.500	0.991																																																																																	
34.0	0.027	0.486	0.966																																																																																	
36.0	0.024	0.458	0.908																																																																																	
40.0	0.021	0.410	0.816																																																																																	
48.0	0.019	0.344	0.679																																																																																	
60.0	0.019	0.278	0.545																																																																																	
70.0	0.019	0.241	0.471																																																																																	
76.0	0.019	0.224	0.434																																																																																	
80.0	0.019	0.213	0.414																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	

Model	MGS304805																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (36V)</th> <th>Input Current [A] (48V)</th> <th>Input Current [A] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.024</td><td>0.019</td><td>0.019</td></tr> <tr><td>1.0</td><td>0.167</td><td>0.127</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.312</td><td>0.235</td><td>0.155</td></tr> <tr><td>3.0</td><td>0.458</td><td>0.344</td><td>0.224</td></tr> <tr><td>4.0</td><td>0.605</td><td>0.455</td><td>0.293</td></tr> <tr><td>5.0</td><td>0.760</td><td>0.567</td><td>0.364</td></tr> <tr><td>6.0</td><td>0.910</td><td>0.682</td><td>0.436</td></tr> <tr><td>6.6</td><td>1.004</td><td>0.748</td><td>0.478</td></tr> </tbody> </table>	Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)	0.0	0.024	0.019	0.019	1.0	0.167	0.127	0.087	2.0	0.312	0.235	0.155	3.0	0.458	0.344	0.224	4.0	0.605	0.455	0.293	5.0	0.760	0.567	0.364	6.0	0.910	0.682	0.436	6.6	1.004	0.748	0.478																		
Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)																																																				
0.0	0.024	0.019	0.019																																																				
1.0	0.167	0.127	0.087																																																				
2.0	0.312	0.235	0.155																																																				
3.0	0.458	0.344	0.224																																																				
4.0	0.605	0.455	0.293																																																				
5.0	0.760	0.567	0.364																																																				
6.0	0.910	0.682	0.436																																																				
6.6	1.004	0.748	0.478																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.024</td><td>0.019</td><td>0.019</td></tr> <tr><td>1.0</td><td>0.167</td><td>0.127</td><td>0.087</td></tr> <tr><td>2.0</td><td>0.312</td><td>0.235</td><td>0.155</td></tr> <tr><td>3.0</td><td>0.458</td><td>0.344</td><td>0.224</td></tr> <tr><td>4.0</td><td>0.605</td><td>0.455</td><td>0.293</td></tr> <tr><td>5.0</td><td>0.760</td><td>0.567</td><td>0.364</td></tr> <tr><td>6.0</td><td>0.910</td><td>0.682</td><td>0.436</td></tr> <tr><td>6.6</td><td>1.004</td><td>0.748</td><td>0.478</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.024	0.019	0.019	1.0	0.167	0.127	0.087	2.0	0.312	0.235	0.155	3.0	0.458	0.344	0.224	4.0	0.605	0.455	0.293	5.0	0.760	0.567	0.364	6.0	0.910	0.682	0.436	6.6	1.004	0.748	0.478	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Current [A]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
0.0	0.024	0.019	0.019																																																				
1.0	0.167	0.127	0.087																																																				
2.0	0.312	0.235	0.155																																																				
3.0	0.458	0.344	0.224																																																				
4.0	0.605	0.455	0.293																																																				
5.0	0.760	0.567	0.364																																																				
6.0	0.910	0.682	0.436																																																				
6.6	1.004	0.748	0.478																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

Model	MGS304805																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p>  <p>The graph plots Input Power [W] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0.0 to 6.0). Three data series are shown for input voltages of 36V, 48V, and 76V. Each series consists of data points connected by dashed lines. A solid diagonal line represents the rated load current range, which is approximately between 2.0A and 6.6A.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.88</td><td>0.92</td><td>1.41</td></tr> <tr> <td>1.0</td><td>6.01</td><td>6.08</td><td>6.58</td></tr> <tr> <td>2.0</td><td>11.23</td><td>11.27</td><td>11.80</td></tr> <tr> <td>3.0</td><td>16.44</td><td>16.49</td><td>16.98</td></tr> <tr> <td>4.0</td><td>21.79</td><td>21.81</td><td>22.30</td></tr> <tr> <td>5.0</td><td>27.23</td><td>27.20</td><td>27.68</td></tr> <tr> <td>6.0</td><td>32.73</td><td>32.64</td><td>33.10</td></tr> <tr> <td>6.6</td><td>36.12</td><td>35.95</td><td>36.36</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.88	0.92	1.41	1.0	6.01	6.08	6.58	2.0	11.23	11.27	11.80	3.0	16.44	16.49	16.98	4.0	21.79	21.81	22.30	5.0	27.23	27.20	27.68	6.0	32.73	32.64	33.10	6.6	36.12	35.95	36.36	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.88	0.92	1.41																																																			
1.0	6.01	6.08	6.58																																																			
2.0	11.23	11.27	11.80																																																			
3.0	16.44	16.49	16.98																																																			
4.0	21.79	21.81	22.30																																																			
5.0	27.23	27.20	27.68																																																			
6.0	32.73	32.64	33.10																																																			
6.6	36.12	35.95	36.36																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


Model	MGS304805																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>33</td> <td>90.5</td> <td>90.8</td> </tr> <tr> <td>36</td> <td>91.4</td> <td>91.6</td> </tr> <tr> <td>40</td> <td>91.8</td> <td>91.9</td> </tr> <tr> <td>48</td> <td>91.4</td> <td>92.0</td> </tr> <tr> <td>55</td> <td>90.6</td> <td>91.8</td> </tr> <tr> <td>60</td> <td>90.3</td> <td>91.5</td> </tr> <tr> <td>70</td> <td>89.2</td> <td>91.2</td> </tr> <tr> <td>76</td> <td>88.8</td> <td>90.7</td> </tr> <tr> <td>80</td> <td>88.2</td> <td>90.5</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	90.5	90.8	36	91.4	91.6	40	91.8	91.9	48	91.4	92.0	55	90.6	91.8	60	90.3	91.5	70	89.2	91.2	76	88.8	90.7	80	88.2	90.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
33	90.5	90.8																																
36	91.4	91.6																																
40	91.8	91.9																																
48	91.4	92.0																																
55	90.6	91.8																																
60	90.3	91.5																																
70	89.2	91.2																																
76	88.8	90.7																																
80	88.2	90.5																																

Model	MGS304805																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p>  <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [36V] (%)</th> <th>Efficiency [48V] (%)</th> <th>Efficiency [76V] (%)</th> </tr> </thead> <tbody> <tr><td>1.0</td><td>83.9</td><td>83.0</td><td>76.7</td></tr> <tr><td>2.0</td><td>89.8</td><td>89.5</td><td>85.4</td></tr> <tr><td>3.0</td><td>91.5</td><td>91.3</td><td>88.6</td></tr> <tr><td>4.0</td><td>92.1</td><td>92.0</td><td>90.0</td></tr> <tr><td>5.0</td><td>92.0</td><td>92.2</td><td>90.6</td></tr> <tr><td>6.0</td><td>91.8</td><td>92.1</td><td>90.8</td></tr> <tr><td>6.6</td><td>91.5</td><td>91.9</td><td>90.9</td></tr> </tbody> </table>			Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)	1.0	83.9	83.0	76.7	2.0	89.8	89.5	85.4	3.0	91.5	91.3	88.6	4.0	92.1	92.0	90.0	5.0	92.0	92.2	90.6	6.0	91.8	92.1	90.8	6.6	91.5	91.9	90.9																			
Load Current [A]	Efficiency [36V] (%)	Efficiency [48V] (%)	Efficiency [76V] (%)																																																			
1.0	83.9	83.0	76.7																																																			
2.0	89.8	89.5	85.4																																																			
3.0	91.5	91.3	88.6																																																			
4.0	92.1	92.0	90.0																																																			
5.0	92.0	92.2	90.6																																																			
6.0	91.8	92.1	90.8																																																			
6.6	91.5	91.9	90.9																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.0</td><td>83.9</td><td>83.0</td><td>76.7</td></tr> <tr><td>2.0</td><td>89.8</td><td>89.5</td><td>85.4</td></tr> <tr><td>3.0</td><td>91.5</td><td>91.3</td><td>88.6</td></tr> <tr><td>4.0</td><td>92.1</td><td>92.0</td><td>90.0</td></tr> <tr><td>5.0</td><td>92.0</td><td>92.2</td><td>90.6</td></tr> <tr><td>6.0</td><td>91.8</td><td>92.1</td><td>90.8</td></tr> <tr><td>6.6</td><td>91.5</td><td>91.9</td><td>90.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	1.0	83.9	83.0	76.7	2.0	89.8	89.5	85.4	3.0	91.5	91.3	88.6	4.0	92.1	92.0	90.0	5.0	92.0	92.2	90.6	6.0	91.8	92.1	90.8	6.6	91.5	91.9	90.9	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
1.0	83.9	83.0	76.7																																																			
2.0	89.8	89.5	85.4																																																			
3.0	91.5	91.3	88.6																																																			
4.0	92.1	92.0	90.0																																																			
5.0	92.0	92.2	90.6																																																			
6.0	91.8	92.1	90.8																																																			
6.6	91.5	91.9	90.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS304805
Item	Line Regulation
Object	+5V6A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
33	5.037	5.036
36	5.037	5.036
40	5.037	5.036
48	5.037	5.036
55	5.037	5.036
60	5.037	5.037
70	5.037	5.037
76	5.037	5.037
80	5.037	5.037

Note: Slanted line shows the range of the rated input voltage.

Model	MGS304805	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+5V6A																																																				
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - -○--- Input Volt. 76V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.039</td><td>5.039</td><td>5.039</td></tr> <tr><td>1.2</td><td>5.038</td><td>5.038</td><td>5.038</td></tr> <tr><td>2.4</td><td>5.038</td><td>5.037</td><td>5.037</td></tr> <tr><td>3.6</td><td>5.037</td><td>5.037</td><td>5.037</td></tr> <tr><td>4.8</td><td>5.036</td><td>5.036</td><td>5.036</td></tr> <tr><td>6.0</td><td>5.036</td><td>5.036</td><td>5.035</td></tr> <tr><td>6.6</td><td>5.035</td><td>5.035</td><td>5.035</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	5.039	5.039	5.039	1.2	5.038	5.038	5.038	2.4	5.038	5.037	5.037	3.6	5.037	5.037	5.037	4.8	5.036	5.036	5.036	6.0	5.036	5.036	5.035	6.6	5.035	5.035	5.035	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0.0	5.039	5.039	5.039																																																		
1.2	5.038	5.038	5.038																																																		
2.4	5.038	5.037	5.037																																																		
3.6	5.037	5.037	5.037																																																		
4.8	5.036	5.036	5.036																																																		
6.0	5.036	5.036	5.035																																																		
6.6	5.035	5.035	5.035																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
Note: Slanted line shows the range of the rated load current.																																																					




COSSEL

Model	MGS304805																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+5V6A																																							
1.Graph																																								
<p>Input Volt. 36V Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>4</td><td>5</td></tr> <tr><td>1.2</td><td>4</td><td>5</td></tr> <tr><td>2.4</td><td>4</td><td>5</td></tr> <tr><td>3.6</td><td>4</td><td>5</td></tr> <tr><td>4.8</td><td>4</td><td>5</td></tr> <tr><td>6.0</td><td>4</td><td>5</td></tr> <tr><td>6.6</td><td>4</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	4	5	1.2	4	5	2.4	4	5	3.6	4	5	4.8	4	5	6.0	4	5	6.6	4	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.0	4	5																																						
1.2	4	5																																						
2.4	4	5																																						
3.6	4	5																																						
4.8	4	5																																						
6.0	4	5																																						
6.6	4	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

Model			
MGS304805			Temperature 25°C
Item	Ripple-Noise	Testing Circuitry	Figure B

1 Graph



Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form


2 Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.0	10	10
1.2	10	15
2.4	10	15
3.6	10	15
4.8	10	15
6.0	10	15
6.6	10	15
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGS304805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V6A

1. Graph



Testing Circuitry Figure B


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	13	13
-40	9	9
-20	7	7
0	6	6
25	5	5
60	4	4
65	4	4
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS304805
Item	Ambient Temperature Drift
Object	+5V6A



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	5.003	5.004	5.005
-40	5.015	5.016	5.016
-20	5.024	5.024	5.025
0	5.030	5.031	5.031
25	5.036	5.036	5.035
60	5.037	5.037	5.036
65	5.036	5.036	5.036
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGS304805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V6A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 36 - 76V

Load Current : 0 - 6A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	36	0	5.040	±13	±0.3
Minimum Voltage	-40	36	6	5.015		

COSEL

Model	MGS304805
Item	Time Lapse Drift
Object	+5V6A

Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Time since start [H]	Output Voltage [V]
0.0	5.036
0.5	5.039
1.0	5.040
2.0	5.041
3.0	5.042
4.0	5.042
5.0	5.043
6.0	5.043
7.0	5.044
8.0	5.044

COSEL


Model	MGS304805	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+5V6A	

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.3	2.0	4.3	0.1	0.5	
100 %		2.3	3.0	5.3	0.1	0.2	



Model	MGS304805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V6A

Testing Circuitry Figure A


1. Graph



2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	31.2	31.1
-40	31.2	31.1
-20	31.2	31.1
0	31.0	31.1
25	31.0	31.1
60	30.8	30.8
65	30.8	30.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS304805	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overshoot Protection																																																								
Object	+5V6A																																																								
1.Graph	<p>—△— Input Volt. 36V —□— Input Volt. 48V —○— Input Volt. 76V</p>  <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overshoot protection is activated.</p>	2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>7.31</td><td>7.26</td><td>7.25</td></tr> <tr><td>4.75</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	5.00	7.31	7.26	7.25	4.75	-	-	-	4.50	-	-	-	4.00	-	-	-	3.50	-	-	-	3.00	-	-	-	2.50	-	-	-	2.00	-	-	-	1.50	-	-	-	1.00	-	-	-	0.50	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																						
5.00	7.31	7.26	7.25																																																						
4.75	-	-	-																																																						
4.50	-	-	-																																																						
4.00	-	-	-																																																						
3.50	-	-	-																																																						
3.00	-	-	-																																																						
2.50	-	-	-																																																						
2.00	-	-	-																																																						
1.50	-	-	-																																																						
1.00	-	-	-																																																						
0.50	-	-	-																																																						
0.00	-	-	-																																																						

Model	MGS304805
Item	Oversupply Protection
Object	+5V6A

1. Graph



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-60	7.07	7.08
-40	7.05	7.06
-20	7.04	7.05
0	7.03	7.04
25	7.03	7.04
60	7.03	7.04
65	7.03	7.04
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)