



TEST DATA OF MGS32415

Regulated DC Power Supply
March 30, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda

Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGS32415	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object																																																																																		
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□--- Load 50% - - -○--- Load 0%</p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>16.2</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>16.4</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>16.6</td><td>0.003</td><td>0.004</td><td>0.003</td></tr> <tr><td>17.0</td><td>0.009</td><td>0.108</td><td>0.208</td></tr> <tr><td>17.4</td><td>0.010</td><td>0.105</td><td>0.206</td></tr> <tr><td>18.0</td><td>0.009</td><td>0.102</td><td>0.198</td></tr> <tr><td>22.0</td><td>0.008</td><td>0.084</td><td>0.161</td></tr> <tr><td>24.0</td><td>0.007</td><td>0.077</td><td>0.148</td></tr> <tr><td>28.0</td><td>0.007</td><td>0.066</td><td>0.127</td></tr> <tr><td>32.0</td><td>0.006</td><td>0.058</td><td>0.111</td></tr> <tr><td>36.0</td><td>0.005</td><td>0.052</td><td>0.099</td></tr> <tr><td>40.0</td><td>0.004</td><td>0.047</td><td>0.090</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	16.0	0.003	0.003	0.003	16.2	0.003	0.003	0.004	16.4	0.003	0.003	0.004	16.6	0.003	0.004	0.003	17.0	0.009	0.108	0.208	17.4	0.010	0.105	0.206	18.0	0.009	0.102	0.198	22.0	0.008	0.084	0.161	24.0	0.007	0.077	0.148	28.0	0.007	0.066	0.127	32.0	0.006	0.058	0.111	36.0	0.005	0.052	0.099	40.0	0.004	0.047	0.090	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
16.0	0.003	0.003	0.003																																																																															
16.2	0.003	0.003	0.004																																																																															
16.4	0.003	0.003	0.004																																																																															
16.6	0.003	0.004	0.003																																																																															
17.0	0.009	0.108	0.208																																																																															
17.4	0.010	0.105	0.206																																																																															
18.0	0.009	0.102	0.198																																																																															
22.0	0.008	0.084	0.161																																																																															
24.0	0.007	0.077	0.148																																																																															
28.0	0.007	0.066	0.127																																																																															
32.0	0.006	0.058	0.111																																																																															
36.0	0.005	0.052	0.099																																																																															
40.0	0.004	0.047	0.090																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	MGS32415	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.009</td><td>0.007</td><td>0.005</td></tr> <tr> <td>0.04</td><td>0.046</td><td>0.035</td><td>0.025</td></tr> <tr> <td>0.08</td><td>0.083</td><td>0.063</td><td>0.043</td></tr> <tr> <td>0.12</td><td>0.121</td><td>0.091</td><td>0.062</td></tr> <tr> <td>0.16</td><td>0.159</td><td>0.119</td><td>0.080</td></tr> <tr> <td>0.20</td><td>0.198</td><td>0.148</td><td>0.099</td></tr> <tr> <td>0.22</td><td>0.218</td><td>0.162</td><td>0.108</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.009	0.007	0.005	0.04	0.046	0.035	0.025	0.08	0.083	0.063	0.043	0.12	0.121	0.091	0.062	0.16	0.159	0.119	0.080	0.20	0.198	0.148	0.099	0.22	0.218	0.162	0.108	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.009	0.007	0.005																																																			
0.04	0.046	0.035	0.025																																																			
0.08	0.083	0.063	0.043																																																			
0.12	0.121	0.091	0.062																																																			
0.16	0.159	0.119	0.080																																																			
0.20	0.198	0.148	0.099																																																			
0.22	0.218	0.162	0.108																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS32415	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V <p>Y-axis: Input Power [W]</p> <p>X-axis: Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.19</td><td>0.20</td><td>0.20</td></tr> <tr><td>0.04</td><td>0.84</td><td>0.90</td><td>0.91</td></tr> <tr><td>0.08</td><td>1.50</td><td>1.52</td><td>1.55</td></tr> <tr><td>0.12</td><td>2.18</td><td>2.19</td><td>2.23</td></tr> <tr><td>0.16</td><td>2.87</td><td>2.87</td><td>2.93</td></tr> <tr><td>0.20</td><td>3.57</td><td>3.56</td><td>3.57</td></tr> <tr><td>0.22</td><td>3.93</td><td>3.90</td><td>3.96</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.19	0.20	0.20	0.04	0.84	0.90	0.91	0.08	1.50	1.52	1.55	0.12	2.18	2.19	2.23	0.16	2.87	2.87	2.93	0.20	3.57	3.56	3.57	0.22	3.93	3.90	3.96	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.19	0.20	0.20																																																			
0.04	0.84	0.90	0.91																																																			
0.08	1.50	1.52	1.55																																																			
0.12	2.18	2.19	2.23																																																			
0.16	2.87	2.87	2.93																																																			
0.20	3.57	3.56	3.57																																																			
0.22	3.93	3.90	3.96																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS32415	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object																																			
1.Graph																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td><td>82.8</td><td>84.9</td> </tr> <tr> <td>18</td><td>82.7</td><td>85.2</td> </tr> <tr> <td>20</td><td>82.5</td><td>85.4</td> </tr> <tr> <td>24</td><td>82.1</td><td>85.5</td> </tr> <tr> <td>30</td><td>81.6</td><td>85.0</td> </tr> <tr> <td>36</td><td>80.7</td><td>84.6</td> </tr> <tr> <td>40</td><td>79.5</td><td>84.2</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	82.8	84.9	18	82.7	85.2	20	82.5	85.4	24	82.1	85.5	30	81.6	85.0	36	80.7	84.6	40	79.5	84.2	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
17	82.8	84.9																																	
18	82.7	85.2																																	
20	82.5	85.4																																	
24	82.1	85.5																																	
30	81.6	85.0																																	
36	80.7	84.6																																	
40	79.5	84.2																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


COSEL

Model	MGS32415	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.04</td><td>73.4</td><td>71.5</td><td>66.8</td></tr> <tr><td>0.08</td><td>80.8</td><td>80.5</td><td>78.4</td></tr> <tr><td>0.12</td><td>83.4</td><td>83.1</td><td>82.0</td></tr> <tr><td>0.16</td><td>84.4</td><td>84.8</td><td>83.6</td></tr> <tr><td>0.20</td><td>85.2</td><td>85.5</td><td>84.6</td></tr> <tr><td>0.22</td><td>85.1</td><td>85.5</td><td>85.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.04	73.4	71.5	66.8	0.08	80.8	80.5	78.4	0.12	83.4	83.1	82.0	0.16	84.4	84.8	83.6	0.20	85.2	85.5	84.6	0.22	85.1	85.5	85.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.04	73.4	71.5	66.8																																																			
0.08	80.8	80.5	78.4																																																			
0.12	83.4	83.1	82.0																																																			
0.16	84.4	84.8	83.6																																																			
0.20	85.2	85.5	84.6																																																			
0.22	85.1	85.5	85.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS32415	Temperature	25°C
Item	Line Regulation	Testing Circuitry	Figure A
Object	+15V0.2A		

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	15.102	15.098
18	15.101	15.097
20	15.101	15.098
24	15.101	15.097
30	15.101	15.098
36	15.101	15.097
40	15.101	15.098
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.




COSEL

Model	MGS32415	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.2A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 18V - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.108</td><td>15.106</td><td>15.108</td></tr> <tr><td>0.04</td><td>15.105</td><td>15.104</td><td>15.104</td></tr> <tr><td>0.08</td><td>15.103</td><td>15.103</td><td>15.102</td></tr> <tr><td>0.12</td><td>15.101</td><td>15.101</td><td>15.101</td></tr> <tr><td>0.16</td><td>15.099</td><td>15.099</td><td>15.099</td></tr> <tr><td>0.20</td><td>15.097</td><td>15.097</td><td>15.097</td></tr> <tr><td>0.22</td><td>15.096</td><td>15.096</td><td>15.096</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	15.108	15.106	15.108	0.04	15.105	15.104	15.104	0.08	15.103	15.103	15.102	0.12	15.101	15.101	15.101	0.16	15.099	15.099	15.099	0.20	15.097	15.097	15.097	0.22	15.096	15.096	15.096	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	15.108	15.106	15.108																																																			
0.04	15.105	15.104	15.104																																																			
0.08	15.103	15.103	15.102																																																			
0.12	15.101	15.101	15.101																																																			
0.16	15.099	15.099	15.099																																																			
0.20	15.097	15.097	15.097																																																			
0.22	15.096	15.096	15.096																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	MGS32415	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.2A		

Input Volt. 24 V
 Cycle 1000 ms



COSEL

Model	MGS32415																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0 to 0.25 A. Two sets of data points are plotted: one for 18V (triangles) and one for 36V (circles). Both sets show an increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 18V)</th> <th>Ripple Voltage [mV] (Input Volt. 36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>15</td></tr> <tr><td>0.04</td><td>15</td><td>10</td></tr> <tr><td>0.08</td><td>30</td><td>20</td></tr> <tr><td>0.12</td><td>50</td><td>40</td></tr> <tr><td>0.16</td><td>65</td><td>45</td></tr> <tr><td>0.20</td><td>95</td><td>55</td></tr> <tr><td>0.22</td><td>105</td><td>60</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 18V)	Ripple Voltage [mV] (Input Volt. 36V)	0.00	5	15	0.04	15	10	0.08	30	20	0.12	50	40	0.16	65	45	0.20	95	55	0.22	105	60														
Load Current [A]	Ripple Voltage [mV] (Input Volt. 18V)	Ripple Voltage [mV] (Input Volt. 36V)																																						
0.00	5	15																																						
0.04	15	10																																						
0.08	30	20																																						
0.12	50	40																																						
0.16	65	45																																						
0.20	95	55																																						
0.22	105	60																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>15</td></tr> <tr><td>0.04</td><td>15</td><td>10</td></tr> <tr><td>0.08</td><td>30</td><td>20</td></tr> <tr><td>0.12</td><td>50</td><td>40</td></tr> <tr><td>0.16</td><td>65</td><td>45</td></tr> <tr><td>0.20</td><td>95</td><td>55</td></tr> <tr><td>0.22</td><td>105</td><td>60</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	5	15	0.04	15	10	0.08	30	20	0.12	50	40	0.16	65	45	0.20	95	55	0.22	105	60	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.00	5	15																																						
0.04	15	10																																						
0.08	30	20																																						
0.12	50	40																																						
0.16	65	45																																						
0.20	95	55																																						
0.22	105	60																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL


Model	MGS32415																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.2A																																							
1.Graph																																								
<p>Legend: —△— Input Volt. 18V ---○--- Input Volt. 36V </p> <table border="1"> <caption>Data extracted from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (18V)</th> <th>Ripple Voltage [mV] (36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>20</td></tr> <tr><td>0.04</td><td>20</td><td>15</td></tr> <tr><td>0.08</td><td>35</td><td>25</td></tr> <tr><td>0.12</td><td>55</td><td>45</td></tr> <tr><td>0.16</td><td>75</td><td>50</td></tr> <tr><td>0.20</td><td>100</td><td>60</td></tr> <tr><td>0.22</td><td>110</td><td>70</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (36V)	0.00	10	20	0.04	20	15	0.08	35	25	0.12	55	45	0.16	75	50	0.20	100	60	0.22	110	70														
Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (36V)																																						
0.00	10	20																																						
0.04	20	15																																						
0.08	35	25																																						
0.12	55	45																																						
0.16	75	50																																						
0.20	100	60																																						
0.22	110	70																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>20</td></tr> <tr><td>0.04</td><td>20</td><td>15</td></tr> <tr><td>0.08</td><td>35</td><td>25</td></tr> <tr><td>0.12</td><td>55</td><td>45</td></tr> <tr><td>0.16</td><td>75</td><td>50</td></tr> <tr><td>0.20</td><td>100</td><td>60</td></tr> <tr><td>0.22</td><td>110</td><td>70</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	10	20	0.04	20	15	0.08	35	25	0.12	55	45	0.16	75	50	0.20	100	60	0.22	110	70	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.00	10	20																																						
0.04	20	15																																						
0.08	35	25																																						
0.12	55	45																																						
0.16	75	50																																						
0.20	100	60																																						
0.22	110	70																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGS32415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A

Testing Circuitry Figure B

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	40	85
-40	40	85
-20	40	85
0	35	75
25	35	65
75	30	60
85	30	60
90	30	60
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model MGS32415

Item Ambient Temperature Drift

Object +15V0.2A

1.Graph

—△— Input Volt. 18V
 - - -□--- Input Volt. 24V
 - - ○ - - Input Volt. 36V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	14.968	14.970	14.971
-40	15.009	15.011	15.012
-20	15.042	15.044	15.044
0	15.070	15.071	15.072
25	15.097	15.097	15.097
75	15.119	15.119	15.119
85	15.120	15.120	15.121
90	15.121	15.121	15.121
--	-	-	-
--	-	-	-
--	-	-	-



Model	MGS32415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V0.2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 18 - 36V

Load Current : 0 - 0.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	85	36	0	15.135	±63	±0.4
Minimum Voltage	-40	18	0.2	15.009		

COSEL

Model	MGS32415	Temperature	25°C
Item	Time Lapse Drift	Testing Circuitry	Figure A
Object	+15V0.2A		

1.Graph




2.Values

Time since start [H]	Output Voltage [V]
0.0	15.094
0.5	15.097
1.0	15.097
2.0	15.097
3.0	15.097
4.0	15.097
5.0	15.097
6.0	15.097
7.0	15.097
8.0	15.097

COSEL


Model	MGS32415	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V0.2A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		2.1	0.7	2.8	0.2	5.3
100 %		2.0	1.0	3.0	0.1	2.7




COSEL

Model	MGS32415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.4	15.5
-40	15.3	15.4
-20	15.2	15.2
0	15.1	15.1
25	15.0	15.1
75	14.9	15.1
85	14.9	15.1
90	14.9	15.1
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model MGS32415

Item Overcurrent Protection

Object +15V0.2A

1.Graph



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
15.0	0.20	0.20	0.20
14.3	0.27	0.27	0.27
13.5	0.28	0.28	0.28
12.0	0.30	0.30	0.29
10.5	0.32	0.32	0.31
9.0	0.35	0.33	0.32
7.5	0.37	0.35	0.34
6.0	0.40	0.38	0.36
4.5	0.42	0.40	0.38
3.0	0.46	0.42	0.40
1.5	0.48	0.45	0.41
0.0	0.44	0.40	0.36

COSEL

Model	MGS32415	Temperature	25°C																																																			
Item	Switching frequency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+15V0.2A																																																					
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - ·○--- Input Volt. 36V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Frequency [kHz]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>644</td><td>694</td><td>725</td></tr> <tr> <td>0.04</td><td>467</td><td>529</td><td>591</td></tr> <tr> <td>0.08</td><td>367</td><td>424</td><td>489</td></tr> <tr> <td>0.12</td><td>300</td><td>355</td><td>417</td></tr> <tr> <td>0.16</td><td>255</td><td>303</td><td>362</td></tr> <tr> <td>0.20</td><td>222</td><td>267</td><td>322</td></tr> <tr> <td>0.22</td><td>215</td><td>259</td><td>312</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Frequency [kHz]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	644	694	725	0.04	467	529	591	0.08	367	424	489	0.12	300	355	417	0.16	255	303	362	0.20	222	267	322	0.22	215	259	312	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Frequency [kHz]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	644	694	725																																																			
0.04	467	529	591																																																			
0.08	367	424	489																																																			
0.12	300	355	417																																																			
0.16	255	303	362																																																			
0.20	222	267	322																																																			
0.22	215	259	312																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	<p>Slanted line shows the range of the rated load current.</p> <p>-When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																					





Figure B (Ripple and Ripple noise Characteristic)