



TEST DATA OF MGS61215

Regulated DC Power Supply
July 28, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda

Design Manager

Prepared by : Ryosuke Nakao
Ryosuke Nakao

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching Frequency (by Load Current)	18
19.Figure of Testing Circuitry	19


(Final Page 19)

COSEL

Model	MGS61215																																																																																	
Item	Input Current (by Input Voltage)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
<p>Temperature 25°C Testing Circuitry Figure A</p>																																																																																		
<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.2</td><td>0.028</td><td>0.417</td><td>0.827</td></tr> <tr><td>8.4</td><td>0.027</td><td>0.407</td><td>0.806</td></tr> <tr><td>8.6</td><td>0.026</td><td>0.398</td><td>0.787</td></tr> <tr><td>8.8</td><td>0.026</td><td>0.388</td><td>0.769</td></tr> <tr><td>9.0</td><td>0.025</td><td>0.380</td><td>0.754</td></tr> <tr><td>10.0</td><td>0.023</td><td>0.342</td><td>0.673</td></tr> <tr><td>12.0</td><td>0.013</td><td>0.286</td><td>0.561</td></tr> <tr><td>16.0</td><td>0.008</td><td>0.217</td><td>0.420</td></tr> <tr><td>18.0</td><td>0.006</td><td>0.195</td><td>0.376</td></tr> <tr><td>20.0</td><td>0.007</td><td>0.178</td><td>0.339</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.003	0.003	0.003	8.0	0.003	0.003	0.003	8.2	0.028	0.417	0.827	8.4	0.027	0.407	0.806	8.6	0.026	0.398	0.787	8.8	0.026	0.388	0.769	9.0	0.025	0.380	0.754	10.0	0.023	0.342	0.673	12.0	0.013	0.286	0.561	16.0	0.008	0.217	0.420	18.0	0.006	0.195	0.376	20.0	0.007	0.178	0.339	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
6.0	0.003	0.003	0.003																																																																															
8.0	0.003	0.003	0.003																																																																															
8.2	0.028	0.417	0.827																																																																															
8.4	0.027	0.407	0.806																																																																															
8.6	0.026	0.398	0.787																																																																															
8.8	0.026	0.388	0.769																																																																															
9.0	0.025	0.380	0.754																																																																															
10.0	0.023	0.342	0.673																																																																															
12.0	0.013	0.286	0.561																																																																															
16.0	0.008	0.217	0.420																																																																															
18.0	0.006	0.195	0.376																																																																															
20.0	0.007	0.178	0.339																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		

COSEL

Model	MGS61215
Item	Input Current (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.00	0.025	0.013	0.007
0.08	0.167	0.127	0.090
0.16	0.309	0.235	0.161
0.24	0.454	0.341	0.232
0.32	0.602	0.450	0.304
0.40	0.754	0.561	0.376
0.44	0.831	0.617	0.413
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGS61215
Item	Input Power (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.00	0.23	0.15	0.12
0.08	1.51	1.52	1.61
0.16	2.77	2.81	2.89
0.24	4.08	4.08	4.17
0.32	5.38	5.39	5.46
0.40	6.71	6.69	6.75
0.44	7.38	7.36	7.41
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGS61215
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.6	87.9	89.5
9.0	87.9	89.6
10.0	87.6	89.6
12.0	87.4	89.9
15.0	86.5	89.5
18.0	84.9	89.0
20.0	84.2	88.5
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	MGS61215	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Graph showing Efficiency [%] vs Load Current [A]. The Y-axis ranges from 55 to 95 in increments of 10. The X-axis ranges from 0.0 to 0.5 in increments of 0.1. Three curves are plotted for different input voltages: 9V (solid line with triangle markers), 12V (dashed line with square markers), and 18V (dash-dot line with circle markers). All curves show efficiency increasing with load current. A slanted line is drawn through the data points, indicating the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9V [%]</th> <th>12V [%]</th> <th>18V [%]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.08</td><td>79.6</td><td>78.9</td><td>74.5</td></tr> <tr><td>0.16</td><td>86.7</td><td>85.4</td><td>83.1</td></tr> <tr><td>0.24</td><td>88.5</td><td>88.5</td><td>86.5</td></tr> <tr><td>0.32</td><td>89.3</td><td>89.2</td><td>88.0</td></tr> <tr><td>0.40</td><td>89.6</td><td>89.9</td><td>89.0</td></tr> <tr><td>0.44</td><td>89.6</td><td>89.8</td><td>89.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	9V [%]	12V [%]	18V [%]	0.00	-	-	-	0.08	79.6	78.9	74.5	0.16	86.7	85.4	83.1	0.24	88.5	88.5	86.5	0.32	89.3	89.2	88.0	0.40	89.6	89.9	89.0	0.44	89.6	89.8	89.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	9V [%]	12V [%]	18V [%]																																																			
0.00	-	-	-																																																			
0.08	79.6	78.9	74.5																																																			
0.16	86.7	85.4	83.1																																																			
0.24	88.5	88.5	86.5																																																			
0.32	89.3	89.2	88.0																																																			
0.40	89.6	89.9	89.0																																																			
0.44	89.6	89.8	89.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.08</td><td>79.6</td><td>78.9</td><td>74.5</td></tr> <tr><td>0.16</td><td>86.7</td><td>85.4</td><td>83.1</td></tr> <tr><td>0.24</td><td>88.5</td><td>88.5</td><td>86.5</td></tr> <tr><td>0.32</td><td>89.3</td><td>89.2</td><td>88.0</td></tr> <tr><td>0.40</td><td>89.6</td><td>89.9</td><td>89.0</td></tr> <tr><td>0.44</td><td>89.6</td><td>89.8</td><td>89.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-	-	-	0.08	79.6	78.9	74.5	0.16	86.7	85.4	83.1	0.24	88.5	88.5	86.5	0.32	89.3	89.2	88.0	0.40	89.6	89.9	89.0	0.44	89.6	89.8	89.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	-	-	-																																																			
0.08	79.6	78.9	74.5																																																			
0.16	86.7	85.4	83.1																																																			
0.24	88.5	88.5	86.5																																																			
0.32	89.3	89.2	88.0																																																			
0.40	89.6	89.9	89.0																																																			
0.44	89.6	89.8	89.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS61215
Item	Line Regulation
Object	+15V0.4A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	15.012	15.011
9.0	15.012	15.012
10.0	15.012	15.011
12.0	15.012	15.011
15.0	15.010	15.010
18.0	15.009	15.009
20.0	15.008	15.007
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGS61215	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.4A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.022</td><td>15.023</td><td>15.023</td></tr> <tr><td>0.08</td><td>15.019</td><td>15.019</td><td>15.016</td></tr> <tr><td>0.16</td><td>15.018</td><td>15.016</td><td>15.014</td></tr> <tr><td>0.24</td><td>15.016</td><td>15.015</td><td>15.012</td></tr> <tr><td>0.32</td><td>15.014</td><td>15.013</td><td>15.010</td></tr> <tr><td>0.40</td><td>15.012</td><td>15.011</td><td>15.009</td></tr> <tr><td>0.44</td><td>15.011</td><td>15.011</td><td>15.007</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	15.022	15.023	15.023	0.08	15.019	15.019	15.016	0.16	15.018	15.016	15.014	0.24	15.016	15.015	15.012	0.32	15.014	15.013	15.010	0.40	15.012	15.011	15.009	0.44	15.011	15.011	15.007	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	15.022	15.023	15.023																																																			
0.08	15.019	15.019	15.016																																																			
0.16	15.018	15.016	15.014																																																			
0.24	15.016	15.015	15.012																																																			
0.32	15.014	15.013	15.010																																																			
0.40	15.012	15.011	15.009																																																			
0.44	15.011	15.011	15.007																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGS61215	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.4A		


Input Volt. 12 V
 Cycle 100 ms



Min.Load (0A)↔
 Load 100% (0.4A)

500 mV/div


2 ms/div

 $t_1, t_2 = 100 \mu s$ 

Min.Load (0A)↔
 Load 50% (0.2A)

500 mV/div

2 ms/div




Load 50% (0.2A)↔
 Load 100% (0.4A)

500 mV/div

2 ms/div

2 ms/div




COSEL

Model	MGS61215
Item	Ripple Voltage (by Load Current)
Object	+15V0.4A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	5	25
0.08	5	5
0.16	5	5
0.24	5	5
0.32	5	5
0.40	5	5
0.44	5	5
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.
 load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form


COSEL

Model	MGS61215																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.4A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>30</td></tr> <tr><td>0.08</td><td>10</td><td>10</td></tr> <tr><td>0.16</td><td>10</td><td>10</td></tr> <tr><td>0.24</td><td>10</td><td>10</td></tr> <tr><td>0.32</td><td>10</td><td>10</td></tr> <tr><td>0.40</td><td>10</td><td>10</td></tr> <tr><td>0.44</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	10	30	0.08	10	10	0.16	10	10	0.24	10	10	0.32	10	10	0.40	10	10	0.44	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	10	30																																						
0.08	10	10																																						
0.16	10	10																																						
0.24	10	10																																						
0.32	10	10																																						
0.40	10	10																																						
0.44	10	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGS61215
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.4A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
80	5	5
85	5	5
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGS61215
Item	Ambient Temperature Drift
Object	+15V0.4A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	14.884	14.884	14.882
-40	14.922	14.923	14.921
-20	14.958	14.959	14.956
0	14.985	14.986	14.983
25	15.012	15.011	15.009
80	15.025	15.025	15.023
85	15.025	15.025	15.023
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGS61215	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V0.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 9 - 18V

Load Current : 0 - 0.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	80	18	0	15.040	±60	±0.4
Minimum Voltage	-40	18	0.4	14.921		

COSEL

Model	MGS61215
Item	Time Lapse Drift
Object	+15V0.4A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph


 Input Volt. 12V
 Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	15.005
0.5	15.012
1.0	15.012
2.0	15.012
3.0	15.012
4.0	15.012
5.0	15.012
6.0	15.012
7.0	15.012
8.0	15.012

COSEL

Model	MGS61215
Item	Rise and Fall Time
Object	+15V0.4A


Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.4	0.5	2.9	0.2	4.1	
100 %		2.4	0.6	3.0	0.1	2.1	



COSEL

Model	MGS61215
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.4A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.2	8.3
-40	7.9	8.1
-20	7.9	7.9
0	7.8	7.8
25	7.8	7.8
80	7.7	7.7
85	7.6	7.6
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	MGS61215
Item	Overcurrent Protection
Object	+15V0.4A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
15.0	0.40	0.40	0.40
14.3	0.51	0.53	0.50
13.5	0.53	0.54	0.51
12.0	0.56	0.57	0.53
10.5	0.60	0.60	0.55
9.0	0.63	0.64	0.58
7.5	0.67	0.67	0.61
6.0	0.72	0.71	0.64
4.5	0.76	0.75	0.67
3.0	0.82	0.79	0.70
1.5	0.87	0.83	0.73
0.0	1.00	0.93	0.74

COSEL

Model	MGS61215	Temperature	25°C																																																			
Item	Switching Frequency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+15V0.4A																																																					
1.Graph	<p>Switching Frequency [kHz]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Frequency [kHz]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>936</td><td>970</td><td>845</td></tr> <tr><td>0.08</td><td>600</td><td>668</td><td>735</td></tr> <tr><td>0.16</td><td>441</td><td>506</td><td>578</td></tr> <tr><td>0.24</td><td>348</td><td>408</td><td>477</td></tr> <tr><td>0.32</td><td>287</td><td>341</td><td>406</td></tr> <tr><td>0.40</td><td>244</td><td>293</td><td>353</td></tr> <tr><td>0.44</td><td>227</td><td>274</td><td>331</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Frequency [kHz]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	936	970	845	0.08	600	668	735	0.16	441	506	578	0.24	348	408	477	0.32	287	341	406	0.40	244	293	353	0.44	227	274	331	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Frequency [kHz]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	936	970	845																																																			
0.08	600	668	735																																																			
0.16	441	506	578																																																			
0.24	348	408	477																																																			
0.32	287	341	406																																																			
0.40	244	293	353																																																			
0.44	227	274	331																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
-When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																						

COSEL





Figure B (Ripple and Ripple noise Characteristic)