

# TEST DATA OF MGW301205

Regulated DC Power Supply  
November 26, 2010

Approved by : Kazunari Asano  
Kazunari Asano

Design Manager

Prepared by : Sho Saito  
Sho Saito

Design Engineer

**COSEL CO.,LTD.**


## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)

Model	MGW301205	Temperature Testing Circuitry      25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100%        - - -□- - Load 50%        - -○--- Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>-0.004</td><td>-0.004</td><td>-0.004</td></tr> <tr><td>4.0</td><td>-0.003</td><td>-0.003</td><td>-0.003</td></tr> <tr><td>6.0</td><td>-0.002</td><td>-0.002</td><td>-0.002</td></tr> <tr><td>7.0</td><td>-0.002</td><td>-0.002</td><td>-0.002</td></tr> <tr><td>8.0</td><td>-0.002</td><td>-0.002</td><td>-0.002</td></tr> <tr><td>8.3</td><td>0.035</td><td>1.728</td><td>3.702</td></tr> <tr><td>8.5</td><td>0.035</td><td>1.686</td><td>3.607</td></tr> <tr><td>9.0</td><td>0.036</td><td>1.588</td><td>3.429</td></tr> <tr><td>10.0</td><td>0.036</td><td>1.443</td><td>3.057</td></tr> <tr><td>10.6</td><td>0.037</td><td>1.361</td><td>2.906</td></tr> <tr><td>12.0</td><td>0.032</td><td>1.202</td><td>2.548</td></tr> <tr><td>14.0</td><td>0.026</td><td>1.034</td><td>2.190</td></tr> <tr><td>16.0</td><td>0.022</td><td>0.908</td><td>1.912</td></tr> <tr><td>18.0</td><td>0.020</td><td>0.813</td><td>1.696</td></tr> <tr><td>20.0</td><td>0.019</td><td>0.735</td><td>1.535</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	-0.004	-0.004	-0.004	4.0	-0.003	-0.003	-0.003	6.0	-0.002	-0.002	-0.002	7.0	-0.002	-0.002	-0.002	8.0	-0.002	-0.002	-0.002	8.3	0.035	1.728	3.702	8.5	0.035	1.686	3.607	9.0	0.036	1.588	3.429	10.0	0.036	1.443	3.057	10.6	0.037	1.361	2.906	12.0	0.032	1.202	2.548	14.0	0.026	1.034	2.190	16.0	0.022	0.908	1.912	18.0	0.020	0.813	1.696	20.0	0.019	0.735	1.535	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	-0.004	-0.004	-0.004																																																																																
4.0	-0.003	-0.003	-0.003																																																																																
6.0	-0.002	-0.002	-0.002																																																																																
7.0	-0.002	-0.002	-0.002																																																																																
8.0	-0.002	-0.002	-0.002																																																																																
8.3	0.035	1.728	3.702																																																																																
8.5	0.035	1.686	3.607																																																																																
9.0	0.036	1.588	3.429																																																																																
10.0	0.036	1.443	3.057																																																																																
10.6	0.037	1.361	2.906																																																																																
12.0	0.032	1.202	2.548																																																																																
14.0	0.026	1.034	2.190																																																																																
16.0	0.022	0.908	1.912																																																																																
18.0	0.020	0.813	1.696																																																																																
20.0	0.019	0.735	1.535																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	MGW301205																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 9V        - - -□- - Input Volt. 12V        - - ○- - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.035</td><td>0.031</td><td>0.020</td></tr> <tr><td>20</td><td>0.658</td><td>0.502</td><td>0.348</td></tr> <tr><td>40</td><td>1.286</td><td>0.967</td><td>0.658</td></tr> <tr><td>60</td><td>1.950</td><td>1.448</td><td>0.974</td></tr> <tr><td>80</td><td>2.614</td><td>1.952</td><td>1.297</td></tr> <tr><td>100</td><td>3.298</td><td>2.454</td><td>1.630</td></tr> <tr><td>110</td><td>3.620</td><td>2.698</td><td>1.799</td></tr> </tbody> </table>			Load Ration [%]	9V [A]	12V [A]	18V [A]	0	0.035	0.031	0.020	20	0.658	0.502	0.348	40	1.286	0.967	0.658	60	1.950	1.448	0.974	80	2.614	1.952	1.297	100	3.298	2.454	1.630	110	3.620	2.698	1.799																			
Load Ration [%]	9V [A]	12V [A]	18V [A]																																																			
0	0.035	0.031	0.020																																																			
20	0.658	0.502	0.348																																																			
40	1.286	0.967	0.658																																																			
60	1.950	1.448	0.974																																																			
80	2.614	1.952	1.297																																																			
100	3.298	2.454	1.630																																																			
110	3.620	2.698	1.799																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.035</td><td>0.031</td><td>0.020</td></tr> <tr><td>20</td><td>0.658</td><td>0.502</td><td>0.348</td></tr> <tr><td>40</td><td>1.286</td><td>0.967</td><td>0.658</td></tr> <tr><td>60</td><td>1.950</td><td>1.448</td><td>0.974</td></tr> <tr><td>80</td><td>2.614</td><td>1.952</td><td>1.297</td></tr> <tr><td>100</td><td>3.298</td><td>2.454</td><td>1.630</td></tr> <tr><td>110</td><td>3.620</td><td>2.698</td><td>1.799</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.035	0.031	0.020	20	0.658	0.502	0.348	40	1.286	0.967	0.658	60	1.950	1.448	0.974	80	2.614	1.952	1.297	100	3.298	2.454	1.630	110	3.620	2.698	1.799	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.035	0.031	0.020																																																			
20	0.658	0.502	0.348																																																			
40	1.286	0.967	0.658																																																			
60	1.950	1.448	0.974																																																			
80	2.614	1.952	1.297																																																			
100	3.298	2.454	1.630																																																			
110	3.620	2.698	1.799																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW301205																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—△— Input Volt. 9V        - - -□--- Input Volt. 12V        - - -○--- Input Volt. 18V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>0.33</td><td>0.39</td><td>0.36</td></tr> <tr> <td>20</td><td>6.00</td><td>6.10</td><td>6.31</td></tr> <tr> <td>40</td><td>11.60</td><td>11.69</td><td>11.93</td></tr> <tr> <td>60</td><td>17.40</td><td>17.39</td><td>17.62</td></tr> <tr> <td>80</td><td>23.28</td><td>23.28</td><td>23.35</td></tr> <tr> <td>100</td><td>29.33</td><td>29.23</td><td>29.25</td></tr> <tr> <td>110</td><td>32.43</td><td>32.28</td><td>32.24</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.33	0.39	0.36	20	6.00	6.10	6.31	40	11.60	11.69	11.93	60	17.40	17.39	17.62	80	23.28	23.28	23.35	100	29.33	29.23	29.25	110	32.43	32.28	32.24	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.33	0.39	0.36																																																			
20	6.00	6.10	6.31																																																			
40	11.60	11.69	11.93																																																			
60	17.40	17.39	17.62																																																			
80	23.28	23.28	23.35																																																			
100	29.33	29.23	29.25																																																			
110	32.43	32.28	32.24																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	MGW301205																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8.5</td> <td>87.4</td> <td>85.9</td> </tr> <tr> <td>9.0</td> <td>87.5</td> <td>86.1</td> </tr> <tr> <td>10.0</td> <td>87.3</td> <td>86.3</td> </tr> <tr> <td>12.0</td> <td>87.1</td> <td>86.4</td> </tr> <tr> <td>15.0</td> <td>86.4</td> <td>86.5</td> </tr> <tr> <td>18.0</td> <td>85.7</td> <td>86.4</td> </tr> <tr> <td>20.0</td> <td>85.1</td> <td>86.3</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	87.4	85.9	9.0	87.5	86.1	10.0	87.3	86.3	12.0	87.1	86.4	15.0	86.4	86.5	18.0	85.7	86.4	20.0	85.1	86.3	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	87.4	85.9																																
9.0	87.5	86.1																																
10.0	87.3	86.3																																
12.0	87.1	86.4																																
15.0	86.4	86.5																																
18.0	85.7	86.4																																
20.0	85.1	86.3																																
--	-	-																																
--	-	-																																

Model	MGW301205																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>Graph showing Efficiency [%] vs Load Ration [%]. The Y-axis ranges from 50 to 100 in increments of 10. The X-axis ranges from 0 to 120 in increments of 40. Three curves are plotted for Input Volt. 9V (solid line with triangle markers), Input Volt. 12V (dashed line with square markers), and Input Volt. 18V (dash-dot line with circle markers). All curves show efficiency increasing with load ratio, with the 18V curve being the highest and the 9V curve being the lowest.</p> <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 9V [%]</th> <th>Input Volt. 12V [%]</th> <th>Input Volt. 18V [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>83.7</td><td>82.3</td><td>79.6</td></tr> <tr><td>40</td><td>86.9</td><td>86.2</td><td>84.5</td></tr> <tr><td>60</td><td>87.0</td><td>87.1</td><td>86.0</td></tr> <tr><td>80</td><td>86.8</td><td>86.8</td><td>86.5</td></tr> <tr><td>100</td><td>86.2</td><td>86.5</td><td>86.4</td></tr> <tr><td>110</td><td>85.7</td><td>86.1</td><td>86.2</td></tr> </tbody> </table>			Load Ration [%]	Input Volt. 9V [%]	Input Volt. 12V [%]	Input Volt. 18V [%]	20	83.7	82.3	79.6	40	86.9	86.2	84.5	60	87.0	87.1	86.0	80	86.8	86.8	86.5	100	86.2	86.5	86.4	110	85.7	86.1	86.2																							
Load Ration [%]	Input Volt. 9V [%]	Input Volt. 12V [%]	Input Volt. 18V [%]																																																			
20	83.7	82.3	79.6																																																			
40	86.9	86.2	84.5																																																			
60	87.0	87.1	86.0																																																			
80	86.8	86.8	86.5																																																			
100	86.2	86.5	86.4																																																			
110	85.7	86.1	86.2																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>83.7</td><td>82.3</td><td>79.6</td></tr> <tr><td>40</td><td>86.9</td><td>86.2</td><td>84.5</td></tr> <tr><td>60</td><td>87.0</td><td>87.1</td><td>86.0</td></tr> <tr><td>80</td><td>86.8</td><td>86.8</td><td>86.5</td></tr> <tr><td>100</td><td>86.2</td><td>86.5</td><td>86.4</td></tr> <tr><td>110</td><td>85.7</td><td>86.1</td><td>86.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	83.7	82.3	79.6	40	86.9	86.2	84.5	60	87.0	87.1	86.0	80	86.8	86.8	86.5	100	86.2	86.5	86.4	110	85.7	86.1	86.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	-	-	-																																																			
20	83.7	82.3	79.6																																																			
40	86.9	86.2	84.5																																																			
60	87.0	87.1	86.0																																																			
80	86.8	86.8	86.5																																																			
100	86.2	86.5	86.4																																																			
110	85.7	86.1	86.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW301205
Item	Line Regulation
Object	+5V2.5A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	5.137	5.077
9.0	5.136	5.078
10.0	5.133	5.078
12.0	5.130	5.078
15.0	5.128	5.078
18.0	5.126	5.078
20.0	5.126	5.078
--	-	-
--	-	-

-5V: Rated output current

## Object -5V2.5A

## 1.Graph




## 2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	-5.142	-5.078
9.0	-5.140	-5.078
10.0	-5.138	-5.078
12.0	-5.135	-5.078
15.0	-5.132	-5.079
18.0	-5.130	-5.079
20.0	-5.130	-5.079
--	-	-
--	-	-

+5V: Rated output current

Note: Slanted line shows the range of the rated input voltage.

Model	MGW301205	Temperature Testing Circuitry      25°C Figure A																																															
Item	Load Regulation																																																
Object	+5V2.5A																																																
1.Graph	<p>—△— Input Volt. 9V      - - -□- - Input Volt. 12V      - · -○- - Input Volt. 18V</p> <table border="1"> <caption>Data for +5V2.5A Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V Output [V]</th> <th>12V Output [V]</th> <th>18V Output [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.524</td><td>5.544</td><td>5.602</td></tr> <tr><td>0.125</td><td>5.332</td><td>5.349</td><td>5.395</td></tr> <tr><td>0.500</td><td>5.198</td><td>5.190</td><td>5.186</td></tr> <tr><td>1.000</td><td>5.159</td><td>5.152</td><td>5.147</td></tr> <tr><td>1.500</td><td>5.131</td><td>5.125</td><td>5.122</td></tr> <tr><td>2.000</td><td>5.104</td><td>5.101</td><td>5.099</td></tr> <tr><td>2.500</td><td>5.079</td><td>5.078</td><td>5.078</td></tr> <tr><td>2.750</td><td>5.066</td><td>5.067</td><td>5.068</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]	0.00	5.524	5.544	5.602	0.125	5.332	5.349	5.395	0.500	5.198	5.190	5.186	1.000	5.159	5.152	5.147	1.500	5.131	5.125	5.122	2.000	5.104	5.101	5.099	2.500	5.079	5.078	5.078	2.750	5.066	5.067	5.068	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]																																														
0.00	5.524	5.544	5.602																																														
0.125	5.332	5.349	5.395																																														
0.500	5.198	5.190	5.186																																														
1.000	5.159	5.152	5.147																																														
1.500	5.131	5.125	5.122																																														
2.000	5.104	5.101	5.099																																														
2.500	5.079	5.078	5.078																																														
2.750	5.066	5.067	5.068																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														
2.Values																																																	
Object	-5V2.5A																																																
1.Graph	<p>—△— Input Volt. 9V      - - -□- - Input Volt. 12V      - · -○- - Input Volt. 18V</p> <table border="1"> <caption>Data for -5V2.5A Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V Output [V]</th> <th>12V Output [V]</th> <th>18V Output [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-5.516</td><td>-5.514</td><td>-5.559</td></tr> <tr><td>0.125</td><td>-5.370</td><td>-5.358</td><td>-5.425</td></tr> <tr><td>0.500</td><td>-5.195</td><td>-5.186</td><td>-5.178</td></tr> <tr><td>1.000</td><td>-5.160</td><td>-5.153</td><td>-5.147</td></tr> <tr><td>1.500</td><td>-5.131</td><td>-5.126</td><td>-5.123</td></tr> <tr><td>2.000</td><td>-5.105</td><td>-5.102</td><td>-5.100</td></tr> <tr><td>2.500</td><td>-5.079</td><td>-5.079</td><td>-5.079</td></tr> <tr><td>2.750</td><td>-5.066</td><td>-5.067</td><td>-5.068</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]	0.00	-5.516	-5.514	-5.559	0.125	-5.370	-5.358	-5.425	0.500	-5.195	-5.186	-5.178	1.000	-5.160	-5.153	-5.147	1.500	-5.131	-5.126	-5.123	2.000	-5.105	-5.102	-5.100	2.500	-5.079	-5.079	-5.079	2.750	-5.066	-5.067	-5.068	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	9V Output [V]	12V Output [V]	18V Output [V]																																														
0.00	-5.516	-5.514	-5.559																																														
0.125	-5.370	-5.358	-5.425																																														
0.500	-5.195	-5.186	-5.178																																														
1.000	-5.160	-5.153	-5.147																																														
1.500	-5.131	-5.126	-5.123																																														
2.000	-5.105	-5.102	-5.100																																														
2.500	-5.079	-5.079	-5.079																																														
2.750	-5.066	-5.067	-5.068																																														
--	-	-	-																																														
--	-	-	-																																														
--	-	-	-																																														
2.Values																																																	
Note:	Slanted line shows the range of the rated load current.																																																





**COSEL**

Model	MGW301205	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+5V2.5A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.50</td><td>2</td><td>2</td></tr> <tr><td>1.00</td><td>2</td><td>2</td></tr> <tr><td>1.50</td><td>2</td><td>2</td></tr> <tr><td>2.00</td><td>3</td><td>2</td></tr> <tr><td>2.50</td><td>3</td><td>2</td></tr> <tr><td>2.75</td><td>3</td><td>2</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	2	2	0.50	2	2	1.00	2	2	1.50	2	2	2.00	3	2	2.50	3	2	2.75	3	2	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.00	2	2																																							
0.50	2	2																																							
1.00	2	2																																							
1.50	2	2																																							
2.00	3	2																																							
2.50	3	2																																							
2.75	3	2																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									


**COSSEL**

Model	MGW301205	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	-5V2.5A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.50</td><td>3</td><td>4</td></tr> <tr><td>1.00</td><td>3</td><td>4</td></tr> <tr><td>1.50</td><td>3</td><td>4</td></tr> <tr><td>2.00</td><td>4</td><td>5</td></tr> <tr><td>2.50</td><td>4</td><td>5</td></tr> <tr><td>2.75</td><td>4</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	2	2	0.50	3	4	1.00	3	4	1.50	3	4	2.00	4	5	2.50	4	5	2.75	4	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.00	2	2																																							
0.50	3	4																																							
1.00	3	4																																							
1.50	3	4																																							
2.00	4	5																																							
2.50	4	5																																							
2.75	4	5																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

**COSEL**

Model	MGW301205
Item	Ripple-Noise
Object	+5V2.5A

## 1. Graph



Temperature 25°C  
Testing Circuitry Figure B

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 18 [V]
0.00	5	5
0.50	5	5
1.00	5	5
1.50	5	5
2.00	5	5
2.50	5	5
2.75	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form

**COSEL**


Model	MGW301205	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple-Noise																																							
Object	-5V2.5A																																							
1.Graph	<p>1. Graph</p> <p>—△— Input Volt. 9V</p> <p>-·○- Input Volt. 18V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>	2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>5</td><td>10</td></tr> <tr><td>1.00</td><td>5</td><td>10</td></tr> <tr><td>1.50</td><td>5</td><td>10</td></tr> <tr><td>2.00</td><td>5</td><td>10</td></tr> <tr><td>2.50</td><td>5</td><td>10</td></tr> <tr><td>2.75</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	5	5	0.50	5	10	1.00	5	10	1.50	5	10	2.00	5	10	2.50	5	10	2.75	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	5	5																																						
0.50	5	10																																						
1.00	5	10																																						
1.50	5	10																																						
2.00	5	10																																						
2.50	5	10																																						
2.75	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p>																																								

Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	MGW301205
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2.5A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	6
-40	3	4
-20	3	3
0	3	3
25	2	2
60	2	2
65	2	2
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

## 1.Graph



## 2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	12	12
-40	9	9
-20	6	6
0	5	5
25	4	4
60	3	3
65	3	3
--	-	-
--	-	-
--	-	-
--	-	-

+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGW301205
Item	Ambient Temperature Drift
Object	+5V2.5A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	5.052	5.053	5.054
-40	5.061	5.061	5.062
-20	5.068	5.068	5.069
0	5.073	5.073	5.073
25	5.077	5.077	5.077
60	5.079	5.079	5.079
65	5.080	5.080	5.079
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-5.051	-5.052	-5.054
-40	-5.059	-5.061	-5.062
-20	-5.067	-5.068	-5.069
0	-5.072	-5.073	-5.074
25	-5.077	-5.077	-5.078
60	-5.079	-5.079	-5.080
65	-5.079	-5.080	-5.080
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW301205	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 2.5A (AVR 2) : 0 - 2.5A

\* Other Output : Rated Load

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$




$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	18		0	5.606	
Minimum Voltage	-40	9	2.5	5.061	±273	±5.5

Object	-5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	18		0	-5.568	
Minimum Voltage	-40	9	2.5	-5.059	±255	±5.1

**COSEL**


Model	MGW301205	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V2.5A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.078</td></tr> <tr><td>0.5</td><td>5.084</td></tr> <tr><td>1.0</td><td>5.083</td></tr> <tr><td>2.0</td><td>5.083</td></tr> <tr><td>3.0</td><td>5.083</td></tr> <tr><td>4.0</td><td>5.083</td></tr> <tr><td>5.0</td><td>5.083</td></tr> <tr><td>6.0</td><td>5.083</td></tr> <tr><td>7.0</td><td>5.083</td></tr> <tr><td>8.0</td><td>5.083</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.078	0.5	5.084	1.0	5.083	2.0	5.083	3.0	5.083	4.0	5.083	5.0	5.083	6.0	5.083	7.0	5.083	8.0	5.083
Time since start [H]	Output Voltage [V]																								
0.0	5.078																								
0.5	5.084																								
1.0	5.083																								
2.0	5.083																								
3.0	5.083																								
4.0	5.083																								
5.0	5.083																								
6.0	5.083																								
7.0	5.083																								
8.0	5.083																								
Object			2.Values																						
1.Graph			 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 12V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.079</td></tr> <tr><td>0.5</td><td>-5.086</td></tr> <tr><td>1.0</td><td>-5.086</td></tr> <tr><td>2.0</td><td>-5.086</td></tr> <tr><td>3.0</td><td>-5.086</td></tr> <tr><td>4.0</td><td>-5.086</td></tr> <tr><td>5.0</td><td>-5.086</td></tr> <tr><td>6.0</td><td>-5.086</td></tr> <tr><td>7.0</td><td>-5.086</td></tr> <tr><td>8.0</td><td>-5.086</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-5.079	0.5	-5.086	1.0	-5.086	2.0	-5.086	3.0	-5.086	4.0	-5.086	5.0	-5.086	6.0	-5.086	7.0	-5.086	8.0	-5.086
Time since start [H]	Output Voltage [V]																								
0.0	-5.079																								
0.5	-5.086																								
1.0	-5.086																								
2.0	-5.086																								
3.0	-5.086																								
4.0	-5.086																								
5.0	-5.086																								
6.0	-5.086																								
7.0	-5.086																								
8.0	-5.086																								

**COSEL**

Model	MGW301205
Item	Rise and Fall Time
Object	+5V2.5A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		3.7	6.9	10.6	0.2	0.9
100 %		3.5	7.2	10.7	0.2	0.4




**COSEL**

Model	MGW301205
Item	Rise and Fall Time
Object	-5V2.5A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		3.1	7.6	10.7	0.2	1.0	
100 %		3.0	7.7	10.7	0.2	0.5	



Model	MGW301205
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2.5A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.2	8.2
-40	8.2	8.3
-20	8.2	8.2
0	8.2	8.3
25	8.2	8.3
60	8.2	8.2
65	8.0	8.2
--	-	-
--	-	-
--	-	-
--	-	-

Object	-5V2.5A
--------	---------

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.1	8.1
-40	8.1	8.2
-20	8.1	8.1
0	8.2	8.2
25	8.1	8.2
60	8.1	8.1
65	8.1	8.1
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGW301205	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+5V2.5A																																																								
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p>	2.Values																																																							
Object	-5V2.5A	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>3.47</td><td>4.16</td><td>4.12</td></tr> <tr><td>4.75</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	5.00	3.47	4.16	4.12	4.75	-	-	-	4.50	-	-	-	4.00	-	-	-	3.50	-	-	-	3.00	-	-	-	2.50	-	-	-	2.00	-	-	-	1.50	-	-	-	1.00	-	-	-	0.50	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
5.00	3.47	4.16	4.12																																																						
4.75	-	-	-																																																						
4.50	-	-	-																																																						
4.00	-	-	-																																																						
3.50	-	-	-																																																						
3.00	-	-	-																																																						
2.50	-	-	-																																																						
2.00	-	-	-																																																						
1.50	-	-	-																																																						
1.00	-	-	-																																																						
0.50	-	-	-																																																						
0.00	-	-	-																																																						
Object	-5V2.5A	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-5.00</td><td>3.44</td><td>4.12</td><td>4.11</td></tr> <tr><td>-4.75</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-0.50</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-5.00	3.44	4.12	4.11	-4.75	-	-	-	-4.50	-	-	-	-4.00	-	-	-	-3.50	-	-	-	-3.00	-	-	-	-2.50	-	-	-	-2.00	-	-	-	-1.50	-	-	-	-1.00	-	-	-	-0.50	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																						
-5.00	3.44	4.12	4.11																																																						
-4.75	-	-	-																																																						
-4.50	-	-	-																																																						
-4.00	-	-	-																																																						
-3.50	-	-	-																																																						
-3.00	-	-	-																																																						
-2.50	-	-	-																																																						
-2.00	-	-	-																																																						
-1.50	-	-	-																																																						
-1.00	-	-	-																																																						
-0.50	-	-	-																																																						
0.00	-	-	-																																																						

Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when overcurrent protection is activated.

Model	MGW301205
Item	Oversupply Protection
Object	+10V2.5A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+10V).

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 12[V]	Input Volt. 18[V]
-60	12.74	12.76
-40	12.81	12.82
-20	12.95	12.97
0	13.09	13.10
25	13.29	13.30
60	13.50	13.58
65	13.57	13.58
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)