

TEST DATA OF MGW301212

Regulated DC Power Supply
December 4, 2010

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Figure of Testing Circuitry	23

(Final Page 23)

Model	MGW301212	Temperature Testing Circuitry 25°C Figure A																																																																																	
Item	Input Current (by Input Voltage)																																																																																		
Object	_____	2.Values																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□- - Load 50% - -○--- Load 0%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>2.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>8.2</td><td>0.047</td><td>2.066</td><td>4.260</td></tr> <tr><td>8.5</td><td>0.047</td><td>1.980</td><td>4.078</td></tr> <tr><td>9.0</td><td>0.047</td><td>1.857</td><td>3.870</td></tr> <tr><td>9.2</td><td>0.047</td><td>1.836</td><td>3.776</td></tr> <tr><td>10.0</td><td>0.047</td><td>1.682</td><td>3.482</td></tr> <tr><td>12.0</td><td>0.046</td><td>1.398</td><td>2.890</td></tr> <tr><td>14.0</td><td>0.045</td><td>1.208</td><td>2.460</td></tr> <tr><td>16.0</td><td>0.039</td><td>1.059</td><td>2.160</td></tr> <tr><td>18.0</td><td>0.036</td><td>0.950</td><td>1.928</td></tr> <tr><td>20.0</td><td>0.034</td><td>0.858</td><td>1.732</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	2.0	0.000	0.000	0.000	4.0	0.000	0.000	0.000	6.0	0.000	0.000	0.000	7.0	0.002	0.002	0.002	8.0	0.002	0.002	0.002	8.2	0.047	2.066	4.260	8.5	0.047	1.980	4.078	9.0	0.047	1.857	3.870	9.2	0.047	1.836	3.776	10.0	0.047	1.682	3.482	12.0	0.046	1.398	2.890	14.0	0.045	1.208	2.460	16.0	0.039	1.059	2.160	18.0	0.036	0.950	1.928	20.0	0.034	0.858	1.732	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
2.0	0.000	0.000	0.000																																																																																
4.0	0.000	0.000	0.000																																																																																
6.0	0.000	0.000	0.000																																																																																
7.0	0.002	0.002	0.002																																																																																
8.0	0.002	0.002	0.002																																																																																
8.2	0.047	2.066	4.260																																																																																
8.5	0.047	1.980	4.078																																																																																
9.0	0.047	1.857	3.870																																																																																
9.2	0.047	1.836	3.776																																																																																
10.0	0.047	1.682	3.482																																																																																
12.0	0.046	1.398	2.890																																																																																
14.0	0.045	1.208	2.460																																																																																
16.0	0.039	1.059	2.160																																																																																
18.0	0.036	0.950	1.928																																																																																
20.0	0.034	0.858	1.732																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																

Model	MGW301212																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 9V - -□--- Input Volt. 12V - -○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [A]</th> <th>12V [A]</th> <th>18V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.047</td><td>0.045</td><td>0.037</td></tr> <tr><td>20</td><td>0.781</td><td>0.596</td><td>0.411</td></tr> <tr><td>40</td><td>1.509</td><td>1.139</td><td>0.772</td></tr> <tr><td>60</td><td>2.264</td><td>1.693</td><td>1.137</td></tr> <tr><td>80</td><td>3.010</td><td>2.262</td><td>1.516</td></tr> <tr><td>100</td><td>3.814</td><td>2.846</td><td>1.898</td></tr> <tr><td>110</td><td>4.202</td><td>3.131</td><td>2.098</td></tr> </tbody> </table>	Load Ration [%]	9V [A]	12V [A]	18V [A]	0	0.047	0.045	0.037	20	0.781	0.596	0.411	40	1.509	1.139	0.772	60	2.264	1.693	1.137	80	3.010	2.262	1.516	100	3.814	2.846	1.898	110	4.202	3.131	2.098																						
Load Ration [%]	9V [A]	12V [A]	18V [A]																																																				
0	0.047	0.045	0.037																																																				
20	0.781	0.596	0.411																																																				
40	1.509	1.139	0.772																																																				
60	2.264	1.693	1.137																																																				
80	3.010	2.262	1.516																																																				
100	3.814	2.846	1.898																																																				
110	4.202	3.131	2.098																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.047</td><td>0.045</td><td>0.037</td></tr> <tr><td>20</td><td>0.781</td><td>0.596</td><td>0.411</td></tr> <tr><td>40</td><td>1.509</td><td>1.139</td><td>0.772</td></tr> <tr><td>60</td><td>2.264</td><td>1.693</td><td>1.137</td></tr> <tr><td>80</td><td>3.010</td><td>2.262</td><td>1.516</td></tr> <tr><td>100</td><td>3.814</td><td>2.846</td><td>1.898</td></tr> <tr><td>110</td><td>4.202</td><td>3.131</td><td>2.098</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.047	0.045	0.037	20	0.781	0.596	0.411	40	1.509	1.139	0.772	60	2.264	1.693	1.137	80	3.010	2.262	1.516	100	3.814	2.846	1.898	110	4.202	3.131	2.098	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																				
0	0.047	0.045	0.037																																																				
20	0.781	0.596	0.411																																																				
40	1.509	1.139	0.772																																																				
60	2.264	1.693	1.137																																																				
80	3.010	2.262	1.516																																																				
100	3.814	2.846	1.898																																																				
110	4.202	3.131	2.098																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	MGW301212																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 9V - - -□--- Input Volt. 12V - · -○--- Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>9V [W]</th> <th>12V [W]</th> <th>18V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.42</td><td>0.54</td><td>0.67</td></tr> <tr><td>20</td><td>7.04</td><td>7.13</td><td>7.36</td></tr> <tr><td>40</td><td>13.56</td><td>13.62</td><td>13.85</td></tr> <tr><td>60</td><td>20.25</td><td>20.24</td><td>20.45</td></tr> <tr><td>80</td><td>27.12</td><td>27.06</td><td>27.14</td></tr> <tr><td>100</td><td>34.19</td><td>34.02</td><td>34.10</td></tr> <tr><td>110</td><td>37.82</td><td>37.57</td><td>37.60</td></tr> </tbody> </table>			Load Ration [%]	9V [W]	12V [W]	18V [W]	0	0.42	0.54	0.67	20	7.04	7.13	7.36	40	13.56	13.62	13.85	60	20.25	20.24	20.45	80	27.12	27.06	27.14	100	34.19	34.02	34.10	110	37.82	37.57	37.60																			
Load Ration [%]	9V [W]	12V [W]	18V [W]																																																			
0	0.42	0.54	0.67																																																			
20	7.04	7.13	7.36																																																			
40	13.56	13.62	13.85																																																			
60	20.25	20.24	20.45																																																			
80	27.12	27.06	27.14																																																			
100	34.19	34.02	34.10																																																			
110	37.82	37.57	37.60																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.42</td><td>0.54</td><td>0.67</td></tr> <tr><td>20</td><td>7.04</td><td>7.13</td><td>7.36</td></tr> <tr><td>40</td><td>13.56</td><td>13.62</td><td>13.85</td></tr> <tr><td>60</td><td>20.25</td><td>20.24</td><td>20.45</td></tr> <tr><td>80</td><td>27.12</td><td>27.06</td><td>27.14</td></tr> <tr><td>100</td><td>34.19</td><td>34.02</td><td>34.10</td></tr> <tr><td>110</td><td>37.82</td><td>37.57</td><td>37.60</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	0.42	0.54	0.67	20	7.04	7.13	7.36	40	13.56	13.62	13.85	60	20.25	20.24	20.45	80	27.12	27.06	27.14	100	34.19	34.02	34.10	110	37.82	37.57	37.60	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	0.42	0.54	0.67																																																			
20	7.04	7.13	7.36																																																			
40	13.56	13.62	13.85																																																			
60	20.25	20.24	20.45																																																			
80	27.12	27.06	27.14																																																			
100	34.19	34.02	34.10																																																			
110	37.82	37.57	37.60																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW301212	Temperature Testing Circuitry 25°C Figure A																																
Item	Efficiency (by Input Voltage)																																	
Object	—																																	
1. Graph		2. Values																																
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>89.3</td><td>88.3</td></tr> <tr><td>9.0</td><td>89.6</td><td>88.5</td></tr> <tr><td>10.0</td><td>89.8</td><td>88.8</td></tr> <tr><td>12.0</td><td>89.5</td><td>89.0</td></tr> <tr><td>15.0</td><td>89.1</td><td>89.0</td></tr> <tr><td>18.0</td><td>88.3</td><td>88.8</td></tr> <tr><td>20.0</td><td>88.0</td><td>88.8</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	89.3	88.3	9.0	89.6	88.5	10.0	89.8	88.8	12.0	89.5	89.0	15.0	89.1	89.0	18.0	88.3	88.8	20.0	88.0	88.8	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	89.3	88.3																																
9.0	89.6	88.5																																
10.0	89.8	88.8																																
12.0	89.5	89.0																																
15.0	89.1	89.0																																
18.0	88.3	88.8																																
20.0	88.0	88.8																																
--	-	-																																
--	-	-																																


Note: Slanted line shows the range of the rated input voltage.

Model	MGW301212																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V <table border="1"> <thead> <tr> <th>Load Ration [%]</th> <th>9V [%]</th> <th>12V [%]</th> <th>18V [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>85.0</td><td>85.5</td><td>82.5</td></tr> <tr><td>40</td><td>89.0</td><td>89.5</td><td>88.5</td></tr> <tr><td>60</td><td>89.3</td><td>89.8</td><td>87.4</td></tr> <tr><td>80</td><td>89.3</td><td>89.5</td><td>89.3</td></tr> <tr><td>100</td><td>88.6</td><td>89.0</td><td>88.8</td></tr> <tr><td>110</td><td>88.1</td><td>88.7</td><td>88.6</td></tr> </tbody> </table>			Load Ration [%]	9V [%]	12V [%]	18V [%]	20	85.0	85.5	82.5	40	89.0	89.5	88.5	60	89.3	89.8	87.4	80	89.3	89.5	89.3	100	88.6	89.0	88.8	110	88.1	88.7	88.6																							
Load Ration [%]	9V [%]	12V [%]	18V [%]																																																			
20	85.0	85.5	82.5																																																			
40	89.0	89.5	88.5																																																			
60	89.3	89.8	87.4																																																			
80	89.3	89.5	89.3																																																			
100	88.6	89.0	88.8																																																			
110	88.1	88.7	88.6																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>86.0</td><td>84.9</td><td>82.2</td></tr> <tr><td>40</td><td>89.3</td><td>88.9</td><td>87.4</td></tr> <tr><td>60</td><td>89.7</td><td>89.8</td><td>88.8</td></tr> <tr><td>80</td><td>89.3</td><td>89.5</td><td>89.3</td></tr> <tr><td>100</td><td>88.6</td><td>89.0</td><td>88.8</td></tr> <tr><td>110</td><td>88.1</td><td>88.7</td><td>88.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0	-	-	-	20	86.0	84.9	82.2	40	89.3	88.9	87.4	60	89.7	89.8	88.8	80	89.3	89.5	89.3	100	88.6	89.0	88.8	110	88.1	88.7	88.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0	-	-	-																																																			
20	86.0	84.9	82.2																																																			
40	89.3	88.9	87.4																																																			
60	89.7	89.8	88.8																																																			
80	89.3	89.5	89.3																																																			
100	88.6	89.0	88.8																																																			
110	88.1	88.7	88.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW301212
Item	Line Regulation
Object	+12V1.25A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	12.200	12.093
9.0	12.198	12.093
10.0	12.196	12.093
12.0	12.193	12.092
15.0	12.190	12.092
18.0	12.188	12.091
20.0	12.187	12.091
--	-	-
--	-	-

-12V: Rated output current

Object -12V1.25A

1.Graph




2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	-12.200	-12.093
9.0	-12.199	-12.093
10.0	-12.197	-12.093
12.0	-12.194	-12.094
15.0	-12.192	-12.094
18.0	-12.191	-12.095
20.0	-12.190	-12.095
--	-	-
--	-	-

+12V: Rated output current

Note: Slanted line shows the range of the rated input voltage.

Model	MGW301212	Temperature Testing Circuitry 25°C Figure A																																																				
Item	Load Regulation																																																					
Object	+12V1.25A																																																					
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - · -○- - Input Volt. 18V</p> <table border="1"> <caption>Data for +12V Output Voltage vs Load Current</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V [V]</th> <th>12V [V]</th> <th>18V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.585</td><td>12.589</td><td>12.596</td></tr> <tr><td>0.063</td><td>12.379</td><td>12.392</td><td>12.416</td></tr> <tr><td>0.250</td><td>12.275</td><td>12.267</td><td>12.262</td></tr> <tr><td>0.500</td><td>12.222</td><td>12.215</td><td>12.209</td></tr> <tr><td>0.750</td><td>12.176</td><td>12.172</td><td>12.167</td></tr> <tr><td>1.000</td><td>12.133</td><td>12.131</td><td>12.129</td></tr> <tr><td>1.250</td><td>12.092</td><td>12.092</td><td>12.091</td></tr> <tr><td>1.375</td><td>12.073</td><td>12.073</td><td>12.072</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9V [V]	12V [V]	18V [V]	0.00	12.585	12.589	12.596	0.063	12.379	12.392	12.416	0.250	12.275	12.267	12.262	0.500	12.222	12.215	12.209	0.750	12.176	12.172	12.167	1.000	12.133	12.131	12.129	1.250	12.092	12.092	12.091	1.375	12.073	12.073	12.072	--	-	-	-	--	-	-	-	--	-	-	-					
Load Current [A]	9V [V]	12V [V]	18V [V]																																																			
0.00	12.585	12.589	12.596																																																			
0.063	12.379	12.392	12.416																																																			
0.250	12.275	12.267	12.262																																																			
0.500	12.222	12.215	12.209																																																			
0.750	12.176	12.172	12.167																																																			
1.000	12.133	12.131	12.129																																																			
1.250	12.092	12.092	12.091																																																			
1.375	12.073	12.073	12.072																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.585</td><td>12.589</td><td>12.596</td></tr> <tr><td>0.063</td><td>12.379</td><td>12.392</td><td>12.416</td></tr> <tr><td>0.250</td><td>12.275</td><td>12.267</td><td>12.262</td></tr> <tr><td>0.500</td><td>12.222</td><td>12.215</td><td>12.209</td></tr> <tr><td>0.750</td><td>12.176</td><td>12.172</td><td>12.167</td></tr> <tr><td>1.000</td><td>12.133</td><td>12.131</td><td>12.129</td></tr> <tr><td>1.250</td><td>12.092</td><td>12.092</td><td>12.091</td></tr> <tr><td>1.375</td><td>12.073</td><td>12.073</td><td>12.072</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.000	12.585	12.589	12.596	0.063	12.379	12.392	12.416	0.250	12.275	12.267	12.262	0.500	12.222	12.215	12.209	0.750	12.176	12.172	12.167	1.000	12.133	12.131	12.129	1.250	12.092	12.092	12.091	1.375	12.073	12.073	12.072	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.000	12.585	12.589	12.596																																																			
0.063	12.379	12.392	12.416																																																			
0.250	12.275	12.267	12.262																																																			
0.500	12.222	12.215	12.209																																																			
0.750	12.176	12.172	12.167																																																			
1.000	12.133	12.131	12.129																																																			
1.250	12.092	12.092	12.091																																																			
1.375	12.073	12.073	12.072																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	-12V: Rated output current																																																					
Object	-12V1.25A	2.Values																																																				
1.Graph	<p>—△— Input Volt. 9V - - -□- - Input Volt. 12V - · -○- - Input Volt. 18V</p> <table border="1"> <caption>Data for -12V Output Voltage vs Load Current</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V [V]</th> <th>12V [V]</th> <th>18V [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-12.542</td><td>-12.533</td><td>-12.542</td></tr> <tr><td>0.063</td><td>-12.359</td><td>-12.362</td><td>-12.369</td></tr> <tr><td>0.250</td><td>-12.271</td><td>-12.264</td><td>-12.259</td></tr> <tr><td>0.500</td><td>-12.221</td><td>-12.215</td><td>-12.211</td></tr> <tr><td>0.750</td><td>-12.176</td><td>-12.173</td><td>-12.170</td></tr> <tr><td>1.000</td><td>-12.134</td><td>-12.132</td><td>-12.132</td></tr> <tr><td>1.250</td><td>-12.093</td><td>-12.094</td><td>-12.095</td></tr> <tr><td>1.375</td><td>-12.073</td><td>-12.075</td><td>-12.076</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9V [V]	12V [V]	18V [V]	0.00	-12.542	-12.533	-12.542	0.063	-12.359	-12.362	-12.369	0.250	-12.271	-12.264	-12.259	0.500	-12.221	-12.215	-12.211	0.750	-12.176	-12.173	-12.170	1.000	-12.134	-12.132	-12.132	1.250	-12.093	-12.094	-12.095	1.375	-12.073	-12.075	-12.076	--	-	-	-	--	-	-	-	--	-	-	-					
Load Current [A]	9V [V]	12V [V]	18V [V]																																																			
0.00	-12.542	-12.533	-12.542																																																			
0.063	-12.359	-12.362	-12.369																																																			
0.250	-12.271	-12.264	-12.259																																																			
0.500	-12.221	-12.215	-12.211																																																			
0.750	-12.176	-12.173	-12.170																																																			
1.000	-12.134	-12.132	-12.132																																																			
1.250	-12.093	-12.094	-12.095																																																			
1.375	-12.073	-12.075	-12.076																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	+12V: Rated output current																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						





COSEL

Model	MGW301212	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+12V1.25A																																								
1.Graph			2.Values																																						
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 120 mV, and the X-axis ranges from 0.0 to 1.6 A. Two curves are shown: one for Input Volt. 9V (solid line with open circles) and one for Input Volt. 18V (dashed line with open triangles). Both curves show a slight increase in ripple voltage as load current increases, with a sharp rise near 1.25A. A slanted line indicates the rated load current range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12</td><td>19</td></tr> <tr><td>0.250</td><td>19</td><td>31</td></tr> <tr><td>0.500</td><td>19</td><td>31</td></tr> <tr><td>0.750</td><td>19</td><td>31</td></tr> <tr><td>1.000</td><td>19</td><td>31</td></tr> <tr><td>1.250</td><td>19</td><td>31</td></tr> <tr><td>1.375</td><td>19</td><td>31</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	12	19	0.250	19	31	0.500	19	31	0.750	19	31	1.000	19	31	1.250	19	31	1.375	19	31	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.000	12	19																																							
0.250	19	31																																							
0.500	19	31																																							
0.750	19	31																																							
1.000	19	31																																							
1.250	19	31																																							
1.375	19	31																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																									

COSSEL

Model	MGW301212	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	-12V1.25A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15</td><td>23</td></tr> <tr><td>0.250</td><td>17</td><td>27</td></tr> <tr><td>0.500</td><td>17</td><td>27</td></tr> <tr><td>0.750</td><td>17</td><td>27</td></tr> <tr><td>1.000</td><td>17</td><td>26</td></tr> <tr><td>1.250</td><td>17</td><td>26</td></tr> <tr><td>1.375</td><td>17</td><td>26</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	15	23	0.250	17	27	0.500	17	27	0.750	17	27	1.000	17	26	1.250	17	26	1.375	17	26	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.000	15	23																																							
0.250	17	27																																							
0.500	17	27																																							
0.750	17	27																																							
1.000	17	26																																							
1.250	17	26																																							
1.375	17	26																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

COSEL

Model	MGW301212	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+12V1.25A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>15</td><td>25</td></tr> <tr><td>0.250</td><td>25</td><td>35</td></tr> <tr><td>0.500</td><td>25</td><td>35</td></tr> <tr><td>0.750</td><td>25</td><td>35</td></tr> <tr><td>1.000</td><td>25</td><td>35</td></tr> <tr><td>1.250</td><td>25</td><td>35</td></tr> <tr><td>1.375</td><td>25</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	15	25	0.250	25	35	0.500	25	35	0.750	25	35	1.000	25	35	1.250	25	35	1.375	25	35	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.000	15	25																																							
0.250	25	35																																							
0.500	25	35																																							
0.750	25	35																																							
1.000	25	35																																							
1.250	25	35																																							
1.375	25	35																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									


Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGW301212	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	-12V1.25A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>20</td><td>25</td></tr> <tr><td>0.250</td><td>20</td><td>30</td></tr> <tr><td>0.500</td><td>20</td><td>30</td></tr> <tr><td>0.750</td><td>20</td><td>30</td></tr> <tr><td>1.000</td><td>20</td><td>30</td></tr> <tr><td>1.250</td><td>20</td><td>30</td></tr> <tr><td>1.375</td><td>20</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.000	20	25	0.250	20	30	0.500	20	30	0.750	20	30	1.000	20	30	1.250	20	30	1.375	20	30	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 9 [V]	Input Volt. 18 [V]																																							
0.000	20	25																																							
0.250	20	30																																							
0.500	20	30																																							
0.750	20	30																																							
1.000	20	30																																							
1.250	20	30																																							
1.375	20	30																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Noise Wave Form</p>																																									

Model	MGW301212
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.25A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	53	49
-40	50	48
-20	39	38
0	31	31
25	23	23
60	21	21
65	21	21
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	33	27
-40	37	33
-20	29	27
0	24	24
25	19	19
60	19	19
65	19	19
--	-	-
--	-	-
--	-	-
--	-	-


+12V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGW301212
Item	Ambient Temperature Drift
Object	+12V1.25A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	12.051	12.053	12.053
-40	12.067	12.069	12.070
-20	12.080	12.080	12.081
0	12.088	12.088	12.088
25	12.094	12.093	12.092
60	12.094	12.093	12.092
65	12.093	12.092	12.090
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-12.049	-12.053	-12.054
-40	-12.066	-12.069	-12.072
-20	-12.079	-12.081	-12.083
0	-12.088	-12.089	-12.091
25	-12.093	-12.094	-12.095
60	-12.093	-12.094	-12.094
65	-12.092	-12.092	-12.093
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW301212	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 1.25A (AVR 2) : 0 - 1.25A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Object		+12V1.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	18	0	12.591	±262	±2.2	
Minimum Voltage	-40	9	1.25	12.067			

Object		-12V1.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	9	0	-12.546	±240	±2.0	
Minimum Voltage	-40	9	1.25	-12.066			

COSEL


Model	MGW301212
Item	Time Lapse Drift
Object	+12V1.25A

1.Graph



Object	-12V1.25A
--------	-----------

1.Graph



Temperature 25°C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	12.092
0.5	12.097
1.0	12.097
2.0	12.096
3.0	12.096
4.0	12.096
5.0	12.096
6.0	12.096
7.0	12.096
8.0	12.096

2.Values


Time since start [H]	Output Voltage [V]
0.0	-12.093
0.5	-12.100
1.0	-12.100
2.0	-12.100
3.0	-12.100
4.0	-12.100
5.0	-12.099
6.0	-12.099
7.0	-12.099
8.0	-12.099

COSEL

Model	MGW301212
Item	Rise and Fall Time
Object	+12V1.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.6	6.8	9.4	0.3	1.4	
100 %		2.6	7.4	10.0	0.1	0.7	




COSEL

Model	MGW301212
Item	Rise and Fall Time
Object	-12V1.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.6	7.0	9.6	0.3	1.5	
100 %		2.6	7.2	9.8	0.1	0.8	



Model	MGW301212
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1.25A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.1	8.2
-40	8.1	8.1
-20	8.1	8.1
0	8.1	8.1
25	8.1	8.0
60	8.0	8.0
65	8.0	8.0
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V1.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	8.0	8.1
-40	8.0	8.0
-20	8.0	8.0
0	8.0	8.0
25	8.0	7.9
60	7.9	7.9
65	7.9	7.8
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

Model	MGW301212	Temperature Testing Circuitry 25°C Figure A																																																										
Item	Overcurrent Protection																																																											
Object	+12V1.25A																																																											
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V</p> <p>Input Volt. 12V</p> <p>Input Volt. 18V</p>	2.Values																																																										
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>1.97</td><td>2.24</td><td>1.99</td></tr> <tr><td>11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	12.00	1.97	2.24	1.99	11.40	-	-	-	10.80	-	-	-	9.60	-	-	-	8.40	-	-	-	7.20	-	-	-	6.00	-	-	-	4.80	-	-	-	3.60	-	-	-	2.40	-	-	-	1.20	-	-	-	0.00	-	-	-	
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																									
12.00	1.97	2.24	1.99																																																									
11.40	-	-	-																																																									
10.80	-	-	-																																																									
9.60	-	-	-																																																									
8.40	-	-	-																																																									
7.20	-	-	-																																																									
6.00	-	-	-																																																									
4.80	-	-	-																																																									
3.60	-	-	-																																																									
2.40	-	-	-																																																									
1.20	-	-	-																																																									
0.00	-	-	-																																																									
Object	-12V1.25A	2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-12.00</td><td>1.93</td><td>2.20</td><td>1.98</td></tr> <tr><td>-11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-12.00	1.93	2.20	1.98	-11.40	-	-	-	-10.80	-	-	-	-9.60	-	-	-	-8.40	-	-	-	-7.20	-	-	-	-6.00	-	-	-	-4.80	-	-	-	-3.60	-	-	-	-2.40	-	-	-	-1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																											
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																									
-12.00	1.93	2.20	1.98																																																									
-11.40	-	-	-																																																									
-10.80	-	-	-																																																									
-9.60	-	-	-																																																									
-8.40	-	-	-																																																									
-7.20	-	-	-																																																									
-6.00	-	-	-																																																									
-4.80	-	-	-																																																									
-3.60	-	-	-																																																									
-2.40	-	-	-																																																									
-1.20	-	-	-																																																									
0.00	-	-	-																																																									
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 9V</p> <p>Input Volt. 12V</p> <p>Input Volt. 18V</p>	<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																										

Model	MGW301212
Item	Oversupply Protection
Object	+24V1.25A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 12[V]	Input Volt. 18[V]
-60	32.18	32.18
-40	32.19	32.19
-20	32.19	32.19
0	32.34	32.34
25	32.98	32.98
60	33.84	33.84
65	33.98	33.98
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+24V).

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)