

TEST DATA OF MGW302412

Regulated DC Power Supply
December 7, 2010

Approved by : *Kazunari Asano*
Kazunari Asano Design Manager

Prepared by : *Sho Saito*
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Figure of Testing Circuitry	23

(Final Page 23)



Model		MGW302412		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			2.Values																																																																																	
<p> △ Load 100% □ Load 50% ○ Load 0% </p> <p style="text-align: center;">Input Current [A]</p> <p style="text-align: center;">Input Voltage [V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4.0</td><td>0.001</td><td>0.001</td><td>0.001</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.6</td><td>0.030</td><td>1.026</td><td>2.088</td></tr> <tr><td>17.0</td><td>0.030</td><td>0.999</td><td>2.032</td></tr> <tr><td>18.0</td><td>0.030</td><td>0.935</td><td>1.903</td></tr> <tr><td>20.0</td><td>0.030</td><td>0.833</td><td>1.700</td></tr> <tr><td>22.0</td><td>0.028</td><td>0.756</td><td>1.548</td></tr> <tr><td>24.0</td><td>0.027</td><td>0.697</td><td>1.418</td></tr> <tr><td>28.0</td><td>0.025</td><td>0.600</td><td>1.219</td></tr> <tr><td>30.0</td><td>0.024</td><td>0.560</td><td>1.133</td></tr> <tr><td>32.0</td><td>0.024</td><td>0.527</td><td>1.065</td></tr> <tr><td>36.0</td><td>0.023</td><td>0.472</td><td>0.961</td></tr> <tr><td>40.0</td><td>0.022</td><td>0.427</td><td>0.857</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	4.0	0.001	0.001	0.001	8.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	16.6	0.030	1.026	2.088	17.0	0.030	0.999	2.032	18.0	0.030	0.935	1.903	20.0	0.030	0.833	1.700	22.0	0.028	0.756	1.548	24.0	0.027	0.697	1.418	28.0	0.025	0.600	1.219	30.0	0.024	0.560	1.133	32.0	0.024	0.527	1.065	36.0	0.023	0.472	0.961	40.0	0.022	0.427	0.857	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
4.0	0.001	0.001	0.001																																																																																	
8.0	0.002	0.002	0.002																																																																																	
16.0	0.002	0.002	0.002																																																																																	
16.6	0.030	1.026	2.088																																																																																	
17.0	0.030	0.999	2.032																																																																																	
18.0	0.030	0.935	1.903																																																																																	
20.0	0.030	0.833	1.700																																																																																	
22.0	0.028	0.756	1.548																																																																																	
24.0	0.027	0.697	1.418																																																																																	
28.0	0.025	0.600	1.219																																																																																	
30.0	0.024	0.560	1.133																																																																																	
32.0	0.024	0.527	1.065																																																																																	
36.0	0.023	0.472	0.961																																																																																	
40.0	0.022	0.427	0.857																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																				



COSEL																																																						
Model	MGW302412	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> Input Volt. 18V Input Volt. 24V Input Volt. 36V </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.030</td><td>0.027</td><td>0.022</td></tr> <tr><td>20</td><td>0.395</td><td>0.296</td><td>0.206</td></tr> <tr><td>40</td><td>0.752</td><td>0.562</td><td>0.384</td></tr> <tr><td>60</td><td>1.118</td><td>0.836</td><td>0.566</td></tr> <tr><td>80</td><td>1.487</td><td>1.111</td><td>0.747</td></tr> <tr><td>100</td><td>1.876</td><td>1.397</td><td>0.935</td></tr> <tr><td>110</td><td>2.064</td><td>1.536</td><td>1.030</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.030	0.027	0.022	20	0.395	0.296	0.206	40	0.752	0.562	0.384	60	1.118	0.836	0.566	80	1.487	1.111	0.747	100	1.876	1.397	0.935	110	2.064	1.536	1.030	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	0.030	0.027	0.022																																																			
20	0.395	0.296	0.206																																																			
40	0.752	0.562	0.384																																																			
60	1.118	0.836	0.566																																																			
80	1.487	1.111	0.747																																																			
100	1.876	1.397	0.935																																																			
110	2.064	1.536	1.030																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			



COSEL																																																						
Model	MGW302412	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> </p> <p> △ Input Volt. 18V □ Input Volt. 24V ○ Input Volt. 36V </p>		<p>2.Values</p>																																																				
<p style="text-align: center;">Input Power [W]</p> <p style="text-align: center;">Load Ration [%]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.54</td><td>0.64</td><td>0.80</td></tr> <tr><td>20</td><td>7.14</td><td>7.09</td><td>7.39</td></tr> <tr><td>40</td><td>13.57</td><td>13.51</td><td>13.79</td></tr> <tr><td>60</td><td>20.12</td><td>20.03</td><td>20.29</td></tr> <tr><td>80</td><td>26.83</td><td>26.68</td><td>26.90</td></tr> <tr><td>100</td><td>33.69</td><td>33.48</td><td>33.60</td></tr> <tr><td>110</td><td>37.19</td><td>36.94</td><td>37.05</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.54	0.64	0.80	20	7.14	7.09	7.39	40	13.57	13.51	13.79	60	20.12	20.03	20.29	80	26.83	26.68	26.90	100	33.69	33.48	33.60	110	37.19	36.94	37.05	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	0.54	0.64	0.80																																																			
20	7.14	7.09	7.39																																																			
40	13.57	13.51	13.79																																																			
60	20.12	20.03	20.29																																																			
80	26.83	26.68	26.90																																																			
100	33.69	33.48	33.60																																																			
110	37.19	36.94	37.05																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			




<p>Model MGW302412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																
Item	Efficiency (by Input Voltage)																																	
Object																																		
<p>1. Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>88.9</td> <td>89.2</td> </tr> <tr> <td>18</td> <td>89.8</td> <td>89.8</td> </tr> <tr> <td>20</td> <td>90.5</td> <td>90.2</td> </tr> <tr> <td>24</td> <td>90.3</td> <td>90.4</td> </tr> <tr> <td>30</td> <td>89.6</td> <td>90.2</td> </tr> <tr> <td>36</td> <td>88.7</td> <td>90.0</td> </tr> <tr> <td>40</td> <td>88.1</td> <td>89.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	88.9	89.2	18	89.8	89.8	20	90.5	90.2	24	90.3	90.4	30	89.6	90.2	36	88.7	90.0	40	88.1	89.8	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	88.9	89.2																																
18	89.8	89.8																																
20	90.5	90.2																																
24	90.3	90.4																																
30	89.6	90.2																																
36	88.7	90.0																																
40	88.1	89.8																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model MGW302412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - Input Volt. 24V ···○··· Input Volt. 36V </p> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>84.5</td><td>85.1</td><td>81.9</td></tr> <tr><td>40</td><td>89.1</td><td>89.6</td><td>87.7</td></tr> <tr><td>60</td><td>90.2</td><td>90.6</td><td>89.4</td></tr> <tr><td>80</td><td>90.2</td><td>90.7</td><td>90.0</td></tr> <tr><td>100</td><td>89.8</td><td>90.4</td><td>90.0</td></tr> <tr><td>110</td><td>89.5</td><td>90.1</td><td>89.8</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	84.5	85.1	81.9	40	89.1	89.6	87.7	60	90.2	90.6	89.4	80	90.2	90.7	90.0	100	89.8	90.4	90.0	110	89.5	90.1	89.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	-	-	-																																																		
20	84.5	85.1	81.9																																																		
40	89.1	89.6	87.7																																																		
60	90.2	90.6	89.4																																																		
80	90.2	90.7	90.0																																																		
100	89.8	90.4	90.0																																																		
110	89.5	90.1	89.8																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL																																			
Model	MGW302412	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V1.25A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>12.191</td><td>12.087</td></tr> <tr><td>18</td><td>12.190</td><td>12.087</td></tr> <tr><td>20</td><td>12.188</td><td>12.087</td></tr> <tr><td>24</td><td>12.184</td><td>12.086</td></tr> <tr><td>30</td><td>12.181</td><td>12.085</td></tr> <tr><td>36</td><td>12.179</td><td>12.085</td></tr> <tr><td>40</td><td>12.178</td><td>12.084</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	12.191	12.087	18	12.190	12.087	20	12.188	12.087	24	12.184	12.086	30	12.181	12.085	36	12.179	12.085	40	12.178	12.084	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	12.191	12.087																																	
18	12.190	12.087																																	
20	12.188	12.087																																	
24	12.184	12.086																																	
30	12.181	12.085																																	
36	12.179	12.085																																	
40	12.178	12.084																																	
--	-	-																																	
--	-	-																																	
Object	-12V1.25A																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>-12.192</td><td>-12.087</td></tr> <tr><td>18</td><td>-12.191</td><td>-12.088</td></tr> <tr><td>20</td><td>-12.190</td><td>-12.088</td></tr> <tr><td>24</td><td>-12.188</td><td>-12.089</td></tr> <tr><td>30</td><td>-12.186</td><td>-12.089</td></tr> <tr><td>36</td><td>-12.185</td><td>-12.090</td></tr> <tr><td>40</td><td>-12.184</td><td>-12.090</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	-12.192	-12.087	18	-12.191	-12.088	20	-12.190	-12.088	24	-12.188	-12.089	30	-12.186	-12.089	36	-12.185	-12.090	40	-12.184	-12.090	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
17	-12.192	-12.087																																	
18	-12.191	-12.088																																	
20	-12.190	-12.088																																	
24	-12.188	-12.089																																	
30	-12.186	-12.089																																	
36	-12.185	-12.090																																	
40	-12.184	-12.090																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	12.550	12.549	12.601
0.063	12.307	12.335	12.367
0.250	12.265	12.260	12.255
0.500	12.214	12.207	12.202
0.750	12.169	12.165	12.160
1.000	12.127	12.124	12.121
1.250	12.087	12.086	12.085
1.375	12.068	12.067	12.066
--	-	-	-
--	-	-	-
--	-	-	-

-12V: Rated output current



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	-12.528	-12.525	-12.538
0.063	-12.294	-12.304	-12.317
0.250	-12.262	-12.257	-12.254
0.500	-12.214	-12.209	-12.206
0.750	-12.169	-12.167	-12.165
1.000	-12.128	-12.127	-12.127
1.250	-12.088	-12.089	-12.090
1.375	-12.068	-12.069	-12.072
--	-	-	-
--	-	-	-
--	-	-	-

+12V: Rated output current




Model	MGW302412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V1.25A		


Input Volt. 24 V
 Other output current rated
 Cycle 1000 ms




Min. Load (0A) ←→
 Load 100% (1.25A)



Min. Load (0A) ←→
 Load 50% (0.625A)



Load 50% (0.625A) ←→
 Load 100% (1.25A)






Model	MGW302412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V1.25A		


Input Volt. 24 V
 Other output current rated
 Cycle 1000 ms




Min. Load (0A) ←→
 Load 100% (1.25A)



Min. Load (0A) ←→
 Load 50% (0.625A)




Load 50% (0.625A) ←→
 Load 100% (1.25A)





Model	MGW302412	Temperature	25°C
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B
Object	+12V1.25A		



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	8	15
0.250	14	25
0.500	14	25
0.750	14	25
1.000	14	25
1.250	14	25
1.375	14	25
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Wave Form



Model	MGW302412	Temperature	25°C
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B
Object	-12V1.25A		



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	10	16
0.250	12	19
0.500	12	19
0.750	12	19
1.000	12	18
1.250	12	18
1.375	12	18
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated output current

Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Wave Form



Model	MGW302412	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	+12V1.25A		

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	10	20
0.250	20	30
0.500	20	30
0.750	20	30
1.000	20	30
1.250	20	30
1.375	20	30
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form



Model	MGW302412	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	-12V1.25A		

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 36 [V]
0.000	15	20
0.250	15	20
0.500	15	20
0.750	15	20
1.000	15	20
1.250	15	20
1.375	15	20
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated output current

Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form



Model	MGW302412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V1.25A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	54	50
-40	51	48
-20	50	48
0	43	43
25	35	35
60	31	31
65	31	31
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

Object	-12V1.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	22	17
-40	26	21
-20	28	24
0	25	23
25	22	21
60	23	22
65	23	22
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



COSEL																																																						
Model	MGW302412																																																					
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+12V1.25A																																																					
1.Graph	<p>—△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V</p> <p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.045</td><td>12.046</td><td>12.047</td></tr> <tr><td>-40</td><td>12.062</td><td>12.062</td><td>12.062</td></tr> <tr><td>-20</td><td>12.073</td><td>12.073</td><td>12.073</td></tr> <tr><td>0</td><td>12.081</td><td>12.081</td><td>12.080</td></tr> <tr><td>25</td><td>12.087</td><td>12.086</td><td>12.085</td></tr> <tr><td>60</td><td>12.088</td><td>12.087</td><td>12.085</td></tr> <tr><td>65</td><td>12.087</td><td>12.086</td><td>12.084</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	12.045	12.046	12.047	-40	12.062	12.062	12.062	-20	12.073	12.073	12.073	0	12.081	12.081	12.080	25	12.087	12.086	12.085	60	12.088	12.087	12.085	65	12.087	12.086	12.084	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
-60	12.045	12.046	12.047																																																			
-40	12.062	12.062	12.062																																																			
-20	12.073	12.073	12.073																																																			
0	12.081	12.081	12.080																																																			
25	12.087	12.086	12.085																																																			
60	12.088	12.087	12.085																																																			
65	12.087	12.086	12.084																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V1.25A																																																					
1.Graph	<p>—△— Input Volt. 18V ---□--- Input Volt. 24V -·-○-·- Input Volt. 36V</p> <p style="text-align: center;">Ambient Temperature [°C] Load 100%</p>	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.047</td><td>-12.050</td><td>-12.053</td></tr> <tr><td>-40</td><td>-12.063</td><td>-12.066</td><td>-12.069</td></tr> <tr><td>-20</td><td>-12.074</td><td>-12.077</td><td>-12.079</td></tr> <tr><td>0</td><td>-12.082</td><td>-12.084</td><td>-12.086</td></tr> <tr><td>25</td><td>-12.087</td><td>-12.089</td><td>-12.090</td></tr> <tr><td>60</td><td>-12.087</td><td>-12.088</td><td>-12.090</td></tr> <tr><td>65</td><td>-12.085</td><td>-12.087</td><td>-12.088</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	-12.047	-12.050	-12.053	-40	-12.063	-12.066	-12.069	-20	-12.074	-12.077	-12.079	0	-12.082	-12.084	-12.086	25	-12.087	-12.089	-12.090	60	-12.087	-12.088	-12.090	65	-12.085	-12.087	-12.088	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
-60	-12.047	-12.050	-12.053																																																			
-40	-12.063	-12.066	-12.069																																																			
-20	-12.074	-12.077	-12.079																																																			
0	-12.082	-12.084	-12.086																																																			
25	-12.087	-12.089	-12.090																																																			
60	-12.087	-12.088	-12.090																																																			
65	-12.085	-12.087	-12.088																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		
Model	MGW302412	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 1.25A (AVR 2) : 0 - 1.25A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ration) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+12V1.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	36	0	12.595	±267	±2.2	
Minimum Voltage	-40	18	1.25	12.062			

Object		-12V1.25A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	60	36	0	-12.536	±237	±2.0	
Minimum Voltage	-40	18	1.25	-12.063			




COSEL																								
Model	MGW302412																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+12V1.25A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.086</td></tr> <tr><td>0.5</td><td>12.091</td></tr> <tr><td>1.0</td><td>12.091</td></tr> <tr><td>2.0</td><td>12.091</td></tr> <tr><td>3.0</td><td>12.091</td></tr> <tr><td>4.0</td><td>12.090</td></tr> <tr><td>5.0</td><td>12.090</td></tr> <tr><td>6.0</td><td>12.091</td></tr> <tr><td>7.0</td><td>12.090</td></tr> <tr><td>8.0</td><td>12.091</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.086	0.5	12.091	1.0	12.091	2.0	12.091	3.0	12.091	4.0	12.090	5.0	12.090	6.0	12.091	7.0	12.090	8.0	12.091
Time since start [H]	Output Voltage [V]																							
0.0	12.086																							
0.5	12.091																							
1.0	12.091																							
2.0	12.091																							
3.0	12.091																							
4.0	12.090																							
5.0	12.090																							
6.0	12.091																							
7.0	12.090																							
8.0	12.091																							
Object	-12V1.25A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.089</td></tr> <tr><td>0.5</td><td>-12.095</td></tr> <tr><td>1.0</td><td>-12.094</td></tr> <tr><td>2.0</td><td>-12.094</td></tr> <tr><td>3.0</td><td>-12.094</td></tr> <tr><td>4.0</td><td>-12.094</td></tr> <tr><td>5.0</td><td>-12.094</td></tr> <tr><td>6.0</td><td>-12.094</td></tr> <tr><td>7.0</td><td>-12.094</td></tr> <tr><td>8.0</td><td>-12.094</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.089	0.5	-12.095	1.0	-12.094	2.0	-12.094	3.0	-12.094	4.0	-12.094	5.0	-12.094	6.0	-12.094	7.0	-12.094	8.0	-12.094
Time since start [H]	Output Voltage [V]																							
0.0	-12.089																							
0.5	-12.095																							
1.0	-12.094																							
2.0	-12.094																							
3.0	-12.094																							
4.0	-12.094																							
5.0	-12.094																							
6.0	-12.094																							
7.0	-12.094																							
8.0	-12.094																							



Model		MGW302412	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V1.25A		


1. Graph

Input Volt. 24 V



2. Values

		[ms]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		2.2	7.3	9.5	0.1	1.4
100 %		2.2	7.8	10.0	0.1	0.7






Model		MGW302412	Temperature 25°C Testing Circuitry Figure A
Item		Rise and Fall Time	
Object		-12V1.25A	

1. Graph


Input Volt. 24 V



2. Values

[ms]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	2.2	7.3	9.5	0.1	1.5
100 %	2.2	7.7	9.9	0.1	0.8





<p>Model MGW302412</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +12V1.25A</p>		<p>Testing Circuitry Figure A</p>																																						
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>15.4</td><td>15.4</td></tr> <tr><td>-40</td><td>15.4</td><td>15.4</td></tr> <tr><td>-20</td><td>15.6</td><td>15.5</td></tr> <tr><td>0</td><td>15.5</td><td>15.5</td></tr> <tr><td>25</td><td>15.4</td><td>15.5</td></tr> <tr><td>60</td><td>15.5</td><td>15.5</td></tr> <tr><td>65</td><td>15.5</td><td>15.5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	15.4	15.4	-40	15.4	15.4	-20	15.6	15.5	0	15.5	15.5	25	15.4	15.5	60	15.5	15.5	65	15.5	15.5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	15.4	15.4																																						
-40	15.4	15.4																																						
-20	15.6	15.5																																						
0	15.5	15.5																																						
25	15.4	15.5																																						
60	15.5	15.5																																						
65	15.5	15.5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Object -12V1.25A</p>																																								
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>15.3</td><td>15.3</td></tr> <tr><td>-40</td><td>15.3</td><td>15.3</td></tr> <tr><td>-20</td><td>15.6</td><td>15.4</td></tr> <tr><td>0</td><td>15.4</td><td>15.4</td></tr> <tr><td>25</td><td>15.4</td><td>15.4</td></tr> <tr><td>60</td><td>15.4</td><td>15.4</td></tr> <tr><td>65</td><td>15.4</td><td>15.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	15.3	15.3	-40	15.3	15.3	-20	15.6	15.4	0	15.4	15.4	25	15.4	15.4	60	15.4	15.4	65	15.4	15.3	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-60	15.3	15.3																																						
-40	15.3	15.3																																						
-20	15.6	15.4																																						
0	15.4	15.4																																						
25	15.4	15.4																																						
60	15.4	15.4																																						
65	15.4	15.3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



<p>Model MGW302412</p> <p>Item Overcurrent Protection</p> <p>Object +12V1.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p> —△ Input Volt. 18V —□ Input Volt. 24V —○ Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>2.28</td><td>2.61</td><td>2.66</td></tr> <tr><td>11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	12.00	2.28	2.61	2.66	11.40	-	-	-	10.80	-	-	-	9.60	-	-	-	8.40	-	-	-	7.20	-	-	-	6.00	-	-	-	4.80	-	-	-	3.60	-	-	-	2.40	-	-	-	1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
12.00	2.28	2.61	2.66																																																						
11.40	-	-	-																																																						
10.80	-	-	-																																																						
9.60	-	-	-																																																						
8.40	-	-	-																																																						
7.20	-	-	-																																																						
6.00	-	-	-																																																						
4.80	-	-	-																																																						
3.60	-	-	-																																																						
2.40	-	-	-																																																						
1.20	-	-	-																																																						
0.00	-	-	-																																																						
<p>Object -12V1.25A</p> <p>1.Graph</p> <p> —△ Input Volt. 18V —□ Input Volt. 24V —○ Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-12.00</td><td>2.26</td><td>2.59</td><td>2.65</td></tr> <tr><td>-11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-12.00	2.26	2.59	2.65	-11.40	-	-	-	-10.80	-	-	-	-9.60	-	-	-	-8.40	-	-	-	-7.20	-	-	-	-6.00	-	-	-	-4.80	-	-	-	-3.60	-	-	-	-2.40	-	-	-	-1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
-12.00	2.26	2.59	2.65																																																						
-11.40	-	-	-																																																						
-10.80	-	-	-																																																						
-9.60	-	-	-																																																						
-8.40	-	-	-																																																						
-7.20	-	-	-																																																						
-6.00	-	-	-																																																						
-4.80	-	-	-																																																						
-3.60	-	-	-																																																						
-2.40	-	-	-																																																						
-1.20	-	-	-																																																						
0.00	-	-	-																																																						



COSEL																																								
Model	MGW302412																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+24V1.25A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 24V</p> <p>---□--- Input Volt. 36V</p> </div> <p style="text-align: center;">Ambient Temperature [°C] Load 0%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>31.92</td><td>31.92</td></tr> <tr><td>-40</td><td>31.93</td><td>31.93</td></tr> <tr><td>-20</td><td>31.93</td><td>31.93</td></tr> <tr><td>0</td><td>32.08</td><td>32.08</td></tr> <tr><td>25</td><td>32.72</td><td>32.72</td></tr> <tr><td>60</td><td>33.57</td><td>33.57</td></tr> <tr><td>65</td><td>33.71</td><td>33.71</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 24[V]	Input Volt. 36[V]	-60	31.92	31.92	-40	31.93	31.93	-20	31.93	31.93	0	32.08	32.08	25	32.72	32.72	60	33.57	33.57	65	33.71	33.71	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 24[V]	Input Volt. 36[V]																																						
-60	31.92	31.92																																						
-40	31.93	31.93																																						
-20	31.93	31.93																																						
0	32.08	32.08																																						
25	32.72	32.72																																						
60	33.57	33.57																																						
65	33.71	33.71																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>Measured as a single output(+24V).</p>																																								




Figure A




Figure B (Ripple and Ripple noise Characteristic)