

TEST DATA OF MGW304805

Regulated DC Power Supply
November 18, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Sho Saito
Sho Saito

Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Figure of Testing Circuitry	23

(Final Page 23)

Model	MGW304805	Temperature Testing Circuitry 25°C Figure A																																											
Item	Input Current (by Input Voltage)																																												
Object	_____	2.Values																																											
1.Graph	<p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- - ○- - Load 0%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>10</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>20</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>30</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>35</td><td>0.000</td><td>0.000</td><td>0.900</td></tr> <tr><td>40</td><td>0.000</td><td>0.350</td><td>0.800</td></tr> <tr><td>50</td><td>0.000</td><td>0.300</td><td>0.650</td></tr> <tr><td>60</td><td>0.000</td><td>0.250</td><td>0.500</td></tr> <tr><td>70</td><td>0.000</td><td>0.200</td><td>0.400</td></tr> <tr><td>80</td><td>0.000</td><td>0.180</td><td>0.350</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	10	0.000	0.000	0.000	20	0.000	0.000	0.000	30	0.000	0.000	0.000	35	0.000	0.000	0.900	40	0.000	0.350	0.800	50	0.000	0.300	0.650	60	0.000	0.250	0.500	70	0.000	0.200	0.400	80	0.000	0.180	0.350
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																										
0	0.000	0.000	0.000																																										
10	0.000	0.000	0.000																																										
20	0.000	0.000	0.000																																										
30	0.000	0.000	0.000																																										
35	0.000	0.000	0.900																																										
40	0.000	0.350	0.800																																										
50	0.000	0.300	0.650																																										
60	0.000	0.250	0.500																																										
70	0.000	0.200	0.400																																										
80	0.000	0.180	0.350																																										

Note: Slanted line shows the range of the rated input voltage.

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
8.0	0.000	0.000	0.000
16.0	0.002	0.002	0.002
24.0	0.002	0.002	0.002
28.0	0.002	0.002	0.002
32.0	0.002	0.002	0.002
33.6	0.014	0.435	0.933
34.0	0.014	0.429	0.921
36.0	0.014	0.401	0.867
37.6	0.014	0.382	0.827
40.0	0.014	0.358	0.775
48.0	0.013	0.301	0.644
60.0	0.012	0.243	0.515
70.0	0.012	0.210	0.444
76.0	0.012	0.195	0.409
80.0	0.012	0.186	0.390
--	-	-	-
--	-	-	-





Model	MGW304805																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 36V [A]</th> <th>Input Volt. 48V [A]</th> <th>Input Volt. 76V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.014</td><td>0.013</td><td>0.012</td></tr> <tr><td>20</td><td>0.170</td><td>0.128</td><td>0.085</td></tr> <tr><td>40</td><td>0.326</td><td>0.244</td><td>0.159</td></tr> <tr><td>60</td><td>0.486</td><td>0.363</td><td>0.234</td></tr> <tr><td>80</td><td>0.650</td><td>0.484</td><td>0.309</td></tr> <tr><td>100</td><td>0.818</td><td>0.608</td><td>0.386</td></tr> <tr><td>110</td><td>0.904</td><td>0.672</td><td>0.425</td></tr> </tbody> </table>			Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]	0	0.014	0.013	0.012	20	0.170	0.128	0.085	40	0.326	0.244	0.159	60	0.486	0.363	0.234	80	0.650	0.484	0.309	100	0.818	0.608	0.386	110	0.904	0.672	0.425																			
Load Ration [%]	Input Volt. 36V [A]	Input Volt. 48V [A]	Input Volt. 76V [A]																																																			
0	0.014	0.013	0.012																																																			
20	0.170	0.128	0.085																																																			
40	0.326	0.244	0.159																																																			
60	0.486	0.363	0.234																																																			
80	0.650	0.484	0.309																																																			
100	0.818	0.608	0.386																																																			
110	0.904	0.672	0.425																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.014</td><td>0.013</td><td>0.012</td></tr> <tr><td>20</td><td>0.170</td><td>0.128</td><td>0.085</td></tr> <tr><td>40</td><td>0.326</td><td>0.244</td><td>0.159</td></tr> <tr><td>60</td><td>0.486</td><td>0.363</td><td>0.234</td></tr> <tr><td>80</td><td>0.650</td><td>0.484</td><td>0.309</td></tr> <tr><td>100</td><td>0.818</td><td>0.608</td><td>0.386</td></tr> <tr><td>110</td><td>0.904</td><td>0.672</td><td>0.425</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.014	0.013	0.012	20	0.170	0.128	0.085	40	0.326	0.244	0.159	60	0.486	0.363	0.234	80	0.650	0.484	0.309	100	0.818	0.608	0.386	110	0.904	0.672	0.425	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.014	0.013	0.012																																																			
20	0.170	0.128	0.085																																																			
40	0.326	0.244	0.159																																																			
60	0.486	0.363	0.234																																																			
80	0.650	0.484	0.309																																																			
100	0.818	0.608	0.386																																																			
110	0.904	0.672	0.425																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	MGW304805																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□--- Input Volt. 48V - - -○--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.50</td><td>0.64</td><td>0.96</td></tr> <tr><td>20</td><td>6.12</td><td>6.14</td><td>6.51</td></tr> <tr><td>40</td><td>11.73</td><td>11.72</td><td>12.12</td></tr> <tr><td>60</td><td>17.47</td><td>17.41</td><td>17.79</td></tr> <tr><td>80</td><td>23.33</td><td>23.23</td><td>23.52</td></tr> <tr><td>100</td><td>29.35</td><td>29.16</td><td>29.39</td></tr> <tr><td>110</td><td>32.42</td><td>32.16</td><td>32.34</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0	0.50	0.64	0.96	20	6.12	6.14	6.51	40	11.73	11.72	12.12	60	17.47	17.41	17.79	80	23.33	23.23	23.52	100	29.35	29.16	29.39	110	32.42	32.16	32.34																			
Load Ration [%]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																			
0	0.50	0.64	0.96																																																			
20	6.12	6.14	6.51																																																			
40	11.73	11.72	12.12																																																			
60	17.47	17.41	17.79																																																			
80	23.33	23.23	23.52																																																			
100	29.35	29.16	29.39																																																			
110	32.42	32.16	32.34																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.50</td><td>0.64</td><td>0.96</td></tr> <tr><td>20</td><td>6.12</td><td>6.14</td><td>6.51</td></tr> <tr><td>40</td><td>11.73</td><td>11.72</td><td>12.12</td></tr> <tr><td>60</td><td>17.47</td><td>17.41</td><td>17.79</td></tr> <tr><td>80</td><td>23.33</td><td>23.23</td><td>23.52</td></tr> <tr><td>100</td><td>29.35</td><td>29.16</td><td>29.39</td></tr> <tr><td>110</td><td>32.42</td><td>32.16</td><td>32.34</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.50	0.64	0.96	20	6.12	6.14	6.51	40	11.73	11.72	12.12	60	17.47	17.41	17.79	80	23.33	23.23	23.52	100	29.35	29.16	29.39	110	32.42	32.16	32.34	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.50	0.64	0.96																																																			
20	6.12	6.14	6.51																																																			
40	11.73	11.72	12.12																																																			
60	17.47	17.41	17.79																																																			
80	23.33	23.23	23.52																																																			
100	29.35	29.16	29.39																																																			
110	32.42	32.16	32.34																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	MGW304805																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>33</td><td>86.0</td><td>85.5</td></tr> <tr> <td>36</td><td>87.2</td><td>86.4</td></tr> <tr> <td>40</td><td>87.8</td><td>87.0</td></tr> <tr> <td>48</td><td>87.4</td><td>87.1</td></tr> <tr> <td>55</td><td>86.9</td><td>87.1</td></tr> <tr> <td>60</td><td>86.6</td><td>87.0</td></tr> <tr> <td>70</td><td>85.5</td><td>86.7</td></tr> <tr> <td>76</td><td>85.1</td><td>86.4</td></tr> <tr> <td>80</td><td>84.7</td><td>86.3</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	86.0	85.5	36	87.2	86.4	40	87.8	87.0	48	87.4	87.1	55	86.9	87.1	60	86.6	87.0	70	85.5	86.7	76	85.1	86.4	80	84.7	86.3
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
33	86.0	85.5																																
36	87.2	86.4																																
40	87.8	87.0																																
48	87.4	87.1																																
55	86.9	87.1																																
60	86.6	87.0																																
70	85.5	86.7																																
76	85.1	86.4																																
80	84.7	86.3																																

Model	MGW304805																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>36V [Efficiency %]</th> <th>48V [Efficiency %]</th> <th>76V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>83.0</td><td>82.7</td><td>78.0</td></tr> <tr><td>40</td><td>86.6</td><td>86.7</td><td>83.8</td></tr> <tr><td>60</td><td>87.2</td><td>87.5</td><td>85.7</td></tr> <tr><td>80</td><td>87.1</td><td>87.5</td><td>86.4</td></tr> <tr><td>100</td><td>86.5</td><td>87.1</td><td>86.4</td></tr> <tr><td>110</td><td>86.2</td><td>86.9</td><td>86.4</td></tr> </tbody> </table>			Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]	20	83.0	82.7	78.0	40	86.6	86.7	83.8	60	87.2	87.5	85.7	80	87.1	87.5	86.4	100	86.5	87.1	86.4	110	86.2	86.9	86.4																							
Load Ration [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]																																																			
20	83.0	82.7	78.0																																																			
40	86.6	86.7	83.8																																																			
60	87.2	87.5	85.7																																																			
80	87.1	87.5	86.4																																																			
100	86.5	87.1	86.4																																																			
110	86.2	86.9	86.4																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>83.0</td><td>82.7</td><td>78.0</td></tr> <tr><td>40</td><td>86.6</td><td>86.7</td><td>83.8</td></tr> <tr><td>60</td><td>87.2</td><td>87.5</td><td>85.7</td></tr> <tr><td>80</td><td>87.1</td><td>87.5</td><td>86.4</td></tr> <tr><td>100</td><td>86.5</td><td>87.1</td><td>86.4</td></tr> <tr><td>110</td><td>86.2</td><td>86.9</td><td>86.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	83.0	82.7	78.0	40	86.6	86.7	83.8	60	87.2	87.5	85.7	80	87.1	87.5	86.4	100	86.5	87.1	86.4	110	86.2	86.9	86.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	-	-	-																																																			
20	83.0	82.7	78.0																																																			
40	86.6	86.7	83.8																																																			
60	87.2	87.5	85.7																																																			
80	87.1	87.5	86.4																																																			
100	86.5	87.1	86.4																																																			
110	86.2	86.9	86.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW304805	Temperature Testing Circuitry 25°C Figure A																															
Item	Line Regulation																																
Object	+5V2.5A																																
1.Graph		2.Values																															
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>5.133</td><td>5.070</td></tr> <tr><td>36</td><td>5.130</td><td>5.071</td></tr> <tr><td>40</td><td>5.129</td><td>5.072</td></tr> <tr><td>48</td><td>5.126</td><td>5.072</td></tr> <tr><td>55</td><td>5.124</td><td>5.072</td></tr> <tr><td>60</td><td>5.123</td><td>5.072</td></tr> <tr><td>70</td><td>5.122</td><td>5.072</td></tr> <tr><td>76</td><td>5.122</td><td>5.072</td></tr> <tr><td>80</td><td>5.122</td><td>5.072</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	5.133	5.070	36	5.130	5.071	40	5.129	5.072	48	5.126	5.072	55	5.124	5.072	60	5.123	5.072	70	5.122	5.072	76	5.122	5.072	80	5.122	5.072
Input Voltage [V]	Output Voltage [V]																																
	Load 50%	Load 100%																															
33	5.133	5.070																															
36	5.130	5.071																															
40	5.129	5.072																															
48	5.126	5.072																															
55	5.124	5.072																															
60	5.123	5.072																															
70	5.122	5.072																															
76	5.122	5.072																															
80	5.122	5.072																															
		-5V: Rated output current																															
Object	-5V2.5A	2.Values																															
1.Graph																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-5.142</td><td>-5.078</td></tr> <tr><td>36</td><td>-5.139</td><td>-5.078</td></tr> <tr><td>40</td><td>-5.136</td><td>-5.077</td></tr> <tr><td>48</td><td>-5.132</td><td>-5.077</td></tr> <tr><td>55</td><td>-5.131</td><td>-5.077</td></tr> <tr><td>60</td><td>-5.130</td><td>-5.077</td></tr> <tr><td>70</td><td>-5.128</td><td>-5.077</td></tr> <tr><td>76</td><td>-5.128</td><td>-5.077</td></tr> <tr><td>80</td><td>-5.127</td><td>-5.077</td></tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-5.142	-5.078	36	-5.139	-5.078	40	-5.136	-5.077	48	-5.132	-5.077	55	-5.131	-5.077	60	-5.130	-5.077	70	-5.128	-5.077	76	-5.128	-5.077	80	-5.127	-5.077
Input Voltage [V]	Output Voltage [V]																																
	Load 50%	Load 100%																															
33	-5.142	-5.078																															
36	-5.139	-5.078																															
40	-5.136	-5.077																															
48	-5.132	-5.077																															
55	-5.131	-5.077																															
60	-5.130	-5.077																															
70	-5.128	-5.077																															
76	-5.128	-5.077																															
80	-5.127	-5.077																															
		+5V: Rated output current																															
Note: Slanted line shows the range of the rated input voltage.																																	

Model	MGW304805	Temperature 25°C Testing Circuitry Figure A																																																				
Item	Load Regulation																																																					
Object	+5V2.5A																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - · -○- - Input Volt. 76V</p>  <table border="1"> <caption>Data for Graph 1 (+5V2.5A)</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.610</td><td>5.636</td><td>5.733</td></tr> <tr><td>0.40</td><td>5.201</td><td>5.192</td><td>5.187</td></tr> <tr><td>0.80</td><td>5.164</td><td>5.157</td><td>5.151</td></tr> <tr><td>1.20</td><td>5.139</td><td>5.134</td><td>5.129</td></tr> <tr><td>1.60</td><td>5.117</td><td>5.113</td><td>5.110</td></tr> <tr><td>2.00</td><td>5.096</td><td>5.094</td><td>5.092</td></tr> <tr><td>2.40</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.50</td><td>5.070</td><td>5.071</td><td>5.071</td></tr> <tr><td>2.75</td><td>5.058</td><td>5.060</td><td>5.061</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	5.610	5.636	5.733	0.40	5.201	5.192	5.187	0.80	5.164	5.157	5.151	1.20	5.139	5.134	5.129	1.60	5.117	5.113	5.110	2.00	5.096	5.094	5.092	2.40	5.075	5.075	5.075	2.50	5.070	5.071	5.071	2.75	5.058	5.060	5.061	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																			
0.0	5.610	5.636	5.733																																																			
0.40	5.201	5.192	5.187																																																			
0.80	5.164	5.157	5.151																																																			
1.20	5.139	5.134	5.129																																																			
1.60	5.117	5.113	5.110																																																			
2.00	5.096	5.094	5.092																																																			
2.40	5.075	5.075	5.075																																																			
2.50	5.070	5.071	5.071																																																			
2.75	5.058	5.060	5.061																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.610</td><td>5.636</td><td>5.733</td></tr> <tr><td>0.40</td><td>5.201</td><td>5.192</td><td>5.187</td></tr> <tr><td>0.80</td><td>5.164</td><td>5.157</td><td>5.151</td></tr> <tr><td>1.20</td><td>5.139</td><td>5.134</td><td>5.129</td></tr> <tr><td>1.60</td><td>5.117</td><td>5.113</td><td>5.110</td></tr> <tr><td>2.00</td><td>5.096</td><td>5.094</td><td>5.092</td></tr> <tr><td>2.40</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.50</td><td>5.070</td><td>5.071</td><td>5.071</td></tr> <tr><td>2.75</td><td>5.058</td><td>5.060</td><td>5.061</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	5.610	5.636	5.733	0.40	5.201	5.192	5.187	0.80	5.164	5.157	5.151	1.20	5.139	5.134	5.129	1.60	5.117	5.113	5.110	2.00	5.096	5.094	5.092	2.40	5.075	5.075	5.075	2.50	5.070	5.071	5.071	2.75	5.058	5.060	5.061	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	5.610	5.636	5.733																																																			
0.40	5.201	5.192	5.187																																																			
0.80	5.164	5.157	5.151																																																			
1.20	5.139	5.134	5.129																																																			
1.60	5.117	5.113	5.110																																																			
2.00	5.096	5.094	5.092																																																			
2.40	5.075	5.075	5.075																																																			
2.50	5.070	5.071	5.071																																																			
2.75	5.058	5.060	5.061																																																			
--	-	-	-																																																			
--	-	-	-																																																			
		-5V: Rated output current																																																				
Object	-5V2.5A	2.Values																																																				
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - · -○- - Input Volt. 76V</p>  <table border="1"> <caption>Data for Graph 1 (-5V2.5A)</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.587</td><td>-5.597</td><td>-5.678</td></tr> <tr><td>0.40</td><td>-5.203</td><td>-5.192</td><td>-5.184</td></tr> <tr><td>0.80</td><td>-5.169</td><td>-5.161</td><td>-5.154</td></tr> <tr><td>1.20</td><td>-5.145</td><td>-5.138</td><td>-5.133</td></tr> <tr><td>1.60</td><td>-5.123</td><td>-5.118</td><td>-5.115</td></tr> <tr><td>2.00</td><td>-5.102</td><td>-5.099</td><td>-5.097</td></tr> <tr><td>2.40</td><td>-5.083</td><td>-5.081</td><td>-5.081</td></tr> <tr><td>2.50</td><td>-5.078</td><td>-5.077</td><td>-5.077</td></tr> <tr><td>2.75</td><td>-5.066</td><td>-5.066</td><td>-5.066</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	-5.587	-5.597	-5.678	0.40	-5.203	-5.192	-5.184	0.80	-5.169	-5.161	-5.154	1.20	-5.145	-5.138	-5.133	1.60	-5.123	-5.118	-5.115	2.00	-5.102	-5.099	-5.097	2.40	-5.083	-5.081	-5.081	2.50	-5.078	-5.077	-5.077	2.75	-5.066	-5.066	-5.066	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																			
0.0	-5.587	-5.597	-5.678																																																			
0.40	-5.203	-5.192	-5.184																																																			
0.80	-5.169	-5.161	-5.154																																																			
1.20	-5.145	-5.138	-5.133																																																			
1.60	-5.123	-5.118	-5.115																																																			
2.00	-5.102	-5.099	-5.097																																																			
2.40	-5.083	-5.081	-5.081																																																			
2.50	-5.078	-5.077	-5.077																																																			
2.75	-5.066	-5.066	-5.066																																																			
--	-	-	-																																																			
--	-	-	-																																																			
		+5V: Rated output current																																																				
Note: Slanted line shows the range of the rated load current.																																																						
Model	MGW304805	Temperature 25°C Testing Circuitry Figure A																																																				
Item	Load Regulation																																																					
Object	+5V2.5A																																																					
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - · -○- - Input Volt. 76V</p>  <table border="1"> <caption>Data for Graph 1 (+5V2.5A)</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.610</td><td>5.636</td><td>5.733</td></tr> <tr><td>0.40</td><td>5.201</td><td>5.192</td><td>5.187</td></tr> <tr><td>0.80</td><td>5.164</td><td>5.157</td><td>5.151</td></tr> <tr><td>1.20</td><td>5.139</td><td>5.134</td><td>5.129</td></tr> <tr><td>1.60</td><td>5.117</td><td>5.113</td><td>5.110</td></tr> <tr><td>2.00</td><td>5.096</td><td>5.094</td><td>5.092</td></tr> <tr><td>2.40</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.50</td><td>5.070</td><td>5.071</td><td>5.071</td></tr> <tr><td>2.75</td><td>5.058</td><td>5.060</td><td>5.061</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	5.610	5.636	5.733	0.40	5.201	5.192	5.187	0.80	5.164	5.157	5.151	1.20	5.139	5.134	5.129	1.60	5.117	5.113	5.110	2.00	5.096	5.094	5.092	2.40	5.075	5.075	5.075	2.50	5.070	5.071	5.071	2.75	5.058	5.060	5.061	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																			
0.0	5.610	5.636	5.733																																																			
0.40	5.201	5.192	5.187																																																			
0.80	5.164	5.157	5.151																																																			
1.20	5.139	5.134	5.129																																																			
1.60	5.117	5.113	5.110																																																			
2.00	5.096	5.094	5.092																																																			
2.40	5.075	5.075	5.075																																																			
2.50	5.070	5.071	5.071																																																			
2.75	5.058	5.060	5.061																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.610</td><td>5.636</td><td>5.733</td></tr> <tr><td>0.40</td><td>5.201</td><td>5.192</td><td>5.187</td></tr> <tr><td>0.80</td><td>5.164</td><td>5.157</td><td>5.151</td></tr> <tr><td>1.20</td><td>5.139</td><td>5.134</td><td>5.129</td></tr> <tr><td>1.60</td><td>5.117</td><td>5.113</td><td>5.110</td></tr> <tr><td>2.00</td><td>5.096</td><td>5.094</td><td>5.092</td></tr> <tr><td>2.40</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>2.50</td><td>5.070</td><td>5.071</td><td>5.071</td></tr> <tr><td>2.75</td><td>5.058</td><td>5.060</td><td>5.061</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	5.610	5.636	5.733	0.40	5.201	5.192	5.187	0.80	5.164	5.157	5.151	1.20	5.139	5.134	5.129	1.60	5.117	5.113	5.110	2.00	5.096	5.094	5.092	2.40	5.075	5.075	5.075	2.50	5.070	5.071	5.071	2.75	5.058	5.060	5.061	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.00	5.610	5.636	5.733																																																			
0.40	5.201	5.192	5.187																																																			
0.80	5.164	5.157	5.151																																																			
1.20	5.139	5.134	5.129																																																			
1.60	5.117	5.113	5.110																																																			
2.00	5.096	5.094	5.092																																																			
2.40	5.075	5.075	5.075																																																			
2.50	5.070	5.071	5.071																																																			
2.75	5.058	5.060	5.061																																																			
--	-	-	-																																																			
--	-	-	-																																																			
		-5V: Rated output current																																																				
Object	-5V2.5A	2.Values																																																				
1.Graph	<p>—△— Input Volt. 36V - - -□- - Input Volt. 48V - · -○- - Input Volt. 76V</p>  <table border="1"> <caption>Data for Graph 1 (-5V2.5A)</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.587</td><td>-5.597</td><td>-5.678</td></tr> <tr><td>0.40</td><td>-5.203</td><td>-5.192</td><td>-5.184</td></tr> <tr><td>0.80</td><td>-5.169</td><td>-5.161</td><td>-5.154</td></tr> <tr><td>1.20</td><td>-5.145</td><td>-5.138</td><td>-5.133</td></tr> <tr><td>1.60</td><td>-5.123</td><td>-5.118</td><td>-5.115</td></tr> <tr><td>2.00</td><td>-5.102</td><td>-5.099</td><td>-5.097</td></tr> <tr><td>2.40</td><td>-5.083</td><td>-5.081</td><td>-5.081</td></tr> <tr><td>2.50</td><td>-5.078</td><td>-5.077</td><td>-5.077</td></tr> <tr><td>2.75</td><td>-5.066</td><td>-5.066</td><td>-5.066</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	-5.587	-5.597	-5.678	0.40	-5.203	-5.192	-5.184	0.80	-5.169	-5.161	-5.154	1.20	-5.145	-5.138	-5.133	1.60	-5.123	-5.118	-5.115	2.00	-5.102	-5.099	-5.097	2.40	-5.083	-5.081	-5.081	2.50	-5.078	-5.077	-5.077	2.75	-5.066	-5.066	-5.066	--	-	-	-	--	-	-	-					
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																			
0.0	-5.587	-5.597	-5.678																																																			
0.40	-5.203	-5.192	-5.184																																																			
0.80	-5.169	-5.161	-5.154																																																			
1.20	-5.145	-5.138	-5.133																																																			
1.60	-5.123	-5.118	-5.115																																																			
2.00	-5.102	-5.099	-5.097																																																			
2.40	-5.083	-5.081	-5.081																																																			
2.50	-5.078	-5.077	-5.077																																																			
2.75	-5.066	-5.066	-5.066																																																			
--	-	-	-																																																			
--	-	-	-																																																			
		+5V: Rated output current																																																				
Note: Slanted line shows the range of the rated load current.																																																						





COSEL

Model	MGW304805																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+5V2.5A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.50</td><td>3</td><td>4</td></tr> <tr><td>1.00</td><td>3</td><td>4</td></tr> <tr><td>1.50</td><td>3</td><td>4</td></tr> <tr><td>2.00</td><td>5</td><td>5</td></tr> <tr><td>2.50</td><td>5</td><td>5</td></tr> <tr><td>2.75</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	2	2	0.50	3	4	1.00	3	4	1.50	3	4	2.00	5	5	2.50	5	5	2.75	5	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	2	2																																						
0.50	3	4																																						
1.00	3	4																																						
1.50	3	4																																						
2.00	5	5																																						
2.50	5	5																																						
2.75	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-5V: Rated output current																																								
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

Model	MGW304805	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	-5V2.5A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.50</td><td>3</td><td>4</td></tr> <tr><td>1.00</td><td>3</td><td>4</td></tr> <tr><td>1.50</td><td>3</td><td>4</td></tr> <tr><td>2.00</td><td>3</td><td>4</td></tr> <tr><td>2.50</td><td>3</td><td>4</td></tr> <tr><td>2.75</td><td>3</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	2	2	0.50	3	4	1.00	3	4	1.50	3	4	2.00	3	4	2.50	3	4	2.75	3	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.00	2	2																																							
0.50	3	4																																							
1.00	3	4																																							
1.50	3	4																																							
2.00	3	4																																							
2.50	3	4																																							
2.75	3	4																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

Model	MGW304805	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple-Noise																																							
Object	+5V2.5A																																							
1.Graph	<p>1. Graph</p> <p>—△— Input Volt. 36V</p> <p>-·○- Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>	2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>10</td><td>10</td></tr> <tr><td>1.00</td><td>10</td><td>10</td></tr> <tr><td>1.50</td><td>10</td><td>10</td></tr> <tr><td>2.00</td><td>10</td><td>10</td></tr> <tr><td>2.50</td><td>10</td><td>10</td></tr> <tr><td>2.75</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	5	5	0.50	10	10	1.00	10	10	1.50	10	10	2.00	10	10	2.50	10	10	2.75	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	5	5																																						
0.50	10	10																																						
1.00	10	10																																						
1.50	10	10																																						
2.00	10	10																																						
2.50	10	10																																						
2.75	10	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								



Model	MGW304805																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-5V2.5A																																							
1. Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 150 mV, and the X-axis ranges from 0.0 to 3.0 A. Two sets of data points are shown for Input Voltages 36V (solid line with open triangles) and 76V (dashed line with open circles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (36V)</th> <th>Ripple Voltage [mV] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>5</td><td>10</td></tr> <tr><td>1.00</td><td>5</td><td>10</td></tr> <tr><td>1.50</td><td>5</td><td>10</td></tr> <tr><td>2.00</td><td>5</td><td>10</td></tr> <tr><td>2.50</td><td>5</td><td>10</td></tr> <tr><td>2.75</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (36V)	Ripple Voltage [mV] (76V)	0.0	5	5	0.50	5	10	1.00	5	10	1.50	5	10	2.00	5	10	2.50	5	10	2.75	5	10	--	-	-	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (36V)	Ripple Voltage [mV] (76V)																																						
0.0	5	5																																						
0.50	5	10																																						
1.00	5	10																																						
1.50	5	10																																						
2.00	5	10																																						
2.50	5	10																																						
2.75	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>5</td><td>10</td></tr> <tr><td>1.00</td><td>5</td><td>10</td></tr> <tr><td>1.50</td><td>5</td><td>10</td></tr> <tr><td>2.00</td><td>5</td><td>10</td></tr> <tr><td>2.50</td><td>5</td><td>10</td></tr> <tr><td>2.75</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+5V: Rated output current</p>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.00	5	5	0.50	5	10	1.00	5	10	1.50	5	10	2.00	5	10	2.50	5	10	2.75	5	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.00	5	5																																						
0.50	5	10																																						
1.00	5	10																																						
1.50	5	10																																						
2.00	5	10																																						
2.50	5	10																																						
2.75	5	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								


Model	MGW304805
-------	-----------

Item	Ripple Voltage (by Ambient Temp.)
------	-----------------------------------

Object	+5V2.5A
--------	---------

1.Graph

--- □ --- Load 50%
— △ — Load 100%



Testing Circuitry Figure A

2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	15	16
-40	10	11
-20	8	9
0	7	8
25	6	6
60	4	5
65	4	5
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

Object	-5V2.5A
--------	---------

1.Graph

--- □ --- Load 50%
— △ — Load 100%



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	12	11
-40	8	8
-20	6	6
0	5	5
25	4	4
60	3	3
65	3	3
--	-	-
--	-	-
--	-	-
--	-	-


+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGW304805
Item	Ambient Temperature Drift
Object	+5V2.5A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	5.051	5.052	5.053
-40	5.059	5.060	5.061
-20	5.065	5.066	5.066
0	5.069	5.070	5.070
25	5.071	5.072	5.072
60	5.071	5.072	5.072
65	5.071	5.071	5.071
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-5.054	-5.054	-5.056
-40	-5.062	-5.063	-5.063
-20	-5.069	-5.069	-5.070
0	-5.073	-5.073	-5.073
25	-5.077	-5.076	-5.076
60	-5.078	-5.077	-5.077
65	-5.078	-5.077	-5.076
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW304805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 2.5A (AVR 2) : 0 - 2.5A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$




$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	-40	76	0	5.818	±380	±7.6	
Minimum Voltage	-40	36	2.5	5.059			

Object		-5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Output		Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	-40	76	0	-5.764	±351	±7.0	
Minimum Voltage	-40	36	2.5	-5.062			

COSEL


Model	MGW304805	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V2.5A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.071</td></tr> <tr><td>0.5</td><td>5.070</td></tr> <tr><td>1.0</td><td>5.070</td></tr> <tr><td>2.0</td><td>5.070</td></tr> <tr><td>3.0</td><td>5.070</td></tr> <tr><td>4.0</td><td>5.070</td></tr> <tr><td>5.0</td><td>5.070</td></tr> <tr><td>6.0</td><td>5.070</td></tr> <tr><td>7.0</td><td>5.070</td></tr> <tr><td>8.0</td><td>5.070</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.071	0.5	5.070	1.0	5.070	2.0	5.070	3.0	5.070	4.0	5.070	5.0	5.070	6.0	5.070	7.0	5.070	8.0	5.070
Time since start [H]	Output Voltage [V]																								
0.0	5.071																								
0.5	5.070																								
1.0	5.070																								
2.0	5.070																								
3.0	5.070																								
4.0	5.070																								
5.0	5.070																								
6.0	5.070																								
7.0	5.070																								
8.0	5.070																								
Object			2.Values																						
1.Graph			 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.077</td></tr> <tr><td>0.5</td><td>-5.083</td></tr> <tr><td>1.0</td><td>-5.083</td></tr> <tr><td>2.0</td><td>-5.083</td></tr> <tr><td>3.0</td><td>-5.083</td></tr> <tr><td>4.0</td><td>-5.083</td></tr> <tr><td>5.0</td><td>-5.084</td></tr> <tr><td>6.0</td><td>-5.084</td></tr> <tr><td>7.0</td><td>-5.084</td></tr> <tr><td>8.0</td><td>-5.084</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-5.077	0.5	-5.083	1.0	-5.083	2.0	-5.083	3.0	-5.083	4.0	-5.083	5.0	-5.084	6.0	-5.084	7.0	-5.084	8.0	-5.084
Time since start [H]	Output Voltage [V]																								
0.0	-5.077																								
0.5	-5.083																								
1.0	-5.083																								
2.0	-5.083																								
3.0	-5.083																								
4.0	-5.083																								
5.0	-5.084																								
6.0	-5.084																								
7.0	-5.084																								
8.0	-5.084																								

COSEL

Model	MGW304805
Item	Rise and Fall Time
Object	+5V2.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.5	9.0	11.5	2.3	0.5	
100 %		2.5	8.8	11.3	1.2	0.3	




COSEL

Model	
Item	Rise and Fall Time
Object	-5V2.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.5	9.0	11.5	2.3	0.6	
100 %		2.5	9.0	11.5	1.2	0.4	




Model MGW304805

Item Minimum Input Voltage
for Regulated Output Voltage

Object +5V2.5A

1.Graph

--- □--- Load 50%
—△— Load 100%



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	31.8	31.7
-40	31.7	31.6
-20	31.7	31.6
0	31.3	31.6
25	31.4	31.3
60	31.3	31.3
65	31.3	31.3
--	-	-
--	-	-
--	-	-
--	-	-

Object -5V2.5A

1.Graph



--- □--- Load 50%
—△— Load 100%



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	31.5	31.5
-40	31.6	31.5
-20	31.5	31.4
0	31.2	31.5
25	31.2	31.1
60	31.1	31.1
65	31.1	31.1
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

Model	MGW304805	Temperature Testing Circuitry 25°C Figure A
Item	Overcurrent Protection	
Object	+5V2.5A	
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values
Object	-5V2.5A	
1.Graph	 <p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 	2.Values
Note: Slanted line shows the range of the rated load current.		
Intermittent operation occurs when overcurrent protection is activated.		

Model	MGW304805
Item	Oversupply Protection
Object	+10V2.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-60	13.29	13.29
-40	13.36	13.36
-20	13.51	13.51
0	13.65	13.65
25	13.86	13.86
60	14.08	14.15
65	14.15	14.15
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+10V).

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)