

# TEST DATA OF MGW304812

Regulated DC Power Supply  
November 18, 2010

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Sho Saito  
Sho Saito Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)



<b>COSEL</b>																																																																																		
Model	MGW304812	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
<p>1.Graph</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> </div> <div style="width: 45%;"> <p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- · -○- · - Load 0%</p> </div> </div>		<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>24.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>28.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>32.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>33.2</td><td>0.019</td><td>0.520</td><td>1.047</td></tr> <tr><td>34.0</td><td>0.019</td><td>0.505</td><td>1.021</td></tr> <tr><td>36.0</td><td>0.019</td><td>0.473</td><td>0.963</td></tr> <tr><td>37.6</td><td>0.019</td><td>0.453</td><td>0.918</td></tr> <tr><td>40.0</td><td>0.019</td><td>0.424</td><td>0.861</td></tr> <tr><td>48.0</td><td>0.018</td><td>0.357</td><td>0.717</td></tr> <tr><td>60.0</td><td>0.017</td><td>0.291</td><td>0.577</td></tr> <tr><td>70.0</td><td>0.016</td><td>0.253</td><td>0.498</td></tr> <tr><td>76.0</td><td>0.016</td><td>0.235</td><td>0.460</td></tr> <tr><td>80.0</td><td>0.016</td><td>0.225</td><td>0.438</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.002	0.002	0.002	16.0	0.002	0.002	0.002	24.0	0.002	0.002	0.002	28.0	0.002	0.002	0.002	32.0	0.002	0.002	0.002	33.2	0.019	0.520	1.047	34.0	0.019	0.505	1.021	36.0	0.019	0.473	0.963	37.6	0.019	0.453	0.918	40.0	0.019	0.424	0.861	48.0	0.018	0.357	0.717	60.0	0.017	0.291	0.577	70.0	0.016	0.253	0.498	76.0	0.016	0.235	0.460	80.0	0.016	0.225	0.438	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
8.0	0.002	0.002	0.002																																																																															
16.0	0.002	0.002	0.002																																																																															
24.0	0.002	0.002	0.002																																																																															
28.0	0.002	0.002	0.002																																																																															
32.0	0.002	0.002	0.002																																																																															
33.2	0.019	0.520	1.047																																																																															
34.0	0.019	0.505	1.021																																																																															
36.0	0.019	0.473	0.963																																																																															
37.6	0.019	0.453	0.918																																																																															
40.0	0.019	0.424	0.861																																																																															
48.0	0.018	0.357	0.717																																																																															
60.0	0.017	0.291	0.577																																																																															
70.0	0.016	0.253	0.498																																																																															
76.0	0.016	0.235	0.460																																																																															
80.0	0.016	0.225	0.438																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																		



Model		MGW304812		Temperature 25°C																																																				
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph			2.Values																																																					
<p>                 —△— Input Volt. 36V                  - - - □ - - Input Volt. 48V                  - · - ○ - · - Input Volt. 76V             </p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.019</td><td>0.018</td><td>0.016</td></tr> <tr><td>20</td><td>0.207</td><td>0.157</td><td>0.108</td></tr> <tr><td>40</td><td>0.385</td><td>0.291</td><td>0.193</td></tr> <tr><td>60</td><td>0.567</td><td>0.427</td><td>0.279</td></tr> <tr><td>80</td><td>0.754</td><td>0.566</td><td>0.366</td></tr> <tr><td>100</td><td>0.947</td><td>0.708</td><td>0.454</td></tr> <tr><td>110</td><td>1.045</td><td>0.779</td><td>0.499</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.019	0.018	0.016	20	0.207	0.157	0.108	40	0.385	0.291	0.193	60	0.567	0.427	0.279	80	0.754	0.566	0.366	100	0.947	0.708	0.454	110	1.045	0.779	0.499	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0	0.019	0.018	0.016																																																					
20	0.207	0.157	0.108																																																					
40	0.385	0.291	0.193																																																					
60	0.567	0.427	0.279																																																					
80	0.754	0.566	0.366																																																					
100	0.947	0.708	0.454																																																					
110	1.045	0.779	0.499																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



<b>COSEL</b>																																																						
Model	MGW304812	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> <span style="display: inline-block; width: 10px; border-bottom: 1px solid black; margin-right: 5px;"></span> <span style="display: inline-block; width: 10px; border-bottom: 1px dashed black; margin-right: 5px;"></span> <span style="display: inline-block; width: 10px; border-bottom: 1px dash-dot black; margin-right: 5px;"></span> </p> <p> <span style="display: inline-block; width: 10px; border-bottom: 1px solid black; margin-right: 5px;"></span> △ — Input Volt. 36V  <span style="display: inline-block; width: 10px; border-bottom: 1px dashed black; margin-right: 5px;"></span> □ --- Input Volt. 48V  <span style="display: inline-block; width: 10px; border-bottom: 1px dash-dot black; margin-right: 5px;"></span> ○ -.- Input Volt. 76V                 </p>		<p>2.Values</p>																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.68</td><td>0.88</td><td>1.23</td></tr> <tr><td>20</td><td>7.43</td><td>7.54</td><td>8.18</td></tr> <tr><td>40</td><td>13.84</td><td>13.93</td><td>14.68</td></tr> <tr><td>60</td><td>20.40</td><td>20.45</td><td>21.18</td></tr> <tr><td>80</td><td>27.13</td><td>27.11</td><td>27.76</td></tr> <tr><td>100</td><td>34.03</td><td>33.94</td><td>34.49</td></tr> <tr><td>110</td><td>37.61</td><td>37.39</td><td>37.91</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.68	0.88	1.23	20	7.43	7.54	8.18	40	13.84	13.93	14.68	60	20.40	20.45	21.18	80	27.13	27.11	27.76	100	34.03	33.94	34.49	110	37.61	37.39	37.91	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.68	0.88	1.23																																																			
20	7.43	7.54	8.18																																																			
40	13.84	13.93	14.68																																																			
60	20.40	20.45	21.18																																																			
80	27.13	27.11	27.76																																																			
100	34.03	33.94	34.49																																																			
110	37.61	37.39	37.91																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			




<b>COSEL</b>																																			
Model	MGW304812	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>87.1</td><td>87.7</td></tr> <tr><td>36</td><td>88.3</td><td>88.5</td></tr> <tr><td>40</td><td>88.6</td><td>89.0</td></tr> <tr><td>48</td><td>87.8</td><td>89.0</td></tr> <tr><td>55</td><td>87.0</td><td>88.8</td></tr> <tr><td>60</td><td>86.5</td><td>88.6</td></tr> <tr><td>70</td><td>85.0</td><td>88.0</td></tr> <tr><td>76</td><td>84.3</td><td>87.6</td></tr> <tr><td>80</td><td>83.7</td><td>87.4</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	33	87.1	87.7	36	88.3	88.5	40	88.6	89.0	48	87.8	89.0	55	87.0	88.8	60	86.5	88.6	70	85.0	88.0	76	84.3	87.6	80	83.7	87.4
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
33	87.1	87.7																																	
36	88.3	88.5																																	
40	88.6	89.0																																	
48	87.8	89.0																																	
55	87.0	88.8																																	
60	86.5	88.6																																	
70	85.0	88.0																																	
76	84.3	87.6																																	
80	83.7	87.4																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model MGW304812</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Efficiency (by Load Current)																																																				
Object	_____																																																				
<p>1.Graph</p> <p>                     —△— Input Volt. 36V                      - - □ - - Input Volt. 48V                      - - ○ - - Input Volt. 76V                 </p> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>81.4</td><td>80.2</td><td>73.9</td></tr> <tr><td>40</td><td>87.3</td><td>86.7</td><td>82.3</td></tr> <tr><td>60</td><td>88.9</td><td>88.6</td><td>85.6</td></tr> <tr><td>80</td><td>89.1</td><td>89.2</td><td>87.1</td></tr> <tr><td>100</td><td>88.8</td><td>89.1</td><td>87.7</td></tr> <tr><td>110</td><td>88.4</td><td>88.9</td><td>87.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	81.4	80.2	73.9	40	87.3	86.7	82.3	60	88.9	88.6	85.6	80	89.1	89.2	87.1	100	88.8	89.1	87.7	110	88.4	88.9	87.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	81.4	80.2	73.9																																																		
40	87.3	86.7	82.3																																																		
60	88.9	88.6	85.6																																																		
80	89.1	89.2	87.1																																																		
100	88.8	89.1	87.7																																																		
110	88.4	88.9	87.7																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



<b>COSEL</b>																																			
Model	MGW304812	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V1.25A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>12.180</td><td>12.090</td></tr> <tr><td>36</td><td>12.179</td><td>12.091</td></tr> <tr><td>40</td><td>12.178</td><td>12.092</td></tr> <tr><td>48</td><td>12.176</td><td>12.092</td></tr> <tr><td>55</td><td>12.175</td><td>12.093</td></tr> <tr><td>60</td><td>12.174</td><td>12.093</td></tr> <tr><td>70</td><td>12.173</td><td>12.093</td></tr> <tr><td>76</td><td>12.173</td><td>12.094</td></tr> <tr><td>80</td><td>12.172</td><td>12.094</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	12.180	12.090	36	12.179	12.091	40	12.178	12.092	48	12.176	12.092	55	12.175	12.093	60	12.174	12.093	70	12.173	12.093	76	12.173	12.094	80	12.172	12.094
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	12.180	12.090																																	
36	12.179	12.091																																	
40	12.178	12.092																																	
48	12.176	12.092																																	
55	12.175	12.093																																	
60	12.174	12.093																																	
70	12.173	12.093																																	
76	12.173	12.094																																	
80	12.172	12.094																																	
Object	-12V1.25A																																		
<p>1.Graph</p> <p style="text-align: right;">             ---□--- Load 50%              —△— Load 100%         </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>33</td><td>-12.181</td><td>-12.086</td></tr> <tr><td>36</td><td>-12.179</td><td>-12.085</td></tr> <tr><td>40</td><td>-12.176</td><td>-12.085</td></tr> <tr><td>48</td><td>-12.172</td><td>-12.084</td></tr> <tr><td>55</td><td>-12.169</td><td>-12.084</td></tr> <tr><td>60</td><td>-12.169</td><td>-12.083</td></tr> <tr><td>70</td><td>-12.167</td><td>-12.083</td></tr> <tr><td>76</td><td>-12.166</td><td>-12.082</td></tr> <tr><td>80</td><td>-12.166</td><td>-12.083</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated output current</p>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	33	-12.181	-12.086	36	-12.179	-12.085	40	-12.176	-12.085	48	-12.172	-12.084	55	-12.169	-12.084	60	-12.169	-12.083	70	-12.167	-12.083	76	-12.166	-12.082	80	-12.166	-12.083
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
33	-12.181	-12.086																																	
36	-12.179	-12.085																																	
40	-12.176	-12.085																																	
48	-12.172	-12.084																																	
55	-12.169	-12.084																																	
60	-12.169	-12.083																																	
70	-12.167	-12.083																																	
76	-12.166	-12.082																																	
80	-12.166	-12.083																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			




Temperature 25°C  
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.000	12.471	12.474	12.487
0.063	12.278	12.269	12.263
0.200	12.254	12.251	12.246
0.400	12.217	12.214	12.209
0.600	12.185	12.183	12.180
0.800	12.155	12.154	12.152
1.000	12.126	12.127	12.126
1.200	12.098	12.099	12.100
1.250	12.091	12.093	12.094
1.375	12.073	12.076	12.078
--	-	-	-

-12V: Rated output current



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.000	-12.505	-12.485	-12.532
0.063	-12.287	-12.284	-12.282
0.200	-12.261	-12.255	-12.250
0.400	-12.217	-12.210	-12.203
0.600	-12.184	-12.177	-12.171
0.800	-12.152	-12.147	-12.143
1.000	-12.122	-12.118	-12.115
1.200	-12.092	-12.091	-12.089
1.250	-12.086	-12.084	-12.083
1.375	-12.068	-12.067	-12.066
--	-	-	-

+12V: Rated output current




Model	MGW304812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V1.25A		


Input Volt. 48 V  
 Other output current rated  
 Cycle 1000 ms




Min. Load (0A) ←→  
 Load 100% (1.25A)



Min. Load (0A) ←→  
 Load 50% (0.625A)



Load 50% (0.625A) ←→  
 Load 100% (1.25A)






Model	MGW304812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V1.25A		


Input Volt. 48 V  
 Other output current rated  
 Cycle 1000 ms




Min. Load (0A) ←→  
 Load 100% (1.25A)



Min. Load (0A) ←→  
 Load 50% (0.625A)




Load 50% (0.625A) ←→  
 Load 100% (1.25A)





Model	MGW304812	Temperature	25°C
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B
Object	+12V1.25A		

1.Graph



2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	8	15
0.250	10	19
0.500	10	19
0.750	10	19
1.000	11	19
1.250	11	19
1.375	11	19
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

Ripple Voltage is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.

Ripple [mVp-p]




Fig.Complex Ripple Wave Form




<p>Model MGW304812</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object -12V1.25A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 36V</p> <p>- -○- - Input Volt. 76V</p> </div> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>8</td><td>14</td></tr> <tr><td>0.250</td><td>15</td><td>27</td></tr> <tr><td>0.500</td><td>15</td><td>27</td></tr> <tr><td>0.750</td><td>15</td><td>27</td></tr> <tr><td>1.000</td><td>15</td><td>25</td></tr> <tr><td>1.250</td><td>15</td><td>25</td></tr> <tr><td>1.375</td><td>15</td><td>25</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	8	14	0.250	15	27	0.500	15	27	0.750	15	27	1.000	15	25	1.250	15	25	1.375	15	25	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.000	8	14																																						
0.250	15	27																																						
0.500	15	27																																						
0.750	15	27																																						
1.000	15	25																																						
1.250	15	25																																						
1.375	15	25																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



Model	MGW304812	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	+12V1.25A		

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	10	20
0.250	15	25
0.500	15	25
0.750	15	25
1.000	15	25
1.250	15	25
1.375	15	25
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current

Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.





Fig.Complex Ripple Noise Wave Form

Model	MGW304812	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure B
Object	-12V1.25A		



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 36 [V]	Input Volt. 76 [V]
0.000	15	20
0.250	20	30
0.500	20	30
0.750	20	30
1.000	20	30
1.250	20	30
1.375	20	30
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated output current

Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.




Fig.Complex Ripple Noise Wave Form



<b>COSEL</b>																																											
Model	MGW304812	Testing Circuitry Figure A																																									
Item	Ripple Voltage (by Ambient Temp.)																																										
Object	+12V1.25A																																										
<p>1.Graph</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 48V</p>		<p>2.Values</p> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>22</td><td>16</td></tr> <tr><td>-40</td><td>27</td><td>22</td></tr> <tr><td>-20</td><td>30</td><td>27</td></tr> <tr><td>0</td><td>28</td><td>26</td></tr> <tr><td>25</td><td>25</td><td>25</td></tr> <tr><td>60</td><td>24</td><td>23</td></tr> <tr><td>65</td><td>24</td><td>23</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated output current</p>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	22	16	-40	27	22	-20	30	27	0	28	26	25	25	25	60	24	23	65	24	23	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Ripple Voltage [mV]																																										
	Load 50%	Load 100%																																									
-60	22	16																																									
-40	27	22																																									
-20	30	27																																									
0	28	26																																									
25	25	25																																									
60	24	23																																									
65	24	23																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
Object	-12V1.25A	Testing Circuitry Figure A																																									
<p>1.Graph</p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: center;">Input Volt. 48V</p> <p>Measured by 100 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>				<p>2.Values</p> <table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>52</td><td>44</td></tr> <tr><td>-40</td><td>47</td><td>42</td></tr> <tr><td>-20</td><td>46</td><td>42</td></tr> <tr><td>0</td><td>41</td><td>38</td></tr> <tr><td>25</td><td>36</td><td>34</td></tr> <tr><td>60</td><td>33</td><td>32</td></tr> <tr><td>65</td><td>33</td><td>32</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated output current</p>		Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	52	44	-40	47	42	-20	46	42	0	41	38	25	36	34	60	33	32	65	33	32	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																										
	Load 50%	Load 100%																																									
-60	52	44																																									
-40	47	42																																									
-20	46	42																																									
0	41	38																																									
25	36	34																																									
60	33	32																																									
65	33	32																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									



<b>COSEL</b>																																																						
Model	MGW304812	Testing Circuitry Figure A																																																				
Item	Ambient Temperature Drift																																																					
Object	+12V1.25A																																																					
1.Graph		—△— Input Volt. 36V - - - □ - - - Input Volt. 48V - · - ○ - · - - Input Volt. 76V	2.Values																																																			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.032</td><td>12.035</td><td>12.037</td></tr> <tr><td>-40</td><td>12.054</td><td>12.057</td><td>12.059</td></tr> <tr><td>-20</td><td>12.072</td><td>12.074</td><td>12.076</td></tr> <tr><td>0</td><td>12.083</td><td>12.085</td><td>12.087</td></tr> <tr><td>25</td><td>12.091</td><td>12.094</td><td>12.094</td></tr> <tr><td>60</td><td>12.093</td><td>12.094</td><td>12.095</td></tr> <tr><td>65</td><td>12.092</td><td>12.093</td><td>12.094</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	12.032	12.035	12.037	-40	12.054	12.057	12.059	-20	12.072	12.074	12.076	0	12.083	12.085	12.087	25	12.091	12.094	12.094	60	12.093	12.094	12.095	65	12.092	12.093	12.094	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-60	12.032	12.035	12.037																																																			
-40	12.054	12.057	12.059																																																			
-20	12.072	12.074	12.076																																																			
0	12.083	12.085	12.087																																																			
25	12.091	12.094	12.094																																																			
60	12.093	12.094	12.095																																																			
65	12.092	12.093	12.094																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object		-12V1.25A																																																				
1.Graph		—△— Input Volt. 36V - - - □ - - - Input Volt. 48V - · - ○ - · - - Input Volt. 76V	2.Values																																																			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.025</td><td>-12.025</td><td>-12.025</td></tr> <tr><td>-40</td><td>-12.048</td><td>-12.047</td><td>-12.047</td></tr> <tr><td>-20</td><td>-12.065</td><td>-12.064</td><td>-12.064</td></tr> <tr><td>0</td><td>-12.077</td><td>-12.075</td><td>-12.075</td></tr> <tr><td>25</td><td>-12.085</td><td>-12.084</td><td>-12.083</td></tr> <tr><td>60</td><td>-12.087</td><td>-12.086</td><td>-12.084</td></tr> <tr><td>65</td><td>-12.086</td><td>-12.085</td><td>-12.083</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	-12.025	-12.025	-12.025	-40	-12.048	-12.047	-12.047	-20	-12.065	-12.064	-12.064	0	-12.077	-12.075	-12.075	25	-12.085	-12.084	-12.083	60	-12.087	-12.086	-12.084	65	-12.086	-12.085	-12.083	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
-60	-12.025	-12.025	-12.025																																																			
-40	-12.048	-12.047	-12.047																																																			
-20	-12.065	-12.064	-12.064																																																			
0	-12.077	-12.075	-12.075																																																			
25	-12.085	-12.084	-12.083																																																			
60	-12.087	-12.086	-12.084																																																			
65	-12.086	-12.085	-12.083																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated ambient temperature.																																																						



<b>COSEL</b>		
Model	MGW304812	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 36 - 76V

Load Current (AVR 1) : 0 - 1.25A (AVR 2) : 0 - 1.25A

\* Other Output : Rated Load

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ration) =  $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Object		+12V1.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	76	0	12.495	±221	±1.8
Minimum Voltage	-40	36	1.25	12.054		

Object		-12V1.25A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	76	0	-12.538	±246	±2.1
Minimum Voltage	-40	76	1.25	-12.047		




<b>COSEL</b>																									
Model	MGW304812	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V1.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt.     48V Load                100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.093</td></tr> <tr><td>0.5</td><td>12.100</td></tr> <tr><td>1.0</td><td>12.100</td></tr> <tr><td>2.0</td><td>12.100</td></tr> <tr><td>3.0</td><td>12.100</td></tr> <tr><td>4.0</td><td>12.100</td></tr> <tr><td>5.0</td><td>12.100</td></tr> <tr><td>6.0</td><td>12.100</td></tr> <tr><td>7.0</td><td>12.100</td></tr> <tr><td>8.0</td><td>12.100</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	12.093	0.5	12.100	1.0	12.100	2.0	12.100	3.0	12.100	4.0	12.100	5.0	12.100	6.0	12.100	7.0	12.100	8.0	12.100
Time since start [H]	Output Voltage [V]																								
0.0	12.093																								
0.5	12.100																								
1.0	12.100																								
2.0	12.100																								
3.0	12.100																								
4.0	12.100																								
5.0	12.100																								
6.0	12.100																								
7.0	12.100																								
8.0	12.100																								
Object	-12V1.25A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt.     48V Load                100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.084</td></tr> <tr><td>0.5</td><td>-12.092</td></tr> <tr><td>1.0</td><td>-12.092</td></tr> <tr><td>2.0</td><td>-12.092</td></tr> <tr><td>3.0</td><td>-12.092</td></tr> <tr><td>4.0</td><td>-12.092</td></tr> <tr><td>5.0</td><td>-12.092</td></tr> <tr><td>6.0</td><td>-12.092</td></tr> <tr><td>7.0</td><td>-12.092</td></tr> <tr><td>8.0</td><td>-12.092</td></tr> </tbody> </table>		Time since start [H]	Output Voltage [V]	0.0	-12.084	0.5	-12.092	1.0	-12.092	2.0	-12.092	3.0	-12.092	4.0	-12.092	5.0	-12.092	6.0	-12.092	7.0	-12.092	8.0	-12.092
Time since start [H]	Output Voltage [V]																								
0.0	-12.084																								
0.5	-12.092																								
1.0	-12.092																								
2.0	-12.092																								
3.0	-12.092																								
4.0	-12.092																								
5.0	-12.092																								
6.0	-12.092																								
7.0	-12.092																								
8.0	-12.092																								



Model		MGW304812	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		+12V1.25A		


1. Graph

Input Volt. 48 V



2. Values

		[ms]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		2.4	7.0	9.4	0.1	1.4
100 %		2.5	7.4	9.9	0.1	0.7






Model		MGW304812	Temperature	25°C
Item		Rise and Fall Time	Testing Circuitry	Figure A
Object		-12V1.25A		


1. Graph

Input Volt. 48 V



2. Values

		[ms]				
Load \ Time	Time	Td	Tr	Ts	Th	Tf
50 %		2.5	6.9	9.4	0.1	1.4
100 %		2.5	7.4	9.9	0.1	0.7






Model	MGW304812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V1.25A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	31.6	31.5
-40	31.7	31.5
-20	31.5	31.5
0	31.2	31.6
25	31.2	31.2
60	31.2	31.1
65	31.2	31.1
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V1.25A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	31.4	31.4
-40	31.5	31.4
-20	31.3	31.2
0	31.1	31.4
25	31.0	30.9
60	31.0	30.9
65	31.0	30.9
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<p>Model MGW304812</p>		<p>Temperature 25°C</p>																																																								
<p>Item Overcurrent Protection</p>		<p>Testing Circuitry Figure A</p>																																																								
<p>Object +12V1.25A</p>																																																										
<p>1.Graph</p> <p> <span style="color: black;">—△</span> Input Volt. 36V  <span style="color: blue;">—□</span> Input Volt. 48V  <span style="color: orange;">—○</span> Input Volt. 76V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>1.93</td><td>2.13</td><td>2.04</td></tr> <tr><td>11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.00	1.93	2.13	2.04	11.40	-	-	-	10.80	-	-	-	9.60	-	-	-	8.40	-	-	-	7.20	-	-	-	6.00	-	-	-	4.80	-	-	-	3.60	-	-	-	2.40	-	-	-	1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
12.00	1.93	2.13	2.04																																																							
11.40	-	-	-																																																							
10.80	-	-	-																																																							
9.60	-	-	-																																																							
8.40	-	-	-																																																							
7.20	-	-	-																																																							
6.00	-	-	-																																																							
4.80	-	-	-																																																							
3.60	-	-	-																																																							
2.40	-	-	-																																																							
1.20	-	-	-																																																							
0.00	-	-	-																																																							
<p>Object -12V1.25A</p>																																																										
<p>1.Graph</p> <p> <span style="color: black;">—△</span> Input Volt. 36V  <span style="color: blue;">—□</span> Input Volt. 48V  <span style="color: orange;">—○</span> Input Volt. 76V                 </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-12.00</td><td>1.88</td><td>2.12</td><td>2.03</td></tr> <tr><td>-11.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-8.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.80</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-3.60</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-2.40</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-1.20</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-12.00	1.88	2.12	2.03	-11.40	-	-	-	-10.80	-	-	-	-9.60	-	-	-	-8.40	-	-	-	-7.20	-	-	-	-6.00	-	-	-	-4.80	-	-	-	-3.60	-	-	-	-2.40	-	-	-	-1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
-12.00	1.88	2.12	2.03																																																							
-11.40	-	-	-																																																							
-10.80	-	-	-																																																							
-9.60	-	-	-																																																							
-8.40	-	-	-																																																							
-7.20	-	-	-																																																							
-6.00	-	-	-																																																							
-4.80	-	-	-																																																							
-3.60	-	-	-																																																							
-2.40	-	-	-																																																							
-1.20	-	-	-																																																							
0.00	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>																																																										



<b>COSEL</b>																																								
Model	MGW304812																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+24V1.25A																																							
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 48V</p> <p>---□--- Input Volt. 76V</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>Measured as a single output(+24V).</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>32.27</td><td>32.30</td></tr> <tr><td>-40</td><td>32.28</td><td>32.31</td></tr> <tr><td>-20</td><td>32.28</td><td>32.31</td></tr> <tr><td>0</td><td>32.43</td><td>32.46</td></tr> <tr><td>25</td><td>33.08</td><td>33.11</td></tr> <tr><td>60</td><td>33.94</td><td>33.97</td></tr> <tr><td>65</td><td>34.08</td><td>34.11</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 48[V]	Input Volt. 76[V]	-60	32.27	32.30	-40	32.28	32.31	-20	32.28	32.31	0	32.43	32.46	25	33.08	33.11	60	33.94	33.97	65	34.08	34.11	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 48[V]	Input Volt. 76[V]																																						
-60	32.27	32.30																																						
-40	32.28	32.31																																						
-20	32.28	32.31																																						
0	32.43	32.46																																						
25	33.08	33.11																																						
60	33.94	33.97																																						
65	34.08	34.11																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




Figure A




Figure B (Ripple and Ripple noise Characteristic)