

TEST DATA OF MGW61215

Regulated DC Power Supply

November 1, 2016

Approved by : Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Ratio (by Load Ratio)	2
3.Input Power (by Load Ratio)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Ratio)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Switching Frequency (by Load Current)	22
19.Figure of Testing Circuitry	23


(Final Page 23)

COSEL

Model	MGW61215																																																																																	
Item	Input Current (by Input Voltage)	Temperature 25°C	Testing Circuitry Figure A																																																																															
Object	—	—	—																																																																															
1.Graph			2.Values																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.001</td></tr> <tr><td>8.2</td><td>0.003</td><td>0.006</td><td>0.001</td></tr> <tr><td>8.4</td><td>0.033</td><td>0.418</td><td>0.840</td></tr> <tr><td>8.6</td><td>0.034</td><td>0.409</td><td>0.819</td></tr> <tr><td>8.8</td><td>0.033</td><td>0.401</td><td>0.798</td></tr> <tr><td>9.0</td><td>0.032</td><td>0.393</td><td>0.783</td></tr> <tr><td>10.0</td><td>0.031</td><td>0.352</td><td>0.698</td></tr> <tr><td>12.0</td><td>0.022</td><td>0.295</td><td>0.580</td></tr> <tr><td>16.0</td><td>0.012</td><td>0.222</td><td>0.431</td></tr> <tr><td>18.0</td><td>0.011</td><td>0.201</td><td>0.387</td></tr> <tr><td>20.0</td><td>0.009</td><td>0.181</td><td>0.348</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.003	0.003	0.004	8.0	0.003	0.003	0.001	8.2	0.003	0.006	0.001	8.4	0.033	0.418	0.840	8.6	0.034	0.409	0.819	8.8	0.033	0.401	0.798	9.0	0.032	0.393	0.783	10.0	0.031	0.352	0.698	12.0	0.022	0.295	0.580	16.0	0.012	0.222	0.431	18.0	0.011	0.201	0.387	20.0	0.009	0.181	0.348	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
6.0	0.003	0.003	0.004																																																																															
8.0	0.003	0.003	0.001																																																																															
8.2	0.003	0.006	0.001																																																																															
8.4	0.033	0.418	0.840																																																																															
8.6	0.034	0.409	0.819																																																																															
8.8	0.033	0.401	0.798																																																																															
9.0	0.032	0.393	0.783																																																																															
10.0	0.031	0.352	0.698																																																																															
12.0	0.022	0.295	0.580																																																																															
16.0	0.012	0.222	0.431																																																																															
18.0	0.011	0.201	0.387																																																																															
20.0	0.009	0.181	0.348																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	MGW61215
Item	Input Current (by Load Ratio)
Object	_____



 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0	0.032	0.022	0.011
20	0.175	0.134	0.092
40	0.318	0.241	0.167
60	0.468	0.349	0.239
80	0.610	0.458	0.308
100	0.783	0.580	0.387
110	0.828	0.623	0.420
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGW61215
Item	Input Power (by Load Ratio)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Ratio [%]	Input Power [W]		
	9[V]	12[V]	18[V]
0	0.27	0.23	0.18
20	1.56	1.60	1.65
40	2.85	2.88	2.98
60	4.15	4.15	4.27
80	5.51	5.48	5.54
100	6.84	6.81	6.87
110	7.50	7.50	7.55
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGW61215
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.6	86.6	88.1
9.0	85.9	88.5
10.0	86.0	88.4
12.0	85.5	88.6
15.0	85.3	88.5
18.0	84.8	87.8
20.0	84.0	87.6
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGW61215
Item	Efficiency (by Load Ratio)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Ratio [%]	Efficiency [%]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0	-	-	-
20	77.0	75.3	72.9
40	84.2	83.5	80.7
60	87.2	87.0	84.6
80	88.0	88.2	87.2
100	88.5	88.6	87.8
110	88.5	88.5	88.0
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGW61215
Item	Line Regulation
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	15.169	15.081
9.0	15.168	15.082
10.0	15.167	15.082
12.0	15.164	15.082
15.0	15.161	15.083
18.0	15.159	15.082
20.0	15.157	15.081
--	-	-
--	-	-

-15V: Rated Load Current

Object -15V0.2A

1.Graph



2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	-15.182	-15.092
9.0	-15.182	-15.092
10.0	-15.179	-15.092
12.0	-15.176	-15.092
15.0	-15.173	-15.092
18.0	-15.170	-15.091
20.0	-15.169	-15.090
--	-	-
--	-	-

+15V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGW61215
Item	Load Regulation
Object	+15V0.2A




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.00	15.368	15.351	15.334
0.04	15.248	15.239	15.230
0.08	15.194	15.188	15.181
0.12	15.152	15.149	15.144
0.16	15.116	15.114	15.112
0.20	15.082	15.082	15.082
0.22	15.065	15.067	15.067
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

-15V: Rated Load Current



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
0.00	-15.385	-15.367	-15.350
0.04	-15.260	-15.252	-15.243
0.08	-15.205	-15.198	-15.191
0.12	-15.162	-15.158	-15.153
0.16	-15.126	-15.124	-15.120
0.20	-15.092	-15.092	-15.091
0.22	-15.076	-15.077	-15.077
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

+15V: Rated Load Current

Note: Slanted line shows the range of the rated load current.

COSEL


Model	MGW61215	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.2A		

Input Volt. 12 V

-15V:rated load current.

Cycle 100 ms


t1,t2 = 100 μ s



Min.Load (0A)↔
Load 100% (0.2A)

200 mV/div

4 ms/div




4 ms/div

Min.Load (0A)↔
Load 50% (0.1A)

200 mV/div

4 ms/div




4 ms/div


Load 50% (0.1A)↔
Load 100% (0.2A)

200 mV/div

4 ms/div



4 ms/div

COSEL

COSEL

Model	MGW61215																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																					
Object	+15V0.2A																																						
1.Graph																																							
		2.Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>5</td><td>5</td></tr> <tr><td>0.16</td><td>5</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>5</td></tr> <tr><td>0.22</td><td>10</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	5	5	0.16	5	5	0.20	10	5	0.22	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 9 [V]	Input Volt. 18 [V]																																					
0.00	5	5																																					
0.04	5	5																																					
0.08	5	5																																					
0.12	5	5																																					
0.16	5	5																																					
0.20	10	5																																					
0.22	10	5																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
-15V: Rated Load Current																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Ripple [mVp-p]</p>																																							
<p>Fig.Complex Ripple Wave Form</p>																																							

COSEL

Model	MGW61215																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.00 to 0.25 A. Two curves are plotted: one for Input Volt. 9V (solid line with open circles) and one for Input Volt. 18V (dashed line with open circles). Both curves remain near zero until a load current of about 0.15A, after which they rise sharply. A slanted line indicates the rated load current range from 0.15A to 0.20A.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>5</td> <td>5</td> </tr> <tr> <td>0.04</td> <td>5</td> <td>5</td> </tr> <tr> <td>0.08</td> <td>5</td> <td>5</td> </tr> <tr> <td>0.12</td> <td>5</td> <td>5</td> </tr> <tr> <td>0.16</td> <td>5</td> <td>5</td> </tr> <tr> <td>0.20</td> <td>10</td> <td>5</td> </tr> <tr> <td>0.22</td> <td>10</td> <td>5</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	5	5	0.16	5	5	0.20	10	5	0.22	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	5	5																																						
0.04	5	5																																						
0.08	5	5																																						
0.12	5	5																																						
0.16	5	5																																						
0.20	10	5																																						
0.22	10	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGW61215																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 9V (triangles) and Input Volt. 18V (circles). Both sets show a sharp increase in ripple voltage starting around 0.18 A, indicated by a slanted line.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>5</td><td>5</td></tr> <tr><td>0.16</td><td>10</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>10</td></tr> <tr><td>0.22</td><td>15</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	5	5	0.16	10	5	0.20	10	10	0.22	15	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	5	5																																						
0.04	5	5																																						
0.08	5	5																																						
0.12	5	5																																						
0.16	10	5																																						
0.20	10	10																																						
0.22	15	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								


COSEL

Model	MGW61215																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.2A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 18 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.04</td><td>5</td><td>5</td></tr> <tr><td>0.08</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>5</td><td>5</td></tr> <tr><td>0.16</td><td>10</td><td>5</td></tr> <tr><td>0.20</td><td>10</td><td>10</td></tr> <tr><td>0.22</td><td>15</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 9 [V]	Input Volt. 18 [V]	0.00	5	5	0.04	5	5	0.08	5	5	0.12	5	5	0.16	10	5	0.20	10	10	0.22	15	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 9 [V]	Input Volt. 18 [V]																																						
0.00	5	5																																						
0.04	5	5																																						
0.08	5	5																																						
0.12	5	5																																						
0.16	10	5																																						
0.20	10	10																																						
0.22	15	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGW61215
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.2A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	5
0	5	5
25	5	5
80	5	5
85	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	5
0	5	5
25	5	5
80	5	5
85	5	5
--	-	-
--	-	-
--	-	-
--	-	-


+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGW61215
Item	Ambient Temperature Drift
Object	+15V0.2A




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	14.990	14.991	14.990
-40	15.022	15.022	15.022
-20	15.047	15.048	15.047
0	15.066	15.067	15.066
25	15.082	15.082	15.082
80	15.090	15.091	15.091
85	15.089	15.091	15.090
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

-15V: Rated Load Current



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
-60	-14.995	-14.996	-14.995
-40	-15.028	-15.029	-15.028
-20	-15.055	-15.055	-15.054
0	-15.075	-15.076	-15.074
25	-15.092	-15.092	-15.091
80	-15.102	-15.103	-15.101
85	-15.102	-15.102	-15.101
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

+15V: Rated Load Current

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW61215	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 9 - 18V

Load Current (AVR 1) : 0 - 0.2A (AVR 2) : 0 - 0.2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	80	9	0	15.414	±318	±2.1
Minimum Voltage	80	9	0.2	14.778		


Object	-15V0.2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	80	9	0	-15.432	±319	±2.1
Minimum Voltage	80	9	0.2	-14.795		

COSEL

Model	MGW61215
Item	Time Lapse Drift
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Input Volt. 12V
Load 100%


Object -15V0.2A

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.076
0.5	15.081
1.0	15.081
2.0	15.081
3.0	15.081
4.0	15.081
5.0	15.081
6.0	15.081
7.0	15.081
8.0	15.081

-15V: Rated Load Current

1.Graph



Input Volt. 12V
Load 100%

2.Values

Time since start [H]	Output Voltage [V]
0.0	-15.089
0.5	-15.095
1.0	-15.095
2.0	-15.095
3.0	-15.095
4.0	-15.095
5.0	-15.095
6.0	-15.095
7.0	-15.095
8.0	-15.095


+15V: Rated Load Current

COSEL

Model	MGW61215
Item	Rise and Fall Time
Object	+15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.4	0.5	2.9	0.5	4.0	
100 %		2.4	0.6	3.0	0.5	1.9	




COSEL

Model	MGW61215
Item	Rise and Fall Time
Object	-15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.4	0.5	2.9	0.6	4.7	
100 %		2.4	0.6	3.0	0.5	2.2	



COSEL

Model	MGW61215
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.2A

1.Graph




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.7	7.7
-40	7.6	7.6
-20	7.5	7.6
0	7.5	7.5
25	7.4	7.5
80	7.3	7.3
85	7.1	7.3
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.2A
--------	----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	7.7	7.7
-40	7.6	7.6
-20	7.5	7.6
0	7.5	7.6
25	7.4	7.5
80	7.3	7.3
85	7.1	7.3
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW61215	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+15V0.2A																																																									
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>14.25</td><td>0.34</td><td>0.37</td><td>0.35</td></tr> <tr><td>13.50</td><td>0.37</td><td>0.39</td><td>0.37</td></tr> <tr><td>12.00</td><td>0.42</td><td>0.44</td><td>0.41</td></tr> <tr><td>10.50</td><td>0.48</td><td>0.49</td><td>0.46</td></tr> <tr><td>9.00</td><td>0.53</td><td>0.54</td><td>0.50</td></tr> <tr><td>7.50</td><td>0.59</td><td>0.60</td><td>0.55</td></tr> <tr><td>6.00</td><td>0.65</td><td>0.65</td><td>0.59</td></tr> <tr><td>4.50</td><td>0.71</td><td>0.71</td><td>0.64</td></tr> <tr><td>3.00</td><td>0.78</td><td>0.76</td><td>0.68</td></tr> <tr><td>1.50</td><td>0.83</td><td>0.80</td><td>0.72</td></tr> <tr><td>0.00</td><td>0.79</td><td>0.75</td><td>0.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	14.25	0.34	0.37	0.35	13.50	0.37	0.39	0.37	12.00	0.42	0.44	0.41	10.50	0.48	0.49	0.46	9.00	0.53	0.54	0.50	7.50	0.59	0.60	0.55	6.00	0.65	0.65	0.59	4.50	0.71	0.71	0.64	3.00	0.78	0.76	0.68	1.50	0.83	0.80	0.72	0.00	0.79	0.75	0.65	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																							
14.25	0.34	0.37	0.35																																																							
13.50	0.37	0.39	0.37																																																							
12.00	0.42	0.44	0.41																																																							
10.50	0.48	0.49	0.46																																																							
9.00	0.53	0.54	0.50																																																							
7.50	0.59	0.60	0.55																																																							
6.00	0.65	0.65	0.59																																																							
4.50	0.71	0.71	0.64																																																							
3.00	0.78	0.76	0.68																																																							
1.50	0.83	0.80	0.72																																																							
0.00	0.79	0.75	0.65																																																							
--	-	-	-																																																							
Object	-15V0.2A																																																									
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>-14.25</td><td>0.34</td><td>0.37</td><td>0.35</td></tr> <tr><td>-13.50</td><td>0.37</td><td>0.39</td><td>0.37</td></tr> <tr><td>-12.00</td><td>0.42</td><td>0.44</td><td>0.41</td></tr> <tr><td>-10.50</td><td>0.48</td><td>0.49</td><td>0.45</td></tr> <tr><td>-9.00</td><td>0.53</td><td>0.55</td><td>0.50</td></tr> <tr><td>-7.50</td><td>0.59</td><td>0.60</td><td>0.55</td></tr> <tr><td>-6.00</td><td>0.65</td><td>0.65</td><td>0.59</td></tr> <tr><td>-4.50</td><td>0.71</td><td>0.71</td><td>0.64</td></tr> <tr><td>-3.00</td><td>0.78</td><td>0.76</td><td>0.68</td></tr> <tr><td>-1.50</td><td>0.84</td><td>0.81</td><td>0.72</td></tr> <tr><td>0.00</td><td>0.79</td><td>0.75</td><td>0.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>			Output Voltage [V]	Load Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	-14.25	0.34	0.37	0.35	-13.50	0.37	0.39	0.37	-12.00	0.42	0.44	0.41	-10.50	0.48	0.49	0.45	-9.00	0.53	0.55	0.50	-7.50	0.59	0.60	0.55	-6.00	0.65	0.65	0.59	-4.50	0.71	0.71	0.64	-3.00	0.78	0.76	0.68	-1.50	0.84	0.81	0.72	0.00	0.79	0.75	0.65	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																							
-14.25	0.34	0.37	0.35																																																							
-13.50	0.37	0.39	0.37																																																							
-12.00	0.42	0.44	0.41																																																							
-10.50	0.48	0.49	0.45																																																							
-9.00	0.53	0.55	0.50																																																							
-7.50	0.59	0.60	0.55																																																							
-6.00	0.65	0.65	0.59																																																							
-4.50	0.71	0.71	0.64																																																							
-3.00	0.78	0.76	0.68																																																							
-1.50	0.84	0.81	0.72																																																							
0.00	0.79	0.75	0.65																																																							
--	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										

COSEL

Model	MGW61215	Temperature	25°C																																																			
Item	Switching Frequency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	+/-15V0.2A																																																					
1.Graph	<p>—△— Input Volt. 9V - - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>9V [kHz]</th> <th>12V [kHz]</th> <th>18V [kHz]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>989</td><td>1087</td><td>1020</td></tr> <tr><td>0.05</td><td>620</td><td>701</td><td>781</td></tr> <tr><td>0.10</td><td>455</td><td>525</td><td>608</td></tr> <tr><td>0.15</td><td>357</td><td>422</td><td>497</td></tr> <tr><td>0.20</td><td>249</td><td>301</td><td>366</td></tr> <tr><td>0.22</td><td>231</td><td>281</td><td>343</td></tr> </tbody> </table>			Load Current [A]	9V [kHz]	12V [kHz]	18V [kHz]	0.00	989	1087	1020	0.05	620	701	781	0.10	455	525	608	0.15	357	422	497	0.20	249	301	366	0.22	231	281	343																							
Load Current [A]	9V [kHz]	12V [kHz]	18V [kHz]																																																			
0.00	989	1087	1020																																																			
0.05	620	701	781																																																			
0.10	455	525	608																																																			
0.15	357	422	497																																																			
0.20	249	301	366																																																			
0.22	231	281	343																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Frequency [kHz]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>989</td><td>1087</td><td>1020</td></tr> <tr><td>0.04</td><td>620</td><td>701</td><td>781</td></tr> <tr><td>0.08</td><td>455</td><td>525</td><td>608</td></tr> <tr><td>0.12</td><td>357</td><td>422</td><td>497</td></tr> <tr><td>0.16</td><td>294</td><td>352</td><td>422</td></tr> <tr><td>0.20</td><td>249</td><td>301</td><td>366</td></tr> <tr><td>0.22</td><td>231</td><td>281</td><td>343</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Frequency [kHz]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	989	1087	1020	0.04	620	701	781	0.08	455	525	608	0.12	357	422	497	0.16	294	352	422	0.20	249	301	366	0.22	231	281	343	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Frequency [kHz]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	989	1087	1020																																																			
0.04	620	701	781																																																			
0.08	455	525	608																																																			
0.12	357	422	497																																																			
0.16	294	352	422																																																			
0.20	249	301	366																																																			
0.22	231	281	343																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
-When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																						

COSEL




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)