

TEST DATA OF MGXS1R52405

Regulated DC Power Supply
February 19, 2018

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Masumi Kitamura
Masumi Kitamura Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL

Model	MGXS1R52405
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
5.0	0.003	0.003	0.003
5.2	0.003	0.003	0.003
5.4	0.003	0.003	0.003
5.5	0.015	0.187	0.341
6.0	0.014	0.167	0.323
9.0	0.011	0.109	0.216
12.0	0.009	0.082	0.159
18.0	0.007	0.056	0.105
24.0	0.007	0.043	0.080
36.0	0.006	0.030	0.055
48.0	0.006	0.024	0.042
60.0	0.006	0.021	0.035
66.0	0.005	0.019	0.033
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGXS1R52405																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V <p>Note: Slanted line shows the range of the rated load current.</p>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.014</td><td>0.009</td><td>0.007</td><td>0.006</td><td>0.006</td></tr> <tr><td>0.06</td><td>0.073</td><td>0.038</td><td>0.021</td><td>0.013</td><td>0.012</td></tr> <tr><td>0.12</td><td>0.135</td><td>0.067</td><td>0.036</td><td>0.020</td><td>0.018</td></tr> <tr><td>0.18</td><td>0.202</td><td>0.097</td><td>0.050</td><td>0.028</td><td>0.023</td></tr> <tr><td>0.24</td><td>0.267</td><td>0.128</td><td>0.065</td><td>0.035</td><td>0.029</td></tr> <tr><td>0.30</td><td>-※</td><td>0.159</td><td>0.080</td><td>0.042</td><td>0.035</td></tr> <tr><td>0.33</td><td>-※</td><td>0.175</td><td>0.087</td><td>0.046</td><td>0.038</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>					Load Current [A]	Input Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	0.00	0.014	0.009	0.007	0.006	0.006	0.06	0.073	0.038	0.021	0.013	0.012	0.12	0.135	0.067	0.036	0.020	0.018	0.18	0.202	0.097	0.050	0.028	0.023	0.24	0.267	0.128	0.065	0.035	0.029	0.30	-※	0.159	0.080	0.042	0.035	0.33	-※	0.175	0.087	0.046	0.038	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0.00	0.014	0.009	0.007	0.006	0.006																																																																													
0.06	0.073	0.038	0.021	0.013	0.012																																																																													
0.12	0.135	0.067	0.036	0.020	0.018																																																																													
0.18	0.202	0.097	0.050	0.028	0.023																																																																													
0.24	0.267	0.128	0.065	0.035	0.029																																																																													
0.30	-※	0.159	0.080	0.042	0.035																																																																													
0.33	-※	0.175	0.087	0.046	0.038																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL


Model	MGXS1R52405																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V <p>Input Power [W]</p> <p>Load Current [A]</p>																																																																																	
	<p>Temperature 25°C Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.08</td><td>0.11</td><td>0.16</td><td>0.27</td><td>0.34</td></tr> <tr><td>0.06</td><td>0.44</td><td>0.46</td><td>0.51</td><td>0.63</td><td>0.70</td></tr> <tr><td>0.12</td><td>0.80</td><td>0.81</td><td>0.85</td><td>0.98</td><td>1.06</td></tr> <tr><td>0.18</td><td>1.19</td><td>1.16</td><td>1.20</td><td>1.33</td><td>1.41</td></tr> <tr><td>0.24</td><td>1.59</td><td>1.53</td><td>1.55</td><td>1.68</td><td>1.76</td></tr> <tr><td>0.30</td><td>-※</td><td>1.90</td><td>1.91</td><td>2.03</td><td>2.11</td></tr> <tr><td>0.33</td><td>-※</td><td>2.09</td><td>2.09</td><td>2.21</td><td>2.29</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>					Load Current [A]	Input Power [W]					6[V]	12[V]	24[V]	48[V]	60[V]	0.00	0.08	0.11	0.16	0.27	0.34	0.06	0.44	0.46	0.51	0.63	0.70	0.12	0.80	0.81	0.85	0.98	1.06	0.18	1.19	1.16	1.20	1.33	1.41	0.24	1.59	1.53	1.55	1.68	1.76	0.30	-※	1.90	1.91	2.03	2.11	0.33	-※	2.09	2.09	2.21	2.29	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0.00	0.08	0.11	0.16	0.27	0.34																																																																													
0.06	0.44	0.46	0.51	0.63	0.70																																																																													
0.12	0.80	0.81	0.85	0.98	1.06																																																																													
0.18	1.19	1.16	1.20	1.33	1.41																																																																													
0.24	1.59	1.53	1.55	1.68	1.76																																																																													
0.30	-※	1.90	1.91	2.03	2.11																																																																													
0.33	-※	2.09	2.09	2.21	2.29																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL

Model	MGXS1R52405
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
5.5	74.9	75.5
6.0	75.9	76.4
9.0	76.9	78.7
12.0	76.9	79.7
24.0	73.7	79.4
36.0	69.9	77.2
48.0	65.4	74.6
60.0	61.3	71.7
66.0	59.3	70.2

※1: Load 70%

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGXS1R52405
Item	Efficiency (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]				
	6[V]	12[V]	24[V]	48[V]	60[V]
0.00	-	-	-	-	-
0.06	69.3	66.5	60.0	48.0	43.0
0.12	75.3	75.1	71.1	61.6	57.1
0.18	76.2	78.1	75.7	68.3	64.7
0.24	76.0	79.4	78.0	72.2	68.8
0.30	-※	79.7	79.2	74.4	71.8
0.33	-※	79.8	79.8	75.5	72.8
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.

COSSEL

Model	MGXS1R52405
Item	Line Regulation
Object	+5V0.3A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
5.5	5.043	-※
6.0	5.043	-※
9.0	5.044	5.042
12.0	5.044	5.043
24.0	5.044	5.043
36.0	5.044	5.043
48.0	5.044	5.044
60.0	5.044	5.044
66.0	5.044	5.044

※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.


COSSEL

Model	MGXS1R52405																																																																																	
Item	Load Regulation																																																																																	
Object	+5V0.3A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 6V - - □ - - Input Volt. 12V - - * - - Input Volt. 24V - - ○ - - Input Volt. 48V - - ◇ - - Input Volt. 60V 																																																																																	
	<p>Temperature 25°C Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.046</td><td>5.046</td><td>5.046</td><td>5.046</td><td>5.046</td></tr> <tr><td>0.06</td><td>5.046</td><td>5.046</td><td>5.046</td><td>5.045</td><td>5.045</td></tr> <tr><td>0.12</td><td>5.045</td><td>5.045</td><td>5.045</td><td>5.045</td><td>5.045</td></tr> <tr><td>0.18</td><td>5.044</td><td>5.045</td><td>5.045</td><td>5.045</td><td>5.045</td></tr> <tr><td>0.24</td><td>5.042</td><td>5.044</td><td>5.045</td><td>5.045</td><td>5.045</td></tr> <tr><td>0.30</td><td>- *</td><td>5.042</td><td>5.044</td><td>5.044</td><td>5.044</td></tr> <tr><td>0.33</td><td>- *</td><td>5.040</td><td>5.044</td><td>5.044</td><td>5.044</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>					Load Current [A]	Output Voltage [V]					6[V]	12[V]	24[V]	48[V]	60[V]	0.00	5.046	5.046	5.046	5.046	5.046	0.06	5.046	5.046	5.046	5.045	5.045	0.12	5.045	5.045	5.045	5.045	5.045	0.18	5.044	5.045	5.045	5.045	5.045	0.24	5.042	5.044	5.045	5.045	5.045	0.30	- *	5.042	5.044	5.044	5.044	0.33	- *	5.040	5.044	5.044	5.044	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0.00	5.046	5.046	5.046	5.046	5.046																																																																													
0.06	5.046	5.046	5.046	5.045	5.045																																																																													
0.12	5.045	5.045	5.045	5.045	5.045																																																																													
0.18	5.044	5.045	5.045	5.045	5.045																																																																													
0.24	5.042	5.044	5.045	5.045	5.045																																																																													
0.30	- *	5.042	5.044	5.044	5.044																																																																													
0.33	- *	5.040	5.044	5.044	5.044																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL


Model	MGXS1R52405	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+5V0.3A		

Input Volt. 24 V
 Cycle 100 ms




Min.Load (0A)↔
 Load 100% (0.3A)

100 mV/div 400 μ s/div

400 μ s/div


Min.Load (0A)↔
 Load 50% (0.15A)

100 mV/div 400 μ s/div

400 μ s/div

Load 50% (0.15A)↔
 Load 100% (0.3A)

100 mV/div 400 μ s/div

400 μ s/div

COSSEL

Model	MGXS1R52405																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+5V0.3A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.0 to 0.4 A. Two curves are plotted: one for Input Volt. 6V (solid line with triangle markers) and one for Input Volt. 60V (dashed line with circle markers). Both curves show an increase in ripple voltage as load current increases. A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 6V)</th> <th>Ripple Voltage [mV] (Input Volt. 60V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>3</td></tr> <tr><td>0.06</td><td>22</td><td>8</td></tr> <tr><td>0.12</td><td>42</td><td>12</td></tr> <tr><td>0.15</td><td>52</td><td>14</td></tr> <tr><td>0.18</td><td>63</td><td>18</td></tr> <tr><td>0.24</td><td>76</td><td>25</td></tr> <tr><td>0.30</td><td>-</td><td>29</td></tr> <tr><td>0.33</td><td>-</td><td>31</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 6V)	Ripple Voltage [mV] (Input Volt. 60V)	0.00	4	3	0.06	22	8	0.12	42	12	0.15	52	14	0.18	63	18	0.24	76	25	0.30	-	29	0.33	-	31	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 6V)	Ripple Voltage [mV] (Input Volt. 60V)																																						
0.00	4	3																																						
0.06	22	8																																						
0.12	42	12																																						
0.15	52	14																																						
0.18	63	18																																						
0.24	76	25																																						
0.30	-	29																																						
0.33	-	31																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 6 [V]</th> <th>Input Volt. 60 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>4</td><td>3</td></tr> <tr><td>0.06</td><td>22</td><td>8</td></tr> <tr><td>0.12</td><td>42</td><td>12</td></tr> <tr><td>0.15</td><td>52</td><td>14</td></tr> <tr><td>0.18</td><td>63</td><td>18</td></tr> <tr><td>0.24</td><td>76</td><td>25</td></tr> <tr><td>0.30</td><td>-</td><td>29</td></tr> <tr><td>0.33</td><td>-</td><td>31</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 6 [V]	Input Volt. 60 [V]	0.00	4	3	0.06	22	8	0.12	42	12	0.15	52	14	0.18	63	18	0.24	76	25	0.30	-	29	0.33	-	31	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 6 [V]	Input Volt. 60 [V]																																						
0.00	4	3																																						
0.06	22	8																																						
0.12	42	12																																						
0.15	52	14																																						
0.18	63	18																																						
0.24	76	25																																						
0.30	-	29																																						
0.33	-	31																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL


Model	MGXS1R52405	Temperature Testing Circuitry	25°C Figure B																																						
Item	Ripple-Noise																																								
Object	+5V0.3A																																								
1.Graph			2.Values																																						
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.0 to 0.4 A. Two curves are plotted: one for Input Volt. 6V (solid line with triangle markers) and one for Input Volt. 60V (dashed line with circle markers). Both curves show an increase in Ripple Voltage as Load Current increases, with a slanted line indicating the range of rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 6 [V]</th> <th>Input Volt. 60 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>7</td> <td>6</td> </tr> <tr> <td>0.06</td> <td>26</td> <td>12</td> </tr> <tr> <td>0.12</td> <td>47</td> <td>16</td> </tr> <tr> <td>0.15</td> <td>57</td> <td>19</td> </tr> <tr> <td>0.18</td> <td>72</td> <td>25</td> </tr> <tr> <td>0.24</td> <td>87</td> <td>33</td> </tr> <tr> <td>0.30</td> <td>-※</td> <td>38</td> </tr> <tr> <td>0.33</td> <td>-※</td> <td>38</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 6 [V]	Input Volt. 60 [V]	0.00	7	6	0.06	26	12	0.12	47	16	0.15	57	19	0.18	72	25	0.24	87	33	0.30	-※	38	0.33	-※	38	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 6 [V]	Input Volt. 60 [V]																																							
0.00	7	6																																							
0.06	26	12																																							
0.12	47	16																																							
0.15	57	19																																							
0.18	72	25																																							
0.24	87	33																																							
0.30	-※	38																																							
0.33	-※	38																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>			<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																						

COSEL

Model	MGXS1R52405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V0.3A

Testing Circuitry Figure B

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	29	54
-40	27	51
-20	26	48
0	24	46
25	23	43
50	22	41
85	21	40
90	21	39
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGXS1R52405
Item	Ambient Temperature Drift
Object	+5V0.3A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	6[V]	12[V]	24[V]	48[V]	60[V]
-60	4.991	4.998	4.998	4.999	5.000
-40	4.998	5.010	5.014	5.015	5.015
-20	5.012	5.021	5.024	5.025	5.025
0	5.023	5.030	5.033	5.033	5.033
25	5.038	5.041	5.043	5.043	5.043
60	5.044	5.045	5.047	5.047	5.047
70	5.044	5.045	5.047	5.047	5.047
75	5.044	5.045	5.047	5.047	5.047
85	5.044	5.045	5.047	5.047	5.047
90	5.044	5.043	5.046	5.047	5.047
--	-	-	-	-	-

Note: In case of input Volt. 6V, Load 70%.
Other case Load 100%.



Model	MGXS1R52405	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V0.3A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 6 - 60V

Load Current : 0 - 0.3A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	85	60	0	5.049	±26	±0.5
Minimum Voltage	-40	6	0.21 ※	4.998		

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.


COSEL

Model	MGXS1R52405	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V0.3A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.042</td></tr> <tr><td>0.5</td><td>5.045</td></tr> <tr><td>1.0</td><td>5.045</td></tr> <tr><td>2.0</td><td>5.045</td></tr> <tr><td>3.0</td><td>5.045</td></tr> <tr><td>4.0</td><td>5.045</td></tr> <tr><td>5.0</td><td>5.045</td></tr> <tr><td>6.0</td><td>5.045</td></tr> <tr><td>7.0</td><td>5.045</td></tr> <tr><td>8.0</td><td>5.045</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.042	0.5	5.045	1.0	5.045	2.0	5.045	3.0	5.045	4.0	5.045	5.0	5.045	6.0	5.045	7.0	5.045	8.0	5.045
Time since start [H]	Output Voltage [V]																								
0.0	5.042																								
0.5	5.045																								
1.0	5.045																								
2.0	5.045																								
3.0	5.045																								
4.0	5.045																								
5.0	5.045																								
6.0	5.045																								
7.0	5.045																								
8.0	5.045																								

COSSEL


Model	MGXS1R52405	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V0.3A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.3	0.3	0.6	0.3	3.2	
100 %		0.3	0.4	0.7	0.3	1.8	




COSEL

Model	MGXS1R52405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V0.3A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	5.2	4.9
-40	5.2	4.9
-20	4.9	4.8
0	4.9	4.8
25	4.8	4.8
60	4.8	4.8
70	4.8	4.8
75	4.8	4.8
85	4.8	4.8
90	4.8	4.8
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGXS1R52405																																																																																							
Item	Overcurrent Protection																																																																																							
Object	+5V0.3A																																																																																							
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V</p>																																																																																							
Note:	Slanted line shows the range of the rated load current.																																																																																							
<p>Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																								
Temperature	25°C																																																																																							
Testing Circuitry	Figure A																																																																																							
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>4.75</td><td>0.303</td><td>0.431</td><td>0.450</td><td>0.466</td><td>0.476</td></tr> <tr><td>4.50</td><td>0.320</td><td>0.452</td><td>0.474</td><td>0.487</td><td>0.498</td></tr> <tr><td>4.00</td><td>0.357</td><td>0.499</td><td>0.527</td><td>0.533</td><td>0.542</td></tr> <tr><td>3.50</td><td>0.401</td><td>0.554</td><td>0.585</td><td>0.582</td><td>0.590</td></tr> <tr><td>3.00</td><td>0.456</td><td>0.616</td><td>0.642</td><td>0.634</td><td>0.641</td></tr> <tr><td>2.50</td><td>0.518</td><td>0.687</td><td>0.706</td><td>0.686</td><td>0.692</td></tr> <tr><td>2.00</td><td>0.593</td><td>0.767</td><td>0.771</td><td>0.741</td><td>0.745</td></tr> <tr><td>1.50</td><td>0.687</td><td>0.858</td><td>0.840</td><td>0.799</td><td>0.803</td></tr> <tr><td>1.00</td><td>0.804</td><td>0.962</td><td>0.914</td><td>0.861</td><td>0.861</td></tr> <tr><td>0.50</td><td>0.948</td><td>1.064</td><td>0.981</td><td>0.908</td><td>0.902</td></tr> <tr><td>0.00</td><td>1.052</td><td>1.056</td><td>0.923</td><td>0.832</td><td>0.820</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	4.75	0.303	0.431	0.450	0.466	0.476	4.50	0.320	0.452	0.474	0.487	0.498	4.00	0.357	0.499	0.527	0.533	0.542	3.50	0.401	0.554	0.585	0.582	0.590	3.00	0.456	0.616	0.642	0.634	0.641	2.50	0.518	0.687	0.706	0.686	0.692	2.00	0.593	0.767	0.771	0.741	0.745	1.50	0.687	0.858	0.840	0.799	0.803	1.00	0.804	0.962	0.914	0.861	0.861	0.50	0.948	1.064	0.981	0.908	0.902	0.00	1.052	1.056	0.923	0.832	0.820	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																							
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																																			
4.75	0.303	0.431	0.450	0.466	0.476																																																																																			
4.50	0.320	0.452	0.474	0.487	0.498																																																																																			
4.00	0.357	0.499	0.527	0.533	0.542																																																																																			
3.50	0.401	0.554	0.585	0.582	0.590																																																																																			
3.00	0.456	0.616	0.642	0.634	0.641																																																																																			
2.50	0.518	0.687	0.706	0.686	0.692																																																																																			
2.00	0.593	0.767	0.771	0.741	0.745																																																																																			
1.50	0.687	0.858	0.840	0.799	0.803																																																																																			
1.00	0.804	0.962	0.914	0.861	0.861																																																																																			
0.50	0.948	1.064	0.981	0.908	0.902																																																																																			
0.00	1.052	1.056	0.923	0.832	0.820																																																																																			
--	-	-	-	-	-																																																																																			

COSSEL

Model	MGXS1R52405																																																																																	
Item	Switching frequency (by Load Current)																																																																																	
Object	+5V0.3A																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>219</td> <td>321</td> <td>415</td> <td>480</td> <td>491</td> </tr> <tr> <td>0.060</td> <td>160</td> <td>268</td> <td>365</td> <td>438</td> <td>454</td> </tr> <tr> <td>0.120</td> <td>125</td> <td>224</td> <td>325</td> <td>400</td> <td>417</td> </tr> <tr> <td>0.150</td> <td>112</td> <td>209</td> <td>307</td> <td>383</td> <td>400</td> </tr> <tr> <td>0.180</td> <td>102</td> <td>195</td> <td>292</td> <td>367</td> <td>384</td> </tr> <tr> <td>0.210</td> <td>93</td> <td>183</td> <td>278</td> <td>353</td> <td>370</td> </tr> <tr> <td>0.240</td> <td>85</td> <td>172</td> <td>266</td> <td>340</td> <td>357</td> </tr> <tr> <td>0.255</td> <td>82</td> <td>167</td> <td>259</td> <td>334</td> <td>351</td> </tr> <tr> <td>0.300</td> <td>-</td> <td>154</td> <td>243</td> <td>316</td> <td>333</td> </tr> <tr> <td>0.330</td> <td>-</td> <td>146</td> <td>233</td> <td>305</td> <td>322</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	0.000	219	321	415	480	491	0.060	160	268	365	438	454	0.120	125	224	325	400	417	0.150	112	209	307	383	400	0.180	102	195	292	367	384	0.210	93	183	278	353	370	0.240	85	172	266	340	357	0.255	82	167	259	334	351	0.300	-	154	243	316	333	0.330	-	146	233	305	322	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0.000	219	321	415	480	491																																																																													
0.060	160	268	365	438	454																																																																													
0.120	125	224	325	400	417																																																																													
0.150	112	209	307	383	400																																																																													
0.180	102	195	292	367	384																																																																													
0.210	93	183	278	353	370																																																																													
0.240	85	172	266	340	357																																																																													
0.255	82	167	259	334	351																																																																													
0.300	-	154	243	316	333																																																																													
0.330	-	146	233	305	322																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
When load current is low, MG operates intermittently, so switching frequency would not become constant.	<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																	

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)