

TEST DATA OF MGXS62412

Regulated DC Power Supply

February 19, 2018

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Masumi Kitamura Masumi Kitamura Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)



Model	MGXS62412	Temperature Testing Circuitry	25°C Figure A																																																																															
Item	Input Current (by Input Voltage)																																																																																	
Object	_____																																																																																	
1.Graph		<p>Input Current [A]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 100% (solid line with triangles) Load 50% (dashed line with squares) Load 0% (dotted line with circles) 																																																																																
		2.Values																																																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>5.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>5.2</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>5.4</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>5.5</td><td>0.035</td><td>0.676</td><td>1.412</td></tr> <tr><td>6.0</td><td>0.033</td><td>0.622</td><td>1.217</td></tr> <tr><td>9.0</td><td>0.024</td><td>0.400</td><td>0.805</td></tr> <tr><td>12.0</td><td>0.019</td><td>0.297</td><td>0.586</td></tr> <tr><td>18.0</td><td>0.015</td><td>0.198</td><td>0.387</td></tr> <tr><td>24.0</td><td>0.012</td><td>0.149</td><td>0.289</td></tr> <tr><td>36.0</td><td>0.008</td><td>0.102</td><td>0.194</td></tr> <tr><td>48.0</td><td>0.005</td><td>0.078</td><td>0.147</td></tr> <tr><td>60.0</td><td>0.006</td><td>0.065</td><td>0.120</td></tr> <tr><td>66.0</td><td>0.006</td><td>0.060</td><td>0.111</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	5.0	0.003	0.003	0.003	5.2	0.003	0.003	0.003	5.4	0.003	0.003	0.003	5.5	0.035	0.676	1.412	6.0	0.033	0.622	1.217	9.0	0.024	0.400	0.805	12.0	0.019	0.297	0.586	18.0	0.015	0.198	0.387	24.0	0.012	0.149	0.289	36.0	0.008	0.102	0.194	48.0	0.005	0.078	0.147	60.0	0.006	0.065	0.120	66.0	0.006	0.060	0.111	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
5.0	0.003	0.003	0.003																																																																															
5.2	0.003	0.003	0.003																																																																															
5.4	0.003	0.003	0.003																																																																															
5.5	0.035	0.676	1.412																																																																															
6.0	0.033	0.622	1.217																																																																															
9.0	0.024	0.400	0.805																																																																															
12.0	0.019	0.297	0.586																																																																															
18.0	0.015	0.198	0.387																																																																															
24.0	0.012	0.149	0.289																																																																															
36.0	0.008	0.102	0.194																																																																															
48.0	0.005	0.078	0.147																																																																															
60.0	0.006	0.065	0.120																																																																															
66.0	0.006	0.060	0.111																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	MGXS62412	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 6V - -□--- Input Volt. 12V - -*--- Input Volt. 24V - -○--- Input Volt. 48V - -◇--- Input Volt. 60V																																																																														
		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.032</td> <td>0.019</td> <td>0.012</td> <td>0.005</td> <td>0.006</td> </tr> <tr> <td>0.10</td> <td>0.258</td> <td>0.129</td> <td>0.067</td> <td>0.037</td> <td>0.031</td> </tr> <tr> <td>0.20</td> <td>0.487</td> <td>0.241</td> <td>0.122</td> <td>0.064</td> <td>0.054</td> </tr> <tr> <td>0.30</td> <td>0.727</td> <td>0.352</td> <td>0.178</td> <td>0.092</td> <td>0.076</td> </tr> <tr> <td>0.40</td> <td>1.006</td> <td>0.467</td> <td>0.233</td> <td>0.120</td> <td>0.098</td> </tr> <tr> <td>0.50</td> <td>-※</td> <td>0.583</td> <td>0.290</td> <td>0.147</td> <td>0.120</td> </tr> <tr> <td>0.55</td> <td>-※</td> <td>0.643</td> <td>0.318</td> <td>0.161</td> <td>0.131</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Input Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	0.00	0.032	0.019	0.012	0.005	0.006	0.10	0.258	0.129	0.067	0.037	0.031	0.20	0.487	0.241	0.122	0.064	0.054	0.30	0.727	0.352	0.178	0.092	0.076	0.40	1.006	0.467	0.233	0.120	0.098	0.50	-※	0.583	0.290	0.147	0.120	0.55	-※	0.643	0.318	0.161	0.131	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																											
0.00	0.032	0.019	0.012	0.005	0.006																																																																											
0.10	0.258	0.129	0.067	0.037	0.031																																																																											
0.20	0.487	0.241	0.122	0.064	0.054																																																																											
0.30	0.727	0.352	0.178	0.092	0.076																																																																											
0.40	1.006	0.467	0.233	0.120	0.098																																																																											
0.50	-※	0.583	0.290	0.147	0.120																																																																											
0.55	-※	0.643	0.318	0.161	0.131																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
		※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.																																																																														

Note: Slanted line shows the range of the rated load current.

COSEL


Model	MGXS62412																																																																												
Item	Input Power (by Load Current)																																																																												
Object	_____																																																																												
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.19</td><td>0.23</td><td>0.29</td><td>0.25</td><td>0.35</td></tr> <tr><td>0.10</td><td>1.53</td><td>1.54</td><td>1.61</td><td>1.76</td><td>1.85</td></tr> <tr><td>0.20</td><td>2.90</td><td>2.87</td><td>2.92</td><td>3.09</td><td>3.23</td></tr> <tr><td>0.30</td><td>4.36</td><td>4.22</td><td>4.25</td><td>4.41</td><td>4.55</td></tr> <tr><td>0.40</td><td>6.00</td><td>5.59</td><td>5.58</td><td>5.74</td><td>5.88</td></tr> <tr><td>0.50</td><td>-※</td><td>6.97</td><td>6.93</td><td>7.07</td><td>7.21</td></tr> <tr><td>0.55</td><td>-※</td><td>7.67</td><td>7.61</td><td>7.74</td><td>7.88</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	6[V]	12[V]	24[V]	48[V]	60[V]	0.00	0.19	0.23	0.29	0.25	0.35	0.10	1.53	1.54	1.61	1.76	1.85	0.20	2.90	2.87	2.92	3.09	3.23	0.30	4.36	4.22	4.25	4.41	4.55	0.40	6.00	5.59	5.58	5.74	5.88	0.50	-※	6.97	6.93	7.07	7.21	0.55	-※	7.67	7.61	7.74	7.88	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	6[V]	12[V]	24[V]	48[V]	60[V]																																																																								
0.00	0.19	0.23	0.29	0.25	0.35																																																																								
0.10	1.53	1.54	1.61	1.76	1.85																																																																								
0.20	2.90	2.87	2.92	3.09	3.23																																																																								
0.30	4.36	4.22	4.25	4.41	4.55																																																																								
0.40	6.00	5.59	5.58	5.74	5.88																																																																								
0.50	-※	6.97	6.93	7.07	7.21																																																																								
0.55	-※	7.67	7.61	7.74	7.88																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
--	-	-	-	-	-																																																																								
2.Values																																																																													
Note: Slanted line shows the range of the rated load current.	<p>Temperature 25°C Testing Circuitry Figure A</p> <p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																												

COSEL

Model	MGXS62412
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
5.5	82.2	79.9
6.0	83.1	81.9
9.0	84.9	84.8
12.0	85.1	86.5
24.0	84.0	87.1
36.0	82.5	86.3
48.0	80.5	85.4
60.0	77.5	83.8
66.0	75.6	82.7

※1: Load 70%

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGXS62412
Item	Efficiency (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]				
	Input Volt. 6[V]	Input Volt. 12[V]	Input Volt. 24[V]	Input Volt. 48[V]	Input Volt. 60[V]
0.00	-	-	-	-	-
0.10	79.0	78.2	74.7	68.5	65.1
0.20	83.1	84.0	82.5	78.0	74.7
0.30	83.0	85.9	85.1	82.2	79.5
0.40	80.5	86.3	86.5	84.1	82.0
0.50	-※	86.5	87.0	85.4	83.7
0.55	-※	86.6	87.2	85.7	84.3
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL

Model	MGXS62412																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V0.5A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: --- □--- Load 50% — △ — Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>5.5</td> <td>12.040</td> <td>- *</td> </tr> <tr> <td>6.0</td> <td>12.040</td> <td>- *</td> </tr> <tr> <td>9.0</td> <td>12.040</td> <td>12.041</td> </tr> <tr> <td>12.0</td> <td>12.040</td> <td>12.041</td> </tr> <tr> <td>24.0</td> <td>12.040</td> <td>12.040</td> </tr> <tr> <td>36.0</td> <td>12.039</td> <td>12.039</td> </tr> <tr> <td>48.0</td> <td>12.038</td> <td>12.039</td> </tr> <tr> <td>60.0</td> <td>12.037</td> <td>12.037</td> </tr> <tr> <td>66.0</td> <td>12.036</td> <td>12.037</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	5.5	12.040	- *	6.0	12.040	- *	9.0	12.040	12.041	12.0	12.040	12.041	24.0	12.040	12.040	36.0	12.039	12.039	48.0	12.038	12.039	60.0	12.037	12.037	66.0	12.036	12.037
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
5.5	12.040	- *																																
6.0	12.040	- *																																
9.0	12.040	12.041																																
12.0	12.040	12.041																																
24.0	12.040	12.040																																
36.0	12.039	12.039																																
48.0	12.038	12.039																																
60.0	12.037	12.037																																
66.0	12.036	12.037																																
<p>* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																		

COSEL

Model	MGXS62412
Item	Load Regulation
Object	+12V0.5A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	6[V]	12[V]	24[V]	48[V]	60[V]
0.00	12.047	12.046	12.045	12.048	12.048
0.10	12.045	12.045	12.044	12.042	12.043
0.20	12.044	12.044	12.043	12.041	12.039
0.30	12.042	12.043	12.042	12.040	12.038
0.40	12.038	12.042	12.041	12.039	12.038
0.50	-※	12.041	12.040	12.038	12.037
0.55	-※	12.040	12.039	12.038	12.036
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.


COSEL

Model	MGXS62412
Item	Dynamic Load Response
Object	+12V0.5A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 24 V
Cycle 100 msMin.Load (0A)↔
Load 100% (0.5A)


500 mV/div

2 ms/div

Min.Load (0A)↔
Load 50% (0.25A)


500 mV/div

2 ms/div

Load 50% (0.25A)↔
Load 100% (0.5A)

500 mV/div

2 ms/div



COSEL


Model	MGXS62412																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.5A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 6 [V]</th> <th>Input Volt. 60 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3</td><td>116</td></tr> <tr><td>0.10</td><td>4</td><td>120</td></tr> <tr><td>0.20</td><td>9</td><td>4</td></tr> <tr><td>0.25</td><td>17</td><td>5</td></tr> <tr><td>0.30</td><td>26</td><td>2</td></tr> <tr><td>0.40</td><td>42</td><td>3</td></tr> <tr><td>0.50</td><td>-※</td><td>3</td></tr> <tr><td>0.55</td><td>-※</td><td>3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 6 [V]	Input Volt. 60 [V]	0.00	3	116	0.10	4	120	0.20	9	4	0.25	17	5	0.30	26	2	0.40	42	3	0.50	-※	3	0.55	-※	3	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 6 [V]	Input Volt. 60 [V]																																						
0.00	3	116																																						
0.10	4	120																																						
0.20	9	4																																						
0.25	17	5																																						
0.30	26	2																																						
0.40	42	3																																						
0.50	-※	3																																						
0.55	-※	3																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGXS62412
Item	Ripple-Noise
Object	+12V0.5A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 6 [V]	Input Volt. 60 [V]
0.00	12	126
0.10	18	132
0.20	20	17
0.25	27	18
0.30	32	17
0.40	46	20
0.50	-	23
0.55	-	22
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current.
 Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGXS62412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.5A

1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	6	7
-40	5	6
-20	5	5
0	5	4
25	5	4
50	4	3
75	4	3
80	4	3
--	-	-
--	-	-
--	-	-

COSEL

Model	MGXS62412
Item	Ambient Temperature Drift
Object	+12V0.5A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	6[V]	12[V]	24[V]	48[V]	60[V]
-60	11.947	11.951	11.951	11.950	11.950
-40	11.978	11.982	11.982	11.981	11.980
-20	12.006	12.006	12.006	12.005	12.003
0	12.023	12.024	12.024	12.023	12.021
25	12.037	12.037	12.037	12.035	12.035
60	12.042	12.041	12.041	12.039	12.038
70	12.041	12.040	12.040	12.039	12.038
75	12.040	12.040	12.040	12.039	12.038
85	12.038	12.038	12.038	12.037	12.036
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of input Volt. 6V, Load 70%.
Other case Load 100%.



Model	MGXS62412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 75°C

Input Voltage : 6 - 60V

Load Current : 0 - 0.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	75	60	0	12.050	±36	±0.3
Minimum Voltage	-40	6	0.35 ※	11.978		

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL


Model	MGXS62412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.5A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.033</td></tr> <tr><td>0.5</td><td>12.039</td></tr> <tr><td>1.0</td><td>12.039</td></tr> <tr><td>2.0</td><td>12.040</td></tr> <tr><td>3.0</td><td>12.040</td></tr> <tr><td>4.0</td><td>12.040</td></tr> <tr><td>5.0</td><td>12.040</td></tr> <tr><td>6.0</td><td>12.040</td></tr> <tr><td>7.0</td><td>12.040</td></tr> <tr><td>8.0</td><td>12.040</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.033	0.5	12.039	1.0	12.039	2.0	12.040	3.0	12.040	4.0	12.040	5.0	12.040	6.0	12.040	7.0	12.040	8.0	12.040
Time since start [H]	Output Voltage [V]																								
0.0	12.033																								
0.5	12.039																								
1.0	12.039																								
2.0	12.040																								
3.0	12.040																								
4.0	12.040																								
5.0	12.040																								
6.0	12.040																								
7.0	12.040																								
8.0	12.040																								

COSEL

Model	MGXS62412
Item	Rise and Fall Time
Object	+12V0.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.5	0.4	0.9	2.0	3.4	
100 %		0.5	0.4	0.9	1.8	1.7	




COSEL

Model	MGXS62412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	5.0	5.0
-40	5.0	5.0
-20	5.0	5.0
0	4.9	5.0
25	4.9	5.0
60	4.8	5.0
70	4.7	4.9
75	4.7	4.9
85	4.6	4.8
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGXS62412																																																																																						
Item	Overcurrent Protection																																																																																						
Object	+12V0.5A																																																																																						
1.Graph																																																																																							
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																																							
<p>Temperature 25°C Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr> <td>11.4</td> <td>0.482</td> <td>0.653</td> <td>0.706</td> <td>0.709</td> <td>0.709</td> </tr> <tr> <td>10.8</td> <td>0.503</td> <td>0.679</td> <td>0.736</td> <td>0.730</td> <td>0.729</td> </tr> <tr> <td>9.6</td> <td>0.549</td> <td>0.739</td> <td>0.798</td> <td>0.776</td> <td>0.771</td> </tr> <tr> <td>8.4</td> <td>0.583</td> <td>0.811</td> <td>0.860</td> <td>0.822</td> <td>0.815</td> </tr> <tr> <td>7.2</td> <td>0.633</td> <td>0.891</td> <td>0.928</td> <td>0.870</td> <td>0.861</td> </tr> <tr> <td>6.0</td> <td>0.708</td> <td>0.984</td> <td>0.993</td> <td>0.921</td> <td>0.911</td> </tr> <tr> <td>4.8</td> <td>0.813</td> <td>1.092</td> <td>1.062</td> <td>0.975</td> <td>0.965</td> </tr> <tr> <td>3.6</td> <td>0.957</td> <td>1.205</td> <td>1.139</td> <td>1.034</td> <td>1.018</td> </tr> <tr> <td>2.4</td> <td>1.145</td> <td>1.325</td> <td>1.226</td> <td>1.095</td> <td>1.073</td> </tr> <tr> <td>1.2</td> <td>1.332</td> <td>1.434</td> <td>1.296</td> <td>1.137</td> <td>1.110</td> </tr> <tr> <td>0.0</td> <td>1.636</td> <td>1.624</td> <td>1.401</td> <td>1.109</td> <td>1.070</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Output Voltage [V]	Load Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	11.4	0.482	0.653	0.706	0.709	0.709	10.8	0.503	0.679	0.736	0.730	0.729	9.6	0.549	0.739	0.798	0.776	0.771	8.4	0.583	0.811	0.860	0.822	0.815	7.2	0.633	0.891	0.928	0.870	0.861	6.0	0.708	0.984	0.993	0.921	0.911	4.8	0.813	1.092	1.062	0.975	0.965	3.6	0.957	1.205	1.139	1.034	1.018	2.4	1.145	1.325	1.226	1.095	1.073	1.2	1.332	1.434	1.296	1.137	1.110	0.0	1.636	1.624	1.401	1.109	1.070	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																						
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																																		
11.4	0.482	0.653	0.706	0.709	0.709																																																																																		
10.8	0.503	0.679	0.736	0.730	0.729																																																																																		
9.6	0.549	0.739	0.798	0.776	0.771																																																																																		
8.4	0.583	0.811	0.860	0.822	0.815																																																																																		
7.2	0.633	0.891	0.928	0.870	0.861																																																																																		
6.0	0.708	0.984	0.993	0.921	0.911																																																																																		
4.8	0.813	1.092	1.062	0.975	0.965																																																																																		
3.6	0.957	1.205	1.139	1.034	1.018																																																																																		
2.4	1.145	1.325	1.226	1.095	1.073																																																																																		
1.2	1.332	1.434	1.296	1.137	1.110																																																																																		
0.0	1.636	1.624	1.401	1.109	1.070																																																																																		
--	-	-	-	-	-																																																																																		

COSEL

Model	MGXS62412
Item	Switching frequency (by Load Current)
Object	+12V0.5A



Note: Slanted line shows the range of the rated load current.

When load current is low, MG operates intermittently, so switching frequency would not become constant.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]				
	6[V]	12[V]	24[V]	48[V]	60[V]
0.000	416	599	757	742	714
0.100	255	438	614	722	651
0.200	183	344	511	626	647
0.250	159	310	472	587	609
0.300	140	283	438	551	574
0.350	126	259	409	520	544
0.400	113	240	383	493	516
0.425	108	231	371	480	503
0.500	-	208	340	445	468
0.550	-	195	322	425	448
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)