



TEST DATA OF MHFS32412

Regulated DC Power Supply

May 27, 2020

Approved by : Kenichi Tsukada
Kenichi Tsukada Design Manager

Prepared by : Yoshihiko Saeki
Yoshihiko Saeki Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Switching frequency (by Load Current)	9
12.Figure of Testing Circuitry	10


(Final Page 10)

COSEL

Model	MHFS32412																																																																																			
Item	Input Current (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																																																		
Object	_____																																																																																			
1.Graph	—△— Input Volt. 9V - - -□--- Input Volt. 12V - - -*--- Input Volt. 18V - - -○--- Input Volt. 24V - - -◇--- Input Volt. 36V																																																																																			
	<p>The graph shows a linear increase of input current with load current for all input voltages. A slanted line is drawn through the origin, representing the rated load current range.</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.022</td><td>0.019</td><td>0.014</td><td>0.006</td><td>0.006</td></tr> <tr><td>0.050</td><td>0.097</td><td>0.075</td><td>0.052</td><td>0.041</td><td>0.030</td></tr> <tr><td>0.100</td><td>0.170</td><td>0.130</td><td>0.089</td><td>0.069</td><td>0.049</td></tr> <tr><td>0.150</td><td>0.245</td><td>0.185</td><td>0.126</td><td>0.096</td><td>0.067</td></tr> <tr><td>0.200</td><td>0.319</td><td>0.241</td><td>0.162</td><td>0.124</td><td>0.086</td></tr> <tr><td>0.225</td><td>0.359</td><td>0.269</td><td>0.181</td><td>0.138</td><td>0.095</td></tr> <tr><td>0.250</td><td>0.400</td><td>0.296</td><td>0.199</td><td>0.152</td><td>0.104</td></tr> <tr><td>0.275</td><td>0.440</td><td>0.325</td><td>0.218</td><td>0.165</td><td>0.113</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.022	0.019	0.014	0.006	0.006	0.050	0.097	0.075	0.052	0.041	0.030	0.100	0.170	0.130	0.089	0.069	0.049	0.150	0.245	0.185	0.126	0.096	0.067	0.200	0.319	0.241	0.162	0.124	0.086	0.225	0.359	0.269	0.181	0.138	0.095	0.250	0.400	0.296	0.199	0.152	0.104	0.275	0.440	0.325	0.218	0.165	0.113	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-											
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
0.00	0.022	0.019	0.014	0.006	0.006																																																																															
0.050	0.097	0.075	0.052	0.041	0.030																																																																															
0.100	0.170	0.130	0.089	0.069	0.049																																																																															
0.150	0.245	0.185	0.126	0.096	0.067																																																																															
0.200	0.319	0.241	0.162	0.124	0.086																																																																															
0.225	0.359	0.269	0.181	0.138	0.095																																																																															
0.250	0.400	0.296	0.199	0.152	0.104																																																																															
0.275	0.440	0.325	0.218	0.165	0.113																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.022</td><td>0.019</td><td>0.014</td><td>0.006</td><td>0.006</td></tr> <tr><td>0.050</td><td>0.097</td><td>0.075</td><td>0.052</td><td>0.041</td><td>0.030</td></tr> <tr><td>0.100</td><td>0.170</td><td>0.130</td><td>0.089</td><td>0.069</td><td>0.049</td></tr> <tr><td>0.150</td><td>0.245</td><td>0.185</td><td>0.126</td><td>0.096</td><td>0.067</td></tr> <tr><td>0.200</td><td>0.319</td><td>0.241</td><td>0.162</td><td>0.124</td><td>0.086</td></tr> <tr><td>0.225</td><td>0.359</td><td>0.269</td><td>0.181</td><td>0.138</td><td>0.095</td></tr> <tr><td>0.250</td><td>0.400</td><td>0.296</td><td>0.199</td><td>0.152</td><td>0.104</td></tr> <tr><td>0.275</td><td>0.440</td><td>0.325</td><td>0.218</td><td>0.165</td><td>0.113</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	0.022	0.019	0.014	0.006	0.006	0.050	0.097	0.075	0.052	0.041	0.030	0.100	0.170	0.130	0.089	0.069	0.049	0.150	0.245	0.185	0.126	0.096	0.067	0.200	0.319	0.241	0.162	0.124	0.086	0.225	0.359	0.269	0.181	0.138	0.095	0.250	0.400	0.296	0.199	0.152	0.104	0.275	0.440	0.325	0.218	0.165	0.113	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-						
Load Current [A]	Input Current [A]																																																																																			
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
0.000	0.022	0.019	0.014	0.006	0.006																																																																															
0.050	0.097	0.075	0.052	0.041	0.030																																																																															
0.100	0.170	0.130	0.089	0.069	0.049																																																																															
0.150	0.245	0.185	0.126	0.096	0.067																																																																															
0.200	0.319	0.241	0.162	0.124	0.086																																																																															
0.225	0.359	0.269	0.181	0.138	0.095																																																																															
0.250	0.400	0.296	0.199	0.152	0.104																																																																															
0.275	0.440	0.325	0.218	0.165	0.113																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Note:	Slanted line shows the range of the rated load current.																																																																																			

COSEL

Model	MHFS32412
Item	Efficiency (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]				
	9[V]	12[V]	18[V]	24[V]	36[V]
0.000	-	-	-	-	-
0.050	70.2	68.7	65.3	63.2	57.9
0.100	78.8	78.0	75.7	73.8	69.1
0.150	81.9	81.2	79.7	78.8	74.9
0.200	83.3	83.2	82.3	81.1	78.0
0.225	83.5	83.9	83.0	82.1	79.2
0.250	83.7	84.1	83.8	82.7	80.2
0.275	83.5	84.4	84.3	83.6	81.0
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	MHFS32412
Item	Line Regulation
Object	+12V0.25A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	11.990	11.993
9.0	11.990	11.993
12.0	11.991	11.993
15.0	11.991	11.993
18.0	11.991	11.993
24.0	11.992	11.993
30.0	11.992	11.993
36.0	11.992	11.994
40.0	11.992	11.994

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	MHFS32412	Temperature	25°C																																																																													
Item	Load Regulation	Testing Circuitry	Figure A																																																																													
Object	+12V0.25A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>12.001</td> <td>12.000</td> <td>11.999</td> <td>11.999</td> <td>11.999</td> </tr> <tr> <td>0.050</td> <td>11.999</td> <td>11.998</td> <td>11.997</td> <td>11.996</td> <td>11.998</td> </tr> <tr> <td>0.100</td> <td>11.998</td> <td>11.997</td> <td>11.996</td> <td>11.995</td> <td>11.995</td> </tr> <tr> <td>0.150</td> <td>11.997</td> <td>11.996</td> <td>11.995</td> <td>11.994</td> <td>11.994</td> </tr> <tr> <td>0.200</td> <td>11.996</td> <td>11.995</td> <td>11.994</td> <td>11.993</td> <td>11.993</td> </tr> <tr> <td>0.225</td> <td>11.995</td> <td>11.995</td> <td>11.993</td> <td>11.993</td> <td>11.993</td> </tr> <tr> <td>0.250</td> <td>11.995</td> <td>11.994</td> <td>11.993</td> <td>11.993</td> <td>11.993</td> </tr> <tr> <td>0.275</td> <td>11.994</td> <td>11.994</td> <td>11.993</td> <td>11.992</td> <td>11.993</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	12.001	12.000	11.999	11.999	11.999	0.050	11.999	11.998	11.997	11.996	11.998	0.100	11.998	11.997	11.996	11.995	11.995	0.150	11.997	11.996	11.995	11.994	11.994	0.200	11.996	11.995	11.994	11.993	11.993	0.225	11.995	11.995	11.993	11.993	11.993	0.250	11.995	11.994	11.993	11.993	11.993	0.275	11.994	11.994	11.993	11.992	11.993	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
0.000	12.001	12.000	11.999	11.999	11.999																																																																											
0.050	11.999	11.998	11.997	11.996	11.998																																																																											
0.100	11.998	11.997	11.996	11.995	11.995																																																																											
0.150	11.997	11.996	11.995	11.994	11.994																																																																											
0.200	11.996	11.995	11.994	11.993	11.993																																																																											
0.225	11.995	11.995	11.993	11.993	11.993																																																																											
0.250	11.995	11.994	11.993	11.993	11.993																																																																											
0.275	11.994	11.994	11.993	11.992	11.993																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+12V0.25A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 24V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p>																																																																															

COSEL


Model	MHFS32412	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+12V0.25A	

Input Volt. 24 V
 Cycle 100 ms



Min.Load (0A) →
 Load 50% (0.125A)


200 mV/div



COSEL


Model	MHFS32412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.25A		

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.3	0.6	1.9	0.2	5.0	
100 %		1.3	0.6	1.9	0.2	1.8	



COSEL

Model	MHFS32412
Item	Overcurrent Protection
Object	+12V0.25A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
11.4	0.366	0.387	0.377	0.371	0.373
10.8	0.380	0.400	0.389	0.379	0.382
9.6	0.416	0.436	0.419	0.404	0.406
8.4	0.456	0.476	0.449	0.431	0.430
7.2	0.502	0.520	0.484	0.463	0.458
6.0	0.553	0.567	0.520	0.496	0.490
4.8	0.612	0.618	0.559	0.531	0.522
3.6	0.656	0.664	0.606	0.569	0.556
2.4	0.679	0.688	0.638	0.602	0.582
1.2	0.821	0.796	0.699	0.651	0.624
0.0	0.904	0.865	0.751	0.616	0.583
--	-	-	-	-	-

Note: Slanted line shows the range of the rated load current.



Model	MHFS32412	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V0.25A	

1.Values

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 9V	Input Volt. 12V	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	11.891	11.892	11.892	11.894	11.895
25	11.989	11.989	11.989	11.990	11.990
75	12.019	12.020	12.020	12.020	12.020

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V0.25A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	7.3	7.3
25	7.2	7.3
75	7.0	7.0

COSEL

Model	MHFS32412	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Switching frequency (by Load Current)																																																																															
Object	+12V0.25A																																																																															
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MH operates intermittently, so switching frequency would not become constant.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Switching Frequency [kHz]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>806</td> <td>898</td> <td>990</td> <td>1009</td> <td>954</td> </tr> <tr> <td>0.050</td> <td>657</td> <td>750</td> <td>837</td> <td>931</td> <td>940</td> </tr> <tr> <td>0.100</td> <td>519</td> <td>614</td> <td>712</td> <td>812</td> <td>874</td> </tr> <tr> <td>0.150</td> <td>441</td> <td>540</td> <td>621</td> <td>739</td> <td>810</td> </tr> <tr> <td>0.200</td> <td>373</td> <td>467</td> <td>554</td> <td>655</td> <td>726</td> </tr> <tr> <td>0.225</td> <td>348</td> <td>433</td> <td>518</td> <td>623</td> <td>695</td> </tr> <tr> <td>0.250</td> <td>321</td> <td>408</td> <td>499</td> <td>592</td> <td>667</td> </tr> <tr> <td>0.275</td> <td>282</td> <td>361</td> <td>471</td> <td>539</td> <td>610</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Switching Frequency [kHz]					9[V]	12[V]	18[V]	24[V]	36[V]	0.000	806	898	990	1009	954	0.050	657	750	837	931	940	0.100	519	614	712	812	874	0.150	441	540	621	739	810	0.200	373	467	554	655	726	0.225	348	433	518	623	695	0.250	321	408	499	592	667	0.275	282	361	471	539	610	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Switching Frequency [kHz]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
0.000	806	898	990	1009	954																																																																											
0.050	657	750	837	931	940																																																																											
0.100	519	614	712	812	874																																																																											
0.150	441	540	621	739	810																																																																											
0.200	373	467	554	655	726																																																																											
0.225	348	433	518	623	695																																																																											
0.250	321	408	499	592	667																																																																											
0.275	282	361	471	539	610																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

COSEL




Figure A




Figure B