



# TEST DATA OF MHFS34805

Regulated DC Power Supply  
May 29, 2020

Approved by : Kenichi Tsukada  
Kenichi Tsukada Design Manager


Prepared by : Yoshihiko Saeki  
Yoshihiko Saeki Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Line Regulation . . . . .	3
4.Load Regulation . . . . .	4
5.Ripple-Noise . . . . .	4
6.Dynamic Load Response . . . . .	5
7.Rise and Fall Time . . . . .	6
8.Overcurrent Protection . . . . .	7
9.Ambient Temperature Drift . . . . .	8
10.Minimum Input Voltage for Regulated Output Voltage . . . . .	8
11.Switching frequency (by Load Current) . . . . .	9
12.Figure of Testing Circuitry . . . . .	10

(Final Page 10)

Model		MHFS34805		Temperature 25°C																																																																														
Item		Input Current (by Load Current)		Testing Circuitry Figure A																																																																														
Object																																																																																		
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>18V</div></div><div><div>---□---</div><div>Input Volt.</div><div>24V</div></div><div><div>-·-·*-·-</div><div>Input Volt.</div><div>36V</div></div><div><div>-·-○-</div><div>Input Volt.</div><div>48V</div></div><div><div>---◇---</div><div>Input Volt.</div><div>76V</div></div></div> <div></div> <div>Note: Slanted line shows the range of the rated load current.</div>		2.Values																																																																														
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="5">Input Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.00</td><td>0.008</td><td>0.007</td><td>0.004</td><td>0.002</td><td>0.003</td></tr><tr><td>0.12</td><td>0.047</td><td>0.036</td><td>0.025</td><td>0.019</td><td>0.014</td></tr><tr><td>0.24</td><td>0.086</td><td>0.065</td><td>0.044</td><td>0.034</td><td>0.024</td></tr><tr><td>0.36</td><td>0.126</td><td>0.094</td><td>0.064</td><td>0.049</td><td>0.033</td></tr><tr><td>0.48</td><td>0.167</td><td>0.124</td><td>0.084</td><td>0.063</td><td>0.043</td></tr><tr><td>0.54</td><td>0.188</td><td>0.140</td><td>0.094</td><td>0.071</td><td>0.047</td></tr><tr><td>0.60</td><td>0.209</td><td>0.155</td><td>0.103</td><td>0.078</td><td>0.052</td></tr><tr><td>0.66</td><td>0.232</td><td>0.171</td><td>0.113</td><td>0.086</td><td>0.056</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Input Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	0.008	0.007	0.004	0.002	0.003	0.12	0.047	0.036	0.025	0.019	0.014	0.24	0.086	0.065	0.044	0.034	0.024	0.36	0.126	0.094	0.064	0.049	0.033	0.48	0.167	0.124	0.084	0.063	0.043	0.54	0.188	0.140	0.094	0.071	0.047	0.60	0.209	0.155	0.103	0.078	0.052	0.66	0.232	0.171	0.113	0.086	0.056	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	0.008	0.007	0.004	0.002	0.003																																																																													
0.12	0.047	0.036	0.025	0.019	0.014																																																																													
0.24	0.086	0.065	0.044	0.034	0.024																																																																													
0.36	0.126	0.094	0.064	0.049	0.033																																																																													
0.48	0.167	0.124	0.084	0.063	0.043																																																																													
0.54	0.188	0.140	0.094	0.071	0.047																																																																													
0.60	0.209	0.155	0.103	0.078	0.052																																																																													
0.66	0.232	0.171	0.113	0.086	0.056																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Model		MHFS34805		Temperature 25°C																																																																														
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																																														
Object																																																																																		
1.Graph		<div><div><div>—△—</div>Input Volt. 18V</div><div><div>---□---</div>Input Volt. 24V</div><div><div>-·-*·-</div>Input Volt. 36V</div><div><div>-·-○-</div>Input Volt. 48V</div><div><div>---◇---</div>Input Volt. 76V</div></div> <p>Note: Slanted line shows the range of the rated load current.</p>		2.Values																																																																														
				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="5">Efficiency [%]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.12</td><td>72.6</td><td>70.8</td><td>68.2</td><td>65.5</td><td>58.6</td></tr><tr><td>0.24</td><td>78.2</td><td>78.0</td><td>76.8</td><td>74.5</td><td>66.1</td></tr><tr><td>0.36</td><td>79.9</td><td>80.2</td><td>79.2</td><td>77.6</td><td>72.1</td></tr><tr><td>0.48</td><td>80.3</td><td>80.9</td><td>80.5</td><td>79.6</td><td>75.0</td></tr><tr><td>0.54</td><td>80.2</td><td>81.1</td><td>80.9</td><td>80.1</td><td>76.2</td></tr><tr><td>0.60</td><td>80.0</td><td>81.0</td><td>81.3</td><td>80.5</td><td>77.1</td></tr><tr><td>0.66</td><td>79.6</td><td>81.0</td><td>81.4</td><td>80.8</td><td>77.7</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	-	-	-	-	-	0.12	72.6	70.8	68.2	65.5	58.6	0.24	78.2	78.0	76.8	74.5	66.1	0.36	79.9	80.2	79.2	77.6	72.1	0.48	80.3	80.9	80.5	79.6	75.0	0.54	80.2	81.1	80.9	80.1	76.2	0.60	80.0	81.0	81.3	80.5	77.1	0.66	79.6	81.0	81.4	80.8	77.7	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.12	72.6	70.8	68.2	65.5	58.6																																																																													
0.24	78.2	78.0	76.8	74.5	66.1																																																																													
0.36	79.9	80.2	79.2	77.6	72.1																																																																													
0.48	80.3	80.9	80.5	79.6	75.0																																																																													
0.54	80.2	81.1	80.9	80.1	76.2																																																																													
0.60	80.0	81.0	81.3	80.5	77.1																																																																													
0.66	79.6	81.0	81.4	80.8	77.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													



Model		MHFS34805	Temperature		25°C																																																		
Item		Line Regulation	Testing Circuitry		Figure A																																																		
Object		+5V0.6A																																																					
1.Graph			2.Values																																																				
<div><div><div><div><div></div><div></div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div></div><div>Load 50%</div><div>Load 100%</div></div> <table><thead><tr><th>Input Voltage [V]</th><th>Output Voltage [V]</th></tr></thead><tbody><tr><td>17.2</td><td>5.033</td></tr><tr><td>18.0</td><td>5.033</td></tr><tr><td>24.0</td><td>5.033</td></tr><tr><td>30.0</td><td>5.033</td></tr><tr><td>36.0</td><td>5.033</td></tr><tr><td>48.0</td><td>5.033</td></tr><tr><td>60.0</td><td>5.033</td></tr><tr><td>75.0</td><td>5.033</td></tr></tbody></table> <p>Note: Slanted line shows the range of the rated input voltage.</p>			Input Voltage [V]	Output Voltage [V]	17.2	5.033	18.0	5.033	24.0	5.033	30.0	5.033	36.0	5.033	48.0	5.033	60.0	5.033	75.0	5.033	<table><thead><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Output Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>17.2</td><td>5.033</td><td>5.033</td></tr><tr><td>18.0</td><td>5.033</td><td>5.033</td></tr><tr><td>24.0</td><td>5.033</td><td>5.033</td></tr><tr><td>30.0</td><td>5.033</td><td>5.033</td></tr><tr><td>36.0</td><td>5.033</td><td>5.034</td></tr><tr><td>48.0</td><td>5.033</td><td>5.034</td></tr><tr><td>60.0</td><td>5.033</td><td>5.034</td></tr><tr><td>76.0</td><td>5.033</td><td>5.034</td></tr><tr><td>80.0</td><td>5.033</td><td>5.034</td></tr></tbody></table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17.2	5.033	5.033	18.0	5.033	5.033	24.0	5.033	5.033	30.0	5.033	5.033	36.0	5.033	5.034	48.0	5.033	5.034	60.0	5.033	5.034	76.0	5.033	5.034	80.0	5.033	5.034
Input Voltage [V]	Output Voltage [V]																																																						
17.2	5.033																																																						
18.0	5.033																																																						
24.0	5.033																																																						
30.0	5.033																																																						
36.0	5.033																																																						
48.0	5.033																																																						
60.0	5.033																																																						
75.0	5.033																																																						
Input Voltage [V]	Output Voltage [V]																																																						
	Load 50%	Load 100%																																																					
17.2	5.033	5.033																																																					
18.0	5.033	5.033																																																					
24.0	5.033	5.033																																																					
30.0	5.033	5.033																																																					
36.0	5.033	5.034																																																					
48.0	5.033	5.034																																																					
60.0	5.033	5.034																																																					
76.0	5.033	5.034																																																					
80.0	5.033	5.034																																																					

BC-11618

Model		MHFS34805	Temperature 25°C Testing Circuitry Figure A
Item		Dynamic Load Response	
Object		+5V0.6A	

Input Volt.	48 V
Cycle	100 ms

Temperature	25°C
Testing Circuitry	Figure A

$$t_1, t_2 = 50 \mu s$$

Load Current

A diagram of a fillet weld joint. It shows two plates meeting at a corner, with a weld filling the gap. The throat thickness, which is the minimum thickness of the weld, is indicated by a dimension line and labeled  $t_2$ .

Min.Load (0A) ←→ Load 100% (0.6A)

200 mV/div

1 ms/div

1 ms/div

Min.Load (0A) ←→ Load 50% (0.3A)

200 mV/div


1 ms/div

1 ms/div




Model	MHFS34805	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V0.6A		

## 1.Graph



## 2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.8	0.4	1.2	0.3	1.2
100 %		0.8	0.4	1.2	0.2	0.5





Model		MHFS34805	Temperature		25°C																																																																																			
Item		Overcurrent Protection	Testing Circuitry		Figure A																																																																																			
Object		+5V0.6A																																																																																						
1.Graph			2.Values																																																																																					
<div><div><div></div><div>Input Volt. 18V</div></div><div><div></div><div>Input Volt. 24V</div></div><div><div></div><div>Input Volt. 36V</div></div><div><div></div><div>Input Volt. 48V</div></div><div><div></div><div>Input Volt. 76V</div></div></div> <div><div>Output Voltage [V]</div><div>Load Current [A]</div></div> <div>Note: Slanted line shows the range of the rated load current.</div>			<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="5">Load Current [A]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>4.75</td><td>0.864</td><td>0.904</td><td>0.886</td><td>0.882</td><td>0.911</td></tr><tr><td>4.50</td><td>0.889</td><td>0.948</td><td>0.915</td><td>0.904</td><td>0.929</td></tr><tr><td>4.00</td><td>0.965</td><td>1.030</td><td>0.965</td><td>0.955</td><td>0.975</td></tr><tr><td>3.50</td><td>1.055</td><td>1.103</td><td>1.020</td><td>1.006</td><td>1.020</td></tr><tr><td>3.00</td><td>1.151</td><td>1.182</td><td>1.087</td><td>1.066</td><td>1.072</td></tr><tr><td>2.50</td><td>1.223</td><td>1.256</td><td>1.149</td><td>1.120</td><td>1.118</td></tr><tr><td>2.00</td><td>1.258</td><td>1.331</td><td>1.220</td><td>1.180</td><td>1.157</td></tr><tr><td>1.50</td><td>1.225</td><td>1.322</td><td>1.251</td><td>1.193</td><td>1.136</td></tr><tr><td>1.00</td><td>1.504</td><td>1.484</td><td>1.287</td><td>1.250</td><td>1.216</td></tr><tr><td>0.50</td><td>1.659</td><td>1.614</td><td>1.397</td><td>1.315</td><td>1.241</td></tr><tr><td>0.00</td><td>1.682</td><td>1.564</td><td>1.345</td><td>1.262</td><td>1.172</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>			Output Voltage [V]	Load Current [A]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	4.75	0.864	0.904	0.886	0.882	0.911	4.50	0.889	0.948	0.915	0.904	0.929	4.00	0.965	1.030	0.965	0.955	0.975	3.50	1.055	1.103	1.020	1.006	1.020	3.00	1.151	1.182	1.087	1.066	1.072	2.50	1.223	1.256	1.149	1.120	1.118	2.00	1.258	1.331	1.220	1.180	1.157	1.50	1.225	1.322	1.251	1.193	1.136	1.00	1.504	1.484	1.287	1.250	1.216	0.50	1.659	1.614	1.397	1.315	1.241	0.00	1.682	1.564	1.345	1.262	1.172	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																																			
4.75	0.864	0.904	0.886	0.882	0.911																																																																																			
4.50	0.889	0.948	0.915	0.904	0.929																																																																																			
4.00	0.965	1.030	0.965	0.955	0.975																																																																																			
3.50	1.055	1.103	1.020	1.006	1.020																																																																																			
3.00	1.151	1.182	1.087	1.066	1.072																																																																																			
2.50	1.223	1.256	1.149	1.120	1.118																																																																																			
2.00	1.258	1.331	1.220	1.180	1.157																																																																																			
1.50	1.225	1.322	1.251	1.193	1.136																																																																																			
1.00	1.504	1.484	1.287	1.250	1.216																																																																																			
0.50	1.659	1.614	1.397	1.315	1.241																																																																																			
0.00	1.682	1.564	1.345	1.262	1.172																																																																																			
--	-	-	-	-	-																																																																																			

**COSEL**

		Testing Circuitry Figure A
Model	MHFS34805	
Item	Ambient Temperature Drift	
Object	+5V0.6A	

## 1.Values

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	5.008	5.008	5.009	5.010	5.010
25	5.032	5.032	5.033	5.033	5.033
75	5.035	5.035	5.035	5.035	5.035

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V0.6A	

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	14.3	14.6
25	14.3	14.4
75	13.8	13.9

Model		MHFS34805		Temperature 25°C																																																																														
Item		Switching frequency (by Load Current)		Testing Circuitry Figure A																																																																														
Object		+5V0.6A																																																																																
1.Graph		<div><div>—△—</div>Input Volt. 18V</div> <div><div>---□---</div>Input Volt. 24V</div> <div><div>-·-·*·-·-</div>Input Volt. 36V</div> <div><div>-·-·○-·-</div>Input Volt. 48V</div> <div><div>---◇---</div>Input Volt. 76V</div>																																																																																
<div>Switching Frequency [kHz]</div> <div><div>Load Current [A]</div></div>		2.Values																																																																																
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="5">Switching Frequency [kHz]</th></tr><tr><th>Input Volt. 18[V]</th><th>Input Volt. 24[V]</th><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.00</td><td>815</td><td>918</td><td>1027</td><td>1031</td><td>1008</td></tr><tr><td>0.12</td><td>644</td><td>762</td><td>829</td><td>959</td><td>906</td></tr><tr><td>0.24</td><td>499</td><td>610</td><td>705</td><td>804</td><td>845</td></tr><tr><td>0.36</td><td>431</td><td>519</td><td>597</td><td>707</td><td>785</td></tr><tr><td>0.48</td><td>356</td><td>434</td><td>517</td><td>625</td><td>699</td></tr><tr><td>0.54</td><td>326</td><td>411</td><td>489</td><td>586</td><td>664</td></tr><tr><td>0.60</td><td>302</td><td>382</td><td>465</td><td>548</td><td>626</td></tr><tr><td>0.66</td><td>260</td><td>337</td><td>434</td><td>499</td><td>574</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Current [A]	Switching Frequency [kHz]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.00	815	918	1027	1031	1008	0.12	644	762	829	959	906	0.24	499	610	705	804	845	0.36	431	519	597	707	785	0.48	356	434	517	625	699	0.54	326	411	489	586	664	0.60	302	382	465	548	626	0.66	260	337	434	499	574	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Current [A]	Switching Frequency [kHz]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0.00	815	918	1027	1031	1008																																																																													
0.12	644	762	829	959	906																																																																													
0.24	499	610	705	804	845																																																																													
0.36	431	519	597	707	785																																																																													
0.48	356	434	517	625	699																																																																													
0.54	326	411	489	586	664																																																																													
0.60	302	382	465	548	626																																																																													
0.66	260	337	434	499	574																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<div>Note: Slanted line shows the range of the rated load current.</div> <div>When load current is low, MH operates intermittently, so switching frequency would not become constant.</div>																																																																																		




Figure A




Figure B