

TEST DATA OF MHFW62412

Regulated DC Power Supply
October 27, 2021

Approved by : _____ Kenichi Tsukada

Design Manager

Prepared by : _____ Yoshihiko Saeki

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Cross Regulation	4,5
5.Ripple-Noise	4,5
6.Dynamic Load Response	6,7
7.Rise and Fall Time	8,9
8.Overcurrent Protection	10
9.Ambient Temperature Drift	11,12
10.Minimum Input Voltage for Regulated Output Voltage	11,12
11.Switching frequency (by Load Current)	13
12.Figure of Testing Circuitry	14

(Final Page 14)

COSEL

Model	MHFW62412
Item	Input Current (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2.Values

Load Ratio [%]	Input Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
0	0.031	0.025	0.018	0.013	0.007
20	0.182	0.136	0.092	0.071	0.052
40	0.333	0.250	0.169	0.129	0.090
60	0.494	0.366	0.243	0.184	0.128
80	0.663	0.487	0.320	0.241	0.164
90	0.752	0.550	0.359	0.270	0.183
100	*1	0.613	0.399	0.299	0.202
110	*1	0.678	0.440	0.328	0.221
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 9V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL

Model	MHFW62412
Item	Efficiency (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Efficiency [%]				
	9[V]	12[V]	18[V]	24[V]	36[V]
0	-	-	-	-	-
20	74.2	74.3	73.4	71.6	64.8
40	80.9	80.9	79.5	78.5	75.1
60	81.7	82.7	83.0	82.1	78.7
80	81.0	82.8	83.9	83.8	81.8
90	80.3	82.6	84.1	84.2	82.5
100	*1	82.2	84.0	84.3	83.2
110	*1	81.7	83.9	84.4	83.6
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


*1 Maximum output current at 9V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL

Model	MHFW62412
Item	Line Regulation
Object	+12V0.25A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	12.153	*1
9.0	12.152	*1
12.0	12.147	12.044
15.0	12.145	12.049
18.0	12.143	12.052
24.0	12.141	12.055
30.0	12.141	12.057
36.0	12.141	12.058
40.0	12.140	12.058

-12V:Rated Load Current

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	-12.194	*1
9.0	-12.192	*1
12.0	-12.175	-12.078
15.0	-12.166	-12.074
18.0	-12.160	-12.072
24.0	-12.154	-12.069
30.0	-12.150	-12.067
36.0	-12.148	-12.066
40.0	-12.147	-12.065

+12V:Rated Load Current

Note: Slanted line shows the range of the rated input voltage.


*1 Maximum output current at 9V input
Voltage is 80% of rated load current.
Refer to instruction manuals for details of
input derating.

COSEL

Model	MHFW62412	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	+12V0.25A																																																																															
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>12.358</td> <td>12.338</td> <td>12.329</td> <td>12.329</td> <td>12.324</td> </tr> <tr> <td>0.05</td> <td>12.247</td> <td>12.234</td> <td>12.224</td> <td>12.221</td> <td>12.218</td> </tr> <tr> <td>0.10</td> <td>12.182</td> <td>12.176</td> <td>12.170</td> <td>12.168</td> <td>12.166</td> </tr> <tr> <td>0.15</td> <td>12.129</td> <td>12.127</td> <td>12.126</td> <td>12.125</td> <td>12.124</td> </tr> <tr> <td>0.20</td> <td>12.079</td> <td>12.083</td> <td>12.086</td> <td>12.087</td> <td>12.088</td> </tr> <tr> <td>0.23</td> <td>12.055</td> <td>12.062</td> <td>12.067</td> <td>12.070</td> <td>12.071</td> </tr> <tr> <td>0.25</td> <td>*1</td> <td>12.041</td> <td>12.049</td> <td>12.052</td> <td>12.055</td> </tr> <tr> <td>0.28</td> <td>*1</td> <td>12.021</td> <td>12.031</td> <td>12.036</td> <td>12.039</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>-12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	12.358	12.338	12.329	12.329	12.324	0.05	12.247	12.234	12.224	12.221	12.218	0.10	12.182	12.176	12.170	12.168	12.166	0.15	12.129	12.127	12.126	12.125	12.124	0.20	12.079	12.083	12.086	12.087	12.088	0.23	12.055	12.062	12.067	12.070	12.071	0.25	*1	12.041	12.049	12.052	12.055	0.28	*1	12.021	12.031	12.036	12.039	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
0.00	12.358	12.338	12.329	12.329	12.324																																																																											
0.05	12.247	12.234	12.224	12.221	12.218																																																																											
0.10	12.182	12.176	12.170	12.168	12.166																																																																											
0.15	12.129	12.127	12.126	12.125	12.124																																																																											
0.20	12.079	12.083	12.086	12.087	12.088																																																																											
0.23	12.055	12.062	12.067	12.070	12.071																																																																											
0.25	*1	12.041	12.049	12.052	12.055																																																																											
0.28	*1	12.021	12.031	12.036	12.039																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+12V0.25A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 24V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p> <p>-12V:Rated Load Current</p>																																																																															

COSEL

Model	MHFW62412	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	-12V0.25A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-12.390</td> <td>-12.362</td> <td>-12.347</td> <td>-12.346</td> <td>-12.337</td> </tr> <tr> <td>0.05</td> <td>-12.277</td> <td>-12.256</td> <td>-12.238</td> <td>-12.231</td> <td>-12.226</td> </tr> <tr> <td>0.10</td> <td>-12.219</td> <td>-12.202</td> <td>-12.186</td> <td>-12.178</td> <td>-12.173</td> </tr> <tr> <td>0.15</td> <td>-12.169</td> <td>-12.156</td> <td>-12.143</td> <td>-12.137</td> <td>-12.132</td> </tr> <tr> <td>0.20</td> <td>-12.126</td> <td>-12.117</td> <td>-12.107</td> <td>-12.102</td> <td>-12.098</td> </tr> <tr> <td>0.23</td> <td>-12.104</td> <td>-12.097</td> <td>-12.089</td> <td>-12.086</td> <td>-12.082</td> </tr> <tr> <td>0.25</td> <td>*1</td> <td>-12.078</td> <td>-12.072</td> <td>-12.070</td> <td>-12.066</td> </tr> <tr> <td>0.28</td> <td>*1</td> <td>-12.059</td> <td>-12.056</td> <td>-12.054</td> <td>-12.051</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-12.390	-12.362	-12.347	-12.346	-12.337	0.05	-12.277	-12.256	-12.238	-12.231	-12.226	0.10	-12.219	-12.202	-12.186	-12.178	-12.173	0.15	-12.169	-12.156	-12.143	-12.137	-12.132	0.20	-12.126	-12.117	-12.107	-12.102	-12.098	0.23	-12.104	-12.097	-12.089	-12.086	-12.082	0.25	*1	-12.078	-12.072	-12.070	-12.066	0.28	*1	-12.059	-12.056	-12.054	-12.051	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
0.00	-12.390	-12.362	-12.347	-12.346	-12.337																																																																											
0.05	-12.277	-12.256	-12.238	-12.231	-12.226																																																																											
0.10	-12.219	-12.202	-12.186	-12.178	-12.173																																																																											
0.15	-12.169	-12.156	-12.143	-12.137	-12.132																																																																											
0.20	-12.126	-12.117	-12.107	-12.102	-12.098																																																																											
0.23	-12.104	-12.097	-12.089	-12.086	-12.082																																																																											
0.25	*1	-12.078	-12.072	-12.070	-12.066																																																																											
0.28	*1	-12.059	-12.056	-12.054	-12.051																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	-12V0.25A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 24V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p> <p>+12V:Rated Load Current</p>																																																																															

COSEL

COSEL

Model	MHFW62412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.25A		

Input Volt. 24 V

+12V:rated load current.

Response. $t_1=t_2=50\mu s$. Typ


Cycle 100 ms



Min.Load (0A)↔
Load 100% (0.25A)

200 mV/div

1 ms/div




1 ms/div

Min.Load (0A)↔
Load 50% (0.125A)

200 mV/div

1 ms/div




1 ms/div

COSEL

Model	MHFW62412
Item	Rise and Fall Time
Object	+12V0.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.2	0.5	1.7	0.2	3.1	
100 %		1.2	0.5	1.7	0.1	0.9	




COSEL

Model	MHFW62412
Item	Rise and Fall Time
Object	-12V0.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.2	0.5	1.7	0.2	3.7
100 %		1.2	0.5	1.7	0.1	1.0



COSEL

Model	MHFW62412	Temperature	25°C																																																																													
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																													
Object	+12V0.25A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — Input Volt. 9V — Input Volt. 12V — Input Volt. 18V — Input Volt. 24V — Input Volt. 36V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.314</td><td>0.394</td><td>0.460</td><td>0.463</td><td>0.455</td></tr> <tr><td>10.8</td><td>0.264</td><td>0.291</td><td>0.317</td><td>0.324</td><td>0.341</td></tr> <tr><td>9.6</td><td>0.409</td><td>0.485</td><td>0.545</td><td>0.543</td><td>0.532</td></tr> <tr><td>8.4</td><td>0.478</td><td>0.554</td><td>0.608</td><td>0.604</td><td>0.587</td></tr> <tr><td>7.2</td><td>0.545</td><td>0.626</td><td>0.675</td><td>0.666</td><td>0.643</td></tr> <tr><td>6.0</td><td>0.623</td><td>0.700</td><td>0.744</td><td>0.729</td><td>0.699</td></tr> <tr><td>4.8</td><td>0.703</td><td>0.778</td><td>0.815</td><td>0.795</td><td>0.760</td></tr> <tr><td>3.6</td><td>0.779</td><td>0.850</td><td>0.879</td><td>0.854</td><td>0.814</td></tr> <tr><td>2.4</td><td>0.868</td><td>0.931</td><td>0.947</td><td>0.916</td><td>0.870</td></tr> <tr><td>1.2</td><td>0.966</td><td>1.018</td><td>1.016</td><td>0.975</td><td>0.919</td></tr> <tr><td>0.0</td><td>0.946</td><td>0.955</td><td>0.909</td><td>0.852</td><td>0.785</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	11.4	0.314	0.394	0.460	0.463	0.455	10.8	0.264	0.291	0.317	0.324	0.341	9.6	0.409	0.485	0.545	0.543	0.532	8.4	0.478	0.554	0.608	0.604	0.587	7.2	0.545	0.626	0.675	0.666	0.643	6.0	0.623	0.700	0.744	0.729	0.699	4.8	0.703	0.778	0.815	0.795	0.760	3.6	0.779	0.850	0.879	0.854	0.814	2.4	0.868	0.931	0.947	0.916	0.870	1.2	0.966	1.018	1.016	0.975	0.919	0.0	0.946	0.955	0.909	0.852	0.785
Output Voltage [V]	Load Current [A]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
11.4	0.314	0.394	0.460	0.463	0.455																																																																											
10.8	0.264	0.291	0.317	0.324	0.341																																																																											
9.6	0.409	0.485	0.545	0.543	0.532																																																																											
8.4	0.478	0.554	0.608	0.604	0.587																																																																											
7.2	0.545	0.626	0.675	0.666	0.643																																																																											
6.0	0.623	0.700	0.744	0.729	0.699																																																																											
4.8	0.703	0.778	0.815	0.795	0.760																																																																											
3.6	0.779	0.850	0.879	0.854	0.814																																																																											
2.4	0.868	0.931	0.947	0.916	0.870																																																																											
1.2	0.966	1.018	1.016	0.975	0.919																																																																											
0.0	0.946	0.955	0.909	0.852	0.785																																																																											
Object	-12V0.25A	2.Values																																																																														
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — Input Volt. 9V — Input Volt. 12V — Input Volt. 18V — Input Volt. 24V — Input Volt. 36V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.355</td><td>0.438</td><td>0.508</td><td>0.510</td><td>0.498</td></tr> <tr><td>-10.8</td><td>0.378</td><td>0.467</td><td>0.530</td><td>0.531</td><td>0.522</td></tr> <tr><td>-9.6</td><td>0.436</td><td>0.528</td><td>0.585</td><td>0.584</td><td>0.572</td></tr> <tr><td>-8.4</td><td>0.505</td><td>0.592</td><td>0.643</td><td>0.639</td><td>0.623</td></tr> <tr><td>-7.2</td><td>0.573</td><td>0.658</td><td>0.705</td><td>0.696</td><td>0.673</td></tr> <tr><td>-6.0</td><td>0.645</td><td>0.727</td><td>0.768</td><td>0.753</td><td>0.724</td></tr> <tr><td>-4.8</td><td>0.720</td><td>0.799</td><td>0.833</td><td>0.814</td><td>0.780</td></tr> <tr><td>-3.6</td><td>0.799</td><td>0.874</td><td>0.899</td><td>0.874</td><td>0.835</td></tr> <tr><td>-2.4</td><td>0.884</td><td>0.950</td><td>0.964</td><td>0.932</td><td>0.887</td></tr> <tr><td>-1.2</td><td>0.987</td><td>1.048</td><td>1.040</td><td>0.992</td><td>0.936</td></tr> <tr><td>0.0</td><td>0.981</td><td>0.994</td><td>0.939</td><td>0.900</td><td>0.825</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p> <p>Maximum output current at 9V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	-11.4	0.355	0.438	0.508	0.510	0.498	-10.8	0.378	0.467	0.530	0.531	0.522	-9.6	0.436	0.528	0.585	0.584	0.572	-8.4	0.505	0.592	0.643	0.639	0.623	-7.2	0.573	0.658	0.705	0.696	0.673	-6.0	0.645	0.727	0.768	0.753	0.724	-4.8	0.720	0.799	0.833	0.814	0.780	-3.6	0.799	0.874	0.899	0.874	0.835	-2.4	0.884	0.950	0.964	0.932	0.887	-1.2	0.987	1.048	1.040	0.992	0.936	0.0	0.981	0.994	0.939	0.900	0.825
Output Voltage [V]	Load Current [A]																																																																															
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																											
-11.4	0.355	0.438	0.508	0.510	0.498																																																																											
-10.8	0.378	0.467	0.530	0.531	0.522																																																																											
-9.6	0.436	0.528	0.585	0.584	0.572																																																																											
-8.4	0.505	0.592	0.643	0.639	0.623																																																																											
-7.2	0.573	0.658	0.705	0.696	0.673																																																																											
-6.0	0.645	0.727	0.768	0.753	0.724																																																																											
-4.8	0.720	0.799	0.833	0.814	0.780																																																																											
-3.6	0.799	0.874	0.899	0.874	0.835																																																																											
-2.4	0.884	0.950	0.964	0.932	0.887																																																																											
-1.2	0.987	1.048	1.040	0.992	0.936																																																																											
0.0	0.981	0.994	0.939	0.900	0.825																																																																											
Note: Slanted line shows the range of the rated load current.		BC-11829																																																																														



Model	MHFW62412	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+12V0.25A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 9V*1	Input Volt. 12V	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	11.962	11.968	11.976	11.980	11.983
25	12.039	12.041	12.048	12.051	12.054
55	12.049	12.051	12.058	12.061	12.063

*1 Load 80%

-12V:Rated Load Current

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V0.25A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	7.2	7.1
25	7.0	7.0
55	7.0	7.2



Model	MHFW62412	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	-12V0.25A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 9V*1	Input Volt. 12V	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	-11.995	-12.000	-11.998	-11.997	-11.995
25	-12.074	-12.075	-12.070	-12.068	-12.065
55	-12.085	-12.084	-12.079	-12.076	-12.073

*1 Load 80%

+12V:Rated Load Current

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	-12V0.25A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	7.2	7.1
25	7.0	7.0
55	7.0	7.2

COSEL

Model	MHFW62412																																																																																		
Item	Switching frequency (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																																																																	
Object	+/-12V0.25A																																																																																		
1.Graph						2.Values																																																																													
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Switching Frequency [kHz]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>781</td> <td>865</td> <td>957</td> <td>978</td> <td>935</td> </tr> <tr> <td>0.05</td> <td>448</td> <td>546</td> <td>662</td> <td>723</td> <td>783</td> </tr> <tr> <td>0.10</td> <td>317</td> <td>399</td> <td>506</td> <td>568</td> <td>637</td> </tr> <tr> <td>0.15</td> <td>243</td> <td>314</td> <td>413</td> <td>471</td> <td>535</td> </tr> <tr> <td>0.20</td> <td>196</td> <td>258</td> <td>347</td> <td>402</td> <td>466</td> </tr> <tr> <td>0.23</td> <td>178</td> <td>237</td> <td>321</td> <td>375</td> <td>437</td> </tr> <tr> <td>0.25</td> <td>*1</td> <td>219</td> <td>299</td> <td>351</td> <td>412</td> </tr> <tr> <td>0.28</td> <td>*1</td> <td>203</td> <td>280</td> <td>330</td> <td>389</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>						Load Current [A]	Switching Frequency [kHz]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	781	865	957	978	935	0.05	448	546	662	723	783	0.10	317	399	506	568	637	0.15	243	314	413	471	535	0.20	196	258	347	402	466	0.23	178	237	321	375	437	0.25	*1	219	299	351	412	0.28	*1	203	280	330	389	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Switching Frequency [kHz]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
0.00	781	865	957	978	935																																																																														
0.05	448	546	662	723	783																																																																														
0.10	317	399	506	568	637																																																																														
0.15	243	314	413	471	535																																																																														
0.20	196	258	347	402	466																																																																														
0.23	178	237	321	375	437																																																																														
0.25	*1	219	299	351	412																																																																														
0.28	*1	203	280	330	389																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
	<p>Note: Slanted line shows the range of the rated load current. When load current is low, MH operates intermittently, so switching frequency would not become constant.</p>						*1 Maximum output current at 9V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																												

COSEL




Figure A

Data Acquisition/Control Unit




Figure B