

TEST DATA OF MHFW64812

Regulated DC Power Supply
October 27, 2021

Approved by : _____ Kenichi Tsukada

Design Manager

Prepared by : _____ Yoshihiko Saeki

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Cross Regulation	4,5
5.Ripple-Noise	4,5
6.Dynamic Load Response	6,7
7.Rise and Fall Time	8,9
8.Overcurrent Protection	10
9.Ambient Temperature Drift	11,12
10.Minimum Input Voltage for Regulated Output Voltage	11,12
11.Switching frequency (by Load Current)	13
12.Figure of Testing Circuitry	14

(Final Page 14)

COSEL

Model	MHFW64812
Item	Input Current (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.013	0.010	0.007	0.005	0.005
20	0.086	0.065	0.045	0.035	0.026
40	0.165	0.123	0.082	0.063	0.043
60	0.244	0.181	0.122	0.092	0.062
80	0.326	0.241	0.160	0.121	0.080
90	0.368	0.271	0.179	0.135	0.089
100	*1	0.302	0.199	0.149	0.097
110	*1	0.333	0.219	0.164	0.106
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 18V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL

Model	MHFW64812	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Efficiency (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
		2.Values																																																																														
<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>77.9</td><td>77.6</td><td>75.4</td><td>73.0</td><td>61.2</td></tr> <tr> <td>40</td><td>81.3</td><td>81.5</td><td>81.4</td><td>80.2</td><td>73.1</td></tr> <tr> <td>60</td><td>82.4</td><td>83.1</td><td>82.6</td><td>81.7</td><td>77.4</td></tr> <tr> <td>80</td><td>82.2</td><td>83.5</td><td>83.9</td><td>83.3</td><td>79.3</td></tr> <tr> <td>90</td><td>81.9</td><td>83.3</td><td>84.1</td><td>83.8</td><td>80.2</td></tr> <tr> <td>100</td><td>*1</td><td>83.2</td><td>84.3</td><td>84.2</td><td>81.5</td></tr> <tr> <td>110</td><td>*1</td><td>82.8</td><td>84.2</td><td>84.3</td><td>82.0</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ratio [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	77.9	77.6	75.4	73.0	61.2	40	81.3	81.5	81.4	80.2	73.1	60	82.4	83.1	82.6	81.7	77.4	80	82.2	83.5	83.9	83.3	79.3	90	81.9	83.3	84.1	83.8	80.2	100	*1	83.2	84.3	84.2	81.5	110	*1	82.8	84.2	84.3	82.0	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																															
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																											
0	-	-	-	-	-																																																																											
20	77.9	77.6	75.4	73.0	61.2																																																																											
40	81.3	81.5	81.4	80.2	73.1																																																																											
60	82.4	83.1	82.6	81.7	77.4																																																																											
80	82.2	83.5	83.9	83.3	79.3																																																																											
90	81.9	83.3	84.1	83.8	80.2																																																																											
100	*1	83.2	84.3	84.2	81.5																																																																											
110	*1	82.8	84.2	84.3	82.0																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																

Note: Slanted line shows the range of the rated load current.


COSEL

Model MHFW64812

Item Line Regulation

Object +12V0.25A

1.Graph

Temperature 25°C
Testing Circuitry Figure A


2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17.2	12.121	*1
18.0	12.120	*1
24.0	12.116	12.016
30.0	12.115	12.019
36.0	12.113	12.022
48.0	12.111	12.024
60.0	12.111	12.025
76.0	12.111	12.025
80.0	12.111	12.025

-12V:Rated Load Current

Object -12V0.25A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17.2	-12.161	*1
18.0	-12.157	*1
24.0	-12.143	-12.047
30.0	-12.138	-12.044
36.0	-12.132	-12.042
48.0	-12.127	-12.039
60.0	-12.125	-12.038
76.0	-12.124	-12.038
80.0	-12.124	-12.037

+12V:Rated Load Current



Note: Slanted line shows the range of the rated input voltage.

*1 Maximum output current at 18V input
Voltage is 80% of rated load current.
Refer to instruction manuals for details of
input derating.

COSEL

Model	MHFW64812	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	+12V0.25A																																																																															
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>12.343</td> <td>12.334</td> <td>12.321</td> <td>12.308</td> <td>12.307</td> </tr> <tr> <td>0.05</td> <td>12.217</td> <td>12.207</td> <td>12.204</td> <td>12.201</td> <td>12.192</td> </tr> <tr> <td>0.10</td> <td>12.149</td> <td>12.146</td> <td>12.140</td> <td>12.140</td> <td>12.139</td> </tr> <tr> <td>0.15</td> <td>12.097</td> <td>12.096</td> <td>12.095</td> <td>12.094</td> <td>12.094</td> </tr> <tr> <td>0.20</td> <td>12.049</td> <td>12.053</td> <td>12.055</td> <td>12.056</td> <td>12.056</td> </tr> <tr> <td>0.23</td> <td>12.026</td> <td>12.032</td> <td>12.036</td> <td>12.037</td> <td>12.039</td> </tr> <tr> <td>0.25</td> <td>*1</td> <td>12.012</td> <td>12.019</td> <td>12.021</td> <td>12.022</td> </tr> <tr> <td>0.28</td> <td>*1</td> <td>11.993</td> <td>12.001</td> <td>12.004</td> <td>12.007</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>-12V:Rated Load Current</p> <p>*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	12.343	12.334	12.321	12.308	12.307	0.05	12.217	12.207	12.204	12.201	12.192	0.10	12.149	12.146	12.140	12.140	12.139	0.15	12.097	12.096	12.095	12.094	12.094	0.20	12.049	12.053	12.055	12.056	12.056	0.23	12.026	12.032	12.036	12.037	12.039	0.25	*1	12.012	12.019	12.021	12.022	0.28	*1	11.993	12.001	12.004	12.007	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	12.343	12.334	12.321	12.308	12.307																																																																											
0.05	12.217	12.207	12.204	12.201	12.192																																																																											
0.10	12.149	12.146	12.140	12.140	12.139																																																																											
0.15	12.097	12.096	12.095	12.094	12.094																																																																											
0.20	12.049	12.053	12.055	12.056	12.056																																																																											
0.23	12.026	12.032	12.036	12.037	12.039																																																																											
0.25	*1	12.012	12.019	12.021	12.022																																																																											
0.28	*1	11.993	12.001	12.004	12.007																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+12V0.25A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 48V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p> <p>-12V:Rated Load Current</p>																																																																															

COSEL

Model	MHFW64812	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	-12V0.25A																																																																															
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - * - - Input Volt. 36V - - ○ - - Input Volt. 48V - - ◇ - - Input Volt. 76V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-12.376</td> <td>-12.360</td> <td>-12.341</td> <td>-12.324</td> <td>-12.320</td> </tr> <tr> <td>0.05</td> <td>-12.248</td> <td>-12.230</td> <td>-12.222</td> <td>-12.216</td> <td>-12.203</td> </tr> <tr> <td>0.10</td> <td>-12.185</td> <td>-12.173</td> <td>-12.158</td> <td>-12.155</td> <td>-12.152</td> </tr> <tr> <td>0.15</td> <td>-12.137</td> <td>-12.124</td> <td>-12.115</td> <td>-12.110</td> <td>-12.108</td> </tr> <tr> <td>0.20</td> <td>-12.091</td> <td>-12.085</td> <td>-12.076</td> <td>-12.074</td> <td>-12.071</td> </tr> <tr> <td>0.23</td> <td>-12.071</td> <td>-12.066</td> <td>-12.059</td> <td>-12.056</td> <td>-12.054</td> </tr> <tr> <td>0.25</td> <td>*1</td> <td>-12.047</td> <td>-12.042</td> <td>-12.040</td> <td>-12.038</td> </tr> <tr> <td>0.28</td> <td>*1</td> <td>-12.029</td> <td>-12.026</td> <td>-12.024</td> <td>-12.022</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-12.376	-12.360	-12.341	-12.324	-12.320	0.05	-12.248	-12.230	-12.222	-12.216	-12.203	0.10	-12.185	-12.173	-12.158	-12.155	-12.152	0.15	-12.137	-12.124	-12.115	-12.110	-12.108	0.20	-12.091	-12.085	-12.076	-12.074	-12.071	0.23	-12.071	-12.066	-12.059	-12.056	-12.054	0.25	*1	-12.047	-12.042	-12.040	-12.038	0.28	*1	-12.029	-12.026	-12.024	-12.022	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	-12.376	-12.360	-12.341	-12.324	-12.320																																																																											
0.05	-12.248	-12.230	-12.222	-12.216	-12.203																																																																											
0.10	-12.185	-12.173	-12.158	-12.155	-12.152																																																																											
0.15	-12.137	-12.124	-12.115	-12.110	-12.108																																																																											
0.20	-12.091	-12.085	-12.076	-12.074	-12.071																																																																											
0.23	-12.071	-12.066	-12.059	-12.056	-12.054																																																																											
0.25	*1	-12.047	-12.042	-12.040	-12.038																																																																											
0.28	*1	-12.029	-12.026	-12.024	-12.022																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	-12V0.25A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 48V Load 100%</p>  <p>10[mV/div]</p> <p>1[μs/div]</p> <p>+12V:Rated Load Current</p>																																																																															

COSEL

Model	MHFW64812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.25A		

Input Volt. 48 V

-12V:rated load current.

Response. $t_1=t_2=50\mu s$. Typ

Cycle 100 ms



Min.Load (0A)↔
Load 100% (0.25A)

200 mV/div

1 ms/div




1 ms/div

Min.Load (0A)↔
Load 50% (0.125A)

200 mV/div

1 ms/div



1 ms/div

COSEL

Model	MHFW64812	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.25A		

Input Volt. 48 V

+12V:rated load current.



Response. $t_1=t_2=50\mu s$. Typ

Cycle 100 ms





Min.Load (0A)↔
Load 100% (0.25A)

200 mV/div



Min.Load (0A)↔
Load 50% (0.125A)

200 mV/div




COSEL

Model	MHFW64812
Item	Rise and Fall Time
Object	+12V0.25A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	0.5	1.2	0.2	3.1	
100 %		0.7	0.5	1.2	0.1	0.9	



COSEL


Model	MHFW64812	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.25A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	0.5	1.2	0.2	3.8	
100 %		0.7	0.5	1.2	0.1	1.1	



COSSEL

Model	MHFW64812	Temperature	25°C																																																																													
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																													
Object	+12V0.25A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.339</td><td>0.428</td><td>0.474</td><td>0.460</td><td>0.453</td></tr> <tr><td>10.8</td><td>0.368</td><td>0.271</td><td>0.497</td><td>0.483</td><td>0.474</td></tr> <tr><td>9.6</td><td>0.439</td><td>0.531</td><td>0.559</td><td>0.541</td><td>0.529</td></tr> <tr><td>8.4</td><td>0.515</td><td>0.607</td><td>0.622</td><td>0.601</td><td>0.574</td></tr> <tr><td>7.2</td><td>0.593</td><td>0.680</td><td>0.686</td><td>0.656</td><td>0.629</td></tr> <tr><td>6.0</td><td>0.669</td><td>0.753</td><td>0.752</td><td>0.721</td><td>0.691</td></tr> <tr><td>4.8</td><td>0.740</td><td>0.824</td><td>0.820</td><td>0.784</td><td>0.743</td></tr> <tr><td>3.6</td><td>0.788</td><td>0.878</td><td>0.873</td><td>0.834</td><td>0.789</td></tr> <tr><td>2.4</td><td>0.856</td><td>0.935</td><td>0.923</td><td>0.886</td><td>0.853</td></tr> <tr><td>1.2</td><td>0.999</td><td>1.055</td><td>1.008</td><td>0.949</td><td>0.889</td></tr> <tr><td>0.0</td><td>0.940</td><td>0.953</td><td>0.874</td><td>0.809</td><td>0.737</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	11.4	0.339	0.428	0.474	0.460	0.453	10.8	0.368	0.271	0.497	0.483	0.474	9.6	0.439	0.531	0.559	0.541	0.529	8.4	0.515	0.607	0.622	0.601	0.574	7.2	0.593	0.680	0.686	0.656	0.629	6.0	0.669	0.753	0.752	0.721	0.691	4.8	0.740	0.824	0.820	0.784	0.743	3.6	0.788	0.878	0.873	0.834	0.789	2.4	0.856	0.935	0.923	0.886	0.853	1.2	0.999	1.055	1.008	0.949	0.889	0.0	0.940	0.953	0.874	0.809	0.737
Output Voltage [V]	Load Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
11.4	0.339	0.428	0.474	0.460	0.453																																																																											
10.8	0.368	0.271	0.497	0.483	0.474																																																																											
9.6	0.439	0.531	0.559	0.541	0.529																																																																											
8.4	0.515	0.607	0.622	0.601	0.574																																																																											
7.2	0.593	0.680	0.686	0.656	0.629																																																																											
6.0	0.669	0.753	0.752	0.721	0.691																																																																											
4.8	0.740	0.824	0.820	0.784	0.743																																																																											
3.6	0.788	0.878	0.873	0.834	0.789																																																																											
2.4	0.856	0.935	0.923	0.886	0.853																																																																											
1.2	0.999	1.055	1.008	0.949	0.889																																																																											
0.0	0.940	0.953	0.874	0.809	0.737																																																																											
Object	-12V0.25A	<p>-12V:Rated Load Current</p>																																																																														
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.385</td><td>0.472</td><td>0.517</td><td>0.502</td><td>0.495</td></tr> <tr><td>-10.8</td><td>0.418</td><td>0.508</td><td>0.543</td><td>0.529</td><td>0.519</td></tr> <tr><td>-9.6</td><td>0.483</td><td>0.575</td><td>0.600</td><td>0.581</td><td>0.569</td></tr> <tr><td>-8.4</td><td>0.553</td><td>0.644</td><td>0.658</td><td>0.636</td><td>0.609</td></tr> <tr><td>-7.2</td><td>0.625</td><td>0.712</td><td>0.716</td><td>0.687</td><td>0.660</td></tr> <tr><td>-6.0</td><td>0.695</td><td>0.779</td><td>0.777</td><td>0.746</td><td>0.716</td></tr> <tr><td>-4.8</td><td>0.758</td><td>0.844</td><td>0.839</td><td>0.804</td><td>0.769</td></tr> <tr><td>-3.6</td><td>0.805</td><td>0.893</td><td>0.893</td><td>0.854</td><td>0.810</td></tr> <tr><td>-2.4</td><td>0.878</td><td>0.956</td><td>0.941</td><td>0.905</td><td>0.871</td></tr> <tr><td>-1.2</td><td>1.030</td><td>1.084</td><td>1.026</td><td>0.966</td><td>0.905</td></tr> <tr><td>0.0</td><td>0.982</td><td>1.004</td><td>0.909</td><td>0.864</td><td>0.790</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-11.4	0.385	0.472	0.517	0.502	0.495	-10.8	0.418	0.508	0.543	0.529	0.519	-9.6	0.483	0.575	0.600	0.581	0.569	-8.4	0.553	0.644	0.658	0.636	0.609	-7.2	0.625	0.712	0.716	0.687	0.660	-6.0	0.695	0.779	0.777	0.746	0.716	-4.8	0.758	0.844	0.839	0.804	0.769	-3.6	0.805	0.893	0.893	0.854	0.810	-2.4	0.878	0.956	0.941	0.905	0.871	-1.2	1.030	1.084	1.026	0.966	0.905	0.0	0.982	1.004	0.909	0.864	0.790
Output Voltage [V]	Load Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
-11.4	0.385	0.472	0.517	0.502	0.495																																																																											
-10.8	0.418	0.508	0.543	0.529	0.519																																																																											
-9.6	0.483	0.575	0.600	0.581	0.569																																																																											
-8.4	0.553	0.644	0.658	0.636	0.609																																																																											
-7.2	0.625	0.712	0.716	0.687	0.660																																																																											
-6.0	0.695	0.779	0.777	0.746	0.716																																																																											
-4.8	0.758	0.844	0.839	0.804	0.769																																																																											
-3.6	0.805	0.893	0.893	0.854	0.810																																																																											
-2.4	0.878	0.956	0.941	0.905	0.871																																																																											
-1.2	1.030	1.084	1.026	0.966	0.905																																																																											
0.0	0.982	1.004	0.909	0.864	0.790																																																																											
Note: Slanted line shows the range of the rated load current.	<p>+12V:Rated Load Current</p> <p>Maximum output current at 18V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																															



Model	MHFW64812	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V0.25A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V*1	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	11.934	11.940	11.946	11.950	11.951
25	12.011	12.012	12.018	12.020	12.021
60	12.023	12.023	12.029	12.031	12.032

*1 Load 80%

-12V:Rated Load Current

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V0.25A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	14.6	14.7
25	14.4	14.4
60	14.2	14.5



Model	MHFW64812	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	-12V0.25A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V*1	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	-11.966	-11.968	-11.967	-11.966	-11.966
25	-12.044	-12.043	-12.039	-12.037	-12.036
60	-12.056	-12.053	-12.049	-12.047	-12.045

*1 Load 80%

+12V:Rated Load Current


Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	-12V0.25A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	14.6	14.7
25	14.4	14.4
60	14.2	14.5

COSEL

Model	MHFW64812
Item	Switching frequency (by Load Current)
Object	+/-12V0.25A



Note: Slanted line shows the range of the rated load current.

When load current is low, MH operates intermittently, so switching frequency would not become constant.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Switching Frequency [kHz]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.00	694	772	852	862	787
0.05	466	554	651	697	740
0.10	340	419	515	564	614
0.15	266	342	424	474	535
0.20	221	284	364	414	473
0.23	204	259	343	386	444
0.25	*1	244	319	366	419
0.28	*1	226	300	344	402
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 18V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL




Figure A

Data Acquisition/Control Unit




Figure B