

TEST DATA OF MHFW64815

Regulated DC Power Supply
October 27, 2021

Approved by : _____ Kenichi Tsukada

Design Manager

Prepared by : _____ Yoshihiko Saeki

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Cross Regulation	4,5
5.Ripple-Noise	4,5
6.Dynamic Load Response	6,7
7.Rise and Fall Time	8,9
8.Overcurrent Protection	10
9.Ambient Temperature Drift	11,12
10.Minimum Input Voltage for Regulated Output Voltage	11,12
11.Switching frequency (by Load Current)	13
12.Figure of Testing Circuitry	14

(Final Page 14)

COSEL

Model	MHFW64815
Item	Input Current (by Load Current)
Object	_____



Note: Slanted line shows the range of the rated load current.


Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Current [A]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0	0.016	0.013	0.010	0.008	0.005
20	0.089	0.068	0.047	0.036	0.026
40	0.165	0.123	0.083	0.063	0.044
60	0.245	0.182	0.121	0.091	0.061
80	0.323	0.240	0.160	0.120	0.079
90	0.364	0.269	0.179	0.135	0.088
100	*1	0.300	0.198	0.149	0.097
110	*1	0.329	0.217	0.163	0.106
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 18V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL

Model	MHFW64815	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Efficiency (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
		2.Values																																																																														
<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>75.8</td><td>74.4</td><td>72.4</td><td>71.1</td><td>61.4</td></tr> <tr> <td>40</td><td>81.2</td><td>81.6</td><td>81.2</td><td>79.7</td><td>72.9</td></tr> <tr> <td>60</td><td>82.1</td><td>82.8</td><td>83.2</td><td>82.7</td><td>78.5</td></tr> <tr> <td>80</td><td>82.8</td><td>83.5</td><td>83.5</td><td>83.5</td><td>80.5</td></tr> <tr> <td>90</td><td>82.7</td><td>83.8</td><td>83.9</td><td>83.5</td><td>81.1</td></tr> <tr> <td>100</td><td>*1</td><td>83.8</td><td>84.5</td><td>83.9</td><td>81.8</td></tr> <tr> <td>110</td><td>*1</td><td>83.9</td><td>84.8</td><td>84.5</td><td>82.1</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ratio [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	75.8	74.4	72.4	71.1	61.4	40	81.2	81.6	81.2	79.7	72.9	60	82.1	82.8	83.2	82.7	78.5	80	82.8	83.5	83.5	83.5	80.5	90	82.7	83.8	83.9	83.5	81.1	100	*1	83.8	84.5	83.9	81.8	110	*1	83.9	84.8	84.5	82.1	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																															
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																											
0	-	-	-	-	-																																																																											
20	75.8	74.4	72.4	71.1	61.4																																																																											
40	81.2	81.6	81.2	79.7	72.9																																																																											
60	82.1	82.8	83.2	82.7	78.5																																																																											
80	82.8	83.5	83.5	83.5	80.5																																																																											
90	82.7	83.8	83.9	83.5	81.1																																																																											
100	*1	83.8	84.5	83.9	81.8																																																																											
110	*1	83.9	84.8	84.5	82.1																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																


Note: Slanted line shows the range of the rated load current.

COSEL

Model	MHFW64815
Item	Line Regulation
Object	+15V0.2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17.2	15.091	*1
18.0	15.091	*1
24.0	15.089	14.988
30.0	15.089	14.994
36.0	15.087	14.996
48.0	15.084	14.998
60.0	15.082	14.998
76.0	15.080	14.999
80.0	15.081	14.999

-15V:Rated Load Current

Object -15V0.2A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17.2	-15.145	*1
18.0	-15.142	*1
24.0	-15.131	-15.035
30.0	-15.126	-15.031
36.0	-15.119	-15.029
48.0	-15.111	-15.027
60.0	-15.106	-15.025
76.0	-15.103	-15.024
80.0	-15.103	-15.024

+15V:Rated Load Current

Note: Slanted line shows the range of the rated input voltage.


*1 Maximum output current at 18V input
Voltage is 80% of rated load current.
Refer to instruction manuals for details of
input derating.

COSEL

Model	MHFW64815	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	+15V0.2A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>15.323</td> <td>15.302</td> <td>15.280</td> <td>15.268</td> <td>15.270</td> </tr> <tr> <td>0.04</td> <td>15.198</td> <td>15.184</td> <td>15.170</td> <td>15.166</td> <td>15.165</td> </tr> <tr> <td>0.08</td> <td>15.129</td> <td>15.127</td> <td>15.117</td> <td>15.113</td> <td>15.109</td> </tr> <tr> <td>0.12</td> <td>15.078</td> <td>15.076</td> <td>15.075</td> <td>15.073</td> <td>15.070</td> </tr> <tr> <td>0.16</td> <td>15.030</td> <td>15.034</td> <td>15.035</td> <td>15.036</td> <td>15.036</td> </tr> <tr> <td>0.18</td> <td>15.008</td> <td>15.014</td> <td>15.017</td> <td>15.018</td> <td>15.019</td> </tr> <tr> <td>0.20</td> <td>*1</td> <td>14.994</td> <td>15.001</td> <td>15.002</td> <td>15.004</td> </tr> <tr> <td>0.22</td> <td>*1</td> <td>14.976</td> <td>14.984</td> <td>14.987</td> <td>14.988</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>-15V:Rated Load Current</p> <p>*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	15.323	15.302	15.280	15.268	15.270	0.04	15.198	15.184	15.170	15.166	15.165	0.08	15.129	15.127	15.117	15.113	15.109	0.12	15.078	15.076	15.075	15.073	15.070	0.16	15.030	15.034	15.035	15.036	15.036	0.18	15.008	15.014	15.017	15.018	15.019	0.20	*1	14.994	15.001	15.002	15.004	0.22	*1	14.976	14.984	14.987	14.988	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	15.323	15.302	15.280	15.268	15.270																																																																											
0.04	15.198	15.184	15.170	15.166	15.165																																																																											
0.08	15.129	15.127	15.117	15.113	15.109																																																																											
0.12	15.078	15.076	15.075	15.073	15.070																																																																											
0.16	15.030	15.034	15.035	15.036	15.036																																																																											
0.18	15.008	15.014	15.017	15.018	15.019																																																																											
0.20	*1	14.994	15.001	15.002	15.004																																																																											
0.22	*1	14.976	14.984	14.987	14.988																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+15V0.2A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 48V</p> <p>Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p> <p>-15V:Rated Load Current</p>																																																																															

COSEL

Model	MHFW64815	Temperature	25°C																																																																													
Item	Cross Regulation	Testing Circuitry	Figure A																																																																													
Object	-15V0.2A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-15.351</td> <td>-15.323</td> <td>-15.296</td> <td>-15.280</td> <td>-15.280</td> </tr> <tr> <td>0.04</td> <td>-15.231</td> <td>-15.208</td> <td>-15.188</td> <td>-15.181</td> <td>-15.178</td> </tr> <tr> <td>0.08</td> <td>-15.163</td> <td>-15.154</td> <td>-15.136</td> <td>-15.127</td> <td>-15.121</td> </tr> <tr> <td>0.12</td> <td>-15.115</td> <td>-15.104</td> <td>-15.096</td> <td>-15.089</td> <td>-15.082</td> </tr> <tr> <td>0.16</td> <td>-15.073</td> <td>-15.066</td> <td>-15.058</td> <td>-15.056</td> <td>-15.050</td> </tr> <tr> <td>0.18</td> <td>-15.052</td> <td>-15.048</td> <td>-15.041</td> <td>-15.039</td> <td>-15.035</td> </tr> <tr> <td>0.20</td> <td>*1</td> <td>-15.031</td> <td>-15.025</td> <td>-15.023</td> <td>-15.020</td> </tr> <tr> <td>0.22</td> <td>*1</td> <td>-15.013</td> <td>-15.009</td> <td>-15.008</td> <td>-15.005</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+15V:Rated Load Current</p> <p>*1 Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>			Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-15.351	-15.323	-15.296	-15.280	-15.280	0.04	-15.231	-15.208	-15.188	-15.181	-15.178	0.08	-15.163	-15.154	-15.136	-15.127	-15.121	0.12	-15.115	-15.104	-15.096	-15.089	-15.082	0.16	-15.073	-15.066	-15.058	-15.056	-15.050	0.18	-15.052	-15.048	-15.041	-15.039	-15.035	0.20	*1	-15.031	-15.025	-15.023	-15.020	0.22	*1	-15.013	-15.009	-15.008	-15.005	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	-15.351	-15.323	-15.296	-15.280	-15.280																																																																											
0.04	-15.231	-15.208	-15.188	-15.181	-15.178																																																																											
0.08	-15.163	-15.154	-15.136	-15.127	-15.121																																																																											
0.12	-15.115	-15.104	-15.096	-15.089	-15.082																																																																											
0.16	-15.073	-15.066	-15.058	-15.056	-15.050																																																																											
0.18	-15.052	-15.048	-15.041	-15.039	-15.035																																																																											
0.20	*1	-15.031	-15.025	-15.023	-15.020																																																																											
0.22	*1	-15.013	-15.009	-15.008	-15.005																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	-15V0.2A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 48V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p> <p>+15V:Rated Load Current</p>																																																																															

COSEL

COSEL


Model	MHFW64815	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V0.2A		

Input Volt. 48 V

+15V:rated load current.

Response. $t_1=t_2=50\mu s$. Typ


Cycle 100 ms



Min.Load (0A)↔
Load 100% (0.2A)

200 mV/div

1 ms/div




1 ms/div

Min.Load (0A)↔
Load 50% (0.1A)

200 mV/div

1 ms/div




1 ms/div

COSEL

Model	MHFW64815
Item	Rise and Fall Time
Object	+15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.7	0.6	1.3	0.2	4.3
100 %		0.7	0.7	1.4	0.1	1.4




COSEL

Model	MHFW64815
Item	Rise and Fall Time
Object	-15V0.2A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	0.6	1.3	0.2	5.6	
100 %		0.7	0.7	1.4	0.1	1.7	



COSEL

Model	MHFW64815	Temperature	25°C																																																																													
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																													
Object	+15V0.2A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>0.273</td><td>0.353</td><td>0.383</td><td>0.384</td><td>0.370</td></tr> <tr><td>13.5</td><td>0.304</td><td>0.386</td><td>0.405</td><td>0.404</td><td>0.390</td></tr> <tr><td>12.0</td><td>0.365</td><td>0.450</td><td>0.476</td><td>0.461</td><td>0.450</td></tr> <tr><td>10.5</td><td>0.433</td><td>0.520</td><td>0.536</td><td>0.516</td><td>0.504</td></tr> <tr><td>9.0</td><td>0.510</td><td>0.600</td><td>0.598</td><td>0.573</td><td>0.549</td></tr> <tr><td>7.5</td><td>0.600</td><td>0.686</td><td>0.660</td><td>0.628</td><td>0.600</td></tr> <tr><td>6.0</td><td>0.686</td><td>0.764</td><td>0.735</td><td>0.700</td><td>0.668</td></tr> <tr><td>4.5</td><td>0.767</td><td>0.844</td><td>0.807</td><td>0.765</td><td>0.727</td></tr> <tr><td>3.0</td><td>0.826</td><td>0.902</td><td>0.865</td><td>0.818</td><td>0.769</td></tr> <tr><td>1.5</td><td>0.931</td><td>0.998</td><td>0.935</td><td>0.879</td><td>0.826</td></tr> <tr><td>0.0</td><td>0.888</td><td>0.895</td><td>0.825</td><td>0.750</td><td>0.689</td></tr> </tbody> </table> <p>-15V:Rated Load Current</p>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	14.3	0.273	0.353	0.383	0.384	0.370	13.5	0.304	0.386	0.405	0.404	0.390	12.0	0.365	0.450	0.476	0.461	0.450	10.5	0.433	0.520	0.536	0.516	0.504	9.0	0.510	0.600	0.598	0.573	0.549	7.5	0.600	0.686	0.660	0.628	0.600	6.0	0.686	0.764	0.735	0.700	0.668	4.5	0.767	0.844	0.807	0.765	0.727	3.0	0.826	0.902	0.865	0.818	0.769	1.5	0.931	0.998	0.935	0.879	0.826	0.0	0.888	0.895	0.825	0.750	0.689
Output Voltage [V]	Load Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
14.3	0.273	0.353	0.383	0.384	0.370																																																																											
13.5	0.304	0.386	0.405	0.404	0.390																																																																											
12.0	0.365	0.450	0.476	0.461	0.450																																																																											
10.5	0.433	0.520	0.536	0.516	0.504																																																																											
9.0	0.510	0.600	0.598	0.573	0.549																																																																											
7.5	0.600	0.686	0.660	0.628	0.600																																																																											
6.0	0.686	0.764	0.735	0.700	0.668																																																																											
4.5	0.767	0.844	0.807	0.765	0.727																																																																											
3.0	0.826	0.902	0.865	0.818	0.769																																																																											
1.5	0.931	0.998	0.935	0.879	0.826																																																																											
0.0	0.888	0.895	0.825	0.750	0.689																																																																											
Object	-15V0.2A																																																																															
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-14.3</td><td>0.304</td><td>0.382</td><td>0.411</td><td>0.412</td><td>0.397</td></tr> <tr><td>-13.5</td><td>0.333</td><td>0.414</td><td>0.428</td><td>0.431</td><td>0.416</td></tr> <tr><td>-12.0</td><td>0.392</td><td>0.475</td><td>0.500</td><td>0.484</td><td>0.473</td></tr> <tr><td>-10.5</td><td>0.456</td><td>0.543</td><td>0.557</td><td>0.536</td><td>0.524</td></tr> <tr><td>-9.0</td><td>0.531</td><td>0.618</td><td>0.616</td><td>0.591</td><td>0.567</td></tr> <tr><td>-7.5</td><td>0.616</td><td>0.702</td><td>0.675</td><td>0.643</td><td>0.614</td></tr> <tr><td>-6.0</td><td>0.700</td><td>0.777</td><td>0.747</td><td>0.711</td><td>0.679</td></tr> <tr><td>-4.5</td><td>0.777</td><td>0.853</td><td>0.816</td><td>0.774</td><td>0.735</td></tr> <tr><td>-3.0</td><td>0.829</td><td>0.906</td><td>0.871</td><td>0.824</td><td>0.775</td></tr> <tr><td>-1.5</td><td>0.945</td><td>1.022</td><td>0.943</td><td>0.886</td><td>0.832</td></tr> <tr><td>0.0</td><td>0.932</td><td>0.942</td><td>0.877</td><td>0.819</td><td>0.771</td></tr> </tbody> </table> <p>+15V:Rated Load Current</p>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-14.3	0.304	0.382	0.411	0.412	0.397	-13.5	0.333	0.414	0.428	0.431	0.416	-12.0	0.392	0.475	0.500	0.484	0.473	-10.5	0.456	0.543	0.557	0.536	0.524	-9.0	0.531	0.618	0.616	0.591	0.567	-7.5	0.616	0.702	0.675	0.643	0.614	-6.0	0.700	0.777	0.747	0.711	0.679	-4.5	0.777	0.853	0.816	0.774	0.735	-3.0	0.829	0.906	0.871	0.824	0.775	-1.5	0.945	1.022	0.943	0.886	0.832	0.0	0.932	0.942	0.877	0.819	0.771
Output Voltage [V]	Load Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
-14.3	0.304	0.382	0.411	0.412	0.397																																																																											
-13.5	0.333	0.414	0.428	0.431	0.416																																																																											
-12.0	0.392	0.475	0.500	0.484	0.473																																																																											
-10.5	0.456	0.543	0.557	0.536	0.524																																																																											
-9.0	0.531	0.618	0.616	0.591	0.567																																																																											
-7.5	0.616	0.702	0.675	0.643	0.614																																																																											
-6.0	0.700	0.777	0.747	0.711	0.679																																																																											
-4.5	0.777	0.853	0.816	0.774	0.735																																																																											
-3.0	0.829	0.906	0.871	0.824	0.775																																																																											
-1.5	0.945	1.022	0.943	0.886	0.832																																																																											
0.0	0.932	0.942	0.877	0.819	0.771																																																																											
Note: Slanted line shows the range of the rated load current.		Maximum output current at 18V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																														



Model	MHFW64815	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+15V0.2A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V*1	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	14.926	14.931	14.939	14.942	14.943
25	14.992	14.992	14.999	15.001	15.002
60	14.994	14.992	14.999	15.000	15.002

*1 Load 80%

-15V:Rated Load Current

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+15V0.2A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	14.4	14.4
25	14.2	14.2
60	14.0	14.1



Model	MHFW64815	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	-15V0.2A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 18V*1	Input Volt. 24V	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	-14.961	-14.967	-14.963	-14.963	-14.962
25	-15.029	-15.029	-15.023	-15.021	-15.019
60	-15.029	-15.027	-15.022	-15.020	-15.017

*1 Load 80%

+15V:Rated Load Current


Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	-15V0.2A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	14.4	14.4
25	14.2	14.2
60	14.0	14.1

COSEL

Model	MHFW64815
Item	Switching frequency (by Load Current)
Object	+/-15V0.2A



Note: Slanted line shows the range of the rated load current.

When load current is low, MH operates intermittently, so switching frequency would not become constant.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Switching Frequency [kHz]				
	18[V]	24[V]	36[V]	48[V]	76[V]
0.00	617	700	798	849	849
0.04	453	532	642	712	764
0.08	348	429	553	619	678
0.12	280	365	470	531	593
0.16	240	312	406	471	543
0.18	224	292	383	441	513
0.20	*1	270	367	421	486
0.22	*1	258	345	404	467
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 18V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL




Figure A

Data Acquisition/Control Unit




Figure B