

COSEL

TEST DATA OF MMB50A-5
(100V INPUT)

Regulated DC Power Supply

Date : Feb. 12. 1999

Approved by : M. Takahime
Design Manager

Prepared by : H. Ishikawa
Design Engineer

コーチセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency (by Input Voltage)	2
効率 (入力電圧特性)	
3. Power Factor (by Input Voltage)	3
力率 (入力電圧特性)	
4. Hold-Up Time	4
出力保持時間	
5. Instantaneous Interruption Compensation	6
瞬時停電保護	
6. Load Regulation	8
静的負荷変動	
7. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
8. Ripple-Noise	11
リップルノイズ	
9. Overcurrent Protection	13
過電流保護	
10. Overvoltage Protection	14
過電圧保護	
11. Inrush Current	15
突入電流	
12. Dynamic Load Responce	16
動的負荷変動	
13. Rise and Fall Time	18
立上り、立下がり時間	
14. Ambient Temperature Drift	20
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	21
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	22
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	23
経時ドリフト	
18. Output Voltage Accuracy	24
定電圧精度	
19. Condensation	25
結露特性	
20. Leakage Current	27
漏洩電流	
21. Conducted Emission	28
雑音端子電圧	
22. Figure of Testing Circuitry	29
測定回路図	

(Final Page 30)

COSEL

Model	MMB50A-5	Temperature 25°C Testing Circuitry Figure A																																												
Item	Line Regulation 静的入力変動																																													
Object	+12.0V 3.00A																																													
1. Graph																																														
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.062</td><td>12.057</td></tr> <tr><td>80</td><td>12.062</td><td>12.061</td></tr> <tr><td>85</td><td>12.062</td><td>12.057</td></tr> <tr><td>90</td><td>12.062</td><td>12.058</td></tr> <tr><td>100</td><td>12.062</td><td>12.057</td></tr> <tr><td>110</td><td>12.062</td><td>12.057</td></tr> <tr><td>120</td><td>12.061</td><td>12.057</td></tr> <tr><td>132</td><td>12.061</td><td>12.057</td></tr> <tr><td>140</td><td>12.061</td><td>12.057</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	12.062	12.057	80	12.062	12.061	85	12.062	12.057	90	12.062	12.058	100	12.062	12.057	110	12.062	12.057	120	12.061	12.057	132	12.061	12.057	140	12.061	12.057	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																												
	Output Volt. [V]	Output Volt. [V]																																												
75	12.062	12.057																																												
80	12.062	12.061																																												
85	12.062	12.057																																												
90	12.062	12.058																																												
100	12.062	12.057																																												
110	12.062	12.057																																												
120	12.061	12.057																																												
132	12.061	12.057																																												
140	12.061	12.057																																												
—	—	—																																												
—	—	—																																												
—	—	—																																												
Object	+12V 1.50A	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>11.986</td><td>11.983</td></tr> <tr><td>80</td><td>11.986</td><td>11.983</td></tr> <tr><td>85</td><td>11.986</td><td>11.983</td></tr> <tr><td>90</td><td>11.986</td><td>11.983</td></tr> <tr><td>100</td><td>11.986</td><td>11.983</td></tr> <tr><td>110</td><td>11.986</td><td>11.983</td></tr> <tr><td>120</td><td>11.986</td><td>11.983</td></tr> <tr><td>132</td><td>11.986</td><td>11.983</td></tr> <tr><td>140</td><td>11.986</td><td>11.983</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	11.986	11.983	80	11.986	11.983	85	11.986	11.983	90	11.986	11.983	100	11.986	11.983	110	11.986	11.983	120	11.986	11.983	132	11.986	11.983	140	11.986	11.983	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50%	Load 100%																																												
	Output Volt. [V]	Output Volt. [V]																																												
75	11.986	11.983																																												
80	11.986	11.983																																												
85	11.986	11.983																																												
90	11.986	11.983																																												
100	11.986	11.983																																												
110	11.986	11.983																																												
120	11.986	11.983																																												
132	11.986	11.983																																												
140	11.986	11.983																																												
—	—	—																																												
—	—	—																																												
—	—	—																																												
1. Graph																																														
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>11.986</td><td>11.983</td></tr> <tr><td>80</td><td>11.986</td><td>11.983</td></tr> <tr><td>85</td><td>11.986</td><td>11.983</td></tr> <tr><td>90</td><td>11.986</td><td>11.983</td></tr> <tr><td>100</td><td>11.986</td><td>11.983</td></tr> <tr><td>110</td><td>11.986</td><td>11.983</td></tr> <tr><td>120</td><td>11.986</td><td>11.983</td></tr> <tr><td>132</td><td>11.986</td><td>11.983</td></tr> <tr><td>140</td><td>11.986</td><td>11.983</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	11.986	11.983	80	11.986	11.983	85	11.986	11.983	90	11.986	11.983	100	11.986	11.983	110	11.986	11.983	120	11.986	11.983	132	11.986	11.983	140	11.986	11.983	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																												
	Output Volt. [V]	Output Volt. [V]																																												
75	11.986	11.983																																												
80	11.986	11.983																																												
85	11.986	11.983																																												
90	11.986	11.983																																												
100	11.986	11.983																																												
110	11.986	11.983																																												
120	11.986	11.983																																												
132	11.986	11.983																																												
140	11.986	11.983																																												
—	—	—																																												
—	—	—																																												
—	—	—																																												
Note:	Slanted line shows the range of the rated input voltage.																																													
(注)	斜線は定格入力電圧範囲を示す。																																													

COSEL

Model	MMB50A-5																																	
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Efficiency [%]</th> <th>Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>71.6</td><td>74.6</td></tr> <tr><td>80</td><td>71.4</td><td>75.2</td></tr> <tr><td>85</td><td>71.0</td><td>75.4</td></tr> <tr><td>90</td><td>70.5</td><td>75.5</td></tr> <tr><td>100</td><td>69.0</td><td>75.5</td></tr> <tr><td>110</td><td>67.5</td><td>75.2</td></tr> <tr><td>120</td><td>65.8</td><td>74.8</td></tr> <tr><td>132</td><td>63.7</td><td>73.9</td></tr> <tr><td>140</td><td>62.2</td><td>73.3</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Efficiency [%]	Efficiency [%]	75	71.6	74.6	80	71.4	75.2	85	71.0	75.4	90	70.5	75.5	100	69.0	75.5	110	67.5	75.2	120	65.8	74.8	132	63.7	73.9	140	62.2	73.3
Input Voltage [V]	Load 50%	Load 100%																																
	Efficiency [%]	Efficiency [%]																																
75	71.6	74.6																																
80	71.4	75.2																																
85	71.0	75.4																																
90	70.5	75.5																																
100	69.0	75.5																																
110	67.5	75.2																																
120	65.8	74.8																																
132	63.7	73.9																																
140	62.2	73.3																																

Note: Slanted line shows the range of the rated input voltage.


(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model MMB50A-5

Item Power Factor (by Input Voltage)
力率(入力電圧特性)

Object



Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	load 50%	load 100%
	Power Factor	Power Factor
75	0.61	0.62
80	0.59	0.60
85	0.58	0.59
90	0.57	0.59
100	0.56	0.57
110	0.55	0.56
120	0.54	0.55
132	0.53	0.54
140	0.52	0.53

COSEL

Model	MMB50A-5	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+12.0V3A																																		
1. Graph	<p>Legend: Load 50% (△), Load 100% (□)</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 50% [mS]</th> <th>Load 100% [mS]</th> </tr> </thead> <tbody> <tr><td>80</td><td>~50</td><td>~30</td></tr> <tr><td>90</td><td>~70</td><td>~50</td></tr> <tr><td>100</td><td>~80</td><td>~60</td></tr> <tr><td>110</td><td>~100</td><td>~70</td></tr> <tr><td>120</td><td>~120</td><td>~80</td></tr> <tr><td>130</td><td>~150</td><td>~100</td></tr> <tr><td>140</td><td>~180</td><td>~120</td></tr> </tbody> </table>			Input Voltage [V]	Load 50% [mS]	Load 100% [mS]	80	~50	~30	90	~70	~50	100	~80	~60	110	~100	~70	120	~120	~80	130	~150	~100	140	~180	~120								
Input Voltage [V]	Load 50% [mS]	Load 100% [mS]																																	
80	~50	~30																																	
90	~70	~50																																	
100	~80	~60																																	
110	~100	~70																																	
120	~120	~80																																	
130	~150	~100																																	
140	~180	~120																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [mS]</th> <th>Hold-Up Time [mS]</th> </tr> </thead> <tbody> <tr><td>75</td><td>50</td><td>20</td></tr> <tr><td>80</td><td>58</td><td>25</td></tr> <tr><td>85</td><td>65</td><td>30</td></tr> <tr><td>90</td><td>74</td><td>35</td></tr> <tr><td>100</td><td>91</td><td>47</td></tr> <tr><td>110</td><td>111</td><td>60</td></tr> <tr><td>120</td><td>132</td><td>74</td></tr> <tr><td>132</td><td>160</td><td>93</td></tr> <tr><td>140</td><td>180</td><td>107</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [mS]	Hold-Up Time [mS]	75	50	20	80	58	25	85	65	30	90	74	35	100	91	47	110	111	60	120	132	74	132	160	93	140	180	107
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [mS]	Hold-Up Time [mS]																																	
75	50	20																																	
80	58	25																																	
85	65	30																																	
90	74	35																																	
100	91	47																																	
110	111	60																																	
120	132	74																																	
132	160	93																																	
140	180	107																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	MMB50A-5	Temperature	25°C																																
Item	Hold-Up Time 出力保持時間	Testing Circuitry	Figure A																																
Object	+12.0V 1.5A																																		
1. Graph	<p>Load 50% (△) Load 100% (□)</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [ms]</th> <th>Hold-Up Time [ms]</th> </tr> </thead> <tbody> <tr><td>75</td><td>46</td><td>24</td></tr> <tr><td>80</td><td>52</td><td>29</td></tr> <tr><td>85</td><td>58</td><td>34</td></tr> <tr><td>90</td><td>64</td><td>39</td></tr> <tr><td>100</td><td>78</td><td>51</td></tr> <tr><td>110</td><td>94</td><td>64</td></tr> <tr><td>120</td><td>110</td><td>79</td></tr> <tr><td>132</td><td>133</td><td>98</td></tr> <tr><td>140</td><td>149</td><td>112</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [ms]	Hold-Up Time [ms]	75	46	24	80	52	29	85	58	34	90	64	39	100	78	51	110	94	64	120	110	79	132	133	98	140	149	112
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [ms]	Hold-Up Time [ms]																																	
75	46	24																																	
80	52	29																																	
85	58	34																																	
90	64	39																																	
100	78	51																																	
110	94	64																																	
120	110	79																																	
132	133	98																																	
140	149	112																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL


Model	MMB50A-5	Temperature 25°C Testing Circuitry Figure A			
Item	Instantaneous Interruption Compensation 瞬時停電保障				
Object	+12.0V 3.00A				
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V (open triangle) Input Volt. 100 V (open square) Input Volt. 132 V (open circle) <p>Y-axis: Instantaneous Compensation Time [mS]</p> <p>X-axis: Load Current [A]</p>	2. Values			
		Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
			Time [mS]		
	0.0	—	—	—	—
	0.6	102	138	230	
	1.2	71	99	177	
	1.8	52	76	140	
	2.4	38	56	113	
	3.0	22	39	90	
	3.3	14	31	80	
	—	—	—	—	
	—	—	—	—	
	—	—	—	—	
	—	—	—	—	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSELTemperature 25°C
Testing Circuitry Figure A

COSEL

Model	MMB50A-5	Temperature Testing Circuitry	25°C Figure A																																															
Item	Load Regulation 靜的負荷変動																																																	
Object	+12.0V 3.00A																																																	
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Load Current [A]</p>	2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85.0[V]</th> <th>100.0[V]</th> <th>132.0[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>12.068</td> <td>12.068</td> <td>12.068</td> </tr> <tr> <td>0.600</td> <td>12.065</td> <td>12.064</td> <td>12.064</td> </tr> <tr> <td>1.200</td> <td>12.063</td> <td>12.062</td> <td>12.062</td> </tr> <tr> <td>1.800</td> <td>12.061</td> <td>12.061</td> <td>12.061</td> </tr> <tr> <td>2.400</td> <td>12.060</td> <td>12.059</td> <td>12.059</td> </tr> <tr> <td>3.000</td> <td>12.058</td> <td>12.058</td> <td>12.057</td> </tr> <tr> <td>3.300</td> <td>12.057</td> <td>12.057</td> <td>12.057</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>	Load Current [A]	Input Volt.	Input Volt.	Input Volt.	85.0[V]	100.0[V]	132.0[V]	0.000	12.068	12.068	12.068	0.600	12.065	12.064	12.064	1.200	12.063	12.062	12.062	1.800	12.061	12.061	12.061	2.400	12.060	12.059	12.059	3.000	12.058	12.058	12.057	3.300	12.057	12.057	12.057	—	—	—	—	—	—	—	—	—	—	—	—	
Load Current [A]	Input Volt.	Input Volt.		Input Volt.																																														
	85.0[V]	100.0[V]	132.0[V]																																															
0.000	12.068	12.068	12.068																																															
0.600	12.065	12.064	12.064																																															
1.200	12.063	12.062	12.062																																															
1.800	12.061	12.061	12.061																																															
2.400	12.060	12.059	12.059																																															
3.000	12.058	12.058	12.057																																															
3.300	12.057	12.057	12.057																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
Object	+12V 1.50A	2. Values																																																
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Load Current [A]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85.0[V]</th> <th>100.0[V]</th> <th>132.0[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>11.990</td> <td>11.990</td> <td>11.990</td> </tr> <tr> <td>0.300</td> <td>11.988</td> <td>11.988</td> <td>11.988</td> </tr> <tr> <td>0.600</td> <td>11.987</td> <td>11.986</td> <td>11.986</td> </tr> <tr> <td>0.900</td> <td>11.985</td> <td>11.985</td> <td>11.985</td> </tr> <tr> <td>1.200</td> <td>11.984</td> <td>11.984</td> <td>11.984</td> </tr> <tr> <td>1.500</td> <td>11.983</td> <td>11.983</td> <td>11.983</td> </tr> <tr> <td>1.650</td> <td>11.983</td> <td>11.982</td> <td>11.982</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>	Load Current [A]	Input Volt.	Input Volt.	Input Volt.	85.0[V]	100.0[V]	132.0[V]	0.000	11.990	11.990	11.990	0.300	11.988	11.988	11.988	0.600	11.987	11.986	11.986	0.900	11.985	11.985	11.985	1.200	11.984	11.984	11.984	1.500	11.983	11.983	11.983	1.650	11.983	11.982	11.982	—	—	—	—	—	—	—	—	—	—	—	—	
Load Current [A]	Input Volt.	Input Volt.		Input Volt.																																														
	85.0[V]	100.0[V]	132.0[V]																																															
0.000	11.990	11.990	11.990																																															
0.300	11.988	11.988	11.988																																															
0.600	11.987	11.986	11.986																																															
0.900	11.985	11.985	11.985																																															
1.200	11.984	11.984	11.984																																															
1.500	11.983	11.983	11.983																																															
1.650	11.983	11.982	11.982																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	MMB50A-5	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																						
Object	+12.0V 3.00A																																								
1. Graph	<p>Input Volt. 85V [mV] □</p> <p>Input Volt. 132V △</p> <table border="1"> <caption>Data points estimated from Figure 1 graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 85V [mV]</th> <th>Ripple Output Volt. 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.6</td><td>5</td><td>5</td></tr> <tr><td>1.2</td><td>5</td><td>5</td></tr> <tr><td>1.8</td><td>5</td><td>5</td></tr> <tr><td>2.4</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>10</td><td>10</td></tr> <tr><td>3.6</td><td>10</td><td>10</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]	0.0	5	5	0.6	5	5	1.2	5	5	1.8	5	5	2.4	10	10	3.0	10	10	3.6	10	10														
Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]																																							
0.0	5	5																																							
0.6	5	5																																							
1.2	5	5																																							
1.8	5	5																																							
2.4	10	10																																							
3.0	10	10																																							
3.6	10	10																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.6</td><td>5</td><td>5</td></tr> <tr><td>1.2</td><td>5</td><td>5</td></tr> <tr><td>1.8</td><td>5</td><td>5</td></tr> <tr><td>2.4</td><td>10</td><td>10</td></tr> <tr><td>3.0</td><td>10</td><td>10</td></tr> <tr><td>3.6</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	0.6	5	5	1.2	5	5	1.8	5	5	2.4	10	10	3.0	10	10	3.6	10	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.0	5	5																																							
0.6	5	5																																							
1.2	5	5																																							
1.8	5	5																																							
2.4	10	10																																							
3.0	10	10																																							
3.6	10	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMB50A-5	Temperature	25°C																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																						
Object	+12.0V 1.50A																																								
1. Graph																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.3</td><td>5</td><td>5</td></tr> <tr><td>0.6</td><td>5</td><td>5</td></tr> <tr><td>0.9</td><td>5</td><td>5</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>1.5</td><td>10</td><td>10</td></tr> <tr><td>1.7</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	0.3	5	5	0.6	5	5	0.9	5	5	1.2	10	10	1.5	10	10	1.7	10	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.0	5	5																																							
0.3	5	5																																							
0.6	5	5																																							
0.9	5	5																																							
1.2	10	10																																							
1.5	10	10																																							
1.7	10	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
Ripple Voltage is shown as p-p in the figure below.																																									
Note: Slanted line shows the range of the rated load current.																																									
リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																									
T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期																																									
Ripple [mVp-p]																																									
Fig. Complex Ripple Wave Form 図 リップル波形詳細図																																									

COSEL

Model	MMB50A-5	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+12.0V 3.00A																																								
1. Graph		2. Values																																							
<p style="text-align: center;">-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.6</td><td>20</td><td>20</td></tr> <tr><td>1.2</td><td>20</td><td>20</td></tr> <tr><td>1.8</td><td>20</td><td>20</td></tr> <tr><td>2.4</td><td>20</td><td>20</td></tr> <tr><td>3.0</td><td>25</td><td>20</td></tr> <tr><td>3.3</td><td>30</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.0	20	20	0.6	20	20	1.2	20	20	1.8	20	20	2.4	20	20	3.0	25	20	3.3	30	20	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.0	20	20																																							
0.6	20	20																																							
1.2	20	20																																							
1.8	20	20																																							
2.4	20	20																																							
3.0	25	20																																							
3.3	30	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>		<p>-11-</p> <p>B C - 3 2 1 3</p>																																							

COSEL

Model	MMB50A-5	Temperature Testing Circuitry	25°C Figure A																																				
Item	Ripple-Noise リップルノイズ																																						
Object	+12.0V 1.50A																																						
1. Graph		2. Values																																					
<p>[mV]</p>		<table border="1"> <thead> <tr> <th>Load current [A]</th> <th>Input Volt. 85 [V] Ripple-Noise [mV]</th> <th>Input Volt. 132 [V] Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>25</td><td>25</td></tr> <tr><td>0.3</td><td>25</td><td>25</td></tr> <tr><td>0.6</td><td>25</td><td>25</td></tr> <tr><td>0.9</td><td>30</td><td>25</td></tr> <tr><td>1.2</td><td>30</td><td>25</td></tr> <tr><td>1.5</td><td>30</td><td>25</td></tr> <tr><td>1.7</td><td>30</td><td>30</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]	0.0	25	25	0.3	25	25	0.6	25	25	0.9	30	25	1.2	30	25	1.5	30	25	1.7	30	30	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]																																					
0.0	25	25																																					
0.3	25	25																																					
0.6	25	25																																					
0.9	30	25																																					
1.2	30	25																																					
1.5	30	25																																					
1.7	30	30																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
<p>Ripple-Noise</p> <p>Load Current</p>																																							
<p>(注) 斜線は定格負荷電流範囲を示す。</p>																																							
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>-----</p>																																							
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																							

COSEL

Model	MMB50A-5	Temperature 25°C Testing Circuitry Figure A		
Item	Overcurrent Protection 過電流保護			
Object	+12.0V 3.00A			
1. Graph	<p>[V] [A]</p>			
2. Values	Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]	
12.00	—	—	—	
11.40	3.720	3.760	3.697	
10.80	3.718	3.730	3.667	
9.60	3.686	3.658	3.582	
8.40	3.622	3.573	3.488	
7.20	3.538	3.471	3.380	
6.00	3.426	3.348	3.254	
4.80	3.280	3.184	3.094	
3.60	3.088	3.004	2.926	
2.40	2.854	2.781	2.718	
1.20	2.562	2.511	2.466	
0.00	2.280	2.301	2.282	
Object	+12V 1.50A			
1. Graph	<p>[V] [A]</p>			
2. Values	Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]
	Load Current [A]	Load Current [A]	Load Current [A]	
12.00	—	—	—	
11.40	1.942	1.921	1.875	
10.80	1.933	1.904	1.861	
9.60	1.906	1.867	1.825	
8.40	1.868	1.823	1.792	
7.20	1.819	1.773	1.740	
6.00	1.755	1.715	1.690	
4.80	1.676	1.638	1.631	
3.60	1.579	1.553	1.562	
2.40	1.465	1.457	1.485	
1.20	1.335	1.350	1.396	
0.00	1.505	1.663	1.827	

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL


Model	MMB50A-5	Testing Circuitry Figure A																																																						
Item	Overtoltage Protection 過電圧保護																																																							
Object	+12.0V 3.00 A																																																							
1. Graph	<p>[V]</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p>	2. Values																																																						
		Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
		[°C]	Operating Point [V]																																																					
		-20	15.46	15.43	15.39																																																			
		-10	15.30	15.27	15.24																																																			
		0	15.23	15.21	15.17																																																			
		10	15.06	15.03	14.98																																																			
		20	14.93	14.90	14.86																																																			
		25	14.81	14.75	14.70																																																			
		30	14.72	14.66	14.61																																																			
		40	14.53	14.49	14.42																																																			
		50	14.35	14.32	14.23																																																			
		60	14.25	14.23	14.10																																																			
		-	-	-	-																																																			
Object	+12V 1.50 A	2. Values																																																						
1. Graph	<p>[V]</p> <p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p>	<table border="1"> <thead> <tr> <th>Ambient Temp.</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th>[°C]</th> <th colspan="3">Operating Point [V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>15.5</td> <td>15.5</td> <td>15.5</td> </tr> <tr> <td>-10</td> <td>15.5</td> <td>15.5</td> <td>15.5</td> </tr> <tr> <td>0</td> <td>15.4</td> <td>15.4</td> <td>15.4</td> </tr> <tr> <td>10</td> <td>15.2</td> <td>15.2</td> <td>15.2</td> </tr> <tr> <td>20</td> <td>15.1</td> <td>15.1</td> <td>15.1</td> </tr> <tr> <td>25</td> <td>15.0</td> <td>15.0</td> <td>14.9</td> </tr> <tr> <td>30</td> <td>14.9</td> <td>14.9</td> <td>14.8</td> </tr> <tr> <td>40</td> <td>14.7</td> <td>14.7</td> <td>14.6</td> </tr> <tr> <td>50</td> <td>14.6</td> <td>14.5</td> <td>14.4</td> </tr> <tr> <td>60</td> <td>14.3</td> <td>14.3</td> <td>14.1</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	[°C]	Operating Point [V]			-20	15.5	15.5	15.5	-10	15.5	15.5	15.5	0	15.4	15.4	15.4	10	15.2	15.2	15.2	20	15.1	15.1	15.1	25	15.0	15.0	14.9	30	14.9	14.9	14.8	40	14.7	14.7	14.6	50	14.6	14.5	14.4	60	14.3	14.3	14.1	-	-	-	-
Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																					
[°C]	Operating Point [V]																																																							
-20	15.5	15.5	15.5																																																					
-10	15.5	15.5	15.5																																																					
0	15.4	15.4	15.4																																																					
10	15.2	15.2	15.2																																																					
20	15.1	15.1	15.1																																																					
25	15.0	15.0	14.9																																																					
30	14.9	14.9	14.8																																																					
40	14.7	14.7	14.6																																																					
50	14.6	14.5	14.4																																																					
60	14.3	14.3	14.1																																																					
-	-	-	-																																																					
		Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
		[°C]	Operating Point [V]																																																					
		-20	15.5	15.5	15.5																																																			
		-10	15.5	15.5	15.5																																																			
		0	15.4	15.4	15.4																																																			
		10	15.2	15.2	15.2																																																			
		20	15.1	15.1	15.1																																																			
		25	15.0	15.0	14.9																																																			
		30	14.9	14.9	14.8																																																			
		40	14.7	14.7	14.6																																																			
		50	14.6	14.5	14.4																																																			
		60	14.3	14.3	14.1																																																			
		-	-	-	-																																																			

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


COSEL


Model	MMB50A-5	Temperature Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object	—	



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

- ① 16.37 [A]
- ② 3.82 [A]





COSEL

COSEL

Model	MMB50A-5	Temperature	25°C
Item	Dynamic Load Response 動的負荷変動	Testing Circuitry	Figure A
Object	+12.0V 1.50A		


Input Volt. 100 V

Cycle 200 mS



100 mV/div


10 mS/div

COSSEL

COSSEL

Model	MMB50A-5	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	+12.0V 1.50A		


1. Graph



2. Values

Load	Time	T d	T r	T s	T h	T f
50 %		5.8	27.0	32.8	57.8	56.3
100 %		5.8	28.3	34.0	33.9	36.2

[mS]



COSEL

Model	MMB50A-5	Testing Circuitry Figure A																																																		
Item	Ambient Temperature Drift 周囲温度変動																																																			
Object	+12.0V 3.00A																																																			
1. Graph	<p style="text-align: center;"> —△— Input Volt. 85.0V —□— Input Volt. 100.0V —○— Input Volt. 132.0V </p>	2. Values																																																		
		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.090</td><td>12.090</td><td>12.089</td></tr> <tr><td>-10</td><td>12.085</td><td>12.084</td><td>12.084</td></tr> <tr><td>0</td><td>12.078</td><td>12.077</td><td>12.077</td></tr> <tr><td>10</td><td>12.070</td><td>12.070</td><td>12.070</td></tr> <tr><td>20</td><td>12.065</td><td>12.065</td><td>12.065</td></tr> <tr><td>25</td><td>12.059</td><td>12.059</td><td>12.059</td></tr> <tr><td>30</td><td>12.053</td><td>12.052</td><td>12.052</td></tr> <tr><td>40</td><td>12.034</td><td>12.034</td><td>12.034</td></tr> <tr><td>50</td><td>12.022</td><td>12.021</td><td>12.021</td></tr> <tr><td>60</td><td>12.011</td><td>12.011</td><td>12.011</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	12.090	12.090	12.089	-10	12.085	12.084	12.084	0	12.078	12.077	12.077	10	12.070	12.070	12.070	20	12.065	12.065	12.065	25	12.059	12.059	12.059	30	12.053	12.052	12.052	40	12.034	12.034	12.034	50	12.022	12.021	12.021	60	12.011	12.011	12.011	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	12.090	12.090	12.089																																																	
-10	12.085	12.084	12.084																																																	
0	12.078	12.077	12.077																																																	
10	12.070	12.070	12.070																																																	
20	12.065	12.065	12.065																																																	
25	12.059	12.059	12.059																																																	
30	12.053	12.052	12.052																																																	
40	12.034	12.034	12.034																																																	
50	12.022	12.021	12.021																																																	
60	12.011	12.011	12.011																																																	
—	—	—	—																																																	
Object	+12V 1.50A	2. Values																																																		
1. Graph	<p style="text-align: center;"> —△— Input Volt. 85.0V —□— Input Volt. 100.0V —○— Input Volt. 132.0V </p>																																																			
		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.010</td><td>12.009</td><td>12.009</td></tr> <tr><td>-10</td><td>12.006</td><td>12.006</td><td>12.006</td></tr> <tr><td>0</td><td>12.002</td><td>12.002</td><td>12.002</td></tr> <tr><td>10</td><td>11.996</td><td>11.995</td><td>11.995</td></tr> <tr><td>20</td><td>11.988</td><td>11.988</td><td>11.988</td></tr> <tr><td>25</td><td>11.983</td><td>11.983</td><td>11.983</td></tr> <tr><td>30</td><td>11.979</td><td>11.979</td><td>11.979</td></tr> <tr><td>40</td><td>11.969</td><td>11.969</td><td>11.969</td></tr> <tr><td>50</td><td>11.960</td><td>11.959</td><td>11.959</td></tr> <tr><td>60</td><td>11.951</td><td>11.950</td><td>11.950</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	12.010	12.009	12.009	-10	12.006	12.006	12.006	0	12.002	12.002	12.002	10	11.996	11.995	11.995	20	11.988	11.988	11.988	25	11.983	11.983	11.983	30	11.979	11.979	11.979	40	11.969	11.969	11.969	50	11.960	11.959	11.959	60	11.951	11.950	11.950	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	12.010	12.009	12.009																																																	
-10	12.006	12.006	12.006																																																	
0	12.002	12.002	12.002																																																	
10	11.996	11.995	11.995																																																	
20	11.988	11.988	11.988																																																	
25	11.983	11.983	11.983																																																	
30	11.979	11.979	11.979																																																	
40	11.969	11.969	11.969																																																	
50	11.960	11.959	11.959																																																	
60	11.951	11.950	11.950																																																	
—	—	—	—																																																	

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	MMB50A-5																																						
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧	Testing Circuitry Figure A																																					
Object	+12.0V3.00A																																						
1. Graph	<p>The graph plots Input Voltage [V] from 0.0 to 100.0 against Ambient Temperature [°C] from -30 to 70. Two sets of data points are shown: Load 50% (represented by squares) and Load 100% (represented by triangles). Both series show a slight increase in input voltage as ambient temperature rises, with a sharp drop-off at higher temperatures. A horizontal dashed line at approximately 32V indicates the minimum input voltage required for regulation.</p>																																						
2. Values	<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Input Volt. [V]</th> <th>Load 100% Input Volt. [V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>31.8</td><td>60.8</td></tr> <tr><td>-10</td><td>31.8</td><td>60.8</td></tr> <tr><td>0</td><td>32.1</td><td>61.4</td></tr> <tr><td>10</td><td>31.8</td><td>62.4</td></tr> <tr><td>20</td><td>31.8</td><td>61.9</td></tr> <tr><td>25</td><td>31.8</td><td>62.4</td></tr> <tr><td>30</td><td>31.9</td><td>62.8</td></tr> <tr><td>40</td><td>32.1</td><td>62.9</td></tr> <tr><td>50</td><td>32.0</td><td>64.2</td></tr> <tr><td>60</td><td>33.4</td><td>64.8</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]	-20	31.8	60.8	-10	31.8	60.8	0	32.1	61.4	10	31.8	62.4	20	31.8	61.9	25	31.8	62.4	30	31.9	62.8	40	32.1	62.9	50	32.0	64.2	60	33.4	64.8	—	—	—
Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]																																					
-20	31.8	60.8																																					
-10	31.8	60.8																																					
0	32.1	61.4																																					
10	31.8	62.4																																					
20	31.8	61.9																																					
25	31.8	62.4																																					
30	31.9	62.8																																					
40	32.1	62.9																																					
50	32.0	64.2																																					
60	33.4	64.8																																					
—	—	—																																					
Object	+12V1.50A	<p>The graph plots Input Voltage [V] from 0.0 to 100.0 against Ambient Temperature [°C] from -30 to 70. Two sets of data points are shown: Load 50% (represented by squares) and Load 100% (represented by triangles). Both series show a slight increase in input voltage as ambient temperature rises, with a sharp drop-off at higher temperatures. A horizontal dashed line at approximately 30.3V indicates the minimum input voltage required for regulation.</p>																																					
2. Values	<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Input Volt. [V]</th> <th>Load 100% Input Volt. [V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>31.0</td><td>55.0</td></tr> <tr><td>-10</td><td>31.3</td><td>55.0</td></tr> <tr><td>0</td><td>30.3</td><td>55.0</td></tr> <tr><td>10</td><td>30.0</td><td>55.1</td></tr> <tr><td>20</td><td>30.0</td><td>56.0</td></tr> <tr><td>25</td><td>30.3</td><td>56.3</td></tr> <tr><td>30</td><td>30.0</td><td>56.3</td></tr> <tr><td>40</td><td>30.4</td><td>57.1</td></tr> <tr><td>50</td><td>30.0</td><td>57.1</td></tr> <tr><td>60</td><td>30.2</td><td>58.0</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]	-20	31.0	55.0	-10	31.3	55.0	0	30.3	55.0	10	30.0	55.1	20	30.0	56.0	25	30.3	56.3	30	30.0	56.3	40	30.4	57.1	50	30.0	57.1	60	30.2	58.0	—	—	—
Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]																																					
-20	31.0	55.0																																					
-10	31.3	55.0																																					
0	30.3	55.0																																					
10	30.0	55.1																																					
20	30.0	56.0																																					
25	30.3	56.3																																					
30	30.0	56.3																																					
40	30.4	57.1																																					
50	30.0	57.1																																					
60	30.2	58.0																																					
—	—	—																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																							

COSSEL


Model	MMB50A-5																																						
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry																																					
Object	+12.0V 3.00A	Figure A																																					
1. Graph	<p>Input Volt. 100 V</p>	2. Values																																					
		<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Ripple Output Volt. [mV]</th> <th>Load 100% Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>10</td><td>20</td></tr> <tr><td>-10</td><td>10</td><td>20</td></tr> <tr><td>0</td><td>5</td><td>15</td></tr> <tr><td>10</td><td>5</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>10</td></tr> <tr><td>50</td><td>5</td><td>10</td></tr> <tr><td>60</td><td>5</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	10	20	-10	10	20	0	5	15	10	5	15	20	5	10	25	5	10	30	5	10	40	5	10	50	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																					
-20	10	20																																					
-10	10	20																																					
0	5	15																																					
10	5	15																																					
20	5	10																																					
25	5	10																																					
30	5	10																																					
40	5	10																																					
50	5	10																																					
60	5	10																																					
—	—	—																																					
Object	+12V 1.50A																																						
1. Graph	<p>Input Volt. 100 V</p>	2. Values																																					
		<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50% Ripple Output Volt. [mV]</th> <th>Load 100% Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>10</td><td>25</td></tr> <tr><td>-10</td><td>10</td><td>20</td></tr> <tr><td>0</td><td>5</td><td>15</td></tr> <tr><td>10</td><td>5</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>10</td></tr> <tr><td>50</td><td>5</td><td>10</td></tr> <tr><td>60</td><td>5</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	10	25	-10	10	20	0	5	15	10	5	15	20	5	10	25	5	10	30	5	10	40	5	10	50	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																					
-20	10	25																																					
-10	10	20																																					
0	5	15																																					
10	5	15																																					
20	5	10																																					
25	5	10																																					
30	5	10																																					
40	5	10																																					
50	5	10																																					
60	5	10																																					
—	—	—																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																							

COSEL

Model	MMB50A-5
Item	Time Lapse Drift 経時ドリフト
Object	+12.0V 3.00A

Temperature 25 °C
Testing Circuitry Figure A

1. Graph




2. Values

Time since start [H]	Output Voltage [V]
0.0	12.061
0.5	12.051
1.0	12.051
2.0	12.051
3.0	12.051
4.0	12.051
5.0	12.051
6.0	12.051
7.0	12.051
8.0	12.051

Object	+12V1.50A
--------	-----------

1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	11.993
0.5	11.989
1.0	11.989
2.0	11.989
3.0	11.989
4.0	11.989
5.0	11.988
6.0	11.988
7.0	11.988
8.0	11.988



Model	MMB50A-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85.0~132.0 V

Load Current (AVR 1) : 0.00~3.00 A

(AVR 2) : 0.00~1.50 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage)/2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85.0~132.0 V

負荷電流 (AVR 1) 0.00~3.00 A

(AVR 2) 0.00~1.50 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値)/2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object	+12.0V3.00A	
--------	-------------	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132.0	0.00	12.094		
Minimum Voltage	50	85.0	3.00	12.019	±38	±0.4

Object	+12V1.50A	
--------	-----------	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	100.0	0.00	12.012		
Minimum Voltage	50	132.0	1.50	11.959	±27	±0.3



Model	MMB50A-5	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+12.0V3A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.06	Input Volt.: 100V, Load Current:3A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:3A
Load Regulation [mV]	8	Input Volt.: 100V, Load Current:0~3A



Model	MMB50A-5	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+12.0V3A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	11.987	Input Volt.: 100V, Load Current:3A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:3A
Load Regulation [mV]	7	Input Volt.: 100V, Load Current:0~3A



Model	MMB50A-5	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure A
Object	<hr/>		

1. Results

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
(A) DENTORI	85 [V]	100 [V]	132 [V]
(B) IEC60950	0.12	0.14	0.19

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
(B) IEC60950	170 [V]	230 [V]	264 [V]
	—	—	—

COSSEL

Model	MMB50A-5	Testing Circuitry Figure D
Item	Conducted Emission 雜音端子電圧	
Object	_____	

1. Graph

Remarks


Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注)斜線は許容値を示す。

NO	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/ μ V]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E