

# TEST DATA OF MMC100B-1

Regulated DC Power Supply  
April 5, 2011

Approved by : Naoki Tonami  
Naoki Tonami                              Design Manager

Prepared by : Hironobu Shimizu  
Hironobu Shimizu                              Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Input Power (by Load Current) . . . . .	2
3.Efficiency (by Input Voltage) . . . . .	3
4.Efficiency (by Load Current) . . . . .	4
5.Power Factor (by Input Voltage) . . . . .	5
6.Power Factor (by Load Current) . . . . .	6
7.Inrush Current . . . . .	7
8.Leakage Current . . . . .	8
9.Line Regulation . . . . .	9
10.Load Regulation . . . . .	11
11.Dynamic Load Response . . . . .	13
12.Ripple Voltage (by Load Current) . . . . .	16
13.Ripple-Noise . . . . .	19
14.Ripple Voltage (by Ambient Temperature) . . . . .	22
15.Ambient Temperature Drift . . . . .	24
16.Output Voltage Accuracy . . . . .	26
17.Time Lapse Drift . . . . .	27
18.Rise and Fall Time . . . . .	29
19.Hold-Up Time . . . . .	32
20.Instantaneous Interruption Compensation . . . . .	35
21.Minimum Input Voltage for Regulated Output Voltage . . . . .	38
22.Overcurrent Protection . . . . .	40
23.Overvoltage Protection . . . . .	42
24.Figure of Testing Circuitry . . . . .	43

(Final Page 43)

**COSEL**

Model	MMC100B-1	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph		2.Values																																																				
<p>—△— Input Volt. 85V        - - □ - - Input Volt. 100V        - - ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 85V [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 132V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.184</td><td>0.172</td><td>0.163</td></tr> <tr><td>20</td><td>0.718</td><td>0.651</td><td>0.562</td></tr> <tr><td>40</td><td>1.260</td><td>1.127</td><td>0.945</td></tr> <tr><td>60</td><td>1.790</td><td>1.594</td><td>1.318</td></tr> <tr><td>80</td><td>2.320</td><td>2.054</td><td>1.686</td></tr> <tr><td>100</td><td>2.862</td><td>2.522</td><td>2.060</td></tr> <tr><td>110</td><td>3.132</td><td>2.758</td><td>2.247</td></tr> </tbody> </table>	Load Ration [%]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]	0	0.184	0.172	0.163	20	0.718	0.651	0.562	40	1.260	1.127	0.945	60	1.790	1.594	1.318	80	2.320	2.054	1.686	100	2.862	2.522	2.060	110	3.132	2.758	2.247																						
Load Ration [%]	Input Volt. 85V [A]	Input Volt. 100V [A]	Input Volt. 132V [A]																																																			
0	0.184	0.172	0.163																																																			
20	0.718	0.651	0.562																																																			
40	1.260	1.127	0.945																																																			
60	1.790	1.594	1.318																																																			
80	2.320	2.054	1.686																																																			
100	2.862	2.522	2.060																																																			
110	3.132	2.758	2.247																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.184</td><td>0.172</td><td>0.163</td></tr> <tr><td>20</td><td>0.718</td><td>0.651</td><td>0.562</td></tr> <tr><td>40</td><td>1.260</td><td>1.127</td><td>0.945</td></tr> <tr><td>60</td><td>1.790</td><td>1.594</td><td>1.318</td></tr> <tr><td>80</td><td>2.320</td><td>2.054</td><td>1.686</td></tr> <tr><td>100</td><td>2.862</td><td>2.522</td><td>2.060</td></tr> <tr><td>110</td><td>3.132</td><td>2.758</td><td>2.247</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ration [%]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.184	0.172	0.163	20	0.718	0.651	0.562	40	1.260	1.127	0.945	60	1.790	1.594	1.318	80	2.320	2.054	1.686	100	2.862	2.522	2.060	110	3.132	2.758	2.247	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Current [A]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	0.184	0.172	0.163																																																			
20	0.718	0.651	0.562																																																			
40	1.260	1.127	0.945																																																			
60	1.790	1.594	1.318																																																			
80	2.320	2.054	1.686																																																			
100	2.862	2.522	2.060																																																			
110	3.132	2.758	2.247																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**


Model MMC100B-1

Item Input Power (by Load Current)

Object \_\_\_\_\_

1.Graph

—△— Input Volt. 85V  
 - -□--- Input Volt. 100V  
 - -○--- Input Volt. 132V


 Temperature 25°C  
 Testing Circuitry Figure A

2.Values

Load Ration [%]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	6.0	6.3	7.6
20	27.5	28.1	29.9
40	52.3	52.8	54.4
60	78.6	78.9	79.4
80	105.9	105.5	105.9
100	134.7	133.5	133.2
110	150.0	148.2	147.0
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	MMC100B-1	Temperature 25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>77.6</td><td>74.7</td></tr> <tr><td>80</td><td>77.9</td><td>75.2</td></tr> <tr><td>85</td><td>78.2</td><td>75.5</td></tr> <tr><td>90</td><td>78.2</td><td>76.0</td></tr> <tr><td>100</td><td>77.9</td><td>76.3</td></tr> <tr><td>110</td><td>77.4</td><td>76.5</td></tr> <tr><td>120</td><td>77.0</td><td>76.7</td></tr> <tr><td>132</td><td>76.4</td><td>76.5</td></tr> <tr><td>140</td><td>75.9</td><td>76.5</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	77.6	74.7	80	77.9	75.2	85	78.2	75.5	90	78.2	76.0	100	77.9	76.3	110	77.4	76.5	120	77.0	76.7	132	76.4	76.5	140	75.9	76.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	77.6	74.7																																
80	77.9	75.2																																
85	78.2	75.5																																
90	78.2	76.0																																
100	77.9	76.3																																
110	77.4	76.5																																
120	77.0	76.7																																
132	76.4	76.5																																
140	75.9	76.5																																

**COSEL**


Model	MMC100B-1	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 85V        - - □ - - Input Volt. 100V        - - ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Efficiency [85V] [%]</th> <th>Efficiency [100V] [%]</th> <th>Efficiency [132V] [%]</th> </tr> </thead> <tbody> <tr><td>20</td><td>74.3</td><td>72.7</td><td>68.3</td></tr> <tr><td>40</td><td>78.0</td><td>77.2</td><td>75.0</td></tr> <tr><td>60</td><td>77.8</td><td>77.5</td><td>77.0</td></tr> <tr><td>80</td><td>77.0</td><td>77.3</td><td>77.0</td></tr> <tr><td>100</td><td>75.7</td><td>76.3</td><td>76.5</td></tr> <tr><td>110</td><td>74.7</td><td>75.6</td><td>76.2</td></tr> <tr><td>120</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Efficiency [85V] [%]	Efficiency [100V] [%]	Efficiency [132V] [%]	20	74.3	72.7	68.3	40	78.0	77.2	75.0	60	77.8	77.5	77.0	80	77.0	77.3	77.0	100	75.7	76.3	76.5	110	74.7	75.6	76.2	120	-	-	-	2.Values																				
Load Ration [%]	Efficiency [85V] [%]	Efficiency [100V] [%]	Efficiency [132V] [%]																																																			
20	74.3	72.7	68.3																																																			
40	78.0	77.2	75.0																																																			
60	77.8	77.5	77.0																																																			
80	77.0	77.3	77.0																																																			
100	75.7	76.3	76.5																																																			
110	74.7	75.6	76.2																																																			
120	-	-	-																																																			
	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>74.3</td><td>72.7</td><td>68.3</td></tr> <tr><td>40</td><td>78.0</td><td>77.2</td><td>75.0</td></tr> <tr><td>60</td><td>77.8</td><td>77.5</td><td>77.0</td></tr> <tr><td>80</td><td>77.0</td><td>77.3</td><td>77.0</td></tr> <tr><td>100</td><td>75.7</td><td>76.3</td><td>76.5</td></tr> <tr><td>110</td><td>74.7</td><td>75.6</td><td>76.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	-	-	-	20	74.3	72.7	68.3	40	78.0	77.2	75.0	60	77.8	77.5	77.0	80	77.0	77.3	77.0	100	75.7	76.3	76.5	110	74.7	75.6	76.2	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	-	-	-																																																			
20	74.3	72.7	68.3																																																			
40	78.0	77.2	75.0																																																			
60	77.8	77.5	77.0																																																			
80	77.0	77.3	77.0																																																			
100	75.7	76.3	76.5																																																			
110	74.7	75.6	76.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSSEL**

Model	MMC100B-1
Item	Power Factor (by Input Voltage)
Object	_____

Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.533	0.589
80	0.524	0.578
85	0.515	0.567
90	0.507	0.559
100	0.491	0.540
110	0.473	0.524
120	0.461	0.510
130	0.449	0.498
140	0.443	0.489

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MMC100B-1																																																					
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 85V        - - □ - - Input Volt. 100V        - - ○ - - Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Volt. 85V</th> <th>Input Volt. 100V</th> <th>Input Volt. 132V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.385</td><td>0.367</td><td>0.351</td></tr> <tr><td>40</td><td>0.450</td><td>0.431</td><td>0.403</td></tr> <tr><td>70</td><td>0.488</td><td>0.468</td><td>0.436</td></tr> <tr><td>100</td><td>0.516</td><td>0.495</td><td>0.456</td></tr> <tr><td>110</td><td>0.537</td><td>0.514</td><td>0.475</td></tr> <tr><td>120</td><td>0.555</td><td>0.530</td><td>0.489</td></tr> </tbody> </table>			Load Ration [%]	Input Volt. 85V	Input Volt. 100V	Input Volt. 132V	0	0.385	0.367	0.351	40	0.450	0.431	0.403	70	0.488	0.468	0.436	100	0.516	0.495	0.456	110	0.537	0.514	0.475	120	0.555	0.530	0.489																							
Load Ration [%]	Input Volt. 85V	Input Volt. 100V	Input Volt. 132V																																																			
0	0.385	0.367	0.351																																																			
40	0.450	0.431	0.403																																																			
70	0.488	0.468	0.436																																																			
100	0.516	0.495	0.456																																																			
110	0.537	0.514	0.475																																																			
120	0.555	0.530	0.489																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.385</td><td>0.367</td><td>0.351</td></tr> <tr><td>20</td><td>0.450</td><td>0.431</td><td>0.403</td></tr> <tr><td>40</td><td>0.488</td><td>0.468</td><td>0.436</td></tr> <tr><td>60</td><td>0.516</td><td>0.495</td><td>0.456</td></tr> <tr><td>80</td><td>0.537</td><td>0.514</td><td>0.475</td></tr> <tr><td>100</td><td>0.555</td><td>0.530</td><td>0.489</td></tr> <tr><td>110</td><td>0.563</td><td>0.538</td><td>0.495</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Power Factor			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.385	0.367	0.351	20	0.450	0.431	0.403	40	0.488	0.468	0.436	60	0.516	0.495	0.456	80	0.537	0.514	0.475	100	0.555	0.530	0.489	110	0.563	0.538	0.495	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Power Factor																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0	0.385	0.367	0.351																																																			
20	0.450	0.431	0.403																																																			
40	0.488	0.468	0.436																																																			
60	0.516	0.495	0.456																																																			
80	0.537	0.514	0.475																																																			
100	0.555	0.530	0.489																																																			
110	0.563	0.538	0.495																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


**COSEL**

Model MMC100B-1

Item Inrush Current


Temperature 25°C  
Testing Circuitry Figure A

Object \_\_\_\_\_

Input  
Current  
[20A/div]

Input Voltage	100 V
Frequency	60 Hz
Load	100 %

Primary inrush current	17.5 A
Secondary inrush current	8.3 A





Model	MMC100B-1	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

### 1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A)DEN-AN	0.15	0.18	0.22
(B)IEC60950-1	0.15	0.19	0.25

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B)IEC60950-1	-	-	-

### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

Model	MMC100B-1
Item	Line Regulation
Object	+5V13A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph

---□--- Load 50%  
—△— Load 100%




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	5.090	5.076
80	5.090	5.076
85	5.090	5.076
90	5.090	5.076
100	5.090	5.076
110	5.090	5.075
120	5.090	5.075
132	5.089	5.075
140	5.089	5.074

Object	+12V2A
--------	--------

## 1.Graph

---□--- Load 50%  
—△— Load 100%



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	11.931	11.929
80	11.931	11.929
85	11.931	11.929
90	11.931	11.929
100	11.931	11.929
110	11.931	11.929
120	11.931	11.929
132	11.931	11.929
140	11.931	11.929



Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MMC100B-1																																	
Item	Line Regulation	Temperature      25°C Testing Circuitry      Figure A																																
Object	-12V1A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50%    —△— Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>-12.083</td><td>-12.083</td></tr> <tr><td>80</td><td>-12.081</td><td>-12.085</td></tr> <tr><td>85</td><td>-12.079</td><td>-12.086</td></tr> <tr><td>90</td><td>-12.078</td><td>-12.087</td></tr> <tr><td>100</td><td>-12.078</td><td>-12.087</td></tr> <tr><td>110</td><td>-12.077</td><td>-12.088</td></tr> <tr><td>120</td><td>-12.077</td><td>-12.089</td></tr> <tr><td>132</td><td>-12.077</td><td>-12.089</td></tr> <tr><td>140</td><td>-12.077</td><td>-12.090</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	-12.083	-12.083	80	-12.081	-12.085	85	-12.079	-12.086	90	-12.078	-12.087	100	-12.078	-12.087	110	-12.077	-12.088	120	-12.077	-12.089	132	-12.077	-12.089	140	-12.077	-12.090
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
75	-12.083	-12.083																																
80	-12.081	-12.085																																
85	-12.079	-12.086																																
90	-12.078	-12.087																																
100	-12.078	-12.087																																
110	-12.077	-12.088																																
120	-12.077	-12.089																																
132	-12.077	-12.089																																
140	-12.077	-12.090																																



**COSEL**

Model	MMC100B-1
Item	Load Regulation
Object	+5V13A

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	5.102	5.101	5.100
2.0	5.098	5.098	5.097
4.0	5.094	5.093	5.093
6.0	5.089	5.089	5.089
8.0	5.085	5.085	5.084
10.0	5.081	5.081	5.080
12.0	5.077	5.076	5.076
13.0	5.074	5.074	5.074
14.3	5.072	5.072	5.071
--	-	-	-
--	-	-	-



## 2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	11.934	11.934	11.934
0.4	11.933	11.933	11.933
0.8	11.932	11.932	11.932
1.2	11.931	11.931	11.931
1.6	11.930	11.930	11.930
2.0	11.929	11.929	11.929
2.2	11.929	11.929	11.929
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.


**COSEL**

Model	MMC100B-1	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	-12V1A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85V</li> <li>Input Volt. 100V</li> <li>Input Volt. 132V</li> </ul>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.086</td><td>-12.086</td><td>-12.077</td></tr> <tr><td>0.2</td><td>-12.077</td><td>-12.077</td><td>-12.070</td></tr> <tr><td>0.4</td><td>-12.077</td><td>-12.076</td><td>-12.072</td></tr> <tr><td>0.6</td><td>-12.078</td><td>-12.078</td><td>-12.074</td></tr> <tr><td>0.8</td><td>-12.080</td><td>-12.080</td><td>-12.077</td></tr> <tr><td>1.0</td><td>-12.082</td><td>-12.081</td><td>-12.080</td></tr> <tr><td>1.1</td><td>-12.083</td><td>-12.084</td><td>-12.082</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-12.086	-12.086	-12.077	0.2	-12.077	-12.077	-12.070	0.4	-12.077	-12.076	-12.072	0.6	-12.078	-12.078	-12.074	0.8	-12.080	-12.080	-12.077	1.0	-12.082	-12.081	-12.080	1.1	-12.083	-12.084	-12.082	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	-12.086	-12.086	-12.077																																																			
0.2	-12.077	-12.077	-12.070																																																			
0.4	-12.077	-12.076	-12.072																																																			
0.6	-12.078	-12.078	-12.074																																																			
0.8	-12.080	-12.080	-12.077																																																			
1.0	-12.082	-12.081	-12.080																																																			
1.1	-12.083	-12.084	-12.082																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**

**COSEL**

**COSEL**

# COSEL


Model	MMC100B-1																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+5V13A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0 to 16 A. Two data series are plotted: Input Volt. 85V (triangles) and Input Volt. 132V (circles). Both series show a slight increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 85V)</th> <th>Ripple Voltage [mV] (Input Volt. 132V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>2.6</td><td>15</td><td>20</td></tr> <tr><td>5.2</td><td>15</td><td>20</td></tr> <tr><td>7.8</td><td>15</td><td>20</td></tr> <tr><td>10.4</td><td>15</td><td>20</td></tr> <tr><td>13.0</td><td>15</td><td>20</td></tr> <tr><td>14.3</td><td>15</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)	0.0	10	10	2.6	15	20	5.2	15	20	7.8	15	20	10.4	15	20	13.0	15	20	14.3	15	20	--	-	-	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 85V)	Ripple Voltage [mV] (Input Volt. 132V)																																						
0.0	10	10																																						
2.6	15	20																																						
5.2	15	20																																						
7.8	15	20																																						
10.4	15	20																																						
13.0	15	20																																						
14.3	15	20																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>2.6</td><td>15</td><td>20</td></tr> <tr><td>5.2</td><td>15</td><td>20</td></tr> <tr><td>7.8</td><td>15</td><td>20</td></tr> <tr><td>10.4</td><td>15</td><td>20</td></tr> <tr><td>13.0</td><td>15</td><td>20</td></tr> <tr><td>14.3</td><td>15</td><td>20</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 85 [V]	Input Volt. 132 [V]	0.0	10	10	2.6	15	20	5.2	15	20	7.8	15	20	10.4	15	20	13.0	15	20	14.3	15	20	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
0.0	10	10																																						
2.6	15	20																																						
5.2	15	20																																						
7.8	15	20																																						
10.4	15	20																																						
13.0	15	20																																						
14.3	15	20																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

**COSSEL**

Model	MMC100B-1
Item	Ripple Voltage (by Load Current)
Object	+12V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	15	15
0.4	20	20
0.8	20	20
1.2	20	20
1.6	20	20
2.0	20	20
2.2	20	20
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


T1: Due to AC Input Line  
T2: Due to Switching


Fig. Complex Ripple Wave Form

**COSEL**

Model	MMC100B-1
Item	Ripple Voltage (by Load Current)
Object	-12V1A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	10	10
0.2	10	10
0.4	10	10
0.6	10	10
0.8	10	10
1.0	10	10
1.1	10	10
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


 T1: Due to AC Input Line  
 T2: Due to Switching



Fig. Complex Ripple Wave Form

**COSEL**

Model	MMC100B-1
Item	Ripple-Noise
Object	+5V13A

Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	30	30
2.6	35	40
5.2	35	45
7.8	35	50
10.4	35	50
13.0	40	55
14.3	40	55
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line  
 T2: Due to Switching





Fig. Complex Ripple Wave Form

**COSEL**

Model	MMC100B-1
Item	Ripple-Noise
Object	+12V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	30	35
0.4	35	40
0.8	35	45
1.2	35	45
1.6	35	45
2.0	40	45
2.2	40	50
--	-	-
--	-	-
--	-	-
--	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	MMC100B-1
Item	Ripple-Noise
Object	-12V1A

## 1.Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 85 [V]	Input Volt. 132 [V]
0.0	30	35
0.2	40	35
0.4	40	35
0.6	45	35
0.8	45	40
1.0	45	40
1.1	45	40
--	-	-
--	-	-
--	-	-
--	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	MMC100B-1
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V13A

## 1.Graph




## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	25	25
-10	20	20
0	20	20
10	20	20
20	15	15
25	15	15
30	15	15
40	15	15
50	15	15
60	15	15
--	-	-

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	40	40
-10	30	35
0	30	30
10	25	30
20	25	25
25	25	25
30	25	25
40	25	25
50	20	20
60	20	20
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


**COSEL**

Model MMC100B-1

Item Ripple Voltage (by Ambient Temp.)

Object -12V1A

## 1.Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.





Fig.Complex Ripple Noise Wave Form

Testing Circuitry Figure A

## 2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-20	10	10
-10	10	10
0	10	10
10	10	10
20	10	10
25	10	10
30	10	10
40	10	10
50	10	10
60	10	10
--	-	-

**COSEL**

Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	5.080	5.079	5.079
-10	5.078	5.078	5.078
0	5.079	5.079	5.079
10	5.079	5.079	5.078
20	5.073	5.073	5.073
25	5.075	5.075	5.074
30	5.076	5.076	5.076
40	5.079	5.079	5.079
50	5.079	5.079	5.079
60	5.078	5.078	5.078
--	-	-	-



## 2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	11.914	11.914	11.914
-10	11.918	11.918	11.919
0	11.923	11.923	11.923
10	11.927	11.927	11.927
20	11.932	11.932	11.932
25	11.934	11.935	11.935
30	11.937	11.937	11.937
40	11.938	11.938	11.938
50	11.936	11.936	11.936
60	11.932	11.932	11.931
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**


Model MMC100B-1

Item Ambient Temperature Drift

Object -12V1A

## 1. Graph

—△— Input Volt. 85V  
 - - □ - - Input Volt. 100V  
 - - ○ - - Input Volt. 132V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-20	-11.951	-11.965	-11.971
-10	-11.981	-11.993	-11.998
0	-12.012	-12.020	-12.026
10	-12.040	-12.048	-12.052
20	-12.062	-12.068	-12.072
25	-12.073	-12.078	-12.082
30	-12.080	-12.087	-12.092
40	-12.096	-12.102	-12.105
50	-12.112	-12.116	-12.119
60	-12.121	-12.126	-12.129
--	-	-	-



Model	MMC100B-1	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : 0 - 50°C

Input Voltage : 85 - 132V

Load Current (AVR 1) : 1.5 - 13A (AVR 2) : 0 - 2A (AVR 3) : 0 - 1A

\* Output Voltage Accuracy =  $\pm$ (Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object		+5V13A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	50	132	1.5	5.106	$\pm 17$	$\pm 0.3$	
Minimum Voltage	20	132	13	5.073			

Object		+12V2A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	40	132	0	11.944	$\pm 12$	$\pm 0.1$	
Minimum Voltage	0	85	2	11.921			

Object		-12V1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]			Value [mV]	Ration [%]	
			Current[A]	Voltage[V]			
Maximum Voltage	50	132	1	-12.119	$\pm 69$	$\pm 0.6$	
Minimum Voltage	0	85	1	-11.982			

**COSEL**

Model	MMC100B-1
Item	Time Lapse Drift
Object	+5V13A


1.Graph

Input Volt.	100V
Load	100%

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values


Time since start [H]	Output Voltage [V]
0.0	5.075
0.5	5.077
1.0	5.077
2.0	5.077
3.0	5.077
4.0	5.077
5.0	5.077
6.0	5.077
7.0	5.077
8.0	5.077



## 2.Values

Time since start [H]	Output Voltage [V]
0.0	11.929
0.5	11.930
1.0	11.930
2.0	11.930
3.0	11.930
4.0	11.930
5.0	11.931
6.0	11.931
7.0	11.931
8.0	11.931


**COSEL**

Model	MMC100B-1	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	-12V1A																							
1.Graph		2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.055</td></tr> <tr><td>0.5</td><td>-12.088</td></tr> <tr><td>1.0</td><td>-12.088</td></tr> <tr><td>2.0</td><td>-12.088</td></tr> <tr><td>3.0</td><td>-12.088</td></tr> <tr><td>4.0</td><td>-12.088</td></tr> <tr><td>5.0</td><td>-12.088</td></tr> <tr><td>6.0</td><td>-12.088</td></tr> <tr><td>7.0</td><td>-12.088</td></tr> <tr><td>8.0</td><td>-12.088</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	-12.055	0.5	-12.088	1.0	-12.088	2.0	-12.088	3.0	-12.088	4.0	-12.088	5.0	-12.088	6.0	-12.088	7.0	-12.088	8.0	-12.088
Time since start [H]	Output Voltage [V]																							
0.0	-12.055																							
0.5	-12.088																							
1.0	-12.088																							
2.0	-12.088																							
3.0	-12.088																							
4.0	-12.088																							
5.0	-12.088																							
6.0	-12.088																							
7.0	-12.088																							
8.0	-12.088																							

**COSEL**


Model	MMC100B-1	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V13A		

## 1. Graph



## 2. Values

Load \ Time	Td	Tr	Ts	Th	Tf	[ms]
50 %	87.8	16.0	103.8	88.0	22.3	
100 %	87.5	16.0	103.5	38.3	13.3	




**COSEL**

Model	MMC100B-1
Item	Rise and Fall Time
Object	+12V2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		87.5	16.0	103.5	96.3	20.3	
100 %		87.5	16.3	103.8	44.8	10.3	



COSEL


Model MMC100B-1

Item Rise and Fall Time

Object -12V1A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		88.0	2.3	90.3	96.5	43.0	
100 %		88.0	2.8	90.8	44.5	23.8	




**COSEL**

Model MMC100B-1

Item Hold-Up Time

Object +5V13A

## 1. Graph

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	28	9
80	38	14
85	48	19
90	60	24
100	84	36
110	112	50
120	141	65
132	181	84
140	210	99

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

Model	MMC100B-1
Item	Hold-Up Time
Object	+12V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	40	17
80	50	22
85	60	27
90	72	33
100	96	45
110	124	58
120	154	73
132	194	93
140	223	107

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model MMC100B-1

Item Hold-Up Time

Object -12V1A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
75	40	16
80	50	21
85	60	26
90	72	31
100	96	43
110	124	57
120	154	72
132	193	92
140	222	106

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
 Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MMC100B-1
Item	Instantaneous Interruption Compensation
Object	+5V13A



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Time [ms]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	-	-	-
2.0	58	97	204
4.0	46	79	166
6.0	37	65	140
8.0	30	55	120
10.0	26	47	104
12.0	22	40	91
13.0	20	38	86
14.3	18	35	80
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

# COSEL

Model	MMC100B-1	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+12V2A																																																					
1.Graph	<p>—△— Input Volt. 85V        - - -□- - Input Volt. 100V        - - ○ - - Input Volt. 132V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>31</td><td>56</td><td>115</td></tr> <tr><td>0.8</td><td>31</td><td>53</td><td>107</td></tr> <tr><td>1.2</td><td>30</td><td>48</td><td>103</td></tr> <tr><td>1.6</td><td>28</td><td>47</td><td>98</td></tr> <tr><td>2.0</td><td>25</td><td>44</td><td>92</td></tr> <tr><td>2.2</td><td>22</td><td>43</td><td>90</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	0.4	31	56	115	0.8	31	53	107	1.2	30	48	103	1.6	28	47	98	2.0	25	44	92	2.2	22	43	90	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																			
0.0	-	-	-																																																			
0.4	31	56	115																																																			
0.8	31	53	107																																																			
1.2	30	48	103																																																			
1.6	28	47	98																																																			
2.0	25	44	92																																																			
2.2	22	43	90																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					


**COSEL**

Model	MMC100B-1	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Instantaneous Interruption Compensation																																																						
Object	-12V1A																																																						
1.Graph	<p>—△— Input Volt. 85V        - - □ - - Input Volt. 100V        - - ○ - - Input Volt. 132V</p>																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.2</td><td>31</td><td>48</td><td>105</td></tr> <tr><td>0.4</td><td>30</td><td>48</td><td>101</td></tr> <tr><td>0.6</td><td>29</td><td>47</td><td>98</td></tr> <tr><td>0.8</td><td>27</td><td>46</td><td>96</td></tr> <tr><td>1.0</td><td>26</td><td>44</td><td>92</td></tr> <tr><td>1.1</td><td>23</td><td>43</td><td>90</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	-	-	-	0.2	31	48	105	0.4	30	48	101	0.6	29	47	98	0.8	27	46	96	1.0	26	44	92	1.1	23	43	90	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																				
0.0	-	-	-																																																				
0.2	31	48	105																																																				
0.4	30	48	101																																																				
0.6	29	47	98																																																				
0.8	27	46	96																																																				
1.0	26	44	92																																																				
1.1	23	43	90																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

**COSEL**

Model	MMC100B-1
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V13A

## 1.Graph




Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	61	67
-10	61	67
0	61	67
10	61	67
20	61	66
25	61	67
30	61	67
40	61	67
50	61	70
60	61	69
--	-	-

Object	+12V2A
--------	--------

## 1.Graph



## 2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	60	63
-10	57	63
0	57	63
10	58	63
20	57	63
25	58	63
30	57	63
40	57	63
50	57	62
60	57	62
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MMC100B-1
Item	Minimum Input Voltage for Regulated Output Voltage
Object	-12V1A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	59	62
-10	56	62
0	56	62
10	56	62
20	56	62
25	56	62
30	56	62
40	56	62
50	56	61
60	56	61
--	-	-

**COSEL**


Model MMC100B-1

Item Overcurrent Protection

Object +5V13A

1.Graph

— Input Volt. 85V  
 — Input Volt. 100V  
 - - - Input Volt. 132V

Temperature 25°C  
Testing Circuitry Figure A


2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
4.75	17.88	18.20	18.86
4.50	17.92	18.21	18.84
4.00	17.93	18.21	18.90
3.50	17.83	18.19	18.74
3.00	18.77	19.01	19.58
2.50	19.78	20.09	20.79
2.00	20.85	21.13	21.92
1.50	21.79	22.17	22.96
1.00	22.81	23.13	24.08
0.50	23.73	24.12	25.05
0.00	24.68	24.99	25.80
--	-	-	-

Object +12V2A

1.Graph

— Input Volt. 85V  
 — Input Volt. 100V  
 - - - Input Volt. 132V



2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
11.40	4.60	4.72	4.97
10.80	4.80	4.91	5.18
9.60	5.18	5.31	5.61
8.40	5.58	5.72	6.08
7.20	6.03	6.18	6.52
6.00	6.46	6.61	6.96
4.80	6.90	7.05	7.46
3.60	7.39	7.54	7.91
2.40	7.83	7.98	8.34
1.20	8.24	8.42	8.78
0.00	8.75	8.99	9.67
--	-	-	-


Note: Slanted line shows the range of the rated load current.

**COSEL**

Model MMC100B-1

Item Overcurrent Protection

Object -12V1A



Note: Slanted line shows the range of the rated load current.


Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
-11.40	3.02	3.12	3.26
-10.80	2.67	2.61	2.63
-9.60	3.42	3.03	2.93
-8.40	3.06	2.76	2.72
-7.20	2.71	2.57	2.55
-6.00	2.53	2.42	2.40
-4.80	2.36	2.29	2.28
-3.60	2.06	1.89	1.86
-2.40	1.71	1.61	1.59
-1.20	1.49	1.42	1.41
0.00	1.31	1.26	1.25
--	-	-	-

Model	MMC100B-1
Item	Oversupply Protection
Object	+5V13A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 85[V]	Input Volt. 132[V]
-20	6.27	6.27
-10	6.27	6.27
0	6.27	6.27
10	6.27	6.27
20	6.27	6.27
25	6.27	6.27
30	6.27	6.27
40	6.27	6.27
50	6.27	6.27
60	6.27	6.26
--	-	-

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)