

TEST DATA OF MUS1R51205

Regulated DC Power Supply
February 4, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9

(Final Page 9)

COSEL

Model	MUS1R51205																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 9V - - ■ - - Input Volt. 12V - · ○ - · Input Volt. 18V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.006</td><td>0.005</td><td>0.004</td></tr> <tr> <td>0.06</td><td>0.040</td><td>0.031</td><td>0.023</td></tr> <tr> <td>0.12</td><td>0.080</td><td>0.060</td><td>0.041</td></tr> <tr> <td>0.18</td><td>0.113</td><td>0.090</td><td>0.061</td></tr> <tr> <td>0.24</td><td>0.159</td><td>0.115</td><td>0.080</td></tr> <tr> <td>0.30</td><td>0.191</td><td>0.149</td><td>0.100</td></tr> <tr> <td>0.33</td><td>0.220</td><td>0.159</td><td>0.108</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	0.006	0.005	0.004	0.06	0.040	0.031	0.023	0.12	0.080	0.060	0.041	0.18	0.113	0.090	0.061	0.24	0.159	0.115	0.080	0.30	0.191	0.149	0.100	0.33	0.220	0.159	0.108	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	0.006	0.005	0.004																																																			
0.06	0.040	0.031	0.023																																																			
0.12	0.080	0.060	0.041																																																			
0.18	0.113	0.090	0.061																																																			
0.24	0.159	0.115	0.080																																																			
0.30	0.191	0.149	0.100																																																			
0.33	0.220	0.159	0.108																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model	MUS1R51205	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 9V - - ■ - - Input Volt. 12V - · ○ - · Input Volt. 18V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.06</td><td>76.8</td><td>75.1</td><td>69.3</td></tr> <tr> <td>0.12</td><td>82.0</td><td>82.0</td><td>77.9</td></tr> <tr> <td>0.18</td><td>84.3</td><td>83.2</td><td>81.3</td></tr> <tr> <td>0.24</td><td>84.2</td><td>84.1</td><td>81.7</td></tr> <tr> <td>0.30</td><td>84.2</td><td>84.2</td><td>83.7</td></tr> <tr> <td>0.33</td><td>84.1</td><td>84.2</td><td>83.3</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-	-	-	0.06	76.8	75.1	69.3	0.12	82.0	82.0	77.9	0.18	84.3	83.2	81.3	0.24	84.2	84.1	81.7	0.30	84.2	84.2	83.7	0.33	84.1	84.2	83.3	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	-	-	-																																																			
0.06	76.8	75.1	69.3																																																			
0.12	82.0	82.0	77.9																																																			
0.18	84.3	83.2	81.3																																																			
0.24	84.2	84.1	81.7																																																			
0.30	84.2	84.2	83.7																																																			
0.33	84.1	84.2	83.3																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MUS1R51205
Item	Line Regulation
Object	+5V0.3A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph





2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8	5.097	5.098
9	5.097	5.098
10	5.097	5.098
12	5.097	5.098
15	5.097	5.098
18	5.097	5.098
20	5.097	5.098
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MUS1R51205	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+5V0.3A																																																					
1.Graph	<p>—▲— Input Volt. 9V - - □ - - Input Volt. 12V - - ○ - - Input Volt. 18V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5.098</td><td>5.098</td><td>5.098</td></tr> <tr><td>0.06</td><td>5.098</td><td>5.098</td><td>5.097</td></tr> <tr><td>0.12</td><td>5.098</td><td>5.097</td><td>5.097</td></tr> <tr><td>0.18</td><td>5.098</td><td>5.097</td><td>5.097</td></tr> <tr><td>0.24</td><td>5.097</td><td>5.097</td><td>5.097</td></tr> <tr><td>0.30</td><td>5.097</td><td>5.097</td><td>5.097</td></tr> <tr><td>0.33</td><td>5.098</td><td>5.097</td><td>5.097</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	5.098	5.098	5.098	0.06	5.098	5.098	5.097	0.12	5.098	5.097	5.097	0.18	5.098	5.097	5.097	0.24	5.097	5.097	5.097	0.30	5.097	5.097	5.097	0.33	5.098	5.097	5.097	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	5.098	5.098	5.098																																																			
0.06	5.098	5.098	5.097																																																			
0.12	5.098	5.097	5.097																																																			
0.18	5.098	5.097	5.097																																																			
0.24	5.097	5.097	5.097																																																			
0.30	5.097	5.097	5.097																																																			
0.33	5.098	5.097	5.097																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+5V0.3A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 12V Load 100%</p>  <p>10[mV/div]</p> <p>2[μs/div]</p>																																																					

COSEL

Model	MUS1R51205	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+5V0.3A	

Input Volt.

12 V

Cycle

1000 ms

Load Current

Response. $t_1=t_2=50\mu s$. TypLoad 0%(0A) \longleftrightarrow
Load 100%(0.3A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.15A) \longleftrightarrow
Load 100%(0.3A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUS1R51205
Item	Rise and Fall Time
Object	+5V0.3A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.6	2.7	3.3	0.1	1.6	
100 %		0.6	3.2	3.8	0.1	0.5	



COSEL

Model	MUS1R51205
Item	Overcurrent Protection
Object	+5V0.3A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
4.75	0.48	0.52	0.55
4.50	0.50	0.54	0.57
4.00	0.54	0.58	0.61
3.50	0.58	0.62	0.66
3.00	0.62	0.67	0.71
2.50	0.68	0.72	0.77
2.00	0.74	0.79	0.83
1.50	0.82	0.86	0.90
1.00	0.90	0.94	0.98
0.50	1.00	1.03	1.06
0.00	1.14	1.15	1.17
--	-	-	-



Model	MUS1R51205	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+5V0.3A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 9V	Input Volt. 12V	Input Volt. 18V
-40	5.059	5.060	5.061
25	5.098	5.099	5.099
85	5.103	5.103	5.103

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V0.3A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	7.2	7.3
25	7.3	7.1
85	7.2	7.2

COSEL




Figure A


Measuring board C1=1 μ F(Ceramic Capacitor)

Figure B