

TEST DATA OF MUS1R51215

Regulated DC Power Supply
February 4, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9

(Final Page 9)

COSEL

Model	MUS1R51215																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	<p style="text-align: center;"> —△— Input Volt. 9V ---□--- Input Volt. 12V ---○--- Input Volt. 18V </p>	2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="3">Input Current [A]</th></tr> <tr> <th>Input Volt. 9[V]</th><th>Input Volt. 12[V]</th><th>Input Volt. 18[V]</th></tr> </thead> <tbody> <tr><td>0.00</td><td>0.011</td><td>0.009</td><td>0.007</td></tr> <tr><td>0.02</td><td>0.042</td><td>0.034</td><td>0.024</td></tr> <tr><td>0.04</td><td>0.080</td><td>0.062</td><td>0.043</td></tr> <tr><td>0.06</td><td>0.112</td><td>0.084</td><td>0.060</td></tr> <tr><td>0.08</td><td>0.153</td><td>0.117</td><td>0.078</td></tr> <tr><td>0.10</td><td>0.185</td><td>0.140</td><td>0.096</td></tr> <tr><td>0.11</td><td>0.210</td><td>0.159</td><td>0.107</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	0.011	0.009	0.007	0.02	0.042	0.034	0.024	0.04	0.080	0.062	0.043	0.06	0.112	0.084	0.060	0.08	0.153	0.117	0.078	0.10	0.185	0.140	0.096	0.11	0.210	0.159	0.107	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	0.011	0.009	0.007																																																			
0.02	0.042	0.034	0.024																																																			
0.04	0.080	0.062	0.043																																																			
0.06	0.112	0.084	0.060																																																			
0.08	0.153	0.117	0.078																																																			
0.10	0.185	0.140	0.096																																																			
0.11	0.210	0.159	0.107																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	MUS1R51215																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.02</td><td>72.2</td><td>67.4</td><td>65.0</td></tr> <tr> <td>0.04</td><td>80.4</td><td>78.5</td><td>75.5</td></tr> <tr> <td>0.06</td><td>83.3</td><td>83.8</td><td>79.0</td></tr> <tr> <td>0.08</td><td>84.6</td><td>84.2</td><td>83.5</td></tr> <tr> <td>0.10</td><td>85.3</td><td>84.9</td><td>83.6</td></tr> <tr> <td>0.11</td><td>85.5</td><td>85.3</td><td>83.8</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-	-	-	0.02	72.2	67.4	65.0	0.04	80.4	78.5	75.5	0.06	83.3	83.8	79.0	0.08	84.6	84.2	83.5	0.10	85.3	84.9	83.6	0.11	85.5	85.3	83.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	-	-	-																																																			
0.02	72.2	67.4	65.0																																																			
0.04	80.4	78.5	75.5																																																			
0.06	83.3	83.8	79.0																																																			
0.08	84.6	84.2	83.5																																																			
0.10	85.3	84.9	83.6																																																			
0.11	85.5	85.3	83.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MUS1R51215																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V0.1A																																	
1.Graph																																		
		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8</td><td>14.965</td><td>14.965</td></tr> <tr> <td>9</td><td>14.966</td><td>14.965</td></tr> <tr> <td>10</td><td>14.966</td><td>14.965</td></tr> <tr> <td>12</td><td>14.966</td><td>14.965</td></tr> <tr> <td>15</td><td>14.966</td><td>14.966</td></tr> <tr> <td>18</td><td>14.966</td><td>14.965</td></tr> <tr> <td>20</td><td>14.966</td><td>14.966</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8	14.965	14.965	9	14.966	14.965	10	14.966	14.965	12	14.966	14.965	15	14.966	14.966	18	14.966	14.965	20	14.966	14.966	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8	14.965	14.965																																
9	14.966	14.965																																
10	14.966	14.965																																
12	14.966	14.965																																
15	14.966	14.966																																
18	14.966	14.965																																
20	14.966	14.966																																
--	-	-																																
--	-	-																																

COSEL

Model	MUS1R51215	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V0.1A																																																					
1.Graph	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>14.968</td><td>14.968</td><td>14.969</td></tr> <tr><td>0.02</td><td>14.967</td><td>14.967</td><td>14.967</td></tr> <tr><td>0.04</td><td>14.966</td><td>14.966</td><td>14.966</td></tr> <tr><td>0.06</td><td>14.966</td><td>14.966</td><td>14.966</td></tr> <tr><td>0.08</td><td>14.965</td><td>14.965</td><td>14.965</td></tr> <tr><td>0.10</td><td>14.965</td><td>14.965</td><td>14.965</td></tr> <tr><td>0.11</td><td>14.965</td><td>14.965</td><td>14.965</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	14.968	14.968	14.969	0.02	14.967	14.967	14.967	0.04	14.966	14.966	14.966	0.06	14.966	14.966	14.966	0.08	14.965	14.965	14.965	0.10	14.965	14.965	14.965	0.11	14.965	14.965	14.965	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																			
0.00	14.968	14.968	14.969																																																			
0.02	14.967	14.967	14.967																																																			
0.04	14.966	14.966	14.966																																																			
0.06	14.966	14.966	14.966																																																			
0.08	14.965	14.965	14.965																																																			
0.10	14.965	14.965	14.965																																																			
0.11	14.965	14.965	14.965																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+15V0.1A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 12V Load 100%</p> <p>10[mV/div]</p> <p>2[μs/div]</p>																																																					

COSEL

Model	MUS1R51215	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V0.1A	

Input Volt.



12 V

Response. $t_1=t_2=50\mu s$. Typ

Cycle

1000 ms

Load Current

Load 0%(0A) \longleftrightarrow
Load 100%(0.1A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.05A) \longleftrightarrow
Load 100%(0.1A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUS1R51215
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.7	3.7	4.4	0.1	2.7
100 %		0.7	4.5	5.2	0.1	0.9



COSEL

Model	MUS1R51215
Item	Overcurrent Protection
Object	+15V0.1A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]
14.25	0.17	0.19	0.20
13.50	0.18	0.19	0.20
12.00	0.19	0.21	0.22
10.50	0.21	0.22	0.24
9.00	0.22	0.24	0.26
7.50	0.24	0.26	0.28
6.00	0.27	0.28	0.30
4.50	0.29	0.31	0.32
3.00	0.33	0.34	0.35
1.50	0.36	0.37	0.38
0.00	0.41	0.42	0.42
--	-	-	-



Model	MUS1R51215	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+15V0.1A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 9V	Input Volt. 12V	Input Volt. 18V
-40	14.870	14.871	14.872
25	14.965	14.966	14.966
85	14.990	14.990	14.990

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+15V0.1A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	7.2	7.3
25	7.2	7.2
85	7.3	7.5

COSEL




Figure A




Figure B