

# TEST DATA OF MUS1R52415

Regulated DC Power Supply  
February 4, 2025

Approved by : Kenichi Tsukada  
Design Manager

Prepared by : Soichiro Kawaguchi  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Load Current) . . . . .	1
2.Efficiency (by Load Current) . . . . .	2
3.Line Regulation . . . . .	3
4.Load Regulation . . . . .	4
5.Ripple-Noise . . . . .	4
6.Dynamic Load Response . . . . .	5
7.Rise and Fall Time . . . . .	6
8.Overcurrent Protection . . . . .	7
9.Ambient Temperature Drift . . . . .	8
10.Minimum Input Voltage for Regulated Output Voltage . . . . .	8
11.Figure of Testing Circuitry . . . . .	9

(Final Page 9)

**COSEL**

Model	MUS1R52415																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph	<p style="text-align: center;"> <span style="color: black;">—△—</span> Input Volt. 18V  <span style="color: black;">---□---</span> Input Volt. 24V  <span style="color: black;">---○---</span> Input Volt. 36V         </p>	2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.006</td><td>0.005</td><td>0.004</td></tr> <tr> <td>0.02</td><td>0.027</td><td>0.022</td><td>0.015</td></tr> <tr> <td>0.04</td><td>0.043</td><td>0.032</td><td>0.026</td></tr> <tr> <td>0.06</td><td>0.064</td><td>0.047</td><td>0.032</td></tr> <tr> <td>0.08</td><td>0.081</td><td>0.063</td><td>0.042</td></tr> <tr> <td>0.10</td><td>0.101</td><td>0.076</td><td>0.052</td></tr> <tr> <td>0.11</td><td>0.111</td><td>0.084</td><td>0.058</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.006	0.005	0.004	0.02	0.027	0.022	0.015	0.04	0.043	0.032	0.026	0.06	0.064	0.047	0.032	0.08	0.081	0.063	0.042	0.10	0.101	0.076	0.052	0.11	0.111	0.084	0.058	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.006	0.005	0.004																																																			
0.02	0.027	0.022	0.015																																																			
0.04	0.043	0.032	0.026																																																			
0.06	0.064	0.047	0.032																																																			
0.08	0.081	0.063	0.042																																																			
0.10	0.101	0.076	0.052																																																			
0.11	0.111	0.084	0.058																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**


Model	MUS1R52415																																																					
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.02</td><td>63.5</td><td>57.4</td><td>57.9</td></tr> <tr> <td>0.04</td><td>77.0</td><td>78.0</td><td>65.8</td></tr> <tr> <td>0.06</td><td>77.9</td><td>79.0</td><td>77.7</td></tr> <tr> <td>0.08</td><td>80.6</td><td>79.5</td><td>79.9</td></tr> <tr> <td>0.10</td><td>82.1</td><td>81.2</td><td>78.8</td></tr> <tr> <td>0.11</td><td>82.5</td><td>81.7</td><td>79.7</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.02	63.5	57.4	57.9	0.04	77.0	78.0	65.8	0.06	77.9	79.0	77.7	0.08	80.6	79.5	79.9	0.10	82.1	81.2	78.8	0.11	82.5	81.7	79.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.02	63.5	57.4	57.9																																																			
0.04	77.0	78.0	65.8																																																			
0.06	77.9	79.0	77.7																																																			
0.08	80.6	79.5	79.9																																																			
0.10	82.1	81.2	78.8																																																			
0.11	82.5	81.7	79.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	MUS1R52415
Item	Line Regulation
Object	+15V0.1A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph





## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	14.985	14.985
18	14.985	14.985
20	14.985	14.985
24	14.985	14.985
30	14.985	14.985
36	14.986	14.985
40	14.986	14.986
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MUS1R52415	Temperature	25°C	
Item	Load Regulation	Testing Circuitry	Figure A	
Object	+15V0.1A	2. Values		
1. Graph	<p>—△— Input Volt. 18V        - - -□- - Input Volt. 24V        - - -○- - Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>			
	<p>Note: Slanted line shows the range of the rated load current.</p>			
Item	Ripple-Noise	Temperature	25°C	
Object	+15V0.1A	Testing Circuitry	Figure B	
1. Graph	<p>Input Voltage 24V        Load 100%</p>  <p>10[mV/div]</p> <p>2[μs/div]</p>			

**COSEL**

Model	MUS1R52415	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V0.1A	

Input Volt. 24 V Response.  $t_1=t_2=50\mu\text{s}$ . Typ

Cycle 1000 ms

Load 0%(0A)  $\longleftrightarrow$   
Load 100%(0.1A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.05A)  $\longleftrightarrow$   
Load 100%(0.1A)

200[mV/div]

1[ms/div]


1[ms/div]

**COSEL**

Model	MUS1R52415
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	3.7	4.4	0.2	2.6	
100 %		0.7	4.7	5.4	0.1	0.9	



**COSEL**

Model	MUS1R52415	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+15V0.1A																																																									
1.Graph	<p>— Input Volt. 18V            — Input Volt. 24V            — Input Volt. 36V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>14.25</td><td>0.15</td><td>0.17</td><td>0.19</td></tr> <tr><td>13.50</td><td>0.16</td><td>0.17</td><td>0.19</td></tr> <tr><td>12.00</td><td>0.17</td><td>0.19</td><td>0.21</td></tr> <tr><td>10.50</td><td>0.19</td><td>0.20</td><td>0.23</td></tr> <tr><td>9.00</td><td>0.20</td><td>0.22</td><td>0.25</td></tr> <tr><td>7.50</td><td>0.22</td><td>0.24</td><td>0.26</td></tr> <tr><td>6.00</td><td>0.24</td><td>0.26</td><td>0.29</td></tr> <tr><td>4.50</td><td>0.27</td><td>0.29</td><td>0.31</td></tr> <tr><td>3.00</td><td>0.30</td><td>0.32</td><td>0.34</td></tr> <tr><td>1.50</td><td>0.33</td><td>0.35</td><td>0.35</td></tr> <tr><td>0.00</td><td>0.37</td><td>0.37</td><td>0.40</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	14.25	0.15	0.17	0.19	13.50	0.16	0.17	0.19	12.00	0.17	0.19	0.21	10.50	0.19	0.20	0.23	9.00	0.20	0.22	0.25	7.50	0.22	0.24	0.26	6.00	0.24	0.26	0.29	4.50	0.27	0.29	0.31	3.00	0.30	0.32	0.34	1.50	0.33	0.35	0.35	0.00	0.37	0.37	0.40	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
14.25	0.15	0.17	0.19																																																							
13.50	0.16	0.17	0.19																																																							
12.00	0.17	0.19	0.21																																																							
10.50	0.19	0.20	0.23																																																							
9.00	0.20	0.22	0.25																																																							
7.50	0.22	0.24	0.26																																																							
6.00	0.24	0.26	0.29																																																							
4.50	0.27	0.29	0.31																																																							
3.00	0.30	0.32	0.34																																																							
1.50	0.33	0.35	0.35																																																							
0.00	0.37	0.37	0.40																																																							
--	-	-	-																																																							



Model	MUS1R52415	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+15V0.1A	

## 1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	14.881	14.882	14.883
25	14.984	14.984	14.985
85	15.020	15.020	15.021

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+15V0.1A	

## 1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	14.0	14.0
25	14.1	14.1
85	14.0	14.0

**COSEL**




Figure A




Figure B