

TEST DATA OF MUS1R5243R3

Regulated DC Power Supply
February 4, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS


1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9

(Final Page 9)

COSEL

Model	MUS1R5243R3																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	<p style="text-align: center;"> —△— Input Volt. 18V ---□--- Input Volt. 24V ---○--- Input Volt. 36V </p>	2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.003</td><td>0.002</td><td>0.002</td></tr> <tr> <td>0.08</td><td>0.021</td><td>0.018</td><td>0.014</td></tr> <tr> <td>0.16</td><td>0.041</td><td>0.030</td><td>0.021</td></tr> <tr> <td>0.24</td><td>0.057</td><td>0.045</td><td>0.031</td></tr> <tr> <td>0.32</td><td>0.077</td><td>0.058</td><td>0.041</td></tr> <tr> <td>0.40</td><td>0.094</td><td>0.072</td><td>0.049</td></tr> <tr> <td>0.44</td><td>0.105</td><td>0.078</td><td>0.054</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.003	0.002	0.002	0.08	0.021	0.018	0.014	0.16	0.041	0.030	0.021	0.24	0.057	0.045	0.031	0.32	0.077	0.058	0.041	0.40	0.094	0.072	0.049	0.44	0.105	0.078	0.054	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.003	0.002	0.002																																																			
0.08	0.021	0.018	0.014																																																			
0.16	0.041	0.030	0.021																																																			
0.24	0.057	0.045	0.031																																																			
0.32	0.077	0.058	0.041																																																			
0.40	0.094	0.072	0.049																																																			
0.44	0.105	0.078	0.054																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						



COSEL

Model	MUS1R5243R3																																																					
Item	Efficiency (by Load Current)																																																					
Object	<hr/>																																																					
1.Graph																																																						
—△— Input Volt. 18V - -□--- Input Volt. 24V - -○--- Input Volt. 36V																																																						
																																																						
Note: Slanted line shows the range of the rated load current.																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.08</td><td>68.8</td><td>59.9</td><td>53.1</td></tr> <tr> <td>0.16</td><td>72.5</td><td>73.3</td><td>69.6</td></tr> <tr> <td>0.24</td><td>75.5</td><td>73.9</td><td>71.0</td></tr> <tr> <td>0.32</td><td>76.9</td><td>75.7</td><td>72.9</td></tr> <tr> <td>0.40</td><td>77.3</td><td>76.6</td><td>74.4</td></tr> <tr> <td>0.44</td><td>77.5</td><td>76.9</td><td>75.0</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.08	68.8	59.9	53.1	0.16	72.5	73.3	69.6	0.24	75.5	73.9	71.0	0.32	76.9	75.7	72.9	0.40	77.3	76.6	74.4	0.44	77.5	76.9	75.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.08	68.8	59.9	53.1																																																			
0.16	72.5	73.3	69.6																																																			
0.24	75.5	73.9	71.0																																																			
0.32	76.9	75.7	72.9																																																			
0.40	77.3	76.6	74.4																																																			
0.44	77.5	76.9	75.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	MUS1R5243R3																																		
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																	
Object	+3.3V0.4A																																		
1.Graph																																			
		2.Values																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>16</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>18</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>20</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>24</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>30</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>36</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>40</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	16	3.347	3.347	18	3.347	3.347	20	3.347	3.347	24	3.347	3.347	30	3.347	3.347	36	3.347	3.347	40	3.347	3.347	--	-	-	--	-	-	
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
16	3.347	3.347																																	
18	3.347	3.347																																	
20	3.347	3.347																																	
24	3.347	3.347																																	
30	3.347	3.347																																	
36	3.347	3.347																																	
40	3.347	3.347																																	
--	-	-																																	
--	-	-																																	

COSEL


Model	MUS1R5243R3	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+3.3V0.4A																																																					
1.Graph	<p>—▲— Input Volt. 18V - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>3.348</td> <td>3.348</td> <td>3.348</td> </tr> <tr> <td>0.08</td> <td>3.348</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>0.16</td> <td>3.347</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>0.24</td> <td>3.347</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>0.32</td> <td>3.347</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>0.40</td> <td>3.347</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>0.44</td> <td>3.347</td> <td>3.347</td> <td>3.347</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	3.348	3.348	3.348	0.08	3.348	3.347	3.347	0.16	3.347	3.347	3.347	0.24	3.347	3.347	3.347	0.32	3.347	3.347	3.347	0.40	3.347	3.347	3.347	0.44	3.347	3.347	3.347	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	3.348	3.348	3.348																																																			
0.08	3.348	3.347	3.347																																																			
0.16	3.347	3.347	3.347																																																			
0.24	3.347	3.347	3.347																																																			
0.32	3.347	3.347	3.347																																																			
0.40	3.347	3.347	3.347																																																			
0.44	3.347	3.347	3.347																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+3.3V0.4A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 24V Load 100%</p>  <p>10[mV/div]</p> <p>2[μs/div]</p>																																																					

COSEL

Model	MUS1R5243R3	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+3.3V0.4A	

Input Volt. 24 V

Cycle 1000 ms

Response. $t_1=t_2=50\mu s$. TypLoad 0%(0A) \longleftrightarrow
Load 100%(0.4A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.2A) \longleftrightarrow
Load 100%(0.4A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUS1R5243R3
Item	Rise and Fall Time
Object	+3.3V0.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		0.6	1.9	2.5	0.1	0.7
100 %		0.6	2.9	3.5	0.1	0.3





Model	MUS1R5243R3	Temperature Testing Circuitry Figure A	25°C																																																							
Item	Overcurrent Protection																																																									
Object	+3.3V0.4A																																																									
1.Graph	<p style="text-align: center;"> — Input Volt. 18V — Input Volt. 24V — Input Volt. 36V </p>  <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																								
			<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>3.14</td><td>0.58</td><td>0.63</td><td>0.70</td></tr> <tr><td>2.97</td><td>0.56</td><td>0.61</td><td>0.68</td></tr> <tr><td>2.64</td><td>0.63</td><td>0.68</td><td>0.75</td></tr> <tr><td>2.31</td><td>0.67</td><td>0.72</td><td>0.79</td></tr> <tr><td>1.98</td><td>0.70</td><td>0.76</td><td>0.83</td></tr> <tr><td>1.65</td><td>0.75</td><td>0.81</td><td>0.89</td></tr> <tr><td>1.32</td><td>0.81</td><td>0.86</td><td>0.94</td></tr> <tr><td>0.99</td><td>0.86</td><td>0.92</td><td>0.98</td></tr> <tr><td>0.66</td><td>0.93</td><td>0.98</td><td>1.03</td></tr> <tr><td>0.33</td><td>1.00</td><td>1.04</td><td>1.08</td></tr> <tr><td>0.00</td><td>1.09</td><td>1.10</td><td>1.11</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	3.14	0.58	0.63	0.70	2.97	0.56	0.61	0.68	2.64	0.63	0.68	0.75	2.31	0.67	0.72	0.79	1.98	0.70	0.76	0.83	1.65	0.75	0.81	0.89	1.32	0.81	0.86	0.94	0.99	0.86	0.92	0.98	0.66	0.93	0.98	1.03	0.33	1.00	1.04	1.08	0.00	1.09	1.10	1.11	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
3.14	0.58	0.63	0.70																																																							
2.97	0.56	0.61	0.68																																																							
2.64	0.63	0.68	0.75																																																							
2.31	0.67	0.72	0.79																																																							
1.98	0.70	0.76	0.83																																																							
1.65	0.75	0.81	0.89																																																							
1.32	0.81	0.86	0.94																																																							
0.99	0.86	0.92	0.98																																																							
0.66	0.93	0.98	1.03																																																							
0.33	1.00	1.04	1.08																																																							
0.00	1.09	1.10	1.11																																																							
--	-	-	-																																																							



Model	MUS1R5243R3	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+3.3V0.4A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	3.329	3.329	3.329
25	3.347	3.347	3.347
85	3.349	3.349	3.349

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+3.3V0.4A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	13.8	13.8
25	13.8	13.9
85	13.8	13.9

COSEL




Figure A




Figure B