



Ref. Certif. No.

**JP-27978-A1-UL**

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product

DC-DC Converter

Name and address of the applicant

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI TOYAMA-SHI TOYAMA 930-0816  
JAPAN

Name and address of the manufacturer

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI TOYAMA-SHI Toyama 930-0816  
JAPAN

Name and address of the factory

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI TOYAMA-SHI Toyama 930-0816  
JAPAN

Note: When more than one factory, please report on page 2

☐ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

See Page 2

Additional information (if necessary may also be reported on page 2)

The report was revised to include corrections.  
Additionally evaluated to EN IEC 62368-1:2020/A11:2020  
National Differences specified in the CB Test Report.

☒ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

E132067-A6193-CB-1 issued on 2025-03-11

This CB Test Certificate is issued by the National Certification Body



☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA  
☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK  
☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN  
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2025-03-11

Original Issue Date: 2025-02-27

Signature:

*M. Takagi*  
Masamichi Takagi



Ref. Certif. No.

JP-27978-A1-UL

**Model Detail(s):**

MUx3yz, MUx1R5yz,

"x" = S or W, "y" = 05, 12, 24 or 48, "z" = 3R3, 05, 12, 15 (when "x" = W, "z" is 12 or 15). May be provided with suffix "&-\$#". ("&" = any letter A to Z or blank, "\$" = G, R (model MUx1R5yz only) or blank, "#" represents one or more digits of any alphanumeric characters 0 to 9 or A to Z or blank.)

**Ratings:**

Input Ratings: MUS1R5053R3: 4.5 - 9 VDC/ 0.38 A maximum, MUS1R50505 and MUS1R50515: 4.5 - 9 VDC/ 0.41 A maximum, MUS1R50512: 4.5 - 9 VDC/ 0.43 A maximum, MUS1R5123R3: 9 - 18 VDC/ 0.20 A maximum, MUS1R51205 and MUS1R51215: 9 - 18 VDC/ 0.21 A maximum, MUS1R51212: 9 - 18 VDC/ 0.22 A maximum, MUS1R5243R3: 18 - 36 VDC/ 0.10 A maximum, MUS1R52405, MUS1R52412 and MUS1R52415: 18 - 36 VDC/ 0.11 A maximum, MUS1R5483R3, MUS1R54805, MUS1R54812 and MUS1R54815: 36- 76 VDC/ 0.06 A maximum

MUW1R50512: 4.5 - 9 VDC/ 0.43 A maximum, MUW1R50515: 4.5 - 9 VDC/ 0.42 A maximum, MUW1R51212: 9 - 18 VDC/ 0.22 A maximum, MUW1R51215: 9 - 18 VDC/ 0.21 A maximum, MUW1R52412 and MUW1R52415: 18 - 36 VDC/ 0.11 A maximum, MUW1R54812 and MUW1R54815: 36- 76 VDC/ 0.06 A maximum

MUS3053R3: 4.5 - 9 VDC/ 0.56 A maximum, MUS30505: 4.5 - 9 VDC/ 0.81 A maximum, MUS30512: 4.5 - 9 VDC/ 0.80 A maximum, MUS30515: 4.5 - 9 VDC/ 0.79 A maximum, MUS3123R3: 9 - 18 VDC/ 0.28 A maximum, MUS31205 and MUS31212: 9 - 18 VDC/ 0.40 A maximum, MUS31215: 9 - 18 VDC/ 0.39 A maximum, MUS3243R3: 18 - 36 VDC/ 0.15 A maximum, MUS32405: 18 - 36 VDC/ 0.21 A maximum, MUS32412 and MUS32415: 18 - 36 VDC/ 0.20 A maximum, MUS3483R3: 36- 76 VDC/ 0.08 A maximum, MUS34805: 36- 76 VDC/ 0.11 A maximum, MUS34812 and MUS34815: 36- 76 VDC/ 0.10 A maximum

MUW30512: 4.5 - 9 VDC/ 0.84 A maximum, MUW30515: 4.5 - 9 VDC/ 0.81 A maximum, MUW31212: 9 - 18 VDC/ 0.42 A maximum, MUW31215: 9 - 18 VDC/ 0.40 A maximum, MUW32412: 18 - 36 VDC/ 0.22 A maximum, MUW32415: 18 - 36 VDC/ 0.21 A maximum, MUW34812 and MUW34815: 36- 76 VDC/ 0.11 A maximum

Output Ratings: See test report for details.

**Summary of Modifications:**

[1] Correction of typo error in Input Ratings in CB Test Report ref. E132067-A6193-CB-1 (Original) from "60 VDC" to "76 VDC".;  
[2] Correction of typo error Page 72 of 118 in Table 5.4.1.4, 9.3, B.1.5, B.2.6 in CB Test Report ref. E132067-A6193-CB-1 (Original) from "12V" to "24V".

**Additional information (if necessary)**

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA  
☐ UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK  
☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN  
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2025-03-11

Original Issue Date: 2025-02-27

Signature:

Masamichi Takagi



Ref. Certif. No.

**JP-27978-UL**

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

**CB TEST CERTIFICATE**

Product

DC-DC Converter

Name and address of the applicant

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI  
TOYAMA-SHI  
TOYAMA 930-0816  
JAPAN

Name and address of the manufacturer

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI  
TOYAMA-SHI  
Toyama 930-0816  
JAPAN

Name and address of the factory

COSEL CO LTD  
1-6-43 KAMIAKAE-MACHI  
TOYAMA-SHI  
Toyama 930-0816  
JAPAN

*Note: When more than one factory, please report on page 2*

☐ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

CTF Stage 2

Model / Type Ref.

See Page 2

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to EN IEC 62368-1:2020/A11:2020  
National Differences specified in the CB Test Report.  
☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

E132067-A6193-CB-1 issued on 2025-02-27

This CB Test Certificate is issued by the National Certification Body



☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA  
☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK  
☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN  
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2025-02-27

Signature:

*M. Takagi*  
Masamichi Takagi



Ref. Certif. No.

JP-27978-UL

**Model Detail(s):**

MUx1R5yz, MUx3yz, "x" = S or W, "y" = 05, 12, 24 or 48, "z" = 3R3, 05, 12, 15 (when "x" = W, "z" is 12 or 15). May be provided with suffix "&-\$#". ("&" = any letter A to Z or blank, "\$" = G, R (model MUx1R5yz only) or blank, "#" represents one or more digits of any alphanumeric characters 0 to 9 or A to Z or blank.)

**Ratings:**

Input Ratings: MUS1R5053R3: 4.5 - 9 VDC/ 0.38 A maximum, MUS1R50505 and MUS1R50515: 4.5 - 9 VDC/ 0.41 A maximum, MUS1R50512: 4.5 - 9 VDC/ 0.43 A maximum, MUS1R5123R3: 9 - 18 VDC/ 0.20 A maximum, MUS1R51205 and MUS1R51215: 9 - 18 VDC/ 0.21 A maximum, MUS1R51212: 9 - 18 VDC/ 0.22 A maximum, MUS1R5243R3: 18 - 36 VDC/ 0.10 A maximum, MUS1R52405, MUS1R52412 and MUS1R52415: 18 - 36 VDC/ 0.11 A maximum, MUS1R5483R3, MUS1R54805, MUS1R54812 and MUS1R54815: 36- 60 VDC/ 0.06 A maximum  
MUW1R50512: 4.5 - 9 VDC/ 0.43 A maximum, MUW1R50515: 4.5 - 9 VDC/ 0.42 A maximum, MUW1R51212: 9 - 18 VDC/ 0.22 A maximum, MUW1R51215: 9 - 18 VDC/ 0.21 A maximum, MUW1R52412 and MUW1R52415: 18 - 36 VDC/ 0.11 A maximum, MUW1R54812 and MUW1R54815: 36- 60 VDC/ 0.06 A maximum  
MUS3053R3: 4.5 - 9 VDC/ 0.56 A maximum, MUS30505: 4.5 - 9 VDC/ 0.81 A maximum, MUS30512: 4.5 - 9 VDC/ 0.80 A maximum, MUS30515: 4.5 - 9 VDC/ 0.79 A maximum, MUS3123R3: 9 - 18 VDC/ 0.28 A maximum, MUS31205 and MUS31212: 9 - 18 VDC/ 0.40 A maximum, MUS31215: 9 - 18 VDC/ 0.39 A maximum, MUS3243R3: 18 - 36 VDC/ 0.15 A maximum, MUS32405: 18 - 36 VDC/ 0.21 A maximum, MUS32412 and MUS32415: 18 - 36 VDC/ 0.20 A maximum, MUS3483R3: 36- 60 VDC/ 0.08 A maximum, MUS34805: 36- 60 VDC/ 0.11 A maximum, MUS34812 and MUS34815: 36- 60 VDC/ 0.10 A maximum  
MUW30512: 4.5 - 9 VDC/ 0.84 A maximum, MUW30515: 4.5 - 9 VDC/ 0.81 A maximum, MUW31212: 9 - 18 VDC/ 0.42 A maximum, MUW31215: 9 - 18 VDC/ 0.40 A maximum, MUW32412: 18 - 36 VDC/ 0.22 A maximum, MUW32415: 18 - 36 VDC/ 0.21 A maximum, MUW34812 and MUW34815: 36- 60 VDC/ 0.11 A maximum  
Output Ratings: See test report for details.

**Additional information (if necessary)**

☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA  
☐ UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK  
☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN  
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2025-02-27

Signature:

Masamichi Takagi