

TEST DATA OF MUS3053R3

Regulated DC Power Supply
February 3, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9


(Final Page 9)

COSEL

Model	MUS3053R3	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.004</td><td>0.004</td><td>0.008</td></tr> <tr><td>0.12</td><td>0.112</td><td>0.104</td><td>0.064</td></tr> <tr><td>0.24</td><td>0.205</td><td>0.197</td><td>0.117</td></tr> <tr><td>0.36</td><td>0.327</td><td>0.290</td><td>0.171</td></tr> <tr><td>0.48</td><td>0.429</td><td>0.388</td><td>0.227</td></tr> <tr><td>0.60</td><td>0.551</td><td>0.494</td><td>0.280</td></tr> <tr><td>0.66</td><td>0.598</td><td>0.547</td><td>0.309</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	0.004	0.004	0.008	0.12	0.112	0.104	0.064	0.24	0.205	0.197	0.117	0.36	0.327	0.290	0.171	0.48	0.429	0.388	0.227	0.60	0.551	0.494	0.280	0.66	0.598	0.547	0.309	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	0.004	0.004	0.008																																																			
0.12	0.112	0.104	0.064																																																			
0.24	0.205	0.197	0.117																																																			
0.36	0.327	0.290	0.171																																																			
0.48	0.429	0.388	0.227																																																			
0.60	0.551	0.494	0.280																																																			
0.66	0.598	0.547	0.309																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	MUS3053R3
Item	Efficiency (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	-	-	-
0.12	76.8	76.2	68.6
0.24	79.8	79.5	75.0
0.36	80.6	80.2	77.0
0.48	80.0	80.3	78.4
0.60	79.8	79.9	79.0
0.66	79.5	79.7	78.7
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MUS3053R3																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+3.3V0.6A																																	
1. Graph																																		
		2. Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>4.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>4.5</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>5.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>6.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>7.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>8.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>9.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>10.0</td> <td>3.351</td> <td>3.351</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.0	3.351	3.351	4.5	3.351	3.351	5.0	3.351	3.351	6.0	3.351	3.351	7.0	3.351	3.351	8.0	3.351	3.351	9.0	3.351	3.351	10.0	3.351	3.351	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.0	3.351	3.351																																
4.5	3.351	3.351																																
5.0	3.351	3.351																																
6.0	3.351	3.351																																
7.0	3.351	3.351																																
8.0	3.351	3.351																																
9.0	3.351	3.351																																
10.0	3.351	3.351																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		


COSEL

Model	MUS3053R3	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+3.3V0.6A																																																					
1.Graph	<p style="text-align: center;"> —△— Input Volt. 4.5V - - □ - - Input Volt. 5V - - ○ - - Input Volt. 9V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
	<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.350</td><td>3.352</td><td>3.351</td></tr> <tr><td>0.12</td><td>3.352</td><td>3.351</td><td>3.351</td></tr> <tr><td>0.24</td><td>3.351</td><td>3.351</td><td>3.351</td></tr> <tr><td>0.36</td><td>3.351</td><td>3.351</td><td>3.351</td></tr> <tr><td>0.48</td><td>3.351</td><td>3.351</td><td>3.351</td></tr> <tr><td>0.60</td><td>3.351</td><td>3.351</td><td>3.351</td></tr> <tr><td>0.66</td><td>3.351</td><td>3.351</td><td>3.351</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	3.350	3.352	3.351	0.12	3.352	3.351	3.351	0.24	3.351	3.351	3.351	0.36	3.351	3.351	3.351	0.48	3.351	3.351	3.351	0.60	3.351	3.351	3.351	0.66	3.351	3.351	3.351	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	3.350	3.352	3.351																																																			
0.12	3.352	3.351	3.351																																																			
0.24	3.351	3.351	3.351																																																			
0.36	3.351	3.351	3.351																																																			
0.48	3.351	3.351	3.351																																																			
0.60	3.351	3.351	3.351																																																			
0.66	3.351	3.351	3.351																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+3.3V0.6A	Testing Circuitry	Figure B																																																			
1.Graph	<p style="text-align: center;"> Input Voltage 5V Load 100% </p> <p>10[mV/div]</p> <p>2[μs/div]</p>																																																					

COSEL

Model	MUS3053R3	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+3.3V0.6A		

Input Volt. 5 V Response. $t_1=t_2=50\mu s$. Typ
Cycle 1000 ms



Load 0%(0A) \longleftrightarrow
Load 100%(0.6A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.3A) \longleftrightarrow
Load 100%(0.6A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUS3053R3
Item	Rise and Fall Time
Object	+3.3V0.6A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.3	2.7	4.0	0.2	1.0	
100 %		1.5	3.4	4.9	0.1	0.4	



COSEL

Model	MUS3053R3	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+3.3V0.6A																																																									
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V</p>																																																									
	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr> <td>3.14</td><td>1.06</td><td>1.09</td><td>1.11</td></tr> <tr> <td>2.97</td><td>1.09</td><td>1.12</td><td>1.14</td></tr> <tr> <td>2.64</td><td>1.16</td><td>1.19</td><td>1.22</td></tr> <tr> <td>2.31</td><td>1.25</td><td>1.27</td><td>1.31</td></tr> <tr> <td>1.98</td><td>1.34</td><td>1.37</td><td>1.41</td></tr> <tr> <td>1.65</td><td>1.44</td><td>1.47</td><td>1.51</td></tr> <tr> <td>1.32</td><td>1.56</td><td>1.59</td><td>1.63</td></tr> <tr> <td>0.99</td><td>1.69</td><td>1.72</td><td>1.76</td></tr> <tr> <td>0.66</td><td>1.84</td><td>1.86</td><td>1.89</td></tr> <tr> <td>0.33</td><td>2.01</td><td>2.03</td><td>2.04</td></tr> <tr> <td>0.00</td><td>2.27</td><td>2.29</td><td>2.23</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	3.14	1.06	1.09	1.11	2.97	1.09	1.12	1.14	2.64	1.16	1.19	1.22	2.31	1.25	1.27	1.31	1.98	1.34	1.37	1.41	1.65	1.44	1.47	1.51	1.32	1.56	1.59	1.63	0.99	1.69	1.72	1.76	0.66	1.84	1.86	1.89	0.33	2.01	2.03	2.04	0.00	2.27	2.29	2.23	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																							
3.14	1.06	1.09	1.11																																																							
2.97	1.09	1.12	1.14																																																							
2.64	1.16	1.19	1.22																																																							
2.31	1.25	1.27	1.31																																																							
1.98	1.34	1.37	1.41																																																							
1.65	1.44	1.47	1.51																																																							
1.32	1.56	1.59	1.63																																																							
0.99	1.69	1.72	1.76																																																							
0.66	1.84	1.86	1.89																																																							
0.33	2.01	2.03	2.04																																																							
0.00	2.27	2.29	2.23																																																							
--	-	-	-																																																							



Model	MUS3053R3	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+3.3V0.6A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 4.5V	Input Volt. 5V	Input Volt. 9V
-40	3.334	3.335	3.335
25	3.352	3.352	3.352
85	3.351	3.350	3.350

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+3.3V0.6A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	3.2	3.2
25	3.1	3.0
85	3.1	3.1

COSEL




Figure A




Figure B