

TEST DATA OF MUS32405

Regulated DC Power Supply
February 3, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Figure of Testing Circuitry	9

(Final Page 9)

COSEL

Model	MUS32405																																																					
Item	Input Current (by Load Current)																																																					
Object	_____																																																					
1.Graph																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.007</td><td>0.004</td><td>0.002</td></tr> <tr> <td>0.12</td><td>0.045</td><td>0.033</td><td>0.024</td></tr> <tr> <td>0.24</td><td>0.082</td><td>0.062</td><td>0.044</td></tr> <tr> <td>0.36</td><td>0.123</td><td>0.093</td><td>0.062</td></tr> <tr> <td>0.48</td><td>0.164</td><td>0.123</td><td>0.083</td></tr> <tr> <td>0.60</td><td>0.205</td><td>0.154</td><td>0.103</td></tr> <tr> <td>0.66</td><td>0.226</td><td>0.169</td><td>0.113</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	0.007	0.004	0.002	0.12	0.045	0.033	0.024	0.24	0.082	0.062	0.044	0.36	0.123	0.093	0.062	0.48	0.164	0.123	0.083	0.60	0.205	0.154	0.103	0.66	0.226	0.169	0.113	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	0.007	0.004	0.002																																																			
0.12	0.045	0.033	0.024																																																			
0.24	0.082	0.062	0.044																																																			
0.36	0.123	0.093	0.062																																																			
0.48	0.164	0.123	0.083																																																			
0.60	0.205	0.154	0.103																																																			
0.66	0.226	0.169	0.113																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


Model	MUS32405	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph	<p>—▲— Input Volt. 18V - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [18V] (%)</th> <th>Efficiency [24V] (%)</th> <th>Efficiency [36V] (%)</th> </tr> </thead> <tbody> <tr><td>0.12</td><td>74.0</td><td>75.2</td><td>68.7</td></tr> <tr><td>0.24</td><td>82.8</td><td>82.4</td><td>76.1</td></tr> <tr><td>0.36</td><td>82.6</td><td>82.5</td><td>82.4</td></tr> <tr><td>0.48</td><td>82.9</td><td>82.8</td><td>82.2</td></tr> <tr><td>0.60</td><td>82.8</td><td>83.0</td><td>82.3</td></tr> <tr><td>0.66</td><td>82.7</td><td>83.0</td><td>82.4</td></tr> </tbody> </table>			Load Current [A]	Efficiency [18V] (%)	Efficiency [24V] (%)	Efficiency [36V] (%)	0.12	74.0	75.2	68.7	0.24	82.8	82.4	76.1	0.36	82.6	82.5	82.4	0.48	82.9	82.8	82.2	0.60	82.8	83.0	82.3	0.66	82.7	83.0	82.4																							
Load Current [A]	Efficiency [18V] (%)	Efficiency [24V] (%)	Efficiency [36V] (%)																																																			
0.12	74.0	75.2	68.7																																																			
0.24	82.8	82.4	76.1																																																			
0.36	82.6	82.5	82.4																																																			
0.48	82.9	82.8	82.2																																																			
0.60	82.8	83.0	82.3																																																			
0.66	82.7	83.0	82.4																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.12</td><td>74.0</td><td>75.2</td><td>68.7</td></tr> <tr><td>0.24</td><td>82.8</td><td>82.4</td><td>76.1</td></tr> <tr><td>0.36</td><td>82.6</td><td>82.5</td><td>82.4</td></tr> <tr><td>0.48</td><td>82.9</td><td>82.8</td><td>82.2</td></tr> <tr><td>0.60</td><td>82.8</td><td>83.0</td><td>82.3</td></tr> <tr><td>0.66</td><td>82.7</td><td>83.0</td><td>82.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	0.12	74.0	75.2	68.7	0.24	82.8	82.4	76.1	0.36	82.6	82.5	82.4	0.48	82.9	82.8	82.2	0.60	82.8	83.0	82.3	0.66	82.7	83.0	82.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.00	-	-	-																																																			
0.12	74.0	75.2	68.7																																																			
0.24	82.8	82.4	76.1																																																			
0.36	82.6	82.5	82.4																																																			
0.48	82.9	82.8	82.2																																																			
0.60	82.8	83.0	82.3																																																			
0.66	82.7	83.0	82.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MUS32405
Item	Line Regulation
Object	+5V0.6A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph





2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	5.111	5.111
18	5.111	5.111
20	5.111	5.111
24	5.111	5.111
30	5.111	5.111
36	5.111	5.111
40	5.111	5.111
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MUS32405	Temperature	25°C	
Item	Load Regulation	Testing Circuitry	Figure A	
Object	+5V0.6A			
1.Graph	<p>—△— Input Volt. 18V - - - □ - - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>			
	<p>Note: Slanted line shows the range of the rated load current.</p>			
Item	Ripple-Noise	Temperature	25°C	
Object	+5V0.6A	Testing Circuitry	Figure B	
1.Graph	<p>Input Voltage 24V Load 100%</p>  <p>10[mV/div]</p> <p>2[μs/div]</p>			

COSEL

Model	MUS32405	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	+5V0.6A		

Input Volt.

24 V

Response. $t_1=t_2=50\mu\text{s}$. Typ

Cycle

100 ms

Load Current

Load 0%(0A) \longleftrightarrow
Load 100%(0.6A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.3A) \longleftrightarrow
Load 100%(0.6A)

200[mV/div]


1[ms/div]

1[ms/div]

COSEL


Model	MUS32405	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V0.6A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.1	3.0	4.1	0.1	1.6	
100 %		1.1	3.6	4.7	0.1	0.5	



COSEL

Model	MUS32405	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+5V0.6A																																																									
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																									
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>4.75</td><td>0.85</td><td>0.89</td><td>0.91</td></tr> <tr> <td>4.50</td><td>0.82</td><td>0.87</td><td>0.88</td></tr> <tr> <td>4.00</td><td>0.94</td><td>0.99</td><td>1.01</td></tr> <tr> <td>3.50</td><td>1.01</td><td>1.06</td><td>1.08</td></tr> <tr> <td>3.00</td><td>1.08</td><td>1.14</td><td>1.16</td></tr> <tr> <td>2.50</td><td>1.18</td><td>1.23</td><td>1.26</td></tr> <tr> <td>2.00</td><td>1.28</td><td>1.33</td><td>1.36</td></tr> <tr> <td>1.50</td><td>1.40</td><td>1.45</td><td>1.46</td></tr> <tr> <td>1.00</td><td>1.54</td><td>1.58</td><td>1.58</td></tr> <tr> <td>0.50</td><td>1.71</td><td>1.73</td><td>1.70</td></tr> <tr> <td>0.00</td><td>1.95</td><td>1.94</td><td>1.85</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	4.75	0.85	0.89	0.91	4.50	0.82	0.87	0.88	4.00	0.94	0.99	1.01	3.50	1.01	1.06	1.08	3.00	1.08	1.14	1.16	2.50	1.18	1.23	1.26	2.00	1.28	1.33	1.36	1.50	1.40	1.45	1.46	1.00	1.54	1.58	1.58	0.50	1.71	1.73	1.70	0.00	1.95	1.94	1.85	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
4.75	0.85	0.89	0.91																																																							
4.50	0.82	0.87	0.88																																																							
4.00	0.94	0.99	1.01																																																							
3.50	1.01	1.06	1.08																																																							
3.00	1.08	1.14	1.16																																																							
2.50	1.18	1.23	1.26																																																							
2.00	1.28	1.33	1.36																																																							
1.50	1.40	1.45	1.46																																																							
1.00	1.54	1.58	1.58																																																							
0.50	1.71	1.73	1.70																																																							
0.00	1.95	1.94	1.85																																																							
--	-	-	-																																																							



Model	MUS32405	Testing Circuitry Figure A
Item	Ambient Temperature Drift	
Object	+5V0.6A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	5.090	5.091	5.092
25	5.114	5.114	5.114
85	5.108	5.108	5.108

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+5V0.6A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	13.9	13.9
25	13.9	13.9
85	13.9	13.9

COSEL




Figure A




Figure B