

TEST DATA OF MUW1R52412

Regulated DC Power Supply
February 7, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Cross Regulation	4, 5
5.Ripple-Noise	4, 5
6.Dynamic Load Response	6, 7
7.Rise and Fall Time	8, 9
8.Overcurrent Protection	10
9.Ambient Temperature Drift	11,12
10.Minimum Input Voltage for Regulated Output Voltage	11,12
11.Figure of Testing Circuitry	13

(Final Page 13)

COSEL

Model	MUW1R52412	Temperature	25°C																																																	
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																	
Object																																																				
1.Graph		2.Values																																																		
<p>Graph showing Input Current [A] vs Load Ratio [%] for three input voltages: 18V, 24V, and 36V.</p> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18V [A]</th> <th>24V [A]</th> <th>36V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.009</td><td>0.006</td><td>0.005</td></tr> <tr><td>20</td><td>0.026</td><td>0.022</td><td>0.015</td></tr> <tr><td>40</td><td>0.044</td><td>0.033</td><td>0.026</td></tr> <tr><td>60</td><td>0.064</td><td>0.049</td><td>0.033</td></tr> <tr><td>80</td><td>0.085</td><td>0.064</td><td>0.043</td></tr> <tr><td>100</td><td>0.105</td><td>0.079</td><td>0.054</td></tr> <tr><td>110</td><td>0.113</td><td>0.087</td><td>0.060</td></tr> </tbody> </table>		Load Ratio [%]	18V [A]	24V [A]	36V [A]	0	0.009	0.006	0.005	20	0.026	0.022	0.015	40	0.044	0.033	0.026	60	0.064	0.049	0.033	80	0.085	0.064	0.043	100	0.105	0.079	0.054	110	0.113	0.087	0.060																			
Load Ratio [%]	18V [A]	24V [A]	36V [A]																																																	
0	0.009	0.006	0.005																																																	
20	0.026	0.022	0.015																																																	
40	0.044	0.033	0.026																																																	
60	0.064	0.049	0.033																																																	
80	0.085	0.064	0.043																																																	
100	0.105	0.079	0.054																																																	
110	0.113	0.087	0.060																																																	
<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.009</td><td>0.006</td><td>0.005</td></tr> <tr><td>20</td><td>0.026</td><td>0.022</td><td>0.015</td></tr> <tr><td>40</td><td>0.044</td><td>0.033</td><td>0.026</td></tr> <tr><td>60</td><td>0.064</td><td>0.049</td><td>0.033</td></tr> <tr><td>80</td><td>0.085</td><td>0.064</td><td>0.043</td></tr> <tr><td>100</td><td>0.105</td><td>0.079</td><td>0.054</td></tr> <tr><td>110</td><td>0.113</td><td>0.087</td><td>0.060</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Input Current [A]			18[V]	24[V]	36[V]	0	0.009	0.006	0.005	20	0.026	0.022	0.015	40	0.044	0.033	0.026	60	0.064	0.049	0.033	80	0.085	0.064	0.043	100	0.105	0.079	0.054	110	0.113	0.087	0.060	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Current [A]																																																			
	18[V]	24[V]	36[V]																																																	
0	0.009	0.006	0.005																																																	
20	0.026	0.022	0.015																																																	
40	0.044	0.033	0.026																																																	
60	0.064	0.049	0.033																																																	
80	0.085	0.064	0.043																																																	
100	0.105	0.079	0.054																																																	
110	0.113	0.087	0.060																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

COSEL


Model	MUW1R52412	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<p>Graph showing Efficiency [%] vs Load Ratio [%] for MUW1R52412 at 25°C. The graph plots efficiency against load ratio for three input voltages: 18V (solid line with triangles), 24V (dashed line with squares), and 36V (dash-dot line with circles). Efficiency increases with load ratio and is higher for higher input voltages.</p> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18[V] (%)</th> <th>24[V] (%)</th> <th>36[V] (%)</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>57.0</td> <td>51.4</td> <td>51.2</td> </tr> <tr> <td>40</td> <td>73.0</td> <td>74.7</td> <td>62.7</td> </tr> <tr> <td>60</td> <td>75.2</td> <td>75.3</td> <td>76.1</td> </tr> <tr> <td>80</td> <td>78.2</td> <td>77.0</td> <td>77.0</td> </tr> <tr> <td>100</td> <td>79.8</td> <td>78.9</td> <td>76.8</td> </tr> <tr> <td>110</td> <td>80.3</td> <td>79.7</td> <td>77.8</td> </tr> </tbody> </table>		Load Ratio [%]	18[V] (%)	24[V] (%)	36[V] (%)	20	57.0	51.4	51.2	40	73.0	74.7	62.7	60	75.2	75.3	76.1	80	78.2	77.0	77.0	100	79.8	78.9	76.8	110	80.3	79.7	77.8																									
Load Ratio [%]	18[V] (%)	24[V] (%)	36[V] (%)																																																			
20	57.0	51.4	51.2																																																			
40	73.0	74.7	62.7																																																			
60	75.2	75.3	76.1																																																			
80	78.2	77.0	77.0																																																			
100	79.8	78.9	76.8																																																			
110	80.3	79.7	77.8																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>57.0</td> <td>51.4</td> <td>51.2</td> </tr> <tr> <td>40</td> <td>73.0</td> <td>74.7</td> <td>62.7</td> </tr> <tr> <td>60</td> <td>75.2</td> <td>75.3</td> <td>76.1</td> </tr> <tr> <td>80</td> <td>78.2</td> <td>77.0</td> <td>77.0</td> </tr> <tr> <td>100</td> <td>79.8</td> <td>78.9</td> <td>76.8</td> </tr> <tr> <td>110</td> <td>80.3</td> <td>79.7</td> <td>77.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Ratio [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	57.0	51.4	51.2	40	73.0	74.7	62.7	60	75.2	75.3	76.1	80	78.2	77.0	77.0	100	79.8	78.9	76.8	110	80.3	79.7	77.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	-	-	-																																																			
20	57.0	51.4	51.2																																																			
40	73.0	74.7	62.7																																																			
60	75.2	75.3	76.1																																																			
80	78.2	77.0	77.0																																																			
100	79.8	78.9	76.8																																																			
110	80.3	79.7	77.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	MUW1R52412
Item	Line Regulation
Object	+12V0.065A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	12.094	12.027
18	12.094	12.028
20	12.094	12.028
24	12.093	12.029
30	12.093	12.030
36	12.093	12.030
40	12.094	12.030
--	-	-
--	-	-

-12V:Rated Load Current

Object -12V0.065A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
16	-12.112	-12.052
18	-12.111	-12.052
20	-12.111	-12.051
24	-12.110	-12.051
30	-12.110	-12.050
36	-12.110	-12.051
40	-12.110	-12.051
--	-	-
--	-	-

+12V:Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MUW1R52412	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.065A																																																					
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (18V)</th> <th>Output Voltage [V] (24V)</th> <th>Output Voltage [V] (36V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.20</td><td>12.20</td><td>12.20</td></tr> <tr><td>0.02</td><td>12.15</td><td>12.15</td><td>12.15</td></tr> <tr><td>0.04</td><td>12.12</td><td>12.12</td><td>12.12</td></tr> <tr><td>0.06</td><td>12.08</td><td>12.08</td><td>12.08</td></tr> <tr><td>0.08</td><td>12.05</td><td>12.05</td><td>12.05</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (18V)	Output Voltage [V] (24V)	Output Voltage [V] (36V)	0.00	12.20	12.20	12.20	0.02	12.15	12.15	12.15	0.04	12.12	12.12	12.12	0.06	12.08	12.08	12.08	0.08	12.05	12.05	12.05																											
Load Current [A]	Output Voltage [V] (18V)	Output Voltage [V] (24V)	Output Voltage [V] (36V)																																																			
0.00	12.20	12.20	12.20																																																			
0.02	12.15	12.15	12.15																																																			
0.04	12.12	12.12	12.12																																																			
0.06	12.08	12.08	12.08																																																			
0.08	12.05	12.05	12.05																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.188</td><td>12.189</td><td>12.189</td></tr> <tr><td>0.013</td><td>12.141</td><td>12.140</td><td>12.141</td></tr> <tr><td>0.026</td><td>12.106</td><td>12.106</td><td>12.106</td></tr> <tr><td>0.039</td><td>12.076</td><td>12.076</td><td>12.076</td></tr> <tr><td>0.052</td><td>12.047</td><td>12.048</td><td>12.048</td></tr> <tr><td>0.065</td><td>12.020</td><td>12.022</td><td>12.023</td></tr> <tr><td>0.072</td><td>12.007</td><td>12.009</td><td>12.010</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	12.188	12.189	12.189	0.013	12.141	12.140	12.141	0.026	12.106	12.106	12.106	0.039	12.076	12.076	12.076	0.052	12.047	12.048	12.048	0.065	12.020	12.022	12.023	0.072	12.007	12.009	12.010	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	12.188	12.189	12.189																																																			
0.013	12.141	12.140	12.141																																																			
0.026	12.106	12.106	12.106																																																			
0.039	12.076	12.076	12.076																																																			
0.052	12.047	12.048	12.048																																																			
0.065	12.020	12.022	12.023																																																			
0.072	12.007	12.009	12.010																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note: Slanted line shows the range of the rated load current.																																																						
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+12V0.065A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 24V Load 100%</p> <p>10[mV/div]</p> <p>2[μs/div]</p> <p>-12V:Rated Load Current</p>																																																					

COSEL

Model	MUW1R52412	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	-12V0.065A																																																					
1.Graph	<p>Input Volt. 18V Input Volt. 24V Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.215</td><td>-12.215</td><td>-12.216</td></tr> <tr><td>0.013</td><td>-12.169</td><td>-12.169</td><td>-12.170</td></tr> <tr><td>0.026</td><td>-12.137</td><td>-12.136</td><td>-12.136</td></tr> <tr><td>0.039</td><td>-12.109</td><td>-12.107</td><td>-12.107</td></tr> <tr><td>0.052</td><td>-12.083</td><td>-12.081</td><td>-12.081</td></tr> <tr><td>0.065</td><td>-12.058</td><td>-12.057</td><td>-12.057</td></tr> <tr><td>0.072</td><td>-12.046</td><td>-12.046</td><td>-12.045</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-12.215	-12.215	-12.216	0.013	-12.169	-12.169	-12.170	0.026	-12.137	-12.136	-12.136	0.039	-12.109	-12.107	-12.107	0.052	-12.083	-12.081	-12.081	0.065	-12.058	-12.057	-12.057	0.072	-12.046	-12.046	-12.045	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.000	-12.215	-12.215	-12.216																																																			
0.013	-12.169	-12.169	-12.170																																																			
0.026	-12.137	-12.136	-12.136																																																			
0.039	-12.109	-12.107	-12.107																																																			
0.052	-12.083	-12.081	-12.081																																																			
0.065	-12.058	-12.057	-12.057																																																			
0.072	-12.046	-12.046	-12.045																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	-12V0.065A	Testing Circuitry	Figure B																																																			
1.Graph	<p>Input Voltage 24V Load 100%</p> <p>10[mV/div]</p> <p>2[μs/div]</p> <p>+12V:Rated Load Current</p>																																																					

COSEL

Model	MUW1R52412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.065A		

Input Volt. 24 V

-12V:Rated Load Current

Cycle 1000 ms

Response. $t_1=t_2=50\mu s$. Typ

Load 0%(0A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.0325A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]

1[ms/div]

COSEL

Model	MUW1R52412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.065A		

Input Volt. 24 V

+12V:Rated Load Current

Cycle 1000 ms

Response. $t_1=t_2=50\mu s$. Typ

Load 0%(0A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.0325A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUW1R52412
Item	Rise and Fall Time
Object	+12V0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	6.6	7.3	0.2	3.1	
100 %		0.7	6.9	7.6	0.1	0.9	




COSEL

Model	MUW1R52412
Item	Rise and Fall Time
Object	-12V0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	6.7	7.4	0.2	4.2	
100 %		0.7	6.6	7.3	0.1	1.2	



COSEL

Model	MUW1R52412	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V0.065A																																																									
1.Graph		2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.13</td><td>0.15</td><td>0.17</td></tr> <tr><td>10.8</td><td>0.14</td><td>0.16</td><td>0.18</td></tr> <tr><td>9.6</td><td>0.16</td><td>0.18</td><td>0.20</td></tr> <tr><td>8.4</td><td>0.18</td><td>0.20</td><td>0.23</td></tr> <tr><td>7.2</td><td>0.21</td><td>0.23</td><td>0.26</td></tr> <tr><td>6.0</td><td>0.23</td><td>0.26</td><td>0.28</td></tr> <tr><td>4.8</td><td>0.26</td><td>0.29</td><td>0.32</td></tr> <tr><td>3.6</td><td>0.30</td><td>0.32</td><td>0.35</td></tr> <tr><td>2.4</td><td>0.34</td><td>0.36</td><td>0.38</td></tr> <tr><td>1.2</td><td>0.38</td><td>0.40</td><td>0.42</td></tr> <tr><td>0.0</td><td>0.43</td><td>0.44</td><td>0.44</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	11.4	0.13	0.15	0.17	10.8	0.14	0.16	0.18	9.6	0.16	0.18	0.20	8.4	0.18	0.20	0.23	7.2	0.21	0.23	0.26	6.0	0.23	0.26	0.28	4.8	0.26	0.29	0.32	3.6	0.30	0.32	0.35	2.4	0.34	0.36	0.38	1.2	0.38	0.40	0.42	0.0	0.43	0.44	0.44	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
11.4	0.13	0.15	0.17																																																							
10.8	0.14	0.16	0.18																																																							
9.6	0.16	0.18	0.20																																																							
8.4	0.18	0.20	0.23																																																							
7.2	0.21	0.23	0.26																																																							
6.0	0.23	0.26	0.28																																																							
4.8	0.26	0.29	0.32																																																							
3.6	0.30	0.32	0.35																																																							
2.4	0.34	0.36	0.38																																																							
1.2	0.38	0.40	0.42																																																							
0.0	0.43	0.44	0.44																																																							
--	-	-	-																																																							
Object		-12V:Rated Load Current																																																								
1.Graph		2.Values																																																								
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.14</td><td>0.16</td><td>0.18</td></tr> <tr><td>-10.8</td><td>0.15</td><td>0.17</td><td>0.19</td></tr> <tr><td>-9.6</td><td>0.17</td><td>0.19</td><td>0.22</td></tr> <tr><td>-8.4</td><td>0.19</td><td>0.21</td><td>0.24</td></tr> <tr><td>-7.2</td><td>0.22</td><td>0.24</td><td>0.27</td></tr> <tr><td>-6.0</td><td>0.24</td><td>0.27</td><td>0.29</td></tr> <tr><td>-4.8</td><td>0.27</td><td>0.30</td><td>0.32</td></tr> <tr><td>-3.6</td><td>0.31</td><td>0.33</td><td>0.36</td></tr> <tr><td>-2.4</td><td>0.34</td><td>0.36</td><td>0.39</td></tr> <tr><td>-1.2</td><td>0.39</td><td>0.40</td><td>0.43</td></tr> <tr><td>0.0</td><td>0.44</td><td>0.45</td><td>0.45</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-11.4	0.14	0.16	0.18	-10.8	0.15	0.17	0.19	-9.6	0.17	0.19	0.22	-8.4	0.19	0.21	0.24	-7.2	0.22	0.24	0.27	-6.0	0.24	0.27	0.29	-4.8	0.27	0.30	0.32	-3.6	0.31	0.33	0.36	-2.4	0.34	0.36	0.39	-1.2	0.39	0.40	0.43	0.0	0.44	0.45	0.45	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
-11.4	0.14	0.16	0.18																																																							
-10.8	0.15	0.17	0.19																																																							
-9.6	0.17	0.19	0.22																																																							
-8.4	0.19	0.21	0.24																																																							
-7.2	0.22	0.24	0.27																																																							
-6.0	0.24	0.27	0.29																																																							
-4.8	0.27	0.30	0.32																																																							
-3.6	0.31	0.33	0.36																																																							
-2.4	0.34	0.36	0.39																																																							
-1.2	0.39	0.40	0.43																																																							
0.0	0.44	0.45	0.45																																																							
--	-	-	-																																																							
Object		+12V:Rated Load Current																																																								
Note: Slanted line shows the range of the rated load current.																																																										



Model	MUW1R52412	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V0.065A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	11.951	11.954	11.956
25	12.020	12.022	12.023
85	12.037	12.038	12.039

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V0.065A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	13.9	13.9
25	13.9	13.9
85	13.8	13.9



Model	MUW1R52412	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	-12V0.065A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 18V	Input Volt. 24V	Input Volt. 36V
-40	-11.987	-11.987	-11.987
25	-12.057	-12.056	-12.056
85	-12.077	-12.076	-12.075

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	-12V0.065A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	13.9	13.9
25	14.0	13.9
85	13.8	13.9

COSEL




Figure A




Figure B