

TEST DATA OF MUW1R54812

Regulated DC Power Supply
February 6, 2025

Approved by : Kenichi Tsukada
Design Manager

Prepared by : Soichiro Kawaguchi
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Cross Regulation	4, 5
5.Ripple-Noise	4, 5
6.Dynamic Load Response	6, 7
7.Rise and Fall Time	8, 9
8.Overcurrent Protection	10
9.Ambient Temperature Drift	11,12
10.Minimum Input Voltage for Regulated Output Voltage	11,12
11.Figure of Testing Circuitry	13

(Final Page 13)

COSEL

Model	MUW1R54812	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph		2.Values																																																				
<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.005</td><td>0.003</td><td>0.002</td></tr> <tr><td>20</td><td>0.013</td><td>0.012</td><td>0.008</td></tr> <tr><td>40</td><td>0.023</td><td>0.017</td><td>0.013</td></tr> <tr><td>60</td><td>0.034</td><td>0.025</td><td>0.016</td></tr> <tr><td>80</td><td>0.043</td><td>0.033</td><td>0.021</td></tr> <tr><td>100</td><td>0.053</td><td>0.040</td><td>0.027</td></tr> <tr><td>110</td><td>0.058</td><td>0.044</td><td>0.029</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	0.005	0.003	0.002	20	0.013	0.012	0.008	40	0.023	0.017	0.013	60	0.034	0.025	0.016	80	0.043	0.033	0.021	100	0.053	0.040	0.027	110	0.058	0.044	0.029	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	0.005	0.003	0.002																																																			
20	0.013	0.012	0.008																																																			
40	0.023	0.017	0.013																																																			
60	0.034	0.025	0.016																																																			
80	0.043	0.033	0.021																																																			
100	0.053	0.040	0.027																																																			
110	0.058	0.044	0.029																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL


Model	MUW1R54812	Temperature	25°C																																																		
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																		
Object	_____	_____																																																			
1.Graph		2.Values																																																			
<p>Graph showing Efficiency [%] vs Load Ratio [%] for three input voltages: 36V, 48V, and 76V.</p> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>36V [Efficiency %]</th> <th>48V [Efficiency %]</th> <th>76V [Efficiency %]</th> </tr> </thead> <tbody> <tr> <td>20</td> <td>61.1</td> <td>50.4</td> <td>45.4</td> </tr> <tr> <td>40</td> <td>72.1</td> <td>74.3</td> <td>59.2</td> </tr> <tr> <td>60</td> <td>74.6</td> <td>74.2</td> <td>73.8</td> </tr> <tr> <td>80</td> <td>78.0</td> <td>76.0</td> <td>74.3</td> </tr> <tr> <td>100</td> <td>79.9</td> <td>78.4</td> <td>73.9</td> </tr> <tr> <td>110</td> <td>80.6</td> <td>79.3</td> <td>74.9</td> </tr> </tbody> </table>			Load Ratio [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]	20	61.1	50.4	45.4	40	72.1	74.3	59.2	60	74.6	74.2	73.8	80	78.0	76.0	74.3	100	79.9	78.4	73.9	110	80.6	79.3	74.9																							
Load Ratio [%]	36V [Efficiency %]	48V [Efficiency %]	76V [Efficiency %]																																																		
20	61.1	50.4	45.4																																																		
40	72.1	74.3	59.2																																																		
60	74.6	74.2	73.8																																																		
80	78.0	76.0	74.3																																																		
100	79.9	78.4	73.9																																																		
110	80.6	79.3	74.9																																																		
<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>20</td> <td>61.1</td> <td>50.4</td> <td>45.4</td> </tr> <tr> <td>40</td> <td>72.1</td> <td>74.3</td> <td>59.2</td> </tr> <tr> <td>60</td> <td>74.6</td> <td>74.2</td> <td>73.8</td> </tr> <tr> <td>80</td> <td>78.0</td> <td>76.0</td> <td>74.3</td> </tr> <tr> <td>100</td> <td>79.9</td> <td>78.4</td> <td>73.9</td> </tr> <tr> <td>110</td> <td>80.6</td> <td>79.3</td> <td>74.9</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Ratio [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	61.1	50.4	45.4	40	72.1	74.3	59.2	60	74.6	74.2	73.8	80	78.0	76.0	74.3	100	79.9	78.4	73.9	110	80.6	79.3	74.9	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Efficiency [%]																																																				
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	-	-	-																																																		
20	61.1	50.4	45.4																																																		
40	72.1	74.3	59.2																																																		
60	74.6	74.2	73.8																																																		
80	78.0	76.0	74.3																																																		
100	79.9	78.4	73.9																																																		
110	80.6	79.3	74.9																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

COSEL

Model	MUW1R54812
Item	Line Regulation
Object	+12V0.065A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
30	12.041	11.976
36	12.041	11.977
40	12.040	11.978
48	12.040	11.979
54	12.041	11.980
60	12.040	11.980
70	12.041	11.981
76	12.041	11.980
80	12.041	11.981

-12V:Rated Load Current

1.Graph






2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
30	-12.078	-12.017
36	-12.077	-12.016
40	-12.075	-12.014
48	-12.075	-12.014
54	-12.075	-12.014
60	-12.075	-12.013
70	-12.076	-12.013
76	-12.076	-12.012
80	-12.076	-12.012



+12V:Rated Load Current


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MUW1R54812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.065A																																																					
1.Graph	<p style="text-align: center;">  Input Volt. 36V Input Volt. 48V Input Volt. 76V </p>  <p>Note: Slanted line shows the range of the rated load current.</p>																																																					
2.Values	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.148</td><td>12.148</td><td>12.149</td></tr> <tr><td>0.013</td><td>12.094</td><td>12.094</td><td>12.095</td></tr> <tr><td>0.026</td><td>12.061</td><td>12.061</td><td>12.062</td></tr> <tr><td>0.039</td><td>12.032</td><td>12.032</td><td>12.033</td></tr> <tr><td>0.052</td><td>12.006</td><td>12.006</td><td>12.006</td></tr> <tr><td>0.065</td><td>11.979</td><td>11.981</td><td>11.982</td></tr> <tr><td>0.072</td><td>11.967</td><td>11.969</td><td>11.970</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table> <p style="text-align: right;">-12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.148	12.148	12.149	0.013	12.094	12.094	12.095	0.026	12.061	12.061	12.062	0.039	12.032	12.032	12.033	0.052	12.006	12.006	12.006	0.065	11.979	11.981	11.982	0.072	11.967	11.969	11.970	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	12.148	12.148	12.149																																																			
0.013	12.094	12.094	12.095																																																			
0.026	12.061	12.061	12.062																																																			
0.039	12.032	12.032	12.033																																																			
0.052	12.006	12.006	12.006																																																			
0.065	11.979	11.981	11.982																																																			
0.072	11.967	11.969	11.970																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+12V0.065A	Testing Circuitry	Figure B																																																			
1.Graph	<p style="text-align: center;"> Input Voltage 48V Load 100% </p>  <p>-12V:Rated Load Current</p>																																																					

COSEL

Model	MUW1R54812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	-12V0.065A																																																					
1.Graph	<p style="text-align: center;"> Input Volt. 36V Input Volt. 48V Input Volt. 76V </p>  <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Load Current [A]</p>																																																					
	<p>2.Values</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.168</td><td>-12.168</td><td>-12.169</td></tr> <tr><td>0.013</td><td>-12.125</td><td>-12.126</td><td>-12.126</td></tr> <tr><td>0.026</td><td>-12.091</td><td>-12.090</td><td>-12.091</td></tr> <tr><td>0.039</td><td>-12.063</td><td>-12.061</td><td>-12.062</td></tr> <tr><td>0.052</td><td>-12.037</td><td>-12.035</td><td>-12.035</td></tr> <tr><td>0.065</td><td>-12.012</td><td>-12.011</td><td>-12.010</td></tr> <tr><td>0.072</td><td>-12.000</td><td>-11.999</td><td>-11.998</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table> <p style="text-align: right;">+12V:Rated Load Current</p>			Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.168	-12.168	-12.169	0.013	-12.125	-12.126	-12.126	0.026	-12.091	-12.090	-12.091	0.039	-12.063	-12.061	-12.062	0.052	-12.037	-12.035	-12.035	0.065	-12.012	-12.011	-12.010	0.072	-12.000	-11.999	-11.998	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	-12.168	-12.168	-12.169																																																			
0.013	-12.125	-12.126	-12.126																																																			
0.026	-12.091	-12.090	-12.091																																																			
0.039	-12.063	-12.061	-12.062																																																			
0.052	-12.037	-12.035	-12.035																																																			
0.065	-12.012	-12.011	-12.010																																																			
0.072	-12.000	-11.999	-11.998																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	-12V0.065A	Testing Circuitry	Figure B																																																			
1.Graph	<p style="text-align: center;">Input Voltage 48V Load 100%</p>  <p style="text-align: center;">10[mV/div]</p> <p style="text-align: center;">2[μs/div]</p> <p style="text-align: center;">+12V:Rated Load Current</p>																																																					

COSEL

COSEL


Model	MUW1R54812
Item	Dynamic Load Response
Object	-12V0.065A

Temperature 25°C
Testing Circuitry Figure A

Input Volt. 48 V

+12V:Rated Load Current

Cycle 1000 ms

Load 0%(0A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]

1[ms/div]

Load 50%(0.0325A) \longleftrightarrow
Load 100%(0.065A)

200[mV/div]

1[ms/div]


1[ms/div]

COSEL

Model	MUW1R54812
Item	Rise and Fall Time
Object	+12V0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.0	7.0	9.0	0.1	2.6	
100 %		2.0	7.1	9.1	0.1	0.8	




COSEL

Model	MUW1R54812
Item	Rise and Fall Time
Object	-12V0.065A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.0	7.5	9.5	0.1	5.3	
100 %		2.0	7.6	9.6	0.1	1.2	



COSEL

Model	MUW1R54812	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V0.065A																																																									
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.13</td><td>0.15</td><td>0.17</td></tr> <tr><td>10.8</td><td>0.14</td><td>0.16</td><td>0.18</td></tr> <tr><td>9.6</td><td>0.16</td><td>0.18</td><td>0.21</td></tr> <tr><td>8.4</td><td>0.19</td><td>0.21</td><td>0.24</td></tr> <tr><td>7.2</td><td>0.21</td><td>0.23</td><td>0.26</td></tr> <tr><td>6.0</td><td>0.24</td><td>0.26</td><td>0.29</td></tr> <tr><td>4.8</td><td>0.27</td><td>0.29</td><td>0.33</td></tr> <tr><td>3.6</td><td>0.31</td><td>0.33</td><td>0.36</td></tr> <tr><td>2.4</td><td>0.35</td><td>0.37</td><td>0.39</td></tr> <tr><td>1.2</td><td>0.39</td><td>0.41</td><td>0.43</td></tr> <tr><td>0.0</td><td>0.44</td><td>0.46</td><td>0.45</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	11.4	0.13	0.15	0.17	10.8	0.14	0.16	0.18	9.6	0.16	0.18	0.21	8.4	0.19	0.21	0.24	7.2	0.21	0.23	0.26	6.0	0.24	0.26	0.29	4.8	0.27	0.29	0.33	3.6	0.31	0.33	0.36	2.4	0.35	0.37	0.39	1.2	0.39	0.41	0.43	0.0	0.44	0.46	0.45	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
11.4	0.13	0.15	0.17																																																							
10.8	0.14	0.16	0.18																																																							
9.6	0.16	0.18	0.21																																																							
8.4	0.19	0.21	0.24																																																							
7.2	0.21	0.23	0.26																																																							
6.0	0.24	0.26	0.29																																																							
4.8	0.27	0.29	0.33																																																							
3.6	0.31	0.33	0.36																																																							
2.4	0.35	0.37	0.39																																																							
1.2	0.39	0.41	0.43																																																							
0.0	0.44	0.46	0.45																																																							
--	-	-	-																																																							
Object	-12V0.065A																																																									
1.Graph	<p>Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.15</td><td>0.16</td><td>0.19</td></tr> <tr><td>-10.8</td><td>0.15</td><td>0.17</td><td>0.20</td></tr> <tr><td>-9.6</td><td>0.17</td><td>0.19</td><td>0.22</td></tr> <tr><td>-8.4</td><td>0.20</td><td>0.22</td><td>0.24</td></tr> <tr><td>-7.2</td><td>0.22</td><td>0.24</td><td>0.27</td></tr> <tr><td>-6.0</td><td>0.25</td><td>0.27</td><td>0.30</td></tr> <tr><td>-4.8</td><td>0.28</td><td>0.30</td><td>0.33</td></tr> <tr><td>-3.6</td><td>0.31</td><td>0.33</td><td>0.36</td></tr> <tr><td>-2.4</td><td>0.35</td><td>0.37</td><td>0.39</td></tr> <tr><td>-1.2</td><td>0.39</td><td>0.41</td><td>0.43</td></tr> <tr><td>0.0</td><td>0.44</td><td>0.45</td><td>0.45</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p>			Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-11.4	0.15	0.16	0.19	-10.8	0.15	0.17	0.20	-9.6	0.17	0.19	0.22	-8.4	0.20	0.22	0.24	-7.2	0.22	0.24	0.27	-6.0	0.25	0.27	0.30	-4.8	0.28	0.30	0.33	-3.6	0.31	0.33	0.36	-2.4	0.35	0.37	0.39	-1.2	0.39	0.41	0.43	0.0	0.44	0.45	0.45	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
-11.4	0.15	0.16	0.19																																																							
-10.8	0.15	0.17	0.20																																																							
-9.6	0.17	0.19	0.22																																																							
-8.4	0.20	0.22	0.24																																																							
-7.2	0.22	0.24	0.27																																																							
-6.0	0.25	0.27	0.30																																																							
-4.8	0.28	0.30	0.33																																																							
-3.6	0.31	0.33	0.36																																																							
-2.4	0.35	0.37	0.39																																																							
-1.2	0.39	0.41	0.43																																																							
0.0	0.44	0.45	0.45																																																							
--	-	-	-																																																							
<p>Note: Slanted line shows the range of the rated load current.</p>																																																										



Model	MUW1R54812	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V0.065A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	11.894	11.897	11.898
25	11.980	11.982	11.983
85	12.007	12.009	12.010

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V0.065A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	28.2	28.2
25	28.4	28.4
85	28.4	28.4



Model	MUW1R54812	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	-12V0.065A	

1.Values

Load 100%


Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 36V	Input Volt. 48V	Input Volt. 76V
-40	-11.924	-11.923	-11.923
25	-12.010	-12.010	-12.009
85	-12.041	-12.040	-12.039

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	-12V0.065A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-40	28.2	28.2
25	28.4	28.4
85	28.4	28.4

COSEL



Data Acquisition/Control Unit

Figure A




Figure B