

TEST DATA OF NAC-16-□□□

Noise Filter
Apr. 22. 2005

Approved by : Toshio Watanabe
Toshio Watanabe Design Manager

Prepared by : Tadayuki Noda
Tadayuki Noda Design Engineer


COSEL CO.,LTD.




CONTENTS


1.Attenuation Characteristics	1
2.Pulse Attenuation Characteristics	4
3.Leakage Current	6
4.Figure of Testing Circuitry	7


(Final Page 8)


COSEL

coSEL



COSEL

COSEL

COSEL



Model	NAC-16-□□□	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results


[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
NAC-16-681	UL1283	0.031	0.040	0.082	0.093	
NAC-16-102	UL1283	0.044	0.056	0.110	0.120	
NAC-16-222	UL1283	0.090	0.120	0.230	0.250	
NAC-16-332	UL1283	0.130	0.170	0.340	0.370	
NAC-16-472	UL1283	0.190	0.240	0.480	0.520	

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL




Attenuation = $20\log(U_{01}/U_{02})$ [dB]
 U_{01} : Voltage in state without filters
 U_{02} : Voltage in state which added filters
 N.A. : Network Analyzer

Reference Connection




Test Connection

Figure A - 1 Differential mode attenuation measurement



Attenuation = $20\log(U_{01}/U_{02})$ [dB]
 U_{01} : Voltage in state without filters
 U_{02} : Voltage in state which added filters
 N.A. : Network Analyzer


Reference Connection




Test Connection

Figure A - 2 Common mode attenuation measurement

COSEL



Pulse attenuation measurement



Input impulse waveform



Output impulse waveform

Figure B Pulse attenuation measurement




Figure C Leakage current measurement (UL1283)