





PBA1000F EMI/EMS Test result

 September 16, 2004
 Design engineering dep.

 Approved : *Takahiro Ueno*

 Prepared : *Kazumasa Uetani*

No.	Test item	Conditions	Conditions of Acceptability	Result
1	Line conduction	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	ok
2	Radiated emission	(1) Rated input(AC100V,120V,230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. FCC Part15 classB , VCCI classB CISPR22 classB , EN55022-B	ok
3	Harmonic current (EN61000-3-2)	(1) Rated input (AC100V,230V) (2) Load 0 - Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$	(1)Meets the undermentioned standard. EN61000-3-2 classA	ok
4	Static electricity immunity test (EN61000-4-2)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4) Contact discharge voltage 8[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok
5	Radiated, radio-frequency, electromagnetic field immunity test (EN61000-4-3)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4)Testing field strength 10[V/m] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok
6	Electrical fast transient/ burst immunity test (EN61000-4-4)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4) Test peak voltage 4[kV] (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok
7	Surge immunity test (EN61000-4-5)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4) Test voltage Line to line 2[kV] (Level 3) Line to earth 4[kV] (Level 4)	(1)The power supply is not stop (2)Circuit does not malfunction. (3)No abnormality of the insulation destruction etc. (4)Parts are no damaged.	ok
8	Immunity to conducted disturbances, induced by radio-frequency fields (EN61000-4-6)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4) Voltage level (e.m.f.) 10[V] (Level 3)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok
9	Power frequency magnetic field immunity test (EN61000-4-8)	(1) Rated input (AC230V) (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$ (4) Magnetic field 30A/m (Level 4)	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok
10	Voltage dips, short interruptions and voltage variations immunity test (EN61000-4-11)	(1) Rated input (AC230V) -30% reduction at 10mS min. -60% reduction at 100mS min. -95% reduction at 5S min. - $\pm 10\%$ variation at 15 minutes (2) Rated load (3) Ambient temp. $25\pm 10^{\circ}\text{C}$	(1)No protection circuit failure. (2)No output voltage drop with control circuit failure. (3)No any other function failure	ok

DATA SHEET							Date	10-Feb-04																																																																																																							
Model	PBA1000F-3R3						Temp.	25 degreeC																																																																																																							
Test	EMI Line conduction & Radiated emission						Humid.	45 %RH																																																																																																							
							Tested by	K.Uotani																																																																																																							
LINE CONDUCTION																																																																																																															
Model Name : PBA1000F-3R3				Temp. : 25																																																																																																											
Model No. :				Humi. : 45																																																																																																											
Serial No. :				Date : 2004/2/10 23:03																																																																																																											
Points : 8				Test Equip. : R3132,ESPC																																																																																																											
Detector : PEAK/QP/Ave.				Comment : K.Uotani																																																																																																											
Line Mode : VA/VB				+3.3V 200A																																																																																																											
Power Supply : AC 230V 50Hz																																																																																																															
Limit1: [EN 55022] Class B(QP)																																																																																																															
Limit2: [EN 55022] Class B(Ave.)																																																																																																															
							Limit1(QP) Limit2(Ave.) VA(PEAK) VB(PEAK) VA(QP) VA(Ave.) VB(QP) VB(Ave.)			AC 230V 50Hz +3.3V 200A																																																																																																					
<table><tr><th>Frequency [MHz]</th><th>Meter Reading (Ave.) [dBuV]</th><th>Meter Reading (QP) [dBuV]</th><th>Factor [dB]</th><th>Level(Ave.) [dBuV]</th><th>Level(QP) [dBuV]</th><th>Line</th><th>Limit(Ave.) [dBuV]</th><th>Limit(QP) [dBuV]</th><th>Margin(Ave.) [dB]</th><th>Margin(QP) [dB]</th></tr><tr><td>0.1542</td><td>18.5</td><td>25.3</td><td>9.8</td><td>28.3</td><td>35.1</td><td>VA</td><td>55.8</td><td>65.8</td><td>27.5</td><td>30.7</td></tr><tr><td>0.1981</td><td>31.9</td><td>31.7</td><td>9.8</td><td>41.7</td><td>41.5</td><td>VB</td><td>53.7</td><td>63.7</td><td>12</td><td>22.2</td></tr><tr><td>0.2643</td><td>24.5</td><td>30.8</td><td>9.8</td><td>34.3</td><td>40.6</td><td>VA</td><td>51.3</td><td>61.3</td><td>17</td><td>20.7</td></tr><tr><td>0.3009</td><td>29.1</td><td>29.1</td><td>9.8</td><td>38.9</td><td>38.9</td><td>VB</td><td>50.2</td><td>60.2</td><td>11.3</td><td>21.3</td></tr><tr><td>0.4111</td><td>10.1</td><td>10.9</td><td>9.9</td><td>20</td><td>20.8</td><td>VA</td><td>47.6</td><td>57.6</td><td>27.6</td><td>36.8</td></tr><tr><td>3.4011</td><td>21.6</td><td>21.5</td><td>10</td><td>31.6</td><td>31.5</td><td>VB</td><td>46</td><td>56</td><td>14.4</td><td>24.5</td></tr><tr><td>29.1782</td><td>27.1</td><td>29.1</td><td>10.5</td><td>37.6</td><td>39.6</td><td>VA</td><td>50</td><td>60</td><td>12.4</td><td>20.4</td></tr><tr><td>29.4595</td><td>24.1</td><td>28.4</td><td>10.5</td><td>34.6</td><td>38.9</td><td>VB</td><td>50</td><td>60</td><td>15.4</td><td>21.1</td></tr></table>													Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]	0.1542	18.5	25.3	9.8	28.3	35.1	VA	55.8	65.8	27.5	30.7	0.1981	31.9	31.7	9.8	41.7	41.5	VB	53.7	63.7	12	22.2	0.2643	24.5	30.8	9.8	34.3	40.6	VA	51.3	61.3	17	20.7	0.3009	29.1	29.1	9.8	38.9	38.9	VB	50.2	60.2	11.3	21.3	0.4111	10.1	10.9	9.9	20	20.8	VA	47.6	57.6	27.6	36.8	3.4011	21.6	21.5	10	31.6	31.5	VB	46	56	14.4	24.5	29.1782	27.1	29.1	10.5	37.6	39.6	VA	50	60	12.4	20.4	29.4595	24.1	28.4	10.5	34.6	38.9	VB	50	60	15.4	21.1
Frequency [MHz]	Meter Reading (Ave.) [dBuV]	Meter Reading (QP) [dBuV]	Factor [dB]	Level(Ave.) [dBuV]	Level(QP) [dBuV]	Line	Limit(Ave.) [dBuV]	Limit(QP) [dBuV]	Margin(Ave.) [dB]	Margin(QP) [dB]																																																																																																					
0.1542	18.5	25.3	9.8	28.3	35.1	VA	55.8	65.8	27.5	30.7																																																																																																					
0.1981	31.9	31.7	9.8	41.7	41.5	VB	53.7	63.7	12	22.2																																																																																																					
0.2643	24.5	30.8	9.8	34.3	40.6	VA	51.3	61.3	17	20.7																																																																																																					
0.3009	29.1	29.1	9.8	38.9	38.9	VB	50.2	60.2	11.3	21.3																																																																																																					
0.4111	10.1	10.9	9.9	20	20.8	VA	47.6	57.6	27.6	36.8																																																																																																					
3.4011	21.6	21.5	10	31.6	31.5	VB	46	56	14.4	24.5																																																																																																					
29.1782	27.1	29.1	10.5	37.6	39.6	VA	50	60	12.4	20.4																																																																																																					
29.4595	24.1	28.4	10.5	34.6	38.9	VB	50	60	15.4	21.1																																																																																																					
RADIATED EMISSION																																																																																																															
Model Name : PBA1000F-3R3				Temp. : 25																																																																																																											
Model No. :				Humi. : 45																																																																																																											
Serial No. :				Date : 2004/2/10 23:03																																																																																																											
Points : 1				Test Equip. : R3132,ESPC																																																																																																											
Detector : PEAK/QP				Comment : K.Uotani																																																																																																											
Polarization : Horizontal				+3.3V 200A																																																																																																											
Power Supply : AC 230V 50Hz																																																																																																															
Limit: [EN 55022] Class B<3m>																																																																																																															
							Limit(QP) Horizontal(PEAK) Vertical(PEAK) Horizontal(QP)			AC 230V 50Hz +3.3V 200A																																																																																																					
<table><tr><th>Frequency [MHz]</th><th>MeterReading (QP) [dBuV]</th><th>Ant. Type</th><th>Antenna Factor [dB/m]</th><th>Cable & Preamp [dB]</th><th>Level(QP) [dBuV/m]</th><th>Angle [°]</th><th>Height [cm]</th><th>Polar.</th><th>Limit [dBuV/m]</th><th>Margin [dB]</th></tr><tr><td>173.85</td><td>56.2</td><td>BL</td><td>8.7</td><td>-31.4</td><td>33.5</td><td>192</td><td>160</td><td>Hori.</td><td>40</td><td>6.5</td></tr></table>													Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]	173.85	56.2	BL	8.7	-31.4	33.5	192	160	Hori.	40	6.5																																																																													
Frequency [MHz]	MeterReading (QP) [dBuV]	Ant. Type	Antenna Factor [dB/m]	Cable & Preamp [dB]	Level(QP) [dBuV/m]	Angle [°]	Height [cm]	Polar.	Limit [dBuV/m]	Margin [dB]																																																																																																					
173.85	56.2	BL	8.7	-31.4	33.5	192	160	Hori.	40	6.5																																																																																																					