



EXTRA TEST DATA OF PBA100F-12

Regulated DC Power Supply
Jun, 08, 2020

COSEL CO.,LTD.






CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Ovvervoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Power Consumption (by Input Voltage)	5
6.Figure of Testing Circuitry	6

(Final Page 6)




COSEL

Model	PBA100F-12	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		



COSEL

Model	PBA100F-12	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	_____		




COSEL


Model	PBA100F-12	Temperature 25°C
Item	Over Voltage Protection	Testing Circuitry A
Object	_____	Input Voltage : 100V

Output
Voltage
[2V/div]

GND




Time
[40ms/div]Output
Voltage
[2V/div]

GND

Time
[20ms/div]

COSEL

Model	PBA100F-12	Temperature Testing Circuitry	25°C A
Item	Hiccup cycle (by Overcurrent Protection)		
Object	Load : Short		



COSEL


Model	PBA100F-12
Item	Input voltage - Power consumption
Object	_____

Temperature 25°C
Testing Circuitry -

Load : 0%

2.Values

Input voltage [V]	Power consumption [W]
85	1.21
100	1.02
115	1.04
200	1.24
230	1.39
264	2.25



Reducing standby power is possible by OFF signal of the remote control.




Figure A