



TEST DATA OF PBA100F-48

Regulated DC Power Supply
Apr.5. 2004

Approved by : Kuniaki Nagahara
Kuniaki Nagahara Design Manager

Prepared by : Katsumi Ishikawa
Katsumi Ishikawa Design Engineer

COSEL CO.,LTD.



CONTENTS

| | |
|--|----|
| 1. Input Current (by Load Current) | 1 |
| 2. Input Power (by Load Current) | 2 |
| 3. Efficiency (by Input Voltage) | 3 |
| 4. Efficiency (by Load Current) | 4 |
| 5. Power Factor (by Input Voltage) | 5 |
| 6. Power Factor (by Load Current) | 6 |
| 7. Inrush Current | 7 |
| 8. Leakage Current | 8 |
| 9. Line Regulation | 9 |
| 10. Load Regulation | 10 |
| 11. Dynamic Load Response | 11 |
| 12. Ripple Voltage (by Load Current) | 12 |
| 13. Ripple-Noise | 13 |
| 14. Ripple Voltage (by Ambient Temperature) | 14 |
| 15. Ambient Temperature Drift | 15 |
| 16. Output Voltage Accuracy | 16 |
| 17. Time Lapse Drift | 17 |
| 18. Rise and Fall Time | 18 |
| 19. Hold-Up Time | 19 |
| 20. Instantaneous Interruption Compensation | 20 |
| 21. Minimum Input Voltage for Regulated Output Voltage | 21 |
| 22. Overcurrent Protection | 22 |
| 23. Ovvervoltage Protection | 23 |
| 24. Figure of Testing Circuitry | 24 |


(Final Page 24)

COSEL

| | |
|--------|---------------------------------|
| Model | PBA100F-48 |
| Item | Input Current (by Load Current) |
| Object | _____ |

1. Graph

- △— Input Volt. 100V
- -□-- Input Volt. 200V
- -○-- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values


| Load Current [A] | Input Current [A] | | |
|------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| 0.00 | 0.095 | 0.063 | 0.069 |
| 0.40 | 0.304 | 0.214 | 0.200 |
| 0.80 | 0.509 | 0.314 | 0.296 |
| 1.20 | 0.722 | 0.412 | 0.383 |
| 1.60 | 0.936 | 0.510 | 0.470 |
| 2.00 | 1.150 | 0.610 | 0.554 |
| 2.10 | 1.203 | 0.634 | 0.576 |
| 2.31 | 1.316 | 0.686 | 0.620 |
| — | — | — | — |
| — | — | — | — |
| — | — | — | — |

COSEL

| | |
|--------|-------------------------------|
| Model | PBA100F-48 |
| Item | Input Power (by Load Current) |
| Object | _____ |

1.Graph

—△— Input Volt. 100V
 - - -□- - Input Volt. 200V
 - - -○- - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

| Load Current [A] | Input Power [W] | | |
|------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| 0.00 | 5.2 | 5.1 | 5.2 |
| 0.40 | 28.3 | 29.0 | 29.4 |
| 0.80 | 49.4 | 49.2 | 49.5 |
| 1.20 | 71.2 | 70.1 | 69.9 |
| 1.60 | 92.8 | 90.8 | 90.7 |
| 2.00 | 114.2 | 111.3 | 111.2 |
| 2.10 | 119.5 | 116.5 | 116.3 |
| 2.31 | 130.8 | 127.3 | 127.0 |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |

COSEL

| Model | PBA100F-48 | Temperature | 25°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|-------------------------------|--------------------------|-------------------------|--------------------------|----|------|------|----|------|------|-----|------|------|-----|------|------|-----|------|------|-----|------|------|-----|------|------|-----|------|------|---|---|---|
| Item | Efficiency (by Input Voltage) | Testing Circuitry | Figure A | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | — | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1. Graph | | 2. Values | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Graph showing Efficiency [%] vs Input Voltage [V]. The Y-axis ranges from 44 to 100 in increments of 4. The X-axis ranges from 50 to 300 in increments of 50. Two data series are plotted: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>78.6</td><td>81.4</td></tr> <tr><td>85</td><td>79.8</td><td>83.3</td></tr> <tr><td>100</td><td>80.4</td><td>84.4</td></tr> <tr><td>120</td><td>80.9</td><td>85.2</td></tr> <tr><td>200</td><td>80.7</td><td>86.6</td></tr> <tr><td>230</td><td>80.8</td><td>86.6</td></tr> <tr><td>264</td><td>80.5</td><td>86.8</td></tr> <tr><td>280</td><td>80.8</td><td>86.7</td></tr> <tr><td>—</td><td>-</td><td>-</td></tr> </tbody> </table> | | Input Voltage [V] | Efficiency Load 50% [%] | Efficiency Load 100% [%] | 75 | 78.6 | 81.4 | 85 | 79.8 | 83.3 | 100 | 80.4 | 84.4 | 120 | 80.9 | 85.2 | 200 | 80.7 | 86.6 | 230 | 80.8 | 86.6 | 264 | 80.5 | 86.8 | 280 | 80.8 | 86.7 | — | - | - |
| Input Voltage [V] | Efficiency Load 50% [%] | Efficiency Load 100% [%] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 75 | 78.6 | 81.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 85 | 79.8 | 83.3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 80.4 | 84.4 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | 80.9 | 85.2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | 80.7 | 86.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 230 | 80.8 | 86.6 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 264 | 80.5 | 86.8 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | 80.8 | 86.7 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| — | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Note: Slanted line shows the range of the rated input voltage.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL


Model PBA100F-48

Item Efficiency (by Load Current)

Object _____

1.Graph

—△— Input Volt. 100V
 - -□-- Input Volt. 200V
 - -○-- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2.Values

| Load Current [A] | Efficiency [%] | | |
|------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| 0.00 | - | - | - |
| 0.40 | 67.9 | 66.3 | 65.4 |
| 0.80 | 77.7 | 78.0 | 77.5 |
| 1.20 | 80.8 | 82.1 | 82.3 |
| 1.60 | 82.6 | 84.4 | 84.5 |
| 2.00 | 83.9 | 86.1 | 86.2 |
| 2.10 | 84.2 | 86.4 | 86.6 |
| 2.31 | 84.6 | 87.0 | 87.2 |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |

COSEL

| Model | PBA100F-48 | Temperature | 25°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------------------------|-------------------|------------------|----------------------|--------------|--|----------|-----------|----|-------|-------|----|-------|-------|-----|-------|-------|-----|-------|-------|-----|-------|-------|-----|-------|-------|-----|-------|-------|-----|-------|-------|---|---|---|
| Item | Power Factor (by Input Voltage) | Testing Circuitry | Figure A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | — | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1. Graph | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | 2. Values | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.995</td><td>0.999</td></tr> <tr> <td>85</td><td>0.989</td><td>0.997</td></tr> <tr> <td>100</td><td>0.980</td><td>0.993</td></tr> <tr> <td>120</td><td>0.960</td><td>0.985</td></tr> <tr> <td>200</td><td>0.828</td><td>0.930</td></tr> <tr> <td>230</td><td>0.768</td><td>0.881</td></tr> <tr> <td>264</td><td>0.701</td><td>0.824</td></tr> <tr> <td>280</td><td>0.603</td><td>0.741</td></tr> <tr> <td>—</td><td>—</td><td>—</td></tr> </tbody> </table> | | | | Input Voltage [V] | Power Factor | | Load 50% | Load 100% | 75 | 0.995 | 0.999 | 85 | 0.989 | 0.997 | 100 | 0.980 | 0.993 | 120 | 0.960 | 0.985 | 200 | 0.828 | 0.930 | 230 | 0.768 | 0.881 | 264 | 0.701 | 0.824 | 280 | 0.603 | 0.741 | — | — | — |
| Input Voltage [V] | Power Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Load 50% | Load 100% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 75 | 0.995 | 0.999 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 85 | 0.989 | 0.997 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 0.980 | 0.993 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | 0.960 | 0.985 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | 0.828 | 0.930 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 230 | 0.768 | 0.881 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 264 | 0.701 | 0.824 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | 0.603 | 0.741 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| — | — | — | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Note: Slanted line shows the range of the rated input voltage.</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL


Model PBA100F-48

Item Power Factor (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 -□--- Input Volt. 200V
 -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2. Values




| Load Current [A] | Power Factor | | |
|------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| 0.00 | 0.544 | 0.405 | 0.325 |
| 0.40 | 0.930 | 0.676 | 0.638 |
| 0.80 | 0.969 | 0.782 | 0.725 |
| 1.20 | 0.985 | 0.849 | 0.793 |
| 1.60 | 0.990 | 0.888 | 0.837 |
| 2.00 | 0.992 | 0.919 | 0.871 |
| 2.10 | 0.993 | 0.931 | 0.877 |
| 2.31 | 0.994 | 0.940 | 0.888 |
| — | - | - | - |
| — | - | - | - |
| — | - | - | - |

COSEL

Model PBA100F-48

Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]Input
Voltage
[100V/div]Input
Current
[20A/div]Input
Voltage
[200V/div]



| | | | |
|--------|-----------------|-------------------|----------|
| Model | PBA100F-48 | Temperature | 25°C |
| Item | Leakage Current | Testing Circuitry | Figure B |
| Object | _____ | | |

1. Results

| Standards | | Input Volt. | | | Note |
|-----------|--------------|-------------|---------|---------|-----------|
| | | 100 [V] | 200 [V] | 230 [V] | |
| DEN-AN | Both phases | 0.15 | 0.28 | 0.34 | Operation |
| | One of phase | 0.25 | 0.53 | 0.62 | stand by |
| IEC60950 | Both phases | 0.15 | 0.34 | 0.38 | Operation |
| | One of phase | 0.25 | 0.58 | 0.67 | stand by |

The value for "One phase" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

| Model | PBA100F-48 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--------------------|--|-------------------|--------------------|--|----------|-----------|----|--------|--------|----|--------|--------|-----|--------|--------|-----|--------|--------|-----|--------|--------|-----|--------|--------|-----|--------|--------|-----|--------|--------|---|---|---|
| Item | Line Regulation | Temperature 25°C Testing Circuitry Figure A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | +48V2.1A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p style="text-align: center;">--- □ --- Load 50% — ▲ — Load 100%</p> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: Slanted line shows the range of the rated input voltage. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>48.042</td><td>48.043</td></tr> <tr> <td>85</td><td>48.044</td><td>48.044</td></tr> <tr> <td>100</td><td>48.045</td><td>48.045</td></tr> <tr> <td>120</td><td>48.046</td><td>48.045</td></tr> <tr> <td>200</td><td>48.043</td><td>48.042</td></tr> <tr> <td>230</td><td>48.045</td><td>48.044</td></tr> <tr> <td>264</td><td>48.047</td><td>48.045</td></tr> <tr> <td>280</td><td>48.047</td><td>48.046</td></tr> <tr> <td>-</td><td>-</td><td>-</td></tr> </tbody> </table> | | | Input Voltage [V] | Output Voltage [V] | | Load 50% | Load 100% | 75 | 48.042 | 48.043 | 85 | 48.044 | 48.044 | 100 | 48.045 | 48.045 | 120 | 48.046 | 48.045 | 200 | 48.043 | 48.042 | 230 | 48.045 | 48.044 | 264 | 48.047 | 48.045 | 280 | 48.047 | 48.046 | - | - | - |
| Input Voltage [V] | Output Voltage [V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Load 50% | Load 100% | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 75 | 48.042 | 48.043 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 85 | 48.044 | 48.044 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 100 | 48.045 | 48.045 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 120 | 48.046 | 48.045 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 200 | 48.043 | 48.042 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 230 | 48.045 | 48.044 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 264 | 48.047 | 48.045 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 280 | 48.047 | 48.046 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL

| Model | PBA100F-48 | Temperature | 25°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------------------|--|--------------------|--------------------|------------------|--------------------|--|--|--------------------|--------------------|--------------------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|------|--------|--------|--------|---|---|---|---|---|---|---|---|---|---|---|---|
| Item | Load Regulation | Testing Circuitry | Figure A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Object | +48V2.1A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.Graph | <p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> — □ — Input Volt. 100V - - ○ - - Input Volt. 200V - · Δ - · Input Volt. 230V | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.Values | <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>48.059</td> <td>48.059</td> <td>48.059</td> </tr> <tr> <td>0.40</td> <td>48.054</td> <td>48.055</td> <td>48.054</td> </tr> <tr> <td>0.80</td> <td>48.054</td> <td>48.055</td> <td>48.054</td> </tr> <tr> <td>1.20</td> <td>48.054</td> <td>48.055</td> <td>48.053</td> </tr> <tr> <td>1.60</td> <td>48.054</td> <td>48.055</td> <td>48.053</td> </tr> <tr> <td>2.00</td> <td>48.054</td> <td>48.054</td> <td>48.052</td> </tr> <tr> <td>2.10</td> <td>48.054</td> <td>48.054</td> <td>48.052</td> </tr> <tr> <td>2.31</td> <td>48.054</td> <td>48.053</td> <td>48.051</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> | | | Load Current [A] | Output Voltage [V] | | | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] | 0.00 | 48.059 | 48.059 | 48.059 | 0.40 | 48.054 | 48.055 | 48.054 | 0.80 | 48.054 | 48.055 | 48.054 | 1.20 | 48.054 | 48.055 | 48.053 | 1.60 | 48.054 | 48.055 | 48.053 | 2.00 | 48.054 | 48.054 | 48.052 | 2.10 | 48.054 | 48.054 | 48.052 | 2.31 | 48.054 | 48.053 | 48.051 | - | - | - | - | - | - | - | - | - | - | - | - |
| Load Current [A] | Output Voltage [V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.00 | 48.059 | 48.059 | 48.059 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.40 | 48.054 | 48.055 | 48.054 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.80 | 48.054 | 48.055 | 48.054 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.20 | 48.054 | 48.055 | 48.053 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.60 | 48.054 | 48.055 | 48.053 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.00 | 48.054 | 48.054 | 48.052 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.10 | 48.054 | 48.054 | 48.052 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.31 | 48.054 | 48.053 | 48.051 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| - | - | - | - | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Note: | Slanted line shows the range of the rated load current. | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

COSEL

| | | | |
|--------|-----------------------|-------------------|----------|
| Model | PBA100F-48 | Temperature | 25°C |
| Item | Dynamic Load Response | Testing Circuitry | Figure A |
| Object | +48V2.1A | | |



Input Volt. 100 V
 Cycle 1000 ms

Load Current



Min. Load (0A) ↔

Load 100% (2.1A)




200 mV/div

10 ms/div

10 ms/div


Min. Load (0A) ↔

Load 50% (1.05A)



200 mV/div

10 ms/div



10 ms/div


* The characteristic of AC200V is equal.

COSEL

| | |
|--------|----------------------------------|
| Model | PBA100F-48 |
| Item | Ripple Voltage (by Load Current) |
| Object | +48V2.1A |

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

| Load Current [A] | Ripple Voltage [mV] | |
|------------------|---------------------|---------------------|
| | Input Volt. 100 [V] | Input Volt. 200 [V] |
| 0.00 | 15 | 15 |
| 0.40 | 30 | 30 |
| 0.80 | 35 | 35 |
| 1.20 | 40 | 35 |
| 1.60 | 45 | 40 |
| 2.00 | 45 | 45 |
| 2.10 | 45 | 45 |
| 2.31 | 50 | 50 |
| - | - | - |
| - | - | - |
| - | - | - |

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.



T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL

| | |
|--------|--------------|
| Model | PBA100F-48 |
| Item | Ripple-Noise |
| Object | +48V2.1A |

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

| Load Current [A] | Ripple-Noise [mV] | |
|------------------|---------------------|---------------------|
| | Input Volt. 100 [V] | Input Volt. 200 [V] |
| 0.00 | 65 | 65 |
| 0.40 | 95 | 95 |
| 0.80 | 95 | 95 |
| 1.20 | 100 | 100 |
| 1.60 | 100 | 100 |
| 2.00 | 100 | 100 |
| 2.10 | 100 | 100 |
| 2.31 | 100 | 100 |
| - | - | - |
| - | - | - |
| - | - | - |


T1: Due to AC Input Line
T2: Due to Switching


Fig. Complex Ripple Wave Form

COSEL

| | |
|--------|-----------------------------------|
| Model | PBA100F-48 |
| Item | Ripple Voltage (by Ambient Temp.) |
| Object | +48V2.1A |

1. Graph

---□--- Input Volt. 100V
 —△— Input Volt. 200V




Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

| Ambient Temperature [°C] | Ripple Voltage [mV] | |
|--------------------------|---------------------|---------------------|
| | Input Volt. 100 [V] | Input Volt. 200 [V] |
| -30 | 195 | 195 |
| -10 | 110 | 110 |
| 0 | 80 | 80 |
| 25 | 45 | 45 |
| 50 | 40 | 40 |
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |

COSEL


Testing Circuitry Figure A

2. Values

| Ambient Temperature [°C] | Output Voltage [V] | | |
|--------------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| -20 | 47.971 | 47.972 | 47.974 |
| -10 | 47.992 | 47.993 | 47.996 |
| 0 | 48.014 | 48.014 | 48.017 |
| 10 | 48.029 | 48.030 | 48.034 |
| 25 | 48.071 | 48.072 | 48.074 |
| 30 | 48.078 | 48.076 | 48.078 |
| 40 | 48.085 | 48.085 | 48.086 |
| 50 | 48.085 | 48.084 | 48.085 |
| 60 | 48.076 | 48.075 | 48.076 |
| -- | - | - | - |
| -- | - | - | - |



| | | |
|--------|-------------------------|----------------------------|
| Model | PBA100F-48 | Testing Circuitry Figure A |
| Item | Output Voltage Accuracy | |
| Object | +48V2.1A | |

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 264V

Load Current : 0 ~ 2.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


| Item | Temperature [°C] | Input Voltage[V] | Output | | Output Voltage Accuracy | |
|-----------------|---------------------|---------------------|------------|------------|-------------------------|------------|
| | | | Current[A] | Voltage[V] | Value [mV] | Ration [%] |
| Maximum Voltage | 50 | 85 | 0 | 48.114 | ±56 | ±0.1 |
| Minimum Voltage | -10 | 200 | 2.1 | 48.003 | | |

COSEL

| | |
|--------|------------------|
| Model | PBA100F-48 |
| Item | Time Lapse Drift |
| Object | +48V2.1A |

Temperature 25°C
 Testing Circuitry Figure A

1.Graph



Input Volt. 100V
 Load 100%

2.Values

| Time since start [H] | Output Voltage [V] |
|-------------------------|-----------------------|
| 0.0 | 48.035 |
| 0.5 | 48.064 |
| 1.0 | 48.065 |
| 2.0 | 48.065 |
| 3.0 | 48.065 |
| 4.0 | 48.066 |
| 5.0 | 48.066 |
| 6.0 | 48.066 |
| 7.0 | 48.066 |
| 8.0 | 48.066 |


* The characteristic of AC200V is equal.

COSEL

| | |
|--------|--------------------|
| Model | PBA100F-48 |
| Item | Rise and Fall Time |
| Object | +48V2.1A |


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


| Input Volt. | Time | Td | Tr | Ts | Th | Tf | [mS] |
|-------------|------|-------|-----|-------|------|------|------|
| 100 V | | 316.5 | 8.5 | 325.0 | 29.3 | 25.2 | |
| 200 V | | 279.5 | 8.5 | 288.0 | 34.4 | 25.2 | |



COSEL

| | |
|--------|--------------|
| Model | PBA100F-48 |
| Item | Hold-Up Time |
| Object | +48V2.1A |

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

| Input Voltage [V] | Hold-Up Time [mS] | |
|-------------------|-------------------|-----------|
| | Load 50% | Load 100% |
| 75 | 50 | 21 |
| 85 | 53 | 23 |
| 100 | 55 | 25 |
| 120 | 58 | 27 |
| 200 | 62 | 31 |
| 230 | 64 | 31 |
| 264 | 65 | 32 |
| 280 | 64 | 32 |
| - | - | - |

COSEL

| | |
|--------|---|
| Model | PBA100F-48 |
| Item | Instantaneous Interruption Compensation |
| Object | +48V2.1A |



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2.Values

| Load Current [A] | Time [mS] | | |
|------------------|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] | Input Volt. 230[V] |
| 0.00 | - | - | - |
| 0.40 | 142 | 155 | 155 |
| 0.80 | 74 | 83 | 85 |
| 1.20 | 48 | 60 | 57 |
| 1.60 | 35 | 41 | 42 |
| 2.00 | 25 | 33 | 32 |
| 2.10 | 25 | 31 | 35 |
| 2.31 | 22 | 28 | 28 |
| - | - | - | - |
| - | - | - | - |
| - | - | - | - |

COSEL

| | |
|--------|---|
| Model | PBA100F-48 |
| Item | Minimum Input Voltage for Regulated Output Voltage |
| Object | +48V2.1A |

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

| Ambient Temperature [°C] | Input Voltage [V] | |
|--------------------------------|----------------------|-----------|
| | Load 50% | Load 100% |
| -20 | 41 | 55 |
| -10 | 41 | 55 |
| 0 | 41 | 55 |
| 10 | 41 | 55 |
| 25 | 41 | 55 |
| 30 | 41 | 56 |
| 40 | 41 | 56 |
| 50 | 41 | 56 |
| 60 | 41 | 57 |
| - | - | - |
| - | - | - |


COSEL

Model PBA100F-48

Item Overcurrent Protection

Object +48V2.1A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 24V to 0V.


Temperature 25°C
Testing Circuitry Figure A

2. Values

| Output Voltage [V] | Load Current [A] | |
|--------------------|--------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] |
| 48.0 | 2.13 | 2.13 |
| 45.6 | 2.57 | 2.57 |
| 43.2 | 2.59 | 2.58 |
| 38.4 | 2.62 | 2.62 |
| 33.6 | 2.64 | 2.64 |
| 28.8 | 2.66 | 2.65 |
| 24.0 | 2.68 | 2.69 |
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |
| - | - | - |

COSEL

| | |
|--------|-----------------------|
| Model | PBA100F-48 |
| Item | Oversupply Protection |
| Object | +48V2.1A |

1.Graph

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A**2.Values**

| Ambient Temperature [°C] | Operating Point [V] | |
|--------------------------|---------------------|--------------------|
| | Input Volt. 100[V] | Input Volt. 200[V] |
| -20 | 60.64 | 60.17 |
| -10 | 61.17 | 61.05 |
| 0 | 61.63 | 61.63 |
| 10 | 62.22 | 62.22 |
| 25 | 63.03 | 63.04 |
| 30 | 63.26 | 63.15 |
| 40 | 63.74 | 63.74 |
| 50 | 64.27 | 64.15 |
| 60 | 64.74 | 64.74 |
| - | - | - |
| - | - | - |




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)